	Spécifications Fonctionnelles	
bouygues TELECOM	**STBL - Subscriptions Offers**	DPPS V2.3 13/11/2026

DATA PROTECTION

This document is classified at "CONFIDENTIAL".

Consequently:

Its distribution must be strictly limited to recipients who have an operational need, as listed on the cover page.
The distribution of this document in paper or electronic form is subject to specific rules outlined in the classification procedure and protection of information.
Its communication to third parties is subject to the prior signature of a confidentiality agreement.
This document should be stored in a locked cabinet or equivalent strong when it is not used.
The availability of this document on a shared server or a collection of documents on the intranet is subject to the establishment of an individualized management of access rights and protection by a strong password encryption and its.
The impressions of this document should be retrieved immediately.
The extracts of this document should keep the same classification markings.
All obsolete copies of this document must be destroyed using a shredder.

VERSIONS HISTORY

INDICE	DATE	LIST OF MODIFICIATIONS	WRITING	VERIF.	APPRO.
1.0	27/07/2023	Document creation	S.BEN HADHRIA	A.CARBILLET	
1.1	20/09/2023	Updating field names and cardinality	S.BEN HADHRIA	A.CARBILLET	
1.2	18/10/2023	Adapting the display of promotional offers	S.BEN HADHRIA	A.CARBILLET	
1.3	20/03/2024	Partners Offer	S.BEN HADHRIA	A.CARBILLET	
1.4	21/03/2024	Partner API	S.BEN HADHRIA	A.CARBILLET	
1.5	30/05/2024	New API version v2 to use to get unmanaged offers	S.BEN HADHRIA	A.CARBILLET	
1.6	07/06/2024	New API version v2 to manage partner API lot 2	S.BEN HADHRIA	A.CARBILLET	
1.7	16/07/2024	Details of finalActivationLink field	S.BEN HADHRIA	A.CARBILLET	
1.8	25/07/2024	nPVR offers	S.BEN HADHRIA	A.CARBILLET	
1.9	02/10/2024	Alignment 24.1 Removal of two fields: LongTitle/LongDescription Addition of a new field: shortName	S.BEN HADHRIA	A.CARBILLET	
1.10	03/12/2024	Search OUT OF SCOPE FOR THE MOMENT	S.BEN HADHRIA	A.CARBILLET	
1.11	09/12/2024	Update of query parameters for getList for ATV	S.BEN HADHRIA	A.CARBILLET	
1.12	09/12/2024	Using commercial.subscriptionStatus to determine the entitlement status of an offer	S.BEN HADHRIA	A.CARBILLET	
2.0	12/09/2025	Customer Journey Adaptation After Subscription	S.BEN HADHRIA	A.CARBILLET	
2.1	06/10/2026	Update triggers for call GET offers	M.BOUZID	A.CARBILLET	
2.2	10/11/2026	Working version initialized from v2.1 for content review			
2.3	13/11/2026	Product specification updated from the v2.2 reorganized draft			

DOCUMENT ESTABLISHED UNDER THE RESPONSIBILITY OF SIGNING

WRITING	VERIFICATION	APPROVAL
Nom : S.BEN HADHRIA Visa : Date : 27/07/2023	Nom : A.CARBILLET Visa : Date :	Nom : Visa : Date :

Table of contents

1. Références **3**

2. Purpose of the document **4**

3. Service overview **5**

3.1. Architecture and responsibilities 5

3.1.1. Global architecture 5

3.2. Offer lifecycle 5

4. Offer retrieval and data model **7**

4.1. Shared DALI request headers 7

4.2. Retrieve the offer list 7

4.2.1. Offer retrieval triggers 7

4.2.2. Principle of offer recovery 7

4.2.3. API to get offers 7

4.2.4. Display metadata and illustrative examples 18

5. User journeys **21**

5.1. Accessing a highlighted offer 21

5.2. Find an offer using a specific search (out of scope for the moment) 21

5.3. Retrieve all eligible offers (subscriptions menu) 21

5.4. Retrieve subscribed offers 22

5.5. Recovery of offers associated with an unsubscribed channel 22

5.6. Recovery of offers associated with a CUP shop 22

5.7. Subscription to an offer 23

5.7.1. Subscription process for an offer associated with a live channel and a CUP asset 23

5.8. Partner application activation 25

5.8.1. Activation status and partner journey 25

5.8.2. Fluid and non-fluid offers 27

5.9. Customer journey adaptation after subscription 29

5.10. Unsubscription of an offer 31

1 Références

Ref	Document Name	Link
[ref 1]	Swagger	lien
[ref 2]	LLD Live & SCUP	lien
[ref 3]	SAG Live & SCUP	lien

2 Purpose of the document

This document specifies the offer service for linear assets, CUP and SVOD. It describes how devices retrieve offer data, access the associated metadata, and request subscription or unsubscription through DALI.

It also specifies how subscription information is retrieved from multimedia asset data through DALI. The service contract and functional behavior are normative; screen layouts and UI illustrations elsewhere in this document are examples only.


3 Service overview

The offer service allows devices to retrieve subscribed and unsubscribed offers through DALI and to request subscriptions or unsubscriptions.

3.1 Architecture and responsibilities

3.1.1 Global architecture

Devices access the offer service through APIM, which forwards their requests to DALI. DALI retrieves offer data from SI BYTEL, offer metadata from KL, and app offer information from AIBO, then returns the response through APIM.




Devices rely on DALI for offer retrieval and subscription actions. DALI retrieves offers from the information system, enriches them with KL metadata, and returns the response; devices do not aggregate KL data or call the information system's subscription APIs directly.

3.2 Offer lifecycle

An offer lifecycle uses three independent dimensions:

- `entitlementState` indicates whether the offer is entitled (`ENTITLED`) or not (`NOT_ENTITLED`).
- `commercial.subscriptionStatus` describes the subscription or cancellation process and drives the transition state shown to the user.
- `commercial.partner.status` describes partner-account activation when the offer requires it.

These dimensions can coexist without meaning the same thing. For example, the shared Disney+ response has `DEACTIVATING`, `ENTITLED`, and `CREATED` at the same time. DALI action links determine which subscription API action is available; process or partner status does not replace those links.



After a subscription starts, the device enters the local `TRANSIENT` state. The general default duration is 120 seconds; partner-specific cooldowns are listed in the TRANSIENT configuration below. Timer expiry ends only the local wait and does not confirm backend completion. Once the timer expires, the product uses the current DALI state:

- `ACTIVATING` with `ENTITLED`: show subscription management instead of “Subscribe”; offer unsubscription only if DALI provides the `unsubscribe` action.
- `DEACTIVATING` with `ENTITLED`: show “Résiliation en cours” and do not issue another unsubscription request.
- `partner.status=CREATED` with `ENTITLED`: show both partner activation and subscription management. Hide the activation prompt when `partner.status=ACTIVE`.

Included offers are separate from this DALI offer lifecycle and are not returned by the nPFS offer API.

4 Offer retrieval and data model

4.1 Shared DALI request headers

Use the common headers below for the product's requests to the DALI offer API through APIM. `M` means mandatory, `O` means optional, and `M*` means mandatory only when the request includes a body. Any additional header required by a specific operation is listed with that operation.

Type of Param	Param	Type	M/O	Valeur
Header	`Authorization`	string	M	Basic credentials and Bearer token through public APIM
Header	`x-kaltura-secret`	string	M	Kaltura secret provisioned through the APIM integration
Header	`x-kaltura-api-version`	string	M	API version required by Swagger
Header	`x-request-id`	string	O	Unique request identifier; UUID format recommended
Header	`X-Dpps-Trace-idcontracts`	string	O	Contract identifier; supplied by APIM where applicable
Header	`x-Dpps-Trace-pfsnocompte`	string	O	Client identifier; supplied by APIM where applicable
Header	`x-version`	string	O	DALI offer API version
Header	`X-User-Agent`	string	O	Caller identifier
Header	`x-message-id`	string	O	Unique interaction/message identifier
Header	`x-source`	string	O	Request sender name
Header	`Content-Type`	string	M*	`application/json` when a request body is present

The product device calls the public APIM gateway and uses Basic authentication plus a Bearer token. The private DALI gateway uses an API key and mutual TLS for backend-to-backend traffic; the device must not call that gateway directly. APIM provides the integration-managed headers identified in the table.

4.2 Retrieve the offer list

4.2.1 Offer retrieval triggers

Type	Trigger	Condition / timing
Startup	App or STB startup	At startup
Scheduled	Periodic retrieval	Every 6 hours, with a randomized offset of ±2 hours
User initiated	Open the “My Subscriptions” menu	On menu entry
Playback consistency	Entitlement inconsistency while zapping	When detected
Catalog update	PDS modification	When `GET lineup` returns `200 OK`

4.2.2 Principle of offer recovery

For a List call, send the stored ETag in `If-None-Match` when available. On `304 Not Modified`, keep the local offer data. On `200 OK`, replace the local offer snapshot with the returned `data`. Update the stored ETag only when the response includes one; otherwise keep the previous value. After subscribe or unsubscribe, apply the action response locally and leave the ETag unchanged until the next scheduled List call.

4.2.3 API to get offers

1. API specification (swagger link)

```
GET /api/offers
```

(le path de l'api est défini dans le swagger)

Header parameters :

Type of Param	Param	Type	M/O	Valeur
Header	See 4.1	-	-	Common request headers
Header	`If-None-Match`	string	O	Previously received ETag for a conditional list request; 304 is returned when unchanged

Query parameters :

The optional `fields` parameter accepts comma-separated field or object selectors.

Type of Param	Param	Type	M/O	Valeur
Query	`categories`	array of strings	O	BOUQUET, APPLICATION, SERVICE, MULTIOFFER, UNMANAGED_APPLICATION
Query	`entitlementState`	string	O	ENTITLED or NOT_ENTITLED; omit to retrieve both states, and always omit when requesting UNMANAGED_APPLICATION
Query	`fields`	array of strings	O	Comma-separated field or object selectors

Response success :

- ***RESPONSE HEADERS***

> **ETAG** : string
>
> Entity tag for current customer records list , Returned Only if pagination not used

- ***RESPONSE Body***
  - **data** : Array
  - **totalElements** : Integer
    - total number of items on offer (subscribed and not subscribed)
  - **totalPages : Integer**
    - total pages
  - **currentPage** :Integer
    - index of current page

NOTE:

- Code 200 or 0 (PFSProxy), with no error nor empty body. Attribute "data" is a list of offer objects,

> and attribute storage gives related data. All data are listed in SAG. The following ones are stored. See below.

- ***Code 304, current data in DB is used.***

Common objects for each offer type

Key in JSONbody.data	Type	M/O	Use
`internalId`	`String`	M	Kaltura unique identifier for DB and actions.
`id`	`String`	M	The id used to enable Dali to make the connection between the SI Offer id and KL offer id used for DB and actions
`category`	`String`	M	Offer Type Used for display.
`images`	`Array`	O	Used for display.
`images[].id`	`String`	M	Used for display.
`images[].allowResize`	`boolean`	M	Used for display.
`images[].type`	`String`	M	Used for display.
`images[].height`	`Integer`	O	
`images[].width`	`Integer`	O	Used for display.
`images[].aspectRatio`	`Double`	M	Used for display.
`images[].url`	`String`	M	Used for display.
`catalogStartDateTime`	`Integer 64`	O	Used for display.
`longDescription`	`String`	~~O~~	~~Used for display.~~ (Not used)
`shortDescription`	`string`	O	Used for display.
`shortTitle`	`string`	O	Offer name are used for display.
`shortName`	`String`	O	Managed by Axis , it is used to set up Tabs in the EPG with all the channels of the offers, and the name of the Tab is the Shortname of the offer
`longTitle`	`string`	~~O~~	~~Description, used for display~~ (Not used)
`options []`	`Array`	O	A table of options contains the list of rights that the user will have when subscribed to the offer.
`options.entitledOptions[]`	`Array`	M	Options list

Key in JSONbody.data	Type	M/O	Use
options.entitledOptions[].name	String	M	An options table The name of the option, such as in the case of nPVR, is equal to quota{nb_hours}.
options.entitledOptions[].status	Boolean	O	This field is optional and will contain the user's rights status for the option (true: the user has rights to the option. False: the user does not have rights).
options.entitledOptions[].value	String	O	This field is optional and will contain the value of the option, such as the number of hours for the nPVR offer. Note: Either the "value" field or the "status" field will be filled in a block entitled "entitledOptions".
options [].type	String	M	Indicates the type of option such as "nPVR" or "PassPub". Since PassPub has been discontinued, only the "nPVR" type will be available as of today
entitlementState	String	O	used to differentiate between a subscribed and unsubscribed offer and to select the type of image for the S or NS offer ... Not be use for unmanaged_application
genre[]	Array of strings	O	Used for display.
editorialWeight	string	O	Used for display (Sort offers)
Links	Object (HATEOAS)	O	Object that describes URLs actions linked to the offer. Particularly used to make an action subscribe or cancel to an offer Each LINK name is the action, and LINK.href is the URL. Not to be used for unmanaged application offers
Actions	Object (HATEOAS)	O	Object that describes URLs actions on the offer. Used to make subscribe, unsubscribe and to filter actions. Each ACTION name is the action, and ACTION.href is the URL. Example: to subscribe to this offer, call up the URL address in the actions.subscribe object Not to be used for unmanaged application offers

« BOUQUET » type

Datamodel specific to the « BOUQUET » type

Key in JSONbody.data	Type	M/O	Use
Commercial	Object	M	Comercial metadata
commercial.id	String	M	Unique commercial identifier used for subscribe or unsubscribe actions
commercial.subscriptionStatus	String	M	Indicates the subscription process state. Allowed values: ACTIVE, ACTIVATING, DEACTIVATING, UNSPECIFIED. In our case, to circumvent the DSI issues with the propagation of subscription information across various platforms (KL, etc.), we can consider the offer as subscribed as soon as we have the "Activating" status. This will allow us to update the user journey and display the "Manage my subscriptions" button instead of the "Subscribe" button.
commercial.commercialType	String/Enum	M	Offer type from a commercial point of view Known values: BONUS, OPTION, OFFERED_SERVICE, PARTNER_SERVICE. Used for display.
commercial.name	String	O	Commercial wording of an offer
commercial.originalAmount	float	M	Offer price before promotion. Used for display.
commercial.finalAmount	float	M	Used to be compared with originalAmount, and then for display in function of the result (See UI Part). Offer price with promotion Used for display. Used for the rules to promotion display (Ex: finalAmount+"euros")
commercial.promotions	Array	O	Object describe the promotion

Key in JSONbody.data	Type	M/O	Use
commercial.promotions[i].price	Float	M	Object describes the promotions applied to the offer, used for display
commercial.promotions[i].order	Integer	O	Order of application of discounts when there are several promotions on offer. Used to determinate the promotion applied to the offer and display
commercial.promotions[i].applyTill	Integer 64	O	Used for display.
commercial.promotions[i].expirationDate	Integer 64	O	Used for display
commercial.promotions[i].duration	Object	O	Used for display.
commercial.promotions[i].duration.durationType	String	O	Duration Unit (Day, month, Year), used for display • one_time : The discount stays attached to the subscription till it is applied on an invoice once. It is removed after that from the subscription. • forever : The discount is attached to the subscription and applied on the invoices till it is explicitly removed. • limited_period : The discount is attached to the subscription and applied on the invoices for a limited duration. This duration starts from the point it is applied to an invoice for the first time and expires after a period specified by period and period_unit
commercial.promotions[i].duration.period	Integer	O	Duration period, min=1 The duration of time for which the discount is attached to the subscription, in period_units. Applicable only when duration_type is limited_period used for display
commercial.promotions[i].duration.periodUnit	String	O	The unit of time for period. Applicable only when duration_type is limited_period. Possible values are : day -- A period of 24 hours. month -- A period of 1 calendar month. year -- A period of 1 calendar year (maybe used to display the period of the promotion)
commercial.promotionalDescription	String	O	Used for display (not used to day)
commercial.startDate	Int64	O	Not used
commercial.endDate	In64	O	Used for Display
parentalRating	Integer	M	Display or not the offer
trailerNonSubscribedOffers[]	Array of Strings	O	Link to the baker channel Used for display when we zap in the live channel
replayShop	Object	M	Used to display the scup row
replayShop.total	Integer	M	Total of cup shop used for display
replayShop. items	Array	O	List of cup shop used for display
replayShop. Items[i].id	String	M	Cup shop kl collection id, not used at to day
replayShop. Items[i].name	String	M	Cup shop kl collection id, not used at to day
replayShop. Items[i].providerId	String	M	Used for display (retrieves the scup shop thumbnail from axis)
replayShop. Items[i].channels	Array	M	List of channels associated to this CUP shop, used for display. Note: this list of channels will be set by DALI in the live shop object. To display the row scup, you only need the channel lcn.
replayShop. Items[i].channels[j].id	String	M	Channel id, not used at the day
replayShop. Items[i].channels[j].name	String	M	Channel name, not used at the day
replayShop. Items[i].channels[j].lcn	String	Integer	Lcn used for display
svodShop	Object	O	Used to display the svod row
svodShop.total	Integer	M	Total of vod shop used for display

Key in JSONbody.data	Type	M/O	Use
svodShop. items	Array	O	List of vod shop used for display
svodShop. Items[i].id	String	M	vod shop kl collection id, not used at to day
svodShop. Items[i].name	String	M	vod shop kl collection id, not used at to day
svodShop. Items[i].provider Id	String	M	Used for display (retrieves the svod shop thumbnail from axis)
liveShop	Object	O	Used to display the live shop row row
liveShop.total	Integer	M	Total of channels used for display
liveShop. items	Array	O	List of channels used for display
liveShop. Items[i].id	String	M	Linear asset id used to get channel thumbnail from the pds
liveShop. Items[i].name	String	M	Linear asset id, not used
liveShop. Items[i].lcn	Integer	O	Linear asset lcn, used for display
liveShop. Items[i].collecti ons	Array	M	The collection in which the linear asset is associated the idea is to know if the channel is associated with a scupshop or not
liveShop. Items[i].collecti ons [j].id	String	M	Collection KL id not used
liveShop. Items[i].collecti ons [j].type	String	M	Collection KL type (CUP_SHOP, VOD_SHOP or LIVE_SHOP), not used
liveShop. Items[i].collecti ons [j].name	string	M	Collection KL name, not used

BOUQUET display metadata and examples

1. Several offers associated to the channel (Offer with promotion)




v

2. Several offers associated to the channel (Offer without promotion)




3. Unsubscribed offer info page with promotion



See section (a) for more details for promotionPrice and PromotionPeriod

a. Unsubscribed offer info page without promotion



d. subscribed offer info page



« APPLICATION » type (partner offers D+, DORCEL,...)

Datamodel specific to the « APPLICATION » type

Key in JSONbody.data	Type	M/O	Use
`commercial`	`Object`	M	Comercial metadata
`commercial.id`	`String`	M	Unique commercial identifier used for subscribe or unsubscribe actions
`commercial.subscriptionStatus`	`String`	M	Indicates the subscription process state. Allowed values: ACTIVE, ACTIVATING, DEACTIVATING, UNSPECIFIED.
`commercial.partner`	`Object`	O	It contains the activation status of the partner offer.

Key in JSONbody.data	Type	M/O	Use
commercial.partner.id	string	O	Identifier of the partner
commercial.partner.status	String	M	Status of the account creation on the partner side. Allowed values: ACTIVE, CANCELED, CREATED, INACTIVE, NON_EXISTENT, UNSUBSCRIBED.
commercial.commercialType	String/Enum	M	Offer type from a commercial point of view Known values: OPTION, BONUS, "OFFERED_SERVICE" "PARTNER_SERVICE". NOT used.
commercial.name	String	O	Commercial wording of an offer
commercial.originalAmount	float	M	Offer price before promotion. Used for display.
commercial.finalAmount	float	M	Used to be compared with originalAmount, and then for display in function of the result (See UI Part). Offer price with promotion Used for display. Used for the rules to promotion display (Ex: finalAmount+"euros")
commercial.promotions	Array	O	Object describe the promotion
commercial.promotions[i].price	Float	M	Object describes the promotions applied to the offer, used for display
commercial.promotions[i].order	Integer	O	Order of application of discounts when there are several promotions on offer. Used to determinate the promotion applied to the offer and display
commercial.promotions[i].applyTill	Integer 64	O	Used for display.
commercial.promotions[i].expirationDate	Integer 64	O	Used for display
commercial.promotions[i].duration	Object	O	Used for display.
commercial.promotions[i].duration.durationType	String	O	Duration Unit (Day, month, Year), used for display • one_time : The discount stays attached to the subscription till it is applied on an invoice once. It is removed after that from the subscription. • forever : The discount is attached to the subscription and applied on the invoices till it is explicitly removed. • limited_period : The discount is attached to the subscription and applied on the invoices for a limited duration. This duration starts from the point it is applied to an invoice for the first time and expires after a period specified by period and period_unit
commercial.promotions[i].duration.period	Integer	O	Duration period, min=1 The duration of time for which the discount is attached to the subscription, in period_units. Applicable only when duration_type is limited_period used for display
commercial.promotions[i].duration.periodUnit	String	O	The unit of time for period. Applicable only when duration_type is limited_period. Possible values are : day -- A period of 24 hours. month -- A period of 1 calendar month. year -- A period of 1 calendar year (maybe used to display the period of the promotion)
commercial.promotionalDescription	String	O	Used for display (not used to day)
commercial.startDate	Int64	O	Not used
commercial.endDate	In64	O	Used for Display
partnerOfferUrl	String	O	Used for display
partnerOfferApk	String	O	Used for display
parentalRating	Integer	M	Display or not the offer
trailerNonSubscribedOffers[]	Array of Strings	O	Link to the baker channel Used for display when we zap in the live channel
relatedBoutique	String	O	Contains the id of the collection associated with the application, not used by FE

Key in JSONbody.data	Type	M/O	Use
subscriptionType	Int	O	'Subscription type used' is used to determine the type of offer - fluid, non-fluid, etc.
activationLink	String	O	The deeplink or QR Code contains the path to activate the account on the app . The QR Code and the deep link are computed by DALI, and the device should use them as such.
finalActivationLink	String	O	Activation Link to be called by devices Computed by DALI The QR Code and the deep link are computed by DALI, and the device should use them as such. For subscriptionType=2, DALI continues to return finalActivationLink and the STB must use it as the QR activation target. For subscriptionType=3, use activationLink instead.
infoPageTemplate	Int	O	Not used for the moment. The info page template will be shared with axis
hide	Boolean	O	This is used for technical offers that should not be displayed.

« UNMANAGED_APPLICATION » type (Canal+)

Datamodel specific to the « UNMANAGED_APPLICATION » type

Key in JSONbody.data	Type	M/O	Use
partnerOfferUrl	String	O	Used for display
partnerOfferApk	String	O	Used for display
parentalRating	Integer	M	Display or not the offer
trailerNonSubscribedOffers[]	Array of Strings	O	Link to the baker channel Used for display when we zap in the live channel
relatedBoutique	String	O	Contains the id of the collection associated with the application, not used by FE
hide	Boolean	O	This is used for technical offers that should not be displayed.

This offer is only eligible for the STB device and is not listed in the offers defined on the DSI side. Therefore, it is necissary to specify the categories of offers supported by the device in the request for obtaining the list of subscribed and unsubscribed offers.

For example, if the device wants to retrieve Canal offers in the list of subscribable offers, it must add the category=UNMANAGED_APPLICATION query parameter to the request.

For other devices that do not support Canal applications and applications not managed by the DSI, the category UNMANAGED_APPLICATION should not be added to the request.

This type of offer can only be subscribed to from the partner app, such as Canal+.

Datamodel specific to the « SERVICE » type

Key in JSONbody.data	Type	M/O	Use
commercial	Object	M	Comercial metadata
commercial.id	String	M	Unique commercial identifier used for subscribe or unsubscribe actions
commercial.subscriptionStatus	String	M	Indicates the subscription process state. Allowed values: ACTIVE, ACTIVATING, DEACTIVATING, UNSPECIFIED.
commercial.commercialType	String/Enum	M	Offer type from a commercial point of view Known values: BONUS, OPTION, OFFERED_SERVICE, PARTNER_SERVICE. Used for display.
commercial.name	String	O	Commercial wording of an offer
commercial.originalAmount	float	M	Offer price before promotion. Used for display.
commercial.finalAmount	float	M	Used to be compared with originalAmount, and then for display in function of the result (See UI Part). Offer price with promotion Used for display. Used for the rules to promotion display (Ex: finalAmount+"euros")

Key in JSONbody.data	Type	M/O	Use
commercial.promotions	Array	O	Object describe the promotion
commercial.promotions[i].price	Float	M	Object describes the promotions applied to the offer, used for display
commercial.promotions[i].order	Integer	O	Order of application of discounts when there are several promotions on offer. Used to determinate the promotion applied to the offer and display
commercial.promotions[i].applyTill	Integer 64	O	Used for display.
commercial.promotions[i].expirationDate	Integer 64	O	Used for display
commercial.promotions[i].duration	Object	O	Used for display.
commercial.promotions[i].duration.durationType	String	O	Duration Unit (Day, month, Year), used for display • one_time : The discount stays attached to the subscription till it is applied on an invoice once. It is removed after that from the subscription. • forever : The discount is attached to the subscription and applied on the invoices till it is explicitly removed. • limited_period : The discount is attached to the subscription and applied on the invoices for a limited duration. This duration starts from the point it is applied to an invoice for the first time and expires after a period specified by period and period_unit
commercial.promotions[i].duration.period	Integer	O	Duration period, min=1 The duration of time for which the discount is attached to the subscription, in period_units. Applicable only when duration_type is limited_period used for display
commercial.promotions[i].duration.periodUnit	String	O	The unit of time for period. Applicable only when duration_type is limited_period. Possible values are : day -- A period of 24 hours. month -- A period of 1 calendar month. year -- A period of 1 calendar year (maybe used to display the period of the promotion)
commercial.promotionalDescription	String	O	Used for display (not used to day)
commercial.startDate	Int64	O	Not used
commercial.endDate	In64	O	Used for Display
relatedBoutique	String	O	Contains the id of the collection associated with the application, not used by FE

nPVR offer

As indicated in paragraph 4.1.3.1, there will be a table of option objects through which we can determine the type of the service offer is nPVR or not unsing the metadata "options[].type" = "nPVR".

Following the retrieval of an "nPVR" offer via the get and list APIs exposed by DALI, the structure of the option field is as follows:

Field	*type*	*M/O*	*Value*
data.options []	Array	O	-
data.options.entitledOptions[]	Array	M	-
data.options.entitledOptions[].name	String	M	quota{nb_hours}
data.options.entitledOptions[].status	Boolean	O	NULL
data.options.entitledOptions[].value	String	O	{nb_hours}
data.options [].type	String	M	"nPVR"

This object must be stored in the local offer database to be utilized by the UI according to marketing needs. Through the metadata returned by DALI following the "list" API call, we can distinguish:

- The type of offer, whether nPVR or not, via options[].type
- The subscription status via data.entitlementState
- The quota of the nPVR offer via data.options.entitledOptions[].value

Datamodel specific to the « MULTIOFFER » type

Key in JSONbody.data	Type	M/O	Use
commercial	Object	M	Comercial metadata

Key in JSONbody.data	Type	M/O	Use
commercial.id	String	M	Unique commercial identifier used for subscribe or unsubscribe actions
commercial.subscriptionStatus	String	M	Indicates the subscription process state. Allowed values: ACTIVE, ACTIVATING, DEACTIVATING, UNSPECIFIED.
commercial.commercialType	String/Enum	M	Offer type from a commercial point of view Known values: BONUS, OPTION, OFFERED_SERVICE, PARTNER_SERVICE. Used for display.
commercial.name	String	O	Commercial wording of an offer
commercial.originalAmount	float	M	Offer price before promotion. Used for display.
commercial.finalAmount	float	M	Used to be compared with originalAmount, and then for display in function of the result (See UI Part). Offer price with promotion Used for display. Used for the rules to promotion display (Ex: finalAmount+"euros")
commercial.promotions	Array	O	Object describe the promotion
commercial.promotions[i].price	Float	M	Object describes the promotions applied to the offer, used for display
commercial.promotions[i].order	Integer	O	Order of application of discounts when there are several promotions on offer. Used to determinate the promotion applied to the offer and display
commercial.promotions[i].applyTill	Integer64	O	Used for display.
commercial.promotions[i].expirationDate	Integer64	O	Used for display
commercial.promotions[i].duration	Object	O	Used for display.
commercial.promotions[i].duration.durationType	String	O	Duration Unit (Day, month, Year), used for display • one_time : The discount stays attached to the subscription till it is applied on an invoice once. It is removed after that from the subscription. • forever : The discount is attached to the subscription and applied on the invoices till it is explicitly removed. • limited_period : The discount is attached to the subscription and applied on the invoices for a limited duration. This duration starts from the point it is applied to an invoice for the first time and expires after a period specified by period and period_unit
commercial.promotions[i].duration.period	Integer	O	Duration period, min=1 The duration of time for which the discount is attached to the subscription, in period_units. Applicable only when duration_type is limited_period used for display
commercial.promotions[i].duration.periodUnit	String	O	The unit of time for period. Applicable only when duration_type is limited_period. Possible values are : day -- A period of 24 hours. month -- A period of 1 calendar month. year -- A period of 1 calendar year (maybe used to display the period of the promotion)
commercial.promotionalDescription	String	O	Used for display (not used to day)
commercial.startDate	Int64	O	Not used
commercial.endDate	In64	O	Used for Display
relatedBoutique	String	O	Contains the id of the collection associated with the application, not used by FE
parentalRating	Integer	M	Display or not the offer

Response Error :

PFSPxyCode	HTTPCode	JSON.error	Cause	Action to do
1(1)	401	Invalid Token	Token is invalid	Authentication process relaunched.
[2-11]	N/A	N/A	PFSProxy Internal Error	Just log error, but App goes on.
400	400	Bad Request	Bad Request	Just log error, but App goes on.

PFSPxyCode	HTTPCode	JSON.error	Cause	Action to do
404	404	Not Found	Not Found	Just log error, but App goes on.
405	405	Method Not Allowed	Method Not Allowed	Just log error, but App goes on.
429	429	Too many requests	Too many requests	Just log error, but App goes on.
500	500	Internal server error	Internal server error	Just log error, but App goes on.
502	502	External server error	External server error	Just log error, but App goes on.
503	503	Internal server error	Internal server error	Just log error, but App goes on.
Other not HTTP	N/A	N/A	All	Just log error, but App goes on.
Other from APIM: See REF []				

- If data already exists in App, no error displayed, current data in DB is used.
- Notice (1): PfsProxy errorCode 1 means "non authenticate" but must be compared to PfsProxy codes enumeration. Example: errorCode == PfsProxy.NON_AUTHENTICATE.
-

4.2.4 Display metadata and illustrative examples

4. Several offers associated to the channel (Offer with promotion)



1. **PromotionPrice :**

If data.commercial.originalAmount != data.commercial.finalAmount

Then

PromotionPrice = data.commercial.finalAmount + "€" + "/mois"

end IF

2. **PromotionPeriod :**

if data.commercial.originalAmount != data.commercial.finalAmount

then

if data.commercial.promotion.duration.durationType = "limited_period"

then

> PeriodPromotion = "pendant" + data.commercial.promotion.duration.period + data.commercial.promotion.duration.periodUnit + "puis" + data.commercial.originalAmount + "€\mois"

Endif


// other duration_type values (one_time and forever) are not yet taken into account

end IF

5. Several offers associated to the channel (Offer without promotion)




6. Unsubscribed offer info page with promotion



See section (a) for more details for promotionPrice and PromotionPeriod

b. Unsubscribed offer info page without promotion




e. subscribed offer info page




5 User journeys

5.1 Accessing a highlighted offer

a. Access to an offer from the Home menu:



Home Page



Détails Offre

b. Solution :

> Retrieving metadata of the featured offer from the local database.

c. Raisons :

- Axis does not distinguish between offers eligible and not eligible to the user.
- If we retrieve offer metadata from KL, there is a risk of displaying offers not eligible to the user.
- We rely on locally stored offers, and if the offer does not exist in the database (not eligible), we do not display it.


5.2 Find an offer using a specific search (out of scope for the moment)

a. Scenario (Accessing an offer through a search):

Recherche dans Bouquet TV



Détails Offre



b. Solution :


> Search and retrieve offer metadata locally.

c. Raisons :

- KL does not distinguish between offers eligible and not eligible to the user after a Ksql search.
- The search must be done locally to avoid the risk of displaying offers not eligible to the user.

5.3 Retrieve all eligible offers (subscriptions menu)

a. Scenario (Accessing an offer from the "My Subscriptions" menu):



d. Solution :


> Retrieve offers as described in section section 4.2

5.4 Retrieve subscribed offers

a. Scenario (Displaying subscribed offers in the "My Subscriptions" menu):



Offre souscrites



Détails de l'offre

b. Solution :

> Retrieve offer metadata locally.

c. Raisons :

- The list of subscribed offers is accessible from the "My Subscriptions" menu.
- We are synchronized with the actual status of subscribed offers when entering the "My Subscriptions" menu.

5.5 Recovery of offers associated with an unsubscribed channel

Scenario (Show offers associated with a chain) :



- This screen will be displayed:
  - In the case of OTT:
    - If the response from the "GetPlaybackContext" phoenix api is NotEntitled and the user does not have rights to this channel.
  - In the case of IPTV:
    - If the VMX client response is "NoRigth" and the user does not have rights to this channel.



- We need to retrieve the list of offers associated with the channel from the offer objects loaded in the UI.
- All offer metadata associated with the chain will be retrieved from the local offer DB.



- In this screen, we use the information already stored locally in the database.

5.6 Recovery of offers associated with a CUP shop

> ***Scenario (Show offers associated with a CUP shop)***



Boutique CUP

When the user selects a CUP shop :

- If several assets are associated with this store, the info sheet for each asset must be displayed (Playback will be launched when the user selects an asset).
- If only one asset is associated with this store, the asset info sheet must be displayed with a view button.



Popup Non-subscribed user

the user selects an asset to play or presses the view button:

- The "getPlaybackContext" api will be launched to retrieve playback rights:
  - If the user has the right to play the asset, playback will start automatically.
  - If the user doesn't have playback rights, a popup will be displayed asking him to subscribe.




Details of the subscription offer

- If the user presses the "Find out how to benefit from this video" button, we can use the metadata and details of offers available locally (iso Live).

5.7 Subscription to an offer

5.7.1 Subscription process for an offer associated with a live channel and a CUP asset



Step 1 : User zaps to an unsubscribed channel

Step 2 : The user presses the subscribe button.

In this step, we must :

> o Retrieve the list of offers associated with the channel locally:

- If the number of offers > 1
  - We display the list of offers (as we do today)
- If the number of offers = 1
  - The info sheet for the offer associated with the channel must be displayed.
- If number of offers = 0
  - Display subscription menu

NOTE :

a. A single Offer associated with the channel:

Display of offer details is based on locally stored offer metadata. (The metadata to be displayed are iso today)

The Information to be displayed is described in section 4.2.4 :

b. Several Offers associated with the channel

> When the user focuses on one of the Offers, the following is displayed:

- Offer name
- Offer description + promotion description
- Offer image
- Number and thumbnails of channels associated with the offer
- Price
- Number of replay shop

> o Display information retrieval is based on locally stored offer metadata (iso to day)
>
> o If the user selects one of the offers, the information described in a) is displayed.

Step 3 :

- If only one offer is associated with the channel
  - This step does not exist
- Else, if several offers are associated with the channel
  - We need to display the detailed info card for the offer selected by the user.

Step 4 :

The user presses the subscribe button and enters his purchase code

- The purchase code must be managed (validated, created, ...with the Kansas platform (iso today).
  - If the purchase code is valid :
    - The device must request DALI to launch the subscription action (The subscription API is available in the HAETOS link in the actions.subscribe offer metadata) with the parameter force = false allowing DALI to check the incompatibility of the offer and return to the device the list of incompatible offers if they exist. The device must request DALI to retrieve the (Details and full API path are in the swagger.) :

```
POST /api/offers/subscribe
```

Header :

Type of Param	Param	Type	M/O	Valeur
Header	See 4.1	-	-	Common request headers
Header	`x-purchase-code`	string	M	Purchase PIN entered by the user

Request body :

Type of Param	Param	Type	M/O	Valeur
Body	`idCommercialOffer`	string	M	Non-empty DSI commercial offer identifier
Body	`force`	boolean	O	`false` initially; `true` only after user confirmation of incompatible offers

a. **If the offer is not incompatible with other offers :**

Success Response :

- `http code 200`
- The Subscribed offer object This objet is decribed in section 4.2.2 (**JSONbody.data Array**)

Error Response :

PFSPxyCode	HTTPCode	JSON.error	Cause	Action to do
1(1)	401	Invalid Token	Token is invalid	Authentication process relaunched.
N/A	403	Forbidden	ApiErrorOfferSubscribe	Product handling is not specified here.
[2-11]	N/A	N/A	PFSProxy Internal Error	Just log error, but App goes on.
400	400	Bad Request	Bad Request	Just log error, but App goes on.
404	404	Not Found	Not Found	Just log error, but App goes on.
405	405	Method Not Allowed	Method Not Allowed	Just log error, but App goes on.
409	409	Conflict	Incompatible offers found	Asks the user to confirm cancellation of incompatible offers
429	429	Too many requests	Too many requests	Just log error, but App goes on.
500	500	Internal server error	Internal server error	Just log error, but App goes on.
502	502	External server error	External server error	Just log error, but App goes on.
503	503	Internal server error	Internal server error	Just log error, but App goes on.
Other not HTTP	N/A	N/A	All	Just log error, but App goes on.
Other from APIM: See REF []				

b. **If the offer is incompatible with other offers :**

> *Success Response :*

- `http code 409`
- Body : `ApiErrorIncompatibleOffer`, with an `incompatibleOffers` array of strings at the top level, as declared by Swagger.

> Exemple :

```
{
  "incompatibleOffers": [
    "offerId1",
    "offerId2",
    "offerId3"
  ]
}
```

1. The device must ask the user to accept the cancellation of incompatible offers before subscribing to the offer.
2. If the user confirms subscription to the offer, then the device must request DALI with the api described in (a) (with **force = true**).
3. The device receives the metadata of the newly subscribed offer and incompatible offers if exist. In this scenario, the device should update its local database directly without the need for a second call to update the list of offers. (the response structure is defined in the swagger ref[1])

> NOTE : The ETAG does not need to be updated at this stage. We'll have to wait for the next updater to update it.


5.8 Partner application activation

5.8.1 Activation status and partner journey

> **What changes compared to the legacy version:**
>
> There is no specific AIBO API to determine the activation status, instead one must call the DALI getOffer API with the commercial offer ID to obtain the activation status. The activation status is found in the commercial object returned by DALI in the Partner object.

Call flow :

> Note: With each entry to display the information of an offer, we must apply this call flow.



- If the user accesses an APPLICATION-type offer
  - We must check the subscription type data.subscriptionType.
    - If data.subscriptionType=2 or 3, then we must know the activation status of the offer:
      - To determine the activation status of an offer, it is necessary to call DALI with the "get" API for the offers by specifying the ID of the relevant offer.
        - The response to this request will contain a "commercial.partner" object, which will indicate the activation status to adjust the user journey accordingly - field described in the table above:
          - If the commercial.partner.status is different from 'ACTIVE', then the QRCode (data.subscriptionType=2 as Disney+) or application thumbnail/deeplink that redirects to the account creation page (data.subscriptionType=3 as DORCEL) must be displayed.

```
            -   [DALI returns `finalActivationLink` for `subscriptionType=2`; the
STB uses it as the QR activation target.]{.revision-blue}

            -   [For `subscriptionType=3`, the STB must use `activationLink`
instead of `finalActivationLink` as the activation deep link. If `activationLink`
is absent or empty, the STB must launch the partner application identified by
`partnerOfferApk`.]{.revision-blue}
```

          - ACTIVE status: The "Your service to activate" row (which contains the QRCode or deeplink for account creation) must be hidden in the offer information sheet.

> **DALI API**

2. API specification (swagger link)

```
GET /api/offers/by-commercial-id/{commercialId}
```

(le path de l'api est défini dans le swagger)

Type of Param	Param	Type	M/O	Valeur
Header	See 4.1	-	-	Common request headers
Path	`commercialId`	string	M	Commercial offer identifier

Response success :

- ***RESPONSE Body***
  - **data** : Array Data contains the entire table defined in (a).
  - **totalElements** : Integer
    - total number of items on offer (subscribed and not subscribed)
  - **totalPages : Integer**
    - total pages
  - **currentPage** :Integer
    - index of current page

NOTE:

- Code 200 or 0 (PFSProxy), with no error nor empty body. Attribute "data" is a list of offer objects,


> and attribute storage gives related data. All data are listed in SAG. The following ones are stored. See below.

Subscribe/unsubscribe :

> There is no impact on the devices for managing the subscription and cancellation of partner offers. The same request and principle as for bouquet offers is applied for subscription and cancellation. DALI chooses which subscription API to call based on the type of offer - fluid or non-fluid.


5.8.2 Fluid and non-fluid offers

- Non-fluid offer (as Disney+)



> After subscribing to the (Disney+) offer (with subscriptionType=2) through the Bytel UI, the subscription status returned by the SI via DALI will be active and the data.entitlmentStatus = ENTITLED, even though the account may not be activated. In this situation, we need to check the account activation status to adjust the journey correctly.
>
> The user has the option to click on the QR Code as described in the schema. In this case, we should call the DALI get API to obtain the account activation status. We maintain the same protection as the legacy with 1 get call per 5 seconds.


- fluid offer (as DORCEL)



After a user subscribes to a `subscriptionType=3` offer such as DORCEL, the STB must use `data.activationLink` as the activation deep link instead of `data.finalActivationLink`. If `activationLink` is absent or empty, the STB must launch the partner application identified by `data.partnerOfferApk`.

The subscription status remains `DEACTIVATING` with `entitlementState=NOT_ENTITLED` until the user activates their account.

5.8.3 Intercept screen management



After launch, adapt the partner-app journey to GetAccountInfo().

When the user confirms a featured offer, the STB retrieves the offer by `ID` and checks `entitlementState`, `commercial.subscriptionStatus`, and `commercial.partner.status`.

- If `entitlementState=NOT_ENTITLED`, display the Intercept screen. If the user selects an offer, display the offer information page and end this flow. If the user selects Sign in, launch the partner application associated with the offer.

- If `entitlementState=ENTITLED` and `commercial.partner.status=ACTIVE`, launch the partner application associated with the offer.
- If `entitlementState=ENTITLED` and `commercial.partner.status` is not `ACTIVE`, check `subscriptionType`:
  - For type `2`, display the offer information page and end this flow.
  - For type `3`, check whether the applicable fluid-partner cooldown (`offers.config.cooldown_for_fluid_partners`) has expired. If it has expired, launch the partner application associated with the offer. Otherwise, display the offer information page and end this flow.

5.9 Customer journey adaptation after subscription

a. Objective

Subscription rights propagation to channels may take several minutes. This enhancement aims to improve the user experience during this delay, until rights are fully propagated from DSI to KL.

b. Current Behavior

After subscribing, if a user attempts playback of a newly subscribed channel before rights propagation:

- A subscription proposal screen is displayed.



- The "Souscrire" button remains visible in the offer info sheet.



- On STB, entitlement retrieval is triggered 30 seconds after subscription via the KL entitlement API.

c. Changes Introduced

1. Transient Subscription Status

   - `TRANSIENT` is a temporary state managed locally by the product (Device), between *not subscribed* and *subscribed*, while the subscription is being processed on the DSI side.
   - This local waiting state is distinct from the commercial and entitlement statuses received from DALI; it is managed by the product rather than obtained from the API response.
   - The subscription starts the local waiting timer. Its duration is controlled by the cooldown settings below.
   - The product enters `TRANSIENT` when this timer starts and remains in this state until the configured cooldown expires.

Config Objet	Param	Type	M/O	Default	Description
`offers.config`	`cooldown_in_seconds`	integer	O	120	Default TRANSIENT duration

Config Objet	Param	Type	M/O	Default	Description
offers.config	cooldown_for_fluid_partners	integer	O	30	TRANSIENT duration for fluid partner offers
offers.config	cooldown_for_non_fluid_partners	integer	O	0	TRANSIENT duration for non-fluid partner offers

- Ensures a single reference point for subscription status checks.
- For fluid partner offers, activation must be disabled while the offer is in `TRANSIENT`.
- Timer expiry ends the local waiting state; it does not, by itself, confirm that DSI processing or entitlement propagation has completed.

2. Playback Behavior During TRANSIENT

> If the channel belongs to an offer in TRANSIENT state and playback fails:

- IPTV: returns NORIGHT.
- OTT Live: getPlaybackContext returns NOT_ENTITLED.
- System behavior:
  • Remove the "OK pour souscrire" button.
  • Display updated message:
  - New: " Votre abonnement est en cours d'activation. Nous vous invitons à patienter quelques minute"
  - Replaces: " Vous n'êtes pas abonné à la chaîne XXX.

> Si vous venez de souscrire, votre abonnement est peut-être en cours d'activation.
>
> Merci de patienter quelques minutes. "
>
> 

3. Offer Info Sheet Update During TRANSIENT
   • Replace "Souscrire" button text with "Souscription en cours".

4. Entitlement Retrieval

> Adjust entitlement retrieval timer.
>
> After 120 seconds, fetch entitlements for all channels:
>
> ```
> POST {{PhoenixURL}}asset/action/list
> ```
>
> Example:
>
> ```
> {
>   "apiVersion": "{{apiVersion}}",
>   "ks": "{{kaltura_ks}}",
>   "filter": {
>     "objectType": "KalturaSearchAssetFilter",
>     "kSql": "(and entitled_assets='entitledSubscriptions' asset_type={{Linear_Asset}})"
>   },
>   "responseProfile": {
>     "objectType": "KalturaOnDemandResponseProfile",
>     "retrievedProperties": "id"
>   },
>   "pager": {
>     "pageSize": 500,
>     "pageIndex": 1
>   }
> }
> ```

5. Offer List Refresh


> Update offers via DALI list API.

- For this use case:

- Do not validate ETag.
- Force list refresh.

5.10 Unsubscription of an offer

Call Flow :



Step 1 : Accessing the information page of a subscribed offer can be done either through the "My Subscriptions" menu , through a search, or through HIGHLIGHTED featured subscribed offers. The construction of this sheet relies on the locally loaded metadata, as described in section 4.2.4

Step 2 :

i. The user presses the unsubscribe button and enters his purchase code

- The purchase code must be validated with the Kansas platform (iso today)
  - If the purchase code is valid
    - The device must request DALI to unsubscribe to the offer(The unsubscription API is available in the HAETOS link in the actions.unsubscribe offer metadata): (Details and full API path are in the swagger.) :

```
POST /api/offers/unsubscribe
```

Header :

Type of Param	Param	Type	M/O	Valeur
Header	See 4.1	-	-	Common request headers
Header	`x-purchase-code`	string	M	Purchase PIN entered by the user

Request body :

Type of Param	Param	Type	M/O	Valeur
Body	`idCommercialOffer`	string	M*	DSI commercial offer identifier
Body	`idOffer`	string	O	Declared by Swagger but not currently used; do not send

- The product flow requires `idCommercialOffer`; the Swagger schema does not include it in the body's `required` list.

Success Response :

- `http code 200`
- unsubscribed offer metadata (metadata of offers impacted by this action)
  - Metadata of the unsubscribed offer :
    - The device should update its local database for this unsubscribed offer y without the need for a second call to update the list of offers. (the response structure is defined in the swagger ref[1])

> NOTE : The ETAG does not need to be updated at this stage. We'll have to wait for the next updater to update it.

Error Response :

PFSPxyCode	HTTPCode	JSON.error	Cause	Action to do
1(1)	401	Invalid Token	Token is invalid	Authentication process relaunched.
N/A	403	Forbidden	CANCELLATION_NOT_ALLOWED	Product handling is not specified here.
[2-11]	N/A	N/A	PFSProxy Internal Error	Just log error, but App goes on.
400	400	Bad Request	Bad Request	Just log error, but App goes on.
404	404	Not Found	Not Found	Just log error, but App goes on.
405	405	Method Not Allowed	Method Not Allowed	Just log error, but App goes on.
429	429	Too many requests	Too many requests	Just log error, but App goes on.
500	500	Internal server error	Internal server error	Just log error, but App goes on.
502	502	External server error	External server error	Just log error, but App goes on.
503	503	Internal server error	Internal server error	Just log error, but App goes on.
Other not HTTP	N/A	N/A	All	Just log error, but App goes on.
Other from APIM: See REF []				