TEST - 4

① USES OF PING COMMAND

Ping is used to check Wheather One device Can Communicate With another device.

→ Checks if a device is reachable

→ Tests network connectivity.

Ex:

Ping 50.0.0.10.

② net bios Protocol

Net BIOS → Network Basic Input / Output System

→ Allows Computers to Communicate With eachother on a network.

→ Can identify Computer using names.

(3) SMB Protocol

SMB = Server Message Block

→ It is used to share files & folders over a network.

→ Also used for printer sharing.

→ Commonly used in Windows network.

(4) Ping Process 50.0.0.10 to 50.0.0.20

S1

PC-A (50.0.0.10) sends Ping message

Ping 50.0.0.20

S2

PC-A checks Wheather 50.0.0.20 is in the same network.

S3

Since both are in same network, PC-A Uses ARP (Address Resolution Protocol) to find MAC address of 50.0.0.20.

S4

PC-A Sends ARP request

Who has 50.0.0.20?

S5

Now PC-B (50.0.0.20) sends ARP Reply

with MAC address.

S6

PC-A Sends an ICMP (Internet Control Message Protocol) Echo Request to PC-B.

S7

PC-B receives the request & Sends an

ICMP Echo reply.

S8

Now PC-A receives the reply & display

Reply from 50.0.0.20