

Gravitational-Wave Detection via Laser Interferometry:

Physical Principles, Detector Architecture, and Fundamental Noise Limits

Mohammad Mahdi Zare

Department of Physics, Sharif University of Technology, Tehran, Iran

Email: zaremohammadmahdi2006@gmail.com

Term Paper · Experimental Methods in Physics · Academic Year 2025–2026

Abstract

Gravitational waves (GWs), direct ripples in spacetime curvature predicted by Albert Einstein’s General Relativity, represent one of the most transformative observational frontiers in modern astrophysics. Direct observation of these ripples yields pristine astrophysical data regarding extreme cosmic catastrophes, including binary black hole and neutron star coalescences. However, because spacetime is exceedingly stiff, the differential strain induced by passing astrophysical waves on terrestrial baselines is minuscule, typically $h \sim 10^{-21}$. Detecting such perturbations requires measuring differential arm length distortions on the order of $\Delta L \sim 10^{-18}$ m across multi-kilometer baselines. This paper presents an analytical and methodological overview of modern ground-based laser interferometric detectors such as LIGO and Virgo. We examine the fundamental physical principles of Michelson Fabry–Pérot interferometry, evaluate the primary noise sources limiting detector strain sensitivity across distinct frequency regimes—specifically terrestrial seismic noise, thermal suspension Brownian noise, and quantum optical noise (shot noise and radiation pressure noise)—and review the cutting-edge suppression methodologies deployed to overcome the Standard Quantum Limit (SQL).

1 Introduction

Gravitational waves (GWs) constitute one of the foundational predictions of Einstein’s General Theory of Relativity (1915). Nearly a century elapsed between their theoretical formulation and their first direct experimental observation. Unlike electromagnetic radiation, which is emitted via the accelerated motion of individual charged particles and is readily absorbed, scattered, or obscured by intervening matter, gravitational radiation is produced by the bulk coherent acceleration of vast astrophysical masses. Consequently, gravitational waves traverse cosmological distances virtually unattenuated, offering an unobstructed window into high-energy phenomena in the strong-field, highly dynamical regime of spacetime.

Because the coupling between mass-energy and spacetime curvature is governed by Einstein’s field equations with a coupling constant of $8\pi G/c^4 \approx 2.07 \times 10^{-43} \text{ N}^{-1}$, spacetime exhibits an enormous intrinsic stiffness. As a result, the physical strain exerted by passing gravitational waves upon matter is exceptionally minute. Terrestrial detection demands instruments characterized by extraordinary displacement sensitivity. Contemporary kilometer-scale laser interferometers, such as the Advanced LIGO (Laser Interferometer Gravitational-Wave Observatory) and Advanced Virgo facilities, integrate state-of-the-art optical topologies, cryogenic technologies, ultra-high vacuum systems, and precision active control engineering to detect length differentials far smaller than the diameter of an atomic nucleus.

This paper is structured as follows: Section 2 introduces the mathematical and physical nature of gravitational radiation in linearized general relativity. Section 3 derives the fundamental

interferometric detection principle. Section 4 details the optical topology and subsystems of advanced detectors. Section 5 through Section 9 provide a rigorous noise budget analysis, categorizing seismic, thermal, and quantum optical noise. Finally, Section 10 synthesizes the overall sensitivity frequency response and highlights future prospects in gravitational-wave astronomy.

2 The Physical Nature of Gravitational Waves

In the weak-field limit of General Relativity, the spacetime metric $g_{\mu\nu}$ can be decomposed into the flat Minkowski background $\eta_{\mu\nu} = \text{diag}(-1, 1, 1, 1)$ and a small metric perturbation $h_{\mu\nu}$ ($|h_{\mu\nu}| \ll 1$):

$$g_{\mu\nu} = \eta_{\mu\nu} + h_{\mu\nu}. \quad (1)$$

Imposing the Lorenz gauge condition $\partial^\mu \bar{h}_{\mu\nu} = 0$ (where $\bar{h}_{\mu\nu} = h_{\mu\nu} - \frac{1}{2}\eta_{\mu\nu}h$ is the trace-reversed metric perturbation), the vacuum Einstein field equations reduce in linearized theory to the wave equation:

$$\square \bar{h}_{\mu\nu} = \left(-\frac{1}{c^2} \frac{\partial^2}{\partial t^2} + \nabla^2 \right) \bar{h}_{\mu\nu} = 0. \quad (2)$$

In the transverse-traceless (TT) gauge, the perturbation tensor for a plane wave propagating along the $+z$ -direction can be expanded into two independent, orthogonal polarization states, denoted as “plus” (h_+) and “cross” ($h_\times$):

$$h_{\mu\nu}^{\text{TT}}(t, z) = \begin{pmatrix} 0 & 0 & 0 & 0 \\ 0 & h_+ & h_\times & 0 \\ 0 & h_\times & -h_+ & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix} \cos \left[\omega \left(t - \frac{z}{c} \right) \right]. \quad (3)$$

The physical effect of a gravitational wave manifests as tidal forces acting on freely falling test masses. Under the action of the h_+ polarization, the proper distance between test particles separated along the x -axis expands by an amount ΔL_x , while the distance between particles along the orthogonal y -axis simultaneously contracts by $\Delta L_y = -\Delta L_x$, alternating cyclically with the wave frequency. The dimensionless strain amplitude h characterizes this quadrupolar fractional length variation:

$$h \sim \frac{\Delta L}{L}. \quad (4)$$

For astrophysical sources situated at cosmological distances (such as the coalescence of stellar-mass binary black holes at hundreds of megaparsecs), the strain reaching Earth is on the order of:

$$h \sim 10^{-21}. \quad (5)$$

The historic milestone GW150914, detected on September 14, 2015 by the twin Advanced LIGO observatories, originated from the merger of two black holes of approximately $36 M_\odot$ and $29 M_\odot$, producing a peak strain of $h \approx 1.0 \times 10^{-21}$ and confirming Einstein’s century-old prediction.

3 Physical Principle of Interferometric Detection

The differential quadrupolar nature of gravitational-wave strain makes a two-arm, perpendicular laser interferometer (an adaptation of the Michelson interferometer) an optimal transducer.

Consider two orthogonal arms of unperturbed coordinate length $L_x = L_y = L$, oriented along the x - and y -axes. For a normally incident gravitational wave with plus polarization $h_+(t)$, the round-trip proper time interval for a photon in the x -arm satisfies:

$$ds^2 = 0 = -c^2 dt^2 + [1 + h_+(t)] dx^2 \implies c dt = \sqrt{1 + h_+(t)} dx \approx \left(1 + \frac{1}{2} h_+(t) \right) dx. \quad (6)$$




Figure 1: Spatial geometry of spacetime perturbations induced by a passing transverse-traceless gravitational wave. The quadrupolar deformation alternates between orthogonal axes over each wave period.




Figure 2: The quadrupolar strain effect of a gravitational wave on orthogonal interferometer test masses. When arm x is stretched, arm y is compressed, producing a differential optical phase shift.

Integrating for round-trip propagation over the arm yields a net differential round-trip time shift $\Delta\tau = \tau_x - \tau_y$ between the two arms:

$$\Delta\tau(t) \approx \frac{L}{c} h_+(t). \quad (7)$$

For monochromatic laser light of carrier frequency $\omega_0 = 2\pi c/\lambda_0$, this differential time delay produces an optical phase difference $\Delta\Phi_{\text{GW}}$ at the recombination beam splitter:

$$\Delta\Phi_{\text{GW}}(t) = \omega_0 \Delta\tau(t) = \frac{4\pi L}{\lambda_0} h(t). \quad (8)$$

Because the phase response scales linearly with the baseline length L , maximizing arm length is paramount to enhancing detector response. For Advanced LIGO, an arm length of $L = 4$ km was selected.

4 Real Detector Architecture and Optical Topology

While conceptually analogous to a simple Michelson interferometer, real-world observatories (LIGO, Virgo, KAGRA) incorporate sophisticated optical enhancement cavities to reach the requisite sub-nuclear displacement sensitivities.




Figure 3: Optical topology of an Advanced LIGO interferometer, illustrating the central beam splitter, 4-km Fabry–Pérot arm cavities, Power Recycling Mirror (PRM), and Signal Recycling Mirror (SRM).

1. **Fabry–Pérot Arm Cavities:** In place of simple end-mirrors, each 4-km arm is converted into a resonant Fabry–Pérot optical cavity. Photons bounce back and forth approximately

$N_{\text{bounce}} \approx 300$ times before exiting toward the beam splitter. This increases the effective optical baseline from 4 km to:

$$L_{\text{eff}} \approx \frac{2\mathcal{F}}{\pi} L \approx 1200 \text{ km}, \quad (9)$$

where $\mathcal{F} \approx 450$ is the optical finesse of the cavity, vastly magnifying the induced phase shift $\Delta\Phi$.

2. **Power Recycling Mirror (PRM):** The interferometer is operated near a dark fringe at the antisymmetric (readout) port, meaning nearly all input laser power is reflected back toward the laser source. A partially transmitting Power Recycling Mirror placed between the laser and the beam splitter forms a resonant cavity with the rest of the interferometer. This recycles the reflected carrier light, boosting the effective laser power circulating inside the 4-km arm cavities from ~ 50 W at the input to approximately ~ 800 kW.
3. **Signal Recycling Mirror (SRM):** Positioned at the dark output port, a Signal Recycling Mirror allows optical tuning of the detector's bandwidth and resonant frequency response to optimize sensitivity for specific astrophysical targets (e.g., binary neutron star inspirals).

5 Measurement Sensitivity and Experimental Challenges

To comprehend the engineering rigor involved, consider the physical displacement corresponding to an astrophysical strain of $h \sim 10^{-21}$ across a 4 km arm:

$$\Delta L = h \cdot L = (10^{-21}) \times (4 \times 10^3 \text{ m}) \approx 4 \times 10^{-18} \text{ m}. \quad (10)$$

This displacement is approximately **one-thousandth the charge radius of a proton** ($\sim 0.84 \times 10^{-15} \text{ m}$) and 10^{-8} times smaller than the Bohr radius of an atom.

Consequently, displacement noise from thermal fluctuations, seismic vibrations, optical quantum noise, or technical disturbances easily overwhelms the gravitational signal unless mitigated through exhaustive physical isolation and stabilization mechanisms. The overarching design objective of a gravitational-wave observatory is therefore to minimize the total equivalent displacement noise spectral density $S_h(f)$.

6 Terrestrial Seismic and Environmental Noise

Seismic noise dominates the detector noise budget at low frequencies ($f \lesssim 10 \text{ Hz}$). Earth's crust is in perpetual microseismic motion driven by ocean waves hitting coastlines (the microseismic peak around $0.1 - 0.3 \text{ Hz}$), seismic activity, wind, and anthropogenic disturbances (traffic, rail networks, industrial operations). Typical ground displacement spectral densities are $x_{\text{ground}}(f) \sim 10^{-7} \text{ m}/\sqrt{\text{Hz}}$ at 1 Hz, which is more than ten orders of magnitude larger than the target signal.

To decouple the test-mass mirrors from ground motion, Advanced LIGO employs a multi-tiered isolation strategy:

- **Active Pre-Isolation (HEPI & BSC-ISI):** High-precision seismometers and capacitive displacement sensors continuously measure ground vibrations. Feedback loops drive hydraulic and electromagnetic actuators to apply real-time counter-forces, attenuating low-frequency vibrations ($0.1 - 10 \text{ Hz}$) before they penetrate the internal stages.

- **Quadruple Pendulum Suspensions:** Each main test mass (a 40 kg fused silica optic) is suspended as the final stage of a four-stage monolithic pendulum chain. A simple pendulum acts as a second-order mechanical low-pass filter with transfer function $T(f) \propto (f_0/f)^2$ for frequencies well above resonance ($f \gg f_0 \sim 1$ Hz). A four-stage cascade suppresses horizontal seismic vibrations by a factor of:

$$|T(f)| \sim \left(\frac{f_0}{f}\right)^8 \sim 10^{-8} \quad \text{at 10 Hz,} \quad (11)$$

effectively rendering ambient seismic noise negligible above 15 Hz.

7 Thermal Brownian and Suspension Noise

In the mid-frequency band ($10 \text{ Hz} \lesssim f \lesssim 100 \text{ Hz}$), sensitivity is fundamentally constrained by thermal noise originating from the thermodynamic fluctuations of the test-mass mirrors, dielectric reflective coatings, and suspension fibers.

In accordance with the Callen–Welton **Fluctuation-Dissipation Theorem**, any physical system exhibiting mechanical energy dissipation (internal friction) necessarily experiences stochastic thermal fluctuations. The displacement noise power spectral density $S_x(f)$ of an internal mechanical mode of mass M and resonant frequency f_0 is given by:

$$S_x(f) = \frac{k_B T}{\pi^2 f M} \frac{f_0^2 \phi(f)}{[(f_0^2 - f^2)^2 + f_0^4 \phi^2(f)]}, \quad (12)$$

where k_B is Boltzmann’s constant, T is temperature, and $\phi(f)$ is the mechanical loss angle (inverse quality factor, $\phi = 1/Q$).

To mitigate thermal noise:

1. **Ultra-High-Q Monolithic Fused Silica:** Test masses are fabricated from ultra-pure synthetic fused silica ($M = 40$ kg) suspended by thin fused silica fibers welded directly to the mirrors. This eliminates metal clamp friction, yielding an exceptionally low loss angle ($\phi \sim 10^{-9}$), which confines thermal energy into extremely narrow resonance spikes outside the detection band.
2. **Low-Loss Dielectric Coatings:** The multi-layer dielectric optical coatings (Ta_2O_5 -doped $\text{TiO}_2/\text{SiO}_2$) represent the dominant contributor to Brownian thermal noise. Advanced doping techniques minimize structural mechanical loss in these thin films.
3. **Cryogenic Cooling (KAGRA & Next-Generation):** The Japanese KAGRA detector uses sapphire mirrors operating at cryogenic temperatures ($T \approx 20$ K). Third-generation facilities (Einstein Telescope, Cosmic Explorer) will similarly deploy cryogenics to suppress the $k_B T$ energy scale.

8 Quantum Optical Noise of Light

At frequencies above 100 Hz, the fundamental noise floor is set by the quantum nature of electromagnetic radiation, arising from zero-point vacuum fluctuations entering the open port of the beam splitter. Quantum noise manifests in two distinct phenomena:

1. **Photon Shot Noise (High Frequencies):** Originates from Poissonian statistical fluctuations in the photon arrival rate at the photodetector. The resulting phase uncertainty translates into an equivalent strain noise:

$$h_{\text{shot}}(f) \propto \frac{1}{L} \sqrt{\frac{\hbar c \lambda_0}{P_{\text{arm}}}}, \quad (13)$$

which is frequency-independent within the cavity bandwidth and scales inversely with the square root of the intracavity circulating optical power P_{arm} .

2. **Radiation Pressure Noise (Low Frequencies):** When laser photons reflect off the test-mass mirrors, they impart momentum ($\Delta p = 2\hbar k$ per photon). Quantum fluctuations in the photon count between the two arms generate differential force fluctuations, physically driving the suspended mirrors:

$$h_{\text{rad}}(f) \propto \frac{1}{M f^2 L} \sqrt{\frac{\hbar P_{\text{arm}}}{c \lambda_0}}. \quad (14)$$




Figure 4: Representative sensitivity curve and fundamental noise budget of Advanced LIGO. The total noise floor reflects the envelope of seismic, thermal suspension, coating Brownian, and quantum optical noise.

Notice the reciprocal dependence on laser power: increasing optical power P_{arm} decreases shot noise but exacerbates radiation pressure noise. The optimal trade-off point defines the **Standard Quantum Limit (SQL)**, a direct consequence of the Heisenberg Uncertainty Principle:

$$h_{\text{SQL}}(f) = \sqrt{\frac{8\hbar}{\pi M (2\pi f)^2 L^2}}. \quad (15)$$

8.1 Quantum Noise Mitigation via Squeezed Vacuum Injection

Modern observatories circumvent the SQL by injecting **frequency-dependent squeezed vacuum states** into the dark port. By utilizing non-linear optical parametric oscillators (OPOs) and 300-meter detuned optical filter cavities, the Heisenberg uncertainty ellipse is rotated as a function of frequency: phase uncertainty is squeezed at high frequencies ($f > 100$ Hz to suppress shot noise), while amplitude uncertainty is squeezed at low frequencies ($f < 50$ Hz to suppress radiation pressure noise).

9 Technical and Environmental Noise Coupling

Beyond fundamental physics limits, subtle environmental and technical couplings must be systematically rejected:

- **Residual Gas Scattering:** Even minute traces of residual gas in the beam tubes cause optical phase noise and beam scattering. LIGO operates under Ultra-High Vacuum (UHV) conditions ($P \sim 10^{-9}$ torr or 10^{-7} Pa), constituting the second largest vacuum enclosure by volume on Earth.
- **Newtonian Gravity Gradient Noise:** Inelastic seismic waves and atmospheric density fluctuations directly alter the local gravitational potential near the test masses. Because gravity cannot be shielded, this represents a hard floor below 10 Hz for surface detectors.
- **Environmental Monitoring Networks:** Hundreds of physical monitoring channels (triaxial seismometers, magnetometers, tiltmeters, cosmic-ray detectors, and microphones) monitor the facility to identify and veto non-astrophysical transient glitches. Coincident detection across widely separated observatories (LIGO Hanford, LIGO Livingston, Virgo in Italy, KAGRA in Japan) ensures statistical confidence.

10 Summary and Outlook

The direct observation of gravitational radiation constitutes a triumph of modern theoretical and experimental physics, synthesizing General Relativity, advanced quantum optics, ultra-low-loss materials science, and active control systems. As demonstrated in this study:

- Terrestrial interferometry achieves displacement sensitivities on the order of $\sim 10^{-18}$ m/ $\sqrt{\text{Hz}}$ at target frequencies of 100 Hz.
- Detector performance is bounded by a partitioned frequency landscape: seismic and gravity gradient noise at $f < 10$ Hz, coating Brownian and suspension thermal noise at $10 \text{ Hz} < f < 100 \text{ Hz}$, and quantum optical noise at $f > 100 \text{ Hz}$.
- The implementation of squeezed light injection and monolithic fused silica suspensions allows terrestrial detectors to routinely surpass the Standard Quantum Limit.

Looking ahead, next-generation facilities including the ground-based **Einstein Telescope** (a European underground cryogenic triangle with 10-km arms) and **Cosmic Explorer** (a 40-km facility in the United States), alongside space-borne interferometers such as the **Laser Interferometer Space Antenna (LISA)** will extend the observational window down to millihertz frequencies, probing supermassive black hole mergers across cosmic history and testing General Relativity to unprecedented precision.

References

- [1] B. P. Abbott *et al.* (LIGO Scientific Collaboration and Virgo Collaboration), “Observation of Gravitational Waves from a Binary Black Hole Merger,” *Phys. Rev. Lett.*, vol. 116, no. 6, p. 061102, 2016.
- [2] J. Aasi *et al.* (LIGO Scientific Collaboration), “Advanced LIGO,” *Class. Quantum Grav.*, vol. 32, no. 7, p. 074001, 2015.
- [3] P. R. Saulson, *Fundamentals of Interferometric Gravitational Wave Detectors*, World Scientific, Singapore, 1994.

- [4] C. M. Caves, “Quantum-mechanical noise in an interferometer,” *Phys. Rev. D*, vol. 23, no. 8, pp. 1693–1708, 1981.
- [5] G. M. Harry (for the LIGO Scientific Collaboration), “Advanced LIGO: the next generation of graviton wave detectors,” *Class. Quantum Grav.*, vol. 27, no. 8, p. 084006, 2010.
- [6] M. Tse *et al.*, “Quantum-Enhanced Advanced LIGO Detectors in the Era of Gravitational-Wave Astronomy,” *Phys. Rev. Lett.*, vol. 123, no. 23, p. 231107, 2019.