

# Operator overloading: comparison

OBJECT-ORIENTED PROGRAMMING IN PYTHON



**Alex Yarosh**  
Content Quality Analyst @ DataCamp



# Object equality

```
class Customer:
    def __init__(self, name, balance):
        self.name, self.balance = name, balance

customer1 = Customer("Maryam Azar", 3000)
customer2 = Customer("Maryam Azar", 3000)
customer1 == customer2
```

False

# Object equality

```
class Customer:
    def __init__(self, name, balance, id):
        self.name, self.balance = name, balance
        self.id = id

customer1 = Customer("Maryam Azar", 3000, 123)
customer2 = Customer("Maryam Azar", 3000, 123)
customer1 == customer2
```

False

# Variables are references

```
customer1 = Customer("Maryam Azar", 3000, 123)  
customer2 = Customer("Maryam Azar", 3000, 123)
```

```
print(customer1)
```

```
<__main__.Customer at 0x1f8598e2e48>
```

```
print(customer2)
```

```
<__main__.Customer at 0x1f8598e2240>
```

# Custom comparison

```
import numpy as np

# Two different arrays containing the same data
array1 = np.array([1,2,3])
array2 = np.array([1,2,3])

array1 == array2
```

True

# Overloading `__eq__()`

```
class Customer:
    def __init__(self, id, name):
        self.id, self.name = id, name
    # Will be called when == is used
    def __eq__(self, other):
        # Diagnostic printout
        print("__eq__() is called")

        # Returns True if all attributes match
        return (self.id == other.id) and \
            (self.name == other.name)
```

- `__eq__()` is called when 2 objects of a class are compared using `==`
- accepts 2 arguments, `self` and `other` - objects to compare
- returns a Boolean

# Comparison of objects

# Two equal objects

```
customer1 = Customer(123, "Maryam Azar")  
customer2 = Customer(123, "Maryam Azar")  
  
customer1 == customer2
```

`--eq__()` is called  
True

# Two unequal objects - different ids

```
customer1 = Customer(123, "Maryam Azar")  
customer2 = Customer(456, "Maryam Azar")  
  
customer1 == customer2
```

`--eq__()` is called  
False

# Other comparison operators

Operator	Method
<code>==</code>	<code>__eq__()</code>
<code>!=</code>	<code>__ne__()</code>
<code>&gt;=</code>	<code>__ge__()</code>
<code>&lt;=</code>	<code>__le__()</code>
<code>&gt;</code>	<code>__gt__()</code>
<code>&lt;</code>	<code>__lt__()</code>

- `__hash__()` to use objects as dictionary keys and in sets



# Let's practice!

## OBJECT-ORIENTED PROGRAMMING IN PYTHON



# Operator overloading: string representation

OBJECT-ORIENTED PROGRAMMING IN PYTHON



**Alex Yarosh**  
Content Quality Analyst @ DataCamp



# Printing an object

```
class Customer:
    def __init__(self, name, balance):
        self.name, self.balance = name, balance

cust = Customer("Maryam Azar", 3000)
print(cust)
```

```
<__main__.Customer at 0x1f8598e2240>
```

```
import numpy as np

arr = np.array([1,2,3])
print(arr)
```

```
[1 2 3]
```

`__str__()`

- `print(obj)`, `str(obj)`

`print(np.array([1, 2, 3]))``[1 2 3]``str(np.array([1, 2, 3]))``[1 2 3]`

- informal, for end user
- **string** representation

`__repr__()`

- `repr(obj)`, printing in console

`repr(np.array([1, 2, 3]))``array([1, 2, 3])``np.array([1, 2, 3])``array([1, 2, 3])`

- formal, for developer
- **reproducible representation**
- fallback for `print()`

# Implementation: str

```
class Customer:
    def __init__(self, name, balance):
        self.name, self.balance = name, balance

    def __str__(self):
        cust_str = """
        Customer:
            name: {name}
            balance: {balance}
        """.format(name = self.name, \
                    balance = self.balance)
        return cust_str
```

```
cust = Customer("Maryam Azar", 3000)

# Will implicitly call __str__()
print(cust)
```

```
Customer:
name: Maryam Azar
balance: 3000
```

# Implementation: repr

```
class Customer:
    def __init__(self, name, balance):
        self.name, self.balance = name, balance

    def __repr__(self):
        # Notice the '...' around name
        return "Customer('{name}', {balance})".format(name = self.name, balance = self.balance)

cust = Customer("Maryam Azar", 3000)
cust # <--- # Will implicitly call __repr__()
```

```
Customer('Maryam Azar', 3000) # <--- not Customer(Maryam Azar, 3000)
```

- Surround string arguments with quotation marks in the `__repr__()` output

# Let's practice!

## OBJECT-ORIENTED PROGRAMMING IN PYTHON



# Exceptions

## OBJECT-ORIENTED PROGRAMMING IN PYTHON



**Alex Yarosh**  
Content Quality Analyst @ DataCamp





```
a = 1
a / 0
```

```
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    1/0
ZeroDivisionError: division by zero
```

```
a = 1
a + "Hello"
```

```
Traceback (most recent call last):
  File "<stdin>", line 2, in <module>
    a + "Hello"
TypeError: unsupported operand type(s) for +: /
'int' and 'str'
```

```
a = [1,2,3]
a[5]
```

```
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    a[5]
IndexError: list index out of range
```

```
a = 1
a + b
```

```
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    a + b
NameError: name 'b' is not defined
```

# Exception handling

- Prevent the program from terminating when an exception is raised
- `try` - `except` - `finally` :

```
try:
    # Try running some code
except ExceptionNameHere:
    # Run this code if ExceptionNameHere happens
except AnotherExceptionHere:    #<-- multiple except blocks
    # Run this code if AnotherExceptionHere happens
...
finally:
    # Run this code no matter what
    #<-- optional
```

# Raising exceptions

- `raise ExceptionNameHere('Error message here')`

```
def make_list_of_ones(length):  
    if length <= 0:  
        raise ValueError("Invalid length!") # <--- Will stop the program and raise an error  
    return [1]*length
```

```
make_list_of_ones(-1)
```

```
Traceback (most recent call last):  
  File "<stdin>", line 1, in <module>  
    make_list_of_ones(-1)  
  File "<stdin>", line 3, in make_list_of_ones  
    raise ValueError("Invalid length!")  
ValueError: Invalid length!
```

# Exceptions are classes

- standard exceptions are inherited from `BaseException` or `Exception`

```
BaseException
+-- Exception
    +-- ArithmeticError
    |
    +-- FloatingPointError
    |
    +-- OverflowError
    |
    +-- ZeroDivisionError
    |
    +-- TypeError
    +-- ValueError
    |
    +-- UnicodeError
    |
    |   +-- UnicodeDecodeError
    |   +-- UnicodeEncodeError
    |   +-- UnicodeTranslateError
    +-- RuntimeError
    ...
+-- SystemExit
...
```

<sup>1</sup> <https://docs.python.org/3/library/exceptions.html>

# Custom exceptions

- Inherit from `Exception` or one of its subclasses
- Usually an empty class

```
class BalanceError(Exception): pass
```

```
class Customer:  
    def __init__(self, name, balance):  
        if balance < 0 :  
            raise BalanceError("Balance has to be non-negative!")  
        else:  
            self.name, self.balance = name, balance
```

```
cust = Customer("Larry Torres", -100)
```

Traceback (most recent call last):

File "script.py", line 11, in <module>

    cust = Customer("Larry Torres", -100)

File "script.py", line 6, in \_\_init\_\_

    raise ValueError("Balance has to be non-negative!")

ValueError: Balance has to be non-negative!

- Exception interrupted the constructor → object not created

```
cust
```

Traceback (most recent call last):

File "<stdin>", line 1, in <module>

    cust

NameError: name 'cust' is not defined



# Catching custom exceptions

```
try:
    cust = Customer("Larry Torres", -100)
except BalanceError:
    cust = Customer("Larry Torres", 0)
```

# Let's practice!

## OBJECT-ORIENTED PROGRAMMING IN PYTHON





