

EXPERIMENT – 01

DDL Commands – CREATE, ALTER, DROP

CREATE:

```
mysql> CREATE DATABASE dbms_lab;
Query OK, 1 row affected (0.03 sec)

mysql> USE dbms_lab;
Database changed
mysql> create table student(Regno int(3), Name char(15), gender char(1), Dob int(10), mobileno int(10), city char(10));
Query OK, 0 rows affected, 3 warnings (0.05 sec)

mysql> desc student;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Regno | int  | YES  |     | NULL    |       |
| Name  | char(15) | YES  |     | NULL    |       |
| gender | char(1) | YES  |     | NULL    |       |
| Dob   | int   | YES  |     | NULL    |       |
| mobileno | int   | YES  |     | NULL    |       |
| city  | char(10) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)

mysql>
mysql> create table faculty(Facno int(3), FacName char(15), gender char(1), Dob int(10), mobileno int(10), DOJ int(10));
Query OK, 0 rows affected, 4 warnings (0.02 sec)
```

```
mysql>
mysql> create table course(courseno int(3), coursedesc char(15), coursetype char(1), semno int(10), hallno int(10), Facno int(10));
Query OK, 0 rows affected, 4 warnings (0.02 sec)

mysql> desc course;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| courseno | int | YES |     | NULL |       |
| coursedesc | char(15) | YES |     | NULL |       |
| coursetype | char(1) | YES |     | NULL |       |
| semno | int | YES |     | NULL |       |
| hallno | int | YES |     | NULL |       |
| Facno | int | YES |     | NULL |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

RENAME & TRUNCATE

ALTER AND DROP:

```
mysql>
mysql> alter table faculty add dept char(10);
Query OK, 0 rows affected (0.06 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc faculty;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Facno | int  | YES  |     | NULL    |       |
| FacName | char(15) | YES  |     | NULL    |       |
| gender | char(1) | YES  |     | NULL    |       |
| Dob    | int    | YES  |     | NULL    |       |
| mobileno | int    | YES  |     | NULL    |       |
| DOJ    | int    | YES  |     | NULL    |       |
| dept   | char(10) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)

mysql> -- DROP COLUMN (drop the 'dept' column you just added to faculty)
mysql> alter table faculty drop column dept;
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc faculty;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Facno | int  | YES  |     | NULL    |       |
| FacName | char(15) | YES  |     | NULL    |       |
| gender | char(1) | YES  |     | NULL    |       |
| Dob    | int    | YES  |     | NULL    |       |
| mobileno | int    | YES  |     | NULL    |       |
| DOJ    | int    | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

RENAME & TRUNCATE

```
mysql>
mysql> -- RENAME TABLE
mysql> rename table department to dept;
Query OK, 0 rows affected (0.02 sec)

mysql> desc dept;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| deptno | int | YES | | NULL | |
| deptname | char(10) | YES | | NULL | |
| depthead | char(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql>
mysql> -- rename it back, if you want to keep using 'department' later
mysql> rename table dept to department;
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> -- TRUNCATE TABLE (removes all rows, keeps structure - table is empty right now, but this is the command to know)
mysql> truncate table student;
Query OK, 0 rows affected (0.02 sec)

mysql> desc student;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Regno | int | YES | | NULL | |
| Name | char(15) | YES | | NULL | |
| gender | char(1) | YES | | NULL | |
| Dob | int | YES | | NULL | |
| mobileno | int | YES | | NULL | |
| city | char(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```