

---


# Joint 3D object recognition and tracking with OpenCV

---

M.Zucchelli R.Orizio M.Rizzini

---

# Scheme



# OpenCV Functions

---

## ● Object Recognition/Database construction

- Feature Detection: `FeatureDetector::create( "SIFT" )` `FeatureDetector::detect`
- Feature Description: `DescriptorExtractor::create( "SIFT" )`,  
`DescriptorExtractor::compute`
- Database Indexing: `flann::Index_<T>::Index_`, `flann::KDTTreeIndexParams;`
- Database Matching: `flann::Index_<T>::knnSearch`
- Homography Estimation: `findHomography(....., CV_RANSAC, ...)`

## ● Object Tracking

- Feature Detection: `FeatureDetector::create( "GFTT" )`, `FeatureDetector::detect`
  - Feature Tracking (KLT Tracker): `calcOpticalFlowPyrLK`
-

# Tips/Details

---

- **Recognition:** Do recognition every  $N$  frames, and tracking in-between (e.g.  $N = 20$ )
  - **Tracking:** Once you found the object, track only the "relevant" GFTT features (i.e. on the object!)
  - **Good labels:** Define (manually) the labels, well spread on the whole object (front, back, side)
  - **Label update:** Don't track the pixel correspondent to the labels, they could be unstable features (on non-textured area). Update label positions using the 2D motion estimated on the GFTT features (use only the nearest to the label?)
  - **Use an object which is rigid and has some texture/detail on it!**
-