Dynamic Routing Protocols

Properties \ Routing Protocol	RIP	OSPF	EIGRP
1-open Standard or Cisco	Open standard	Open standard	Cisco Protocol
2-DV or LS	Distance Vector	Link state	Advanced D.V
3-AD Value	120	110	90
4-Metric	hop count	10^8 / BW(bps)	Equation at BW , Delay
5-Max hop Count	15	unlimited	100
6-Updating Address	V1 (255.255.255.255) V2 (224.0.0.9)	224.0.0.5	224.0.0.10
7-Classfull/Classless	v1(Classfull) v2(Classless)	Classless	Classless
8-Load Sharing	Equal Load Sharing	Equal Load Sharing	Equal and None Equal LS
9-Symbol of it at RT	R	O , OIA , OE	D, DEX
10-Configuration	R1(config)#router rip R1(config-router)#Version 2 R1(config-router)#no auto-summary R1(config-router)#network 192.168.1.0 R1(config-router)#network 192.168.10.0	R1(config)#router ospf 1 R1(config-router)#router-id 1.1.1.1 R1(config-router)#network 192.168.1.0 0.0.0.255 area 0	R1(config)#router eigrp 1 R1(config-router)#no auto-summary R1(config-router)#network 192.168.1.0 0.0.0.255