MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION

Product name :RF-P2

Name of company :Hitachi Industrial Equipment Systems Co., Ltd

Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan

Tel :+81-294-36-8682 Fax :+81-294-36-8975

Recommended use of the chemical

and restrictions on use :Printing Ink for industrial Marking

2 HAZARDS IDENTIFICATION

Physico-chemical endpoints :Flammable liquid Category 2

Acute toxicity - oral :Category 5 Acute toxicity - dermal :Not identified Acute toxicity - inhalation(air) :Not identified Acute toxicity - inhalation (vapors) :Not available Acute toxicity - inhalation (dust, mist) :Not identified Skin corrosion/irritation :Not identified Eye damage/irritation :Category 2 Sensitization - respiratory :Not identified Sensitization - skin :Not identified Germ cell mutagenicity :Category 1 Carcinogenicity :Not identified Toxic to reproduction :Category 1 Effects on or via lactation :Not identified

Specific target organ systemic toxicity

(Single exposure) :Category 1 (Repeated exposure) :Category 1 Aspiration toxicity :Not identified

Hazardous to the aquatic environment

-Acute hazard :Not identified -Chronic hazard :Not identified

GHS label elements

Hazard symbols:Flame, Exclamation mark, Health hazard







Signal word: Danger

Hazard statement and precautionary statement:

- · Highly flammable liquid and vapour
- May be harmful if swallowed
- Causes eye irritation
- May cause bad effect to genetic or fetus
- May damage fertility or the unborn child
- Causes damage to organs-single exposure
- Causes damage to organs through prolonged or repeated exposure

Precautionary statements:

 Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response

- In case of fire, use dry chemical, CO₂, water splay (fog) or form for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

Storage

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

Disposal

Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition;

Chemical nameconcentration (%)CAS numberMethanol50-6067-56-1Ethanol1-564-17-5

4 First-aid measures

Inhalation;

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the neatest medial facility for examination and treatment by a physician as soon as possible.

Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as son as possible.

Eve contact:

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible, and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medial attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water splay (fog) or form.

Fire fighting procedures:

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20) place. Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines;

ACGIH TLV-TWA (ppm)

Methanol :200(skin) Ethanol :1000

ACGIH STEL(ppm)

Methanol :250(skin) Ethanol :No data

9 Physical and chemical properties

Appearance

Upper/lower flammability or explosive limits :Lower 5.5 vol%,Upper 44 vol% (methanol)

Vapor pressure :12.3kPa (20) (methanol)

Relative density (Air = 1) :2.1 (methanol) Relative density :0.89(20)

Solubility (Water) :water;infinite(methanol)

Partition coefficient: n-octanol/water :Log Pow=-0.82/-0.66(methanol)

Auto-ignition temperature :464 (methanol)

Decomposition temperature :No measurement

10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

Acute toxicity;

Methanol

Category 5:Oral 6200(Rat LD50(mg/kg))

Not available: Dermal 15800(RabbitLD50(mg/kg))

Not available:Inhalation >22500(Rat LC50(ppm/8H))

Ethanol

Not available:Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))

Not identified: Dermal No data

Not available:Inhalation 31600 (Vaper) (Rat LC50(ppm/4h))

Skin corrosion/irritation;

Methanol

Not identified

Ethanol

Not identified

Serious eye damage/irritation;

Methanol

Category 2A

Ethanol

Category 2A

Respiratory or skin sensitization;

Methanol

Not identified

Ethanol

Not identified

Germ cell mutagenicity;

Methanol

Not available

Ethanol

Category 1B

Carcinogenicity;

Methanol

Not identified

Ethanol

Not available Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))

Reproductive toxicity;

Methanol

Not identified

Ethanol

Category 1A

STOST-single exposure;

Methanol

Category 1(Central nervous system, Sensory system, systemic toxicity)

Ethanol

Category 3(Respiratory)

STOST-repeated exposure;

Methanol

Category 1(Central nervous system, sensory system)

Ethanol

Category 1(Liver) 2(Nervous system)

Aspiration hazard.

Methanol

Not identified

Ethanol

Not identified

12 Ecological information

Toxicity:

Methanol

brine shrimp 24h-LC50(mg/L):900.73

Ethanol

trout 24h-LC50 (g/L):11.2 Carp 96h-LC50 (g/L):18 ~ 13.4 Creek Chub 24h-C50(g/L):7 Guppy 7d-LC50(g/L):11

Persistence and degradability:

Methanol None known Ethanol

None known

Bioaccumulative potential:

Methanol None known Ethanol None known

Mobility in soil:

Methanol
None known
Ethanol
None known

13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.

Do not dump into sewer, on the ground or into any body of water.

Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number :1210

UN Proper Shipping Name :Printing ink, flammable Transport hazard class :Class 3(Flammable liquid)

Packing Group : Environmental hazards :No

15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

16 References

- Solvent, dye MSDS
- Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards