

# MATERIAL SAFETY DATA SHEET

## 1 IDENTIFICATION

Product name :JP-K72  
Name of company :Hitachi Industrial Equipment Systems Co., Ltd  
Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan  
Tel :+81-294-36-8682  
Fax :+81-294-36-8975  
Recommended use of the chemical  
and restrictions on use :Printing Ink for industrial Marking

## 2 HAZARDS IDENTIFICATION

Physico-chemical endpoints	:Flammable liquid Category 2
Acute toxicity - oral	:Category 5
Acute toxicity - dermal	:Not available
Acute toxicity - inhalation (air)	:Not identified
Acute toxicity - inhalation (vapors)	:Caegory 5
Acute toxicity - inhalation (dust, mist)	:Not identified
Skin corrosion/irritation	:Category 2
Eye damage/irritation	:Category 2
Sensitization - respiratory	:Not identified
Sensitization - skin	:Not identified
Germ cell mutagenicity	:Not available
Carcinogenicity	:Not available
Toxic to reproduction	:Not available
Effects on or via lactation	:Not identified
Specific target organ systemic toxicity (Single exposure)	:Category 1 Central nervous system :Category 2 Kidney :Category 3 Airway irritant
(Repeated exposure)	:Category 1 Central nervous system :Category 1 Peripheral nervous system
Aspiration toxicity	:Category 2
Hazardous to the aquatic environment	
-Acute hazard	:Not available
-Chronic hazard	:Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**GHS label elements**

Hazard symbols: Flame, Exclamation mark, Health hazard



**Signal word:** Danger

**Hazard statement and precautionary statement:**

- Highly flammable liquid and vapour
- May be harmful if swallowed
- May be harmful if inhaled
- Causes skin irritation
- Causes eye irritation
- Causes damage to central nervous system-single exposure
- May cause damage to kidney-single exposure
- May cause damage to airway irritant-single exposure
- Causes damage to central nervous system and peripheral nervous system through prolonged or repeated exposure
- May be harmful if swallowed and enters airways

**Precautionary statements:**

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

**Prevention**

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

**Response**

- In case of fire, use dry chemical, CO<sub>2</sub>, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Storage**

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

**Disposal**

- Waste must be disposed of according to applicable regulations.

### 3 Composition/information on ingredients

**Substance or mixture;** mixture

**Composition;**

Chemical name	concentration (%)	CAS number
2-butanone	80-90	78-93-3
Chrome -Complex Dye	1-10	TSCA Registered

### 4 First-aid measures

**Inhalation;**

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

**Skin contact;**

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

**Eye contact;**

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

**Ingestion;**

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

### 5 Fire-fighting measures

**Suitable extinguishing media;**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Fire fighting procedures;**

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

**Unusual fire/explosion hazard;**

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

**Special protective equipment and precautions for fire fighters;**

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## 6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

## 7 Handling and storage

### Handling;

Use only in the well-ventilated areas.  
Make available in the work area emergency shower and eyes wash.  
Avoid contact with skin or eyes.

### Storage;

Close up the container and keep it in dark cool(0~20 ) place.  
Keep away from combustible materials and sources of ignition.

## 8 Exposure controls/personal protection

### Exposure guidelines;

ACGIH TLV-TWA (ppm)	
2-butanone	:200
Chrome -Complex Dye	:None known
ACGIH STEL(ppm)	
2-butanone	:300
Chrome -Complex Dye	:None known

## 9 Physical and chemical properties

Appearance	
Physical state	:Liquid
Color	:black
Odor	:Solvent odor
Boiling point	:80 (2-butanone)
Flash point	:-7.6 (closed cup)
Upper/lower flammability or explosive limits	:Lower 1.8 vol%, Upper 11.5 vol% (2-butanone)
Vapor pressure	:10.5kPa (20 ) (2-butanone)
Relative density (Air = 1)	:2.41 (2-butanone)
Relative density	:0.85(20 )
Solubility (Water)	:29g/100mL (20 )(2-butanone)
Partition coefficient: n-octanol/water	:0.29 (2-butanone)
Auto-ignition temperature	:505 (2-butanone)
Decomposition temperature	:No measurement

## 10 Stability and reactivity

Stability: The product is stable.  
Conditions and materials to avoid: Not available  
Hazardous decomposition products: These products are carbon oxides

## 11 Toxicological information

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Acute toxicity;**

2-butanone

Category 5:Oral 5520(Rat LD50 (mg/kg))

Not available:Dermal &gt; 8000(Rabbit LD50 (mg/kg))

Category 5:Inhalation 11700 (Vaper) (Rat LC50(ppm/4h))

Chrome -Complex Dye

Oral &gt;5000 (Rat LD50 (mg/kg) )

Dermal &gt;2000 (Rat LD50 (mg/kg) )

Inhalation None known

**Skin corrosion/irritation;**

2-butanone

Category 2:Frequent/prolonged contact may irritate and cause dermatitis. Low order of toxicity.

Chrome -Complex Dye

No (Rabbit test-OECD404 1981)

**Serious eye damage/irritation;**

2-butanone

Category 2B:Eye contact:severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

Chrome -Complex Dye

No (Rabbit test-84/449/EEC B.5)

**Respiratory or skin sensitization;**

2-butanone

Not identified

Chrome -Complex Dye

No (Guinea pig test-84/449/EC B.6)

**Germ cell mutagenicity;**

2-butanone

Not available

Chrome -Complex Dye

Not identified

**Carcinogenicity;**

2-butanone

Not available

Chrome -Complex Dye

Not identified

**Reproductive toxicity;**

2-butanone

Not available

Chrome -Complex Dye

Not identified

**STOST-single exposure;**

2-butanone

Category 1(Central nervous system),Category 2(Kidney),Category 3(Respiratory)

Chrome -Complex Dye

Not identified

**STOST-repeated exposure;**

2-butanone

Category 1(Central nervous system,Peripheral nervous system)

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Chrome -Complex Dye  
None known

**Aspiration hazard.**

2-butanone  
Category 1 Vapor concentrations above exposure  
Chrome -Complex Dye  
None known

## 12 Ecological information

**Toxicity:**

2-butanone  
killifish 96h-LC50(mg/L):>100  
killifish 14d-LC50 (mg/L):100  
killifish 14d-NOEC (mg/L):100  
Chrome -Complex Dye  
Carp LC50(mg/L):2  
Daphnia EC50(mg/L):1000(Darp.Mag Straus 1820 test)

**Persistence and degradability:**

2-butanone  
None known  
Chrome -Complex Dye  
None known

**Bioaccumulative potential:**

2-butanone  
None known  
Chrome -Complex Dye  
None known

**Mobility in soil:**

2-butanone  
None known  
Chrome -Complex Dye  
None known

## 13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.  
Do not dump into sewer, on the ground or into any body of water.  
Follow national and local regulations.

## 14 Transport information

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	:
Environmental hazards	:No

## 15 Regulatory information

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

## 16 References

- 1) Solvent, dye MSDS
- 2) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.