

MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION

Product name :TH-73
 Name of company :Hitachi Industrial Equipment Systems Co., Ltd
 Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan
 Tel :+81-294-36-8682
 Fax :+81-294-36-8975
 Recommended use of the chemical
 and restrictions on use :Printing Ink for industrial Marking


2 HAZARDS IDENTIFICATION

Classification of the substance or mixture :mixture
 Physico-chemical endpoints :Flammable liquid category 2
 Acute toxicity - oral :Category 5
 Acute toxicity - dermal :Not available
 Acute toxicity - inhalation (vapors) :Category 5
 Acute toxicity - inhalation (dust, mist) :Not available
 Skin corrosion/irritation :Category 2
 Eye damage/irritation :Category 2
 Sensitization - respiratory :Not identified
 Sensitization - skin :Not identified
 Germ cell mutagenicity :Not identified
 Carcinogenicity :Not available
 Toxic to reproduction :Category 1
 Effects on or via lactation :Not identified
 Specific target organ systemic toxicity
 (Single exposure) :Category 1 Sensory system
 :Category 1 Systemic toxicity
 :Category 1 Central nervous system
 :Category 2 Kidney
 :Category 3 Respiratory system
 (Repeated exposure) :Category 1 liver
 :Category 1 Sensory system, organum auditus
 :Category 1 Central nervous system, peripheral nervous
 system
 Aspiration toxicity :Category 2
 Hazardous to the aquatic environment
 -Acute hazard :Not available
 -Chronic hazard :Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

GHS label elements

Hazard symbols: Flame, Exclamation mark, Health hazard



Signal word: Danger

Hazard statement and precautionary statement:

- Highly flammable liquid and vapour
- May be harmful if swallowed
- May be harmful if inhaled
- Causes skin irritation
- Causes eye irritation
- May damage fertility or the unborn child
- Causes damage to Sensory system, systemic toxicity and central nervous system-single exposure
- May cause damage to kidney-single exposure
- May cause respiratory irritation-single exposure
- Causes damage to liver, central nervous system, organum auditus, sensory system and peripheral nervous system through prolonged or repeated exposure.

Precautionary statements:

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response

- In case of fire, use dry chemical, CO₂, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

Storage

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

Disposal

- Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition;

Chemical name	concentration (%)	CAS number
2-butanone	80-90	78-93-3
Ethanol	15-25	64-17-5
Methanol	10-20	67-56-1
1-butanol	1-3	71-36-3

4 First-aid measures

Inhalation;

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water spray (fog) or foam.

Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20) place.

Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines;

ACGIH TLV-TWA (ppm)

2-butanone :200

Ethanol :1000

Methanol :200(skin)

1-butanol :20(skin)

ACGIH STEL(ppm)

2-butanone :300

Ethanol :No data

Methanol :250(skin)

1-butanol :None known

9 Physical and chemical properties

Appearance

Physical state :Liquid

Color :Clear

Odor :Solvent odor

Boiling point :80 (2-butanone)

Flash point :−4 (closed cup)

Upper/lower flammability or explosive limits :Lower 1.8 vol%, Upper 11.5 vol% (2-butanone)

Vapor pressure :10.5kPa (20) (2-butanone)

Relative density (Air = 1) :2.41 (2-butanone)

Relative density :0.805 (20)

Solubility (Water) :29g/100mL (20)(2-butanone)

Partition coefficient: n-octanol/water :0.29 (2-butanone)

Auto-ignition temperature :505 (2-butanone)

Decomposition temperature :No measurement

10 Stability and reactivity

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

Acute toxicity;

2-butanone

Category 5:Oral 5520(Rat LD50 (mg/kg))

Not available:Dermal > 8000(Rabbit LD50 (mg/kg))

Category 5:Inhalation 11700 (Vaper) (Rat LC50(ppm/4h))

Ethanol

Not available:Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))

Not identified:Dermal No data

Not available:Inhalation 31600 (Vaper) (Rat LC50(ppm/4h))

Methanol

Category 5:Oral 6200(Rat LD50(mg/kg))

Not available:Dermal 15800(RabbitLD50(mg/kg))

Not available:Inhalation >22500(Rat LC50(ppm/8H))

1-butanol

Category 4:Oral 790(Rat LD50(mg/kg))

Category 5:Deraml 3402(Rabbit LD50 mg/kg))

Not available:Inhalation

Skin corrosion/irritation;

2-butanone

Category 2:Frequent/prolonged contact may irritate and cause dermatitis. Low order of toxicity.

Ethanol

Not identified

Methanol

Not identified

1-butanol

Category 2

Serious eye damage/irritation;

2-butanone

Category 2B:Eye contact:severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

Ethanol

Category 2A

Methanol

Category 2A

1-butanol

Category2

Respiratory or skin sensitization;

2-butanone

Not identified

Ethanol

Not identified

Methanol

Not identified

1-butanol

Not identified

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Germ cell mutagenicity;

2-butanone
Not available
Ethanol
Category 1B
Methanol
Not available
1-butanol
Not available

Carcinogenicity;

2-butanone
Not available
Ethanol
Not available Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))
Methanol
Not identified
1-butanol
Not available

Reproductive toxicity;

2-butanone
Not available
Ethanol
Category 1A
Methanol
Not identified
1-butanol
Not available

STOST-single exposure;

2-butanone
Category 1(Central nervous system),Category 2(Kidney),Category 3(Respiratory)
Ethanol
Category 3(Respiratory)
Methanol
Category 1(Central nervous system,Sensory system,systemic toxicity)
1-butanol
Category 3(inhalation, anesthetic action)

STOST-repeated exposure;

2-butanone
Category 1(Central nervous system,Peripheral nervous system)
Ethanol
Category 1(Liver) 2(Nervous system)
Methanol
Category 1(Central nervous system,sensory system)
1-butanol
Category 1(central nervous system, organum auditus)

Aspiration hazard.

2-butanone
Category 1 Vapor concentrations above exposure
Ethanol
Not identified
Methanol

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Not identified
1-butanol
Category 2

LD50 (50% Lethal Dose)、LC50 (50% Lethal Concentration)

12 Ecological information

Toxicity:

2-butanone
killifish 96h-LC50(mg/L):>100
killifish 14d-LC50 (mg/L):100
killifish 14d-NOEC (mg/L):100
Ethanol
trout 24h-LC50(g/L):11.2
Carp 96h-LC50 (g/L):18 ~ 13.4
Creek Chub 24h-C50(g/L):7
Guppy 7d-LC50(g/L):11
Methanol
brine shrimp 24h-LC50 (mg/L):900.73
1-butanol
goldfish TLm (mg/L):1900

Persistence and degradability:

2-butanone
None known
Ethanol
None known
Methanol
None known
1-butanol
None known

Bioaccumulative potential:

2-butanone
None known
Ethanol
None known
Methanol
None known
1-butanol
May causes mobile in soil

Mobility in soil:

2-butanone
None known
Ethanol
None known
Methanol
None known
1-butanol
None known

13 Disposal considerations

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.
Do not dump into sewer, on the ground or into any body of water.
Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	:
Environmental hazards	:No

15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

16 References

- 1) Solvent, dye MSDS
- 2) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.