

MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION

Product name :JP-Y30
 Name of company :Hitachi Industrial Equipment Systems Co., Ltd
 Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan
 Tel :+81-294-36-8682
 Fax :+81-294-36-8975
 Recommended use of the chemical
 and restrictions on use :Printing Ink for industrial Marking

2 HAZARDS IDENTIFICATION

Physico-chemical endpoints	:Flammable liquid Category 2
Acute toxicity - oral	:Not available
Acute toxicity - dermal	:Not identified
Acute toxicity - inhalation (air)	:Not identified
Acute toxicity - inhalation (vapors)	:Not available
Acute toxicity - inhalation (dust, mist)	:Not identified
Skin corrosion/irritation	:Category 2
Eye damage/irritation	:Category 2
Sensitization - respiratory	:Not identified
Sensitization - skin	:Not identified
Germ cell mutagenicity	:Category 1
Carcinogenicity	:Category 2
Toxic to reproduction	:Category 1
Effects on or via lactation	:Not identified
Specific target organ systemic toxicity (Single exposure)	:Category 1 Respiratory system, Central nervous system :Category 1 Systemic toxicity, Kidney :Category 1 Liver :Category 2 Lungs :Category 3 Respiratory system, Anesthetizing action
(Repeated exposure)	:Category 1 Liver, Kidney :Category 1 Central nervous system :Category 1 Spleen :Category 2 Arterial system, Nervous
Aspiration toxicity	:Not identified
Hazardous to the aquatic environment	
-Acute hazard	:Not available
-Chronic hazard	:Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

GHS label elements

Hazard symbols:

**Signal word:** Danger**Hazard statement and precautionary statement:**

- Highly flammable liquid and vapour
- Causes skin irritation
- Causes eye irritation
- May cause genetic defects
- Suspected of causing cancer
- May damage fertility or the unborn child
- Causes damage to respiratory system , central nervous system systemic toxicity, kidney and liver -single exposure
- May cause damage to lungs - single exposure
- May cause respiratory irritation,drowsiness or dizziness-single exposure
- Causes damage to liver, kidney ,central nervous system and spleen through prolonged or repeated exposure.
- May cause damage to arterial system, nervous through prolonged or repeated exposure

Precautionary statements:

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response

- In case of fire, use dry chemical, CO₂, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

- Collect spillage.

Storage

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

Disposal

- Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition;

Chemical name	concentration (%)	CAS number
Ethanol	32-34	64-17-5
Cyclohexanone	15-19	108-94-1
Ethyl Acetate	15-19	141-78-6
2-Propanol	7-9	67-63-0
2-butanone	7-9	78-93-3
Titanium oxide	5-7	13463-67-7
Cellulose nitrate	1-10	9004-70-0
Chrome -Complex Dye	2	TSCA Registered

4 First-aid measures

Inhalation;

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medial facility for examination and treatment by a physician as soon as possible.

Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as son as possible.

Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medial attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water splay (fog) or form.

Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.
Make available in the work area emergency shower and eyes wash.
Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20) place.
Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines;

ACGIH TLV-TWA (ppm)	
Ethanol	:1000
Cyclohexanone	:25(skin)
Ethyl Acetate	:400
2-Propanol	:200
2-butanone	:200
Titanium oxide	:10mg/m3
Cellulose nitrate	:None known
Chrome -Complex Dye	:None known

ACGIH STEL(ppm)	
Ethanol	:No data
Cyclohexanone	:None known
Ethyl Acetate	:400
2-Propanol	:4500
2-butanone	:300
Titanium oxide	:None known
Cellulose nitrate	:None known
Chrome -Complex Dye	:None known

9 Physical and chemical properties

Appearance

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Physical state	:Liquid
Color	:Yellow
Odor	:Solvent odor
Boiling point	: 78.3 (ethanol)
Flash point	:-9.0 (closed cup)
Upper/lower flammability or explosive limits	:Lower 4.3 vol%, Upper 19 vol%(ethanol)
Vapor pressure	: 5.9kPa(20)(ethanol)
Vapor density (Air = 1)	:1.59(ethanol)
Relative density	:0.91(20)
Solubility (Water)	:water;infinite(ethanol)
Partition coefficient: n-octanol/water	:-0.32(ethanol)
Auto-ignition temperature	:390 (ethanol)
Decomposition temperature	:No data

10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

Acute toxicity;

Ethanol

TDLo(ori,man): 700mg/kg(NTOTDY 8,77,1986)

LD50(ori,rat): 9000mg/kg(VCVGK* -, 93, 1984)

LC50(ihl,rat): 20000ppm/10H(NPIRI* 1,44,1974)

TCLo(ihl,human): 2500mg/m3/20M(VCVGK* -, 93,1984)

Cyclohexanone

LD50(ori,rat): 1800mg/kg(VCVGK* -, 455, 1994)

LC50(ihl,rat): 19000mg/m3(VCVGK* -, 455, 1994)

LD50(skin,rabbit): 1mL/kg(AIHAAP 30, 470, 1969)

LDLo(ori,human): 714.3mg/kg(VCVGK* -, 455, 1994)

TCLo(ihl,human): 0.09mg/m3(VCVGK* -, 455, 1994)

Ethyl Acetate

LD50(ori,rat): 5620mg/kg(YKYUA6 32,, 1241, 1981)

LC50(ihl,mouse): 45gm/m3/2H(85GMAT -, 65, 1982)

2-Propanol

LD50(ori,rat): 5000mg/kg(VCVGK* -, 97, 1984)

LC50(ihl,rat): 72600mg/m3(VCVGK* -, 97, 1984)

LC50(ihl,mouse): 53000mg/m3(VCVGK* -, 97, 1984)

TDLo(ori,human): 286mg/kg(VCVGK* -, 97, 1984)

2-butanone

LD50(ori,rat): 2737mg/kg(TXAPA9 19, 699, 1971)

LCLo(ihl,rat): 23500mg/m3/8H(AIHAAP 20, 364, 1959)

LD50(skin,rabbit): 6480mg/kg(SHELL* MSDS-5390-4)

TCLo(ihl,human): 1000mg/m3(VCVGK* -, 417, 1994)

LDLo(ori,human): 714.3mg/kg(VCVGK* -, 417, 1994)

Titanium oxide

None known

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Cellulose nitrate
>5000(Rat LD50(mg/kg))
Chrome -Complex Dye
Oral >5000 (Rat LD50 (mg/kg))
Dermal >2000 (Rat LD50(mg/kg))
Inhalation None known

Skin corrosion/irritation;

Ethanol
Skin; rabbit; 20mg/24H; Moderate(85JCAE -, 189, 1986)
Cyclohexanone
Skin; rabbit; 500mg; Mild; Open(UCDS**)
Skin; human; 50%/48H; Mild(ADVEA4 27, 189, 1992)
Ethyl Acetate
No irritation: human(DFGOT vol.12,1999)
No irritation:rabbit(IUCLID 2000)
2-Propanol
Skin; rabbit; 500mg; Mild(NTIS** AD-A106-944)
2-butanone
Skin; rabbit; 402mg/24H; Mild(TXAPA9 19, 276, 1971)
Titanium oxide
None known
Cellulose nitrate
None known
Chrome -Complex Dye
No (Rabbit test-OECD404 1981)

Serious eye damage/irritation;

Ethanol
rabbit; 100mg/4S; Moderate(FCTOD7 20,573,1982)
Cyclohexanone
Eye; rabbit; 250?g/24H; Severe(85JCAE -,289,1986)
Ethyl Acetate
Eye; human; 400 ppm (JIHTAB 25,282,1943)
2-Propanol
Eye; rabbit; 100mg/24H; Moderate(85JCAE -,191,1986)
2-butanone
Eye; rabbit; 80mg(TXAPA9 19, 276, 1971)
Titanium oxide
None known
Cellulose nitrate
None known
Chrome -Complex Dye
No (Rabbit test-84/449/EEC B.5)

Respiratory or skin sensitization;

Ethanol
Not available
Cyclohexanone
Skin; rabbit; 500mg; Mild; Open(UCDS**)
Skin; human; 50%/48H; Mild(ADVEA4 27, 189, 1992)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ethyl Acetate
Not available
2-Propanol
Not available
2-butanone
Not available
Titanium oxide
None known
Cellulose nitrate
None known
Chrome -Complex Dye
No (Giunea pig test-84/449/EC B.6)

Germ cell mutagenicity;

Ethanol
DNA damage; *S.cerevisiae*; 850mmol/L(MUREAV 326,165,1995)
Mutation in microorganisms; *S.typhimurium*; 11pph(ENVRAL 52, 225, 1990)
Cytogenetic analysis; human; lymphocyte; 2.5pph/24H(MUREAV 537, 117, 2003)
Cyclohexanone
Mutation in microorganisms; *S.typhimurium*; cells; 20?L/L(EJMBA2 18,213,1983)
Cytogenetic analysis; human; lymphocyte; 5?g/L(GISAAA 46(5), 76, 1981)
Mutation in mammalian somatic cells; hamster; ovary; 7500?L/L(ENMUDM 7(Suppl 3), 60, 1985)
Ethyl Acetate
Cytogenetic analysis; hamster; fibroblast; 9 gm/L(FCTOD7 22,623,1984)
Sex chromosome loss and nondisjunction; *S.cerevisiae*; 24400ppm(MUREAV 149, 339, 1985)
2-Propanol
TDLo(ori,rat): 8gm/kg(female 6-15 D preg)(RTOPDW 23,183,1996)
TCLo(ihl,rat): 3500ppm/7H(female 1-19 D preg)(FCTOD7 26,247,1988)
2-butanone
Reverse mutation assay in *S.typhimurium* and *E.coli*; Negative
Sex chromosome loss and nondisjunction; *S.cerevisiae*; 33800ppm(MUREAV 149, 339, 1985)
Titanium oxide
None known
Cellulose nitrate
None known
Chrome -Complex Dye
None known

Carcinogenicity;

Ethanol
TDLo(ori,mouse): 320mg/kg/50W-I(CALEDQ 13,345,1981)
Cyclohexanone
Not available
Ethyl Acetate
Not available
2-Propanol
Not available
2-butanone
Not available
Titanium oxide
None known

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Cellulose nitrate
None known
Chrome -Complex Dye
None known

Reproductive toxicity;

Ethanol
TDLo(ori,woman): 250mg/kg(37 W preg); Effects on Embryo or Fetus - other effects to embryo(AJOGAH 145,251,1983)
TDLo(ori,rat): 22.5gm/kg(female 11-20 D preg); Specific Developmental Abnormalities - Central Nervous Systems(NETEEC 24, 719, 2002)
Cyclohexanone
TCLo(ihl,rat): 105mg/m3/4H(1-20 D preg); Fertility - pre - implantation mortality(TPKVAL 14,26,1975)
TDLo(ori,mouse): 11mg/kg(8-12 D preg); Effects on Newborn - growth statistics(TCMUD8 6,361,1986)
Ethyl Acetate
Not available
2-Propanol
TDLo(ori,rat): 8gm/kg(female 6-15 D preg)(RTOPDW 23,183,1996)
TCLo(ihl,rat): 3500ppm/7H(female 1-19 D preg)(FCTOD7 26,247,1988)
2-butanone
TCLo(ihl,rat): 2900mg/m3(female 6-10 D preg); Specific Developmental Abnormalities - craniofacial(VCVGK* -, 418, 1994)
Titanium oxide
None known
Cellulose nitrate
None known
Chrome -Complex Dye
None known

STOST-single exposure;

Ethanol
Human ihl, 5000ppm(9,4mg/L), respiratory tract irritation and confusion(ACGIH 2001)
Cyclohexanone
None known
Ethyl Acetate
The above part respiratory organ stimulation by 400ppm, human(ACGIH, 2001; DFGOT, vol 12,1999)
Anesthesia and lung damage by the lethal concentration(DFGOT, vol 12,1999)
2-Propanol
Not available
2-butanone
The influence of the central nervous system, rat/mouse(EHC 143, 1992; PATTY 4th, 1994; IRIS 2003)
The influence of kidney, oral, rat(DFGOT vol 12,1999; IRIS 2003; ATSDR 1992)
The respiratory tract irritation, human (ACGIH 7th, 2001; DFGOT vol 12,1999; PATTY 4th, 1994; ATSDR 1992)
Titanium oxide
None known
Cellulose nitrate

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

None known
 Chrome -Complex Dye
 None known

STOST-repeated exposure;

Ethanol
 Not available
 Cyclohexanone
 None known
 Ethyl Acetate
 Not available
 2-Propanol
 Not available
 2-butanone
 The sensory paralysis of hand and arm, human(EHC 143, 1992; DFGOT vol 12, 1999; IRIS 2003)
 The dmade of central nervous system, human(DFGOT vol 12, 1999; IRIS 2003)
 Titanium oxide
 None known
 Cellulose nitrate
 None known
 Chrome -Complex Dye
 None known

Aspiration hazard.

Ethanol
 Not available
 Cyclohexanone
 None known
 Ethyl Acetate
 Not available
 2-Propanol
 Not available
 2-butanone
 Not available
 Titanium oxide
 None known
 Cellulose nitrate
 None known
 Chrome -Complex Dye
 None known

12 Ecological information

Toxicity:

Ethanol
 TDLo(ori,man): 700mg/kg(NTOTDY 8,77,1986)
 LD50(ori,rat): 9000mg/kg(VCVGK* -, 93, 1984)
 LC50(ihl,rat): 20000ppm/10H(NPIRI* 1,44,1974)
 TCLo(ihl,human): 2500mg/m3/20M(VCVGK* -, 93,1984)
 Cyclohexanone

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

LD50(ori,rat): 1800mg/kg(VCVGK* -, 455, 1994)
 LC50(ihl,rat): 19000mg/m3(VCVGK* -, 455, 1994)
 LD50(skin,rabbit): 1mL/kg(AIHAAP 30, 470, 1969)
 LDLo(ori,human): 714.3mg/kg(VCVGK* -, 455, 1994)
 TCLo(ihl,human): 0.09mg/m3(VCVGK* -, 455, 1994)
 Ethyl Acetate
 LD50(ori,rat): 5620mg/kg(YKYUA6 32,, 1241, 1981)
 LC50(ihl,mouse): 45gm/m3/2H(85GMAT -, 65, 1982)
 2-Propanol
 LD50(ori,rat): 5000mg/kg(VCVGK* -, 97, 1984)
 LC50(ihl,rat): 72600mg/m3(VCVGK* -, 97, 1984)
 LC50(ihl,mouse): 53000mg/m3(VCVGK* -, 97, 1984)
 TDLo(ori,human): 286mg/kg(VCVGK* -, 97, 1984)
 2-butanone
 LD50(ori,rat): 2737mg/kg(TXAPA9 19, 699, 1971)
 LCLo(ihl,rat): 23500mg/m3/8H(AIHAAP 20, 364, 1959)
 LD50(skin,rabbit): 6480mg/kg(SHELL* MSDS-5390-4)
 TCLo(ihl,human): 1000mg/m3(VCVGK* -, 417, 1994)
 LDLo(ori,human): 714.3mg/kg(VCVGK* -, 417, 1994)
 Titanium oxide
 None known
 Cellulose nitrate
 >5000(Rat LD50(mg/kg))
 Chrome -Complex Dye
 Oral >5000 (Rat LD50 (mg/kg))
 Dermal >2000 (Rat LD50 (mg/kg))
 Inhalation None known

Persistence and degradability:

Ethanol
 This material is biodegradable.
 Cyclohexanone
 This material is biodegradable.
 Ethyl Acetate
 This material is biodegradable.
 2-Propanol
 This material is biodegradable.
 2-butanone
 Not available
 Titanium oxide
 None known
 Cellulose nitrate
 None known
 Chrome -Complex Dye
 None known

Bioaccumulative potential:

Ethanol
 Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Cyclohexanone
 Not available
 Ethyl Acetate
 Not available
 2-Propanol
 Not available
 2-butanone
 Not available
 Titanium oxide
 None known
 Cellulose nitrate
 None known
 Chrome -Complex Dye
 None known

Mobility in soil:

Ethanol
 Not available
 Cyclohexanone
 None known
 Ethyl Acetate
 Not available
 2-Propanol
 Not available
 2-butanone
 Not available
 Titanium oxide
 None known
 Cellulose nitrate
 None known
 Chrome -Complex Dye
 None known

13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.
 Do not dump into sewer, on the ground or into any body of water.
 Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	:
Environmental hazards	:No

15 Regulatory information

Follow all regulations in your country.
 Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

16 References

- 1) Solvent, dye MSDS
- 2) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.