MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION

Product name :TH-60

Name of company :Hitachi Industrial Equipment Systems Co., Ltd

Address :1-1, Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan

Tel :+81-294-36-8682 Fax :+81-294-36-8975

Recommended use of the chemical

and restrictions on use :Printing Ink for industrial Marking

2 HAZARDS IDENTIFICATION

Physico-chemical endpoints :Flammable liquid Category 2

Acute toxicity - oral :Not available Acute toxicity - dermal :Category 5 Acute toxicity - inhalation(air) :Not identified Acute toxicity - inhalation (vapors) :Not available Acute toxicity - inhalation (dust, mist) :Not available Skin corrosion/irritation :Category 3 Eye damage/irritation :Category 2 Sensitization - respiratory :Not identified Sensitization - skin :Not identified Germ cell mutagenicity :Category 1 Carcinogenicity :Not available Toxic to reproduction :Category 1 Effects on or via lactation :Not identified

Specific target organ systemic toxicity

(Single exposure) :Category 1 Kidney

:Category 1 Systemic toxicity

:Category 1 Central nervous system

:Category 3 Respiratory system, an esthetizing action

(Repeated exposure) :Category 1 liver

:Category 2 Arterial system, nervous and spleen

Aspiration toxicity :Category 2

Hazardous to the aquatic environment

-Acute hazard :Not available -Chronic hazard :Not available

GHS label elements

Hazard symbols:Flame,Exclamation mark,Health hazard







Signal word: Danger

Hazard statement and precautionary statement:

- · Highly flammable liquid and vapour
- May be harmful in contact with skin-Dermal
- Causes mild skin irritation
- Causes eye irritation
- May cause bad effect to genetic or fetus
- May damage fertility or the unborn child
- Cause damage to ,Kidney, Systemic toxicity and Central nervous system-single exposure
- May cause respiratory irritation-single exposure
- Causes damage to liver-through prolonged or repeated exposure
- May causes damage to Arterial system, nervous and spleen-through prolonged or repeated exposure
- May be harmful if swallowed and enters airways

Precautionary statements:

 Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response

- In case of fire, use dry chemical, CO₂, water splay (fog) or form for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

Storage

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

Disposal

Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition;

Chemical name	concentration (%)	CAS number
Ethanol	80-90	64-17-5
2-Propanol	5-10	67-63-0
2-Methyl-1-propanol	1-10	78-83-1

4 First-aid measures

Inhalation:

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the neatest medial facility for examination and treatment by a physician as soon as possible.

Skin contact:

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as son as possible.

Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible, and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medial attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water splay (fog) or form.

Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20) place. Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines;

ACGIH TLV-TWA (ppm)

Ethanol :1000 2-Propanol :200 2-Methyl-1-propanol :50

ACGIH STEL(ppm)

Ethanol :No data
2-Propanol :4500
2-Methyl-1-propanol :None known

9 Physical and chemical properties

Appearance

Physical state :Liquid
Color :Clear
Odor :Solvent odor

Boiling point : 78.3 (ethanol)
Flash point :16.0 (closed cup)

Upper/lower flammability or explosive limits :Lower 4.3 vol%, Upper 19 vol% (ethanol)

Vapor pressure : 5.9kPa(20)(ethanol)

Relative density (Air = 1) :1.59(ethanol)
Relative density :0.81(20)

Solubility (Water) :water;infinite(ethanol)

Partition coefficient: n-octanol/water :-0.32(ethanol)
Auto-ignition temperature :390 (ethanol)
Decomposition temperature :No measurement

10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

```
Acute toxicity;
  Ethanol
    Not available: Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))
    Not identified: Dermal No data
    Not available:Inhalation 31600 (Vaper) (Rat LC50(ppm/4h))
  2-Propanol
    LD50(orl,rat): 5000mg/kg(VCVGK* -, 97, 1984)
    skin:No data
    LC50(ihl,rat): 72600mg/m3(VCVGK* -, 97, 1984)
  2-Methyl-1-propanol
    LD50(orl,rat): 2460mg/kg(AMIHBC 10,61,1954)
    LD50(orl,mouse): 3500mg/kg(VCVGK* -, 102,1984)
    LD50(skin,rabbit): 3400mg/kg(NPIRI* 1,11,1974)
Skin corrosion/irritation:
  Ethanol
    Not identified
  2-Propanol
    Skin; rabbit; 500mg; Mild(NTIS** AD-A106-944)
  2-Methyl-1-propanol
    rabbit; 500mg/24H; Severe(ACGIH(7th, 2001))
Serious eye damage/irritation:
  Ethanol
    Category 2A
  2-Propanol
    Eye; rabbit; 100mg/24H; Moderate(85JCAE -,191,1986)
  2-Methyl-1-propanol
    rabbit; 2mg; Severe(PATTY (4th, 1994); DFGOT vol 19(2003))
Respiratory or skin sensitization;
  Ethanol
    Not identified
  2-Propanol
    Not available
  2-Methyl-1-propanol
    Not available
Germ cell mutagenicity;
  Ethanol
    Category 1B
  2-Propanol
    Cytogenetic analysis; rat-inhalation; 1030?g/m3/16W-I(GTPZAB 25(7),33,1981)
  2-Methyl-1-propanol
    Mutation in microorganisms; E.coli; 25000ppm(ABMGAJ 23,843,1969)
Carcinogenicity;
  Ethanol
    Not available Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))
  2-Propanol
    Not available
  2-Methyl-1-propanol
    Not available
```

Reproductive toxicity;

Ethanol

Category 1A

2-Propanol

TDLo(orl,rat): 8gm/kg(female 6-15 D preg)(RTOPDW 23,183,1996)

TCLo(ihl,rat): 3500ppm/7H(female 1-19 D preg)(FCTOD7 26,247,1988)

2-Methyl-1-propanol

Mutation in microorganisms; E.coli; 25000ppm(ABMGAJ 23,843,1969)

STOST-single exposure;

Ethanol

Category 3(Respiratory)

2-Propanol

Not available

2-Methyl-1-propanol

Irritation of human pharyngeal(EHC 65, 1987; PATTY 4th, 1994)

The lowing of startle response and hypoactivity by ihl, rat, 3000ppm/6H(SIDS, 2004)

STOST-repeated exposure;

Ethanol

Category 1(Liver) 2(Nervous system)

2-Propanol

Not available

2-Methyl-1-propanol

Not available

Aspiration hazard.

Ethanol

Not identified

2-Propanol

Not available

2-Methyl-1-propanol

Not available

12 Ecological information

Toxicity:

Ethanol

trout 24h-LC50(g/L):11.2

Carp 96h-LC50 (g/L):18 ~ 13.4

Creek Chub 24h-C50(g/L):7

Guppy 7d-LC50(g/L):11

2-Propanol

LC50(guppies):7060/7days

2-Methyl-1-propanol

Not available

Persistence and degradability:

Ethanol

None known

2-Propanol

This material is biodegradable.

2-Methyl-1-propanol

This material is biodegradable.

Bioaccumulative potential:

Ethanol

None known

2-Propanol

Not available

2-Methyl-1-propanol

Not available

Mobility in soil:

Ethanol

None known

2-Propanol

Not available

2-Methyl-1-propanol

Not available

13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.

Do not dump into sewer, on the ground or into any body of water.

Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number :1210

UN Proper Shipping Name :Printing ink, flammable Transport hazard class :Class 3(Flammable liquid)

Packing Group :

Environmental hazards :No

15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

16 References

- 1) Solvent, dye MSDS
- 2) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards