

Derivation and Numerical Simulations of a Coupled Moment System for Modeling Sedimentation in Suspensions of Rod-Like Particles

Bella My Phuong Quynh Duong, Christiane Helzel

Heinrich-Heine University Düsseldorf

September 23, 2024



Table of Contents


- 1 Motivation
- 2 Shear Flow
- 3 Hierarchy of Moment Equations for Shear Flow
- 4 Numerical Simulations

Overview

- 1 Motivation
- 2 Shear Flow
- 3 Hierarchy of Moment Equations for Shear Flow
- 4 Numerical Simulations

Guazzelli et al examined a dilute suspension of rod-like particles influenced by gravity.

- In an initially homogeneous suspension, rod-like particles form clusters where they are denser.
- The clusters create downward flows balanced by upward flows.
- Particles in a cluster mostly align with gravity, occasionally flipping.



Mathematical Model for the Sedimentation of Rod-Like Particles

Coupling of a kinetic Smoluchowski equation with Navier-Stokes equation

$$\begin{aligned}
 \partial_t f + \nabla_{\mathbf{x}} \cdot (\mathbf{u} f) + \nabla_{\mathbf{n}} \cdot (P_{\mathbf{n}} \nabla_{\mathbf{x}} \mathbf{u} f) - \nabla_{\mathbf{x}} \cdot ((I + \mathbf{n} \otimes \mathbf{n}) \mathbf{e}_3 f) \\
 = D_r \Delta_{\mathbf{n}} f + \gamma \nabla_{\mathbf{x}} \cdot (I + \mathbf{n} \otimes \mathbf{n}) \nabla_{\mathbf{x}} f, \\
 \sigma = \int_{S^{d-1}} (\mathbf{n} \otimes \mathbf{n} - I) f d\mathbf{n}, \\
 \text{Re} (\partial_t \mathbf{u} + (\mathbf{u} \cdot \nabla_{\mathbf{x}}) \mathbf{u}) = \Delta_{\mathbf{x}} \mathbf{u} - \nabla_{\mathbf{x}} p + \delta \gamma \nabla_{\mathbf{x}} \cdot \sigma - \delta \int_{S^{d-1}} f d\mathbf{n} \mathbf{e}_3, \\
 \nabla_{\mathbf{x}} \cdot \mathbf{u} = 0,
 \end{aligned}$$

where $f = f(\mathbf{x}, t, \mathbf{n})$, $\mathbf{x} \in \mathbb{R}^3$, $\mathbf{n} \in S^2$ is a density distribution function of particle orientation. D_r, γ, δ and Re are non-dimensional parameters.

Helzel & Tzavaras, 2017

Here we consider the case $\gamma = 0$.

Status of Project

So far...

- Investigate hierarchy of moment equations for simplified model with f on S^1
 - Transform high dimensional scalar PDE (in space and orientation) into a lower dimensional system of moment equations (in space)

Dahm, Helzel, MMS 2022, Dahm, Giesselmann, Helzel, JCP 2024

Now

Status of Project

So far...

- Investigate hierarchy of moment equations for simplified model with f on S^1
 - Transform high dimensional scalar PDE (in space and orientation) into a lower dimensional system of moment equations (in space)
 - Investigate accuracy of moment closure system

Dahm, Helzel, MMS 2022, Dahm, Giesselmann, Helzel, JCP 2024

Now

Status of Project

So far...

- Investigate hierarchy of moment equations for simplified model with f on S^1
 - Transform high dimensional scalar PDE (in space and orientation) into a lower dimensional system of moment equations (in space)
 - Investigate accuracy of moment closure system

Dahm, Helzel, MMS 2022, Dahm, Giesselmann, Helzel, JCP 2024

Now

- Derive and approximate hierarchies of moment equations for the coupled kinetic-fluid model with f on S^2 .

Overview


- 1 Motivation
- 2 Shear Flow
- 3 Hierarchy of Moment Equations for Shear Flow
- 4 Numerical Simulations

Shear Flow

For a *shear flow* assume $\mathbf{u} = (0, 0, w(x, t))^T$, $f = f(x, t, \phi, \theta)$.

We have

$$\begin{aligned} \sin \theta \partial_t f(x, t, \phi, \theta) + \partial_x (\cos \phi \cos \theta \sin^2 \theta f) \\ + \partial_\theta (w_x \sin^3 \theta \cos \phi f) = D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f \right) + \partial_\theta (\sin \theta \partial_\theta f) \right), \quad (1) \\ \text{Re} \partial_t w(x, t) = \partial_{xx} w + \delta \left(\bar{\rho} - \int_0^{2\pi} \int_0^\pi f \sin \theta d\theta d\phi \right). \end{aligned}$$



Overview

- 1 Motivation
- 2 Shear Flow
- 3 Hierarchy of Moment Equations for Shear Flow
- 4 Numerical Simulations

Ansatz for Derivation of Moment Equations

Consider approximation of the form

$$f(\mathbf{x}, t, \phi, \theta) \approx f^N(\mathbf{x}, t, \phi, \theta) := \sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(\mathbf{x}, t) \cdot P_{2n}^i(\phi, \theta), \quad (2)$$

where $P_{2n}^i(\phi, \theta)$, $n = 0, \dots, N$, $i = -2n, \dots, 2n$

- are harmonic polynomial basis functions, i.e., the eigenfunctions of the Laplace-Beltrami operator with the eigenvalue $-2n(2n+1)$

Ansatz for Derivation of Moment Equations

Consider approximation of the form

$$f(\mathbf{x}, t, \phi, \theta) \approx f^N(\mathbf{x}, t, \phi, \theta) := \sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(\mathbf{x}, t) \cdot P_{2n}^i(\phi, \theta), \quad (2)$$

where $P_{2n}^i(\phi, \theta)$, $n = 0, \dots, N$, $i = -2n, \dots, 2n$

- are harmonic polynomial basis functions, i.e., the eigenfunctions of the Laplace-Beltrami operator with the eigenvalue $-2n(2n+1)$
- form an orthonormal basis, wrt. the L_2 -inner product on the sphere

$$(g, h)_{S^2} := \int_0^{2\pi} \int_0^\pi g(\phi, \theta) h(\phi, \theta) \cdot \sin(\theta) d\theta d\phi,$$

Ansatz for Derivation of Moment Equations

Consider approximation of the form

$$f(\mathbf{x}, t, \phi, \theta) \approx f^N(\mathbf{x}, t, \phi, \theta) := \sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(\mathbf{x}, t) \cdot P_{2n}^i(\phi, \theta), \quad (2)$$

where $P_{2n}^i(\phi, \theta)$, $n = 0, \dots, N$, $i = -2n, \dots, 2n$

- are harmonic polynomial basis functions, i.e., the eigenfunctions of the Laplace-Beltrami operator with the eigenvalue $-2n(2n+1)$
- form an orthonormal basis, wrt. the L_2 -inner product on the sphere

$$(g, h)_{S^2} := \int_0^{2\pi} \int_0^\pi g(\phi, \theta) h(\phi, \theta) \cdot \sin(\theta) d\theta d\phi,$$

- every square integrable function on S^2 can be expressed as a linear combination of spherical harmonics $f(\phi, \theta) = \sum_{n=0}^\infty \sum_{i=-n}^n c_n^i \cdot P_n^i(\phi, \theta)$.

Derivation of Moment Equations

We derive the moment equations by

- Insert ansatz $f^N = \sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(x, t) \cdot P_{2n}^i(\phi, \theta)$ into kinetic equation

$$\begin{aligned} \sin \theta \partial_t f^N(x, t, \phi, \theta) &+ \partial_x (\cos \phi \cos \theta \sin^2 \theta f^N) \\ &= -\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right) \end{aligned}$$

- Multiply consecutively with all basis functions used in the ansatz and integrate the resulting equations over the sphere

Derivation of Moment Equations

We derive the moment equations by

- Insert ansatz $f^N = \sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(x, t) \cdot P_{2n}^i(\phi, \theta)$ into kinetic equation

$$\begin{aligned} \sin \theta \partial_t f^N(x, t, \phi, \theta) + \partial_x (\cos \phi \cos \theta \sin^2 \theta f^N) \\ = -\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right) \end{aligned}$$

- Multiply consecutively with all basis functions used in the ansatz and integrate the resulting equations over the sphere

The system of moment equations has the general form

$$\partial_t Q + A \partial_x Q = D(w_x) Q + D_r E Q, \quad (3)$$

where $Q = (c_0^0(x, t), c_2^{-2}(x, t), \dots, c_{2N}^{2N}(x, t))^T$ represents the vector of the moments and

$A, D, E \in \mathbb{R}^{(N+1)(2N+1) \times (N+1)(2N+1)}$.

Derivation: A Closer Look

Consider

$$\underbrace{\sin \theta \partial_t f^N(x, t, \phi, \theta)}_{[1]} + \underbrace{\partial_x (\cos \phi \cos \theta \sin^2 \theta f^N)}_{[2]} \\ = -\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)$$

Derivation: A Closer Look

Consider

$$\underbrace{\sin \theta \partial_t f^N(x, t, \phi, \theta)}_{[1]} + \underbrace{\partial_x (\cos \phi \cos \theta \sin^2 \theta f^N)}_{[2]}$$

$$= -\partial_\theta (w_x \sin^3 \theta \cos \phi f^N) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)$$

For $k = 0, \dots, N$, $l = -2k, \dots, 2k$ we obtain for term [1]

$$\begin{aligned} & \int_0^{2\pi} \int_0^\pi \sin \theta \partial_t \left(\sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(x, t) \cdot P_{2n}^i(\phi, \theta) \right) P_{2k}^l(\phi, \theta) \\ &= \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) \int_0^{2\pi} \int_0^\pi \sin \theta P_{2n}^i(\phi, \theta) P_{2k}^l(\phi, \theta) d\phi d\theta \\ &= \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) (P_{2n}^i(\phi, \theta) P_{2k}^l(\phi, \theta))_{S^2} = \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) \cdot \delta_{n,k} \delta_{i,l} \\ &= \partial_t c_{2k}^l(x, t) \end{aligned}$$

Derivation: A Closer Look

Consider

$$\underbrace{\sin \theta \partial_t f^N(x, t, \phi, \theta)}_{[1]} + \underbrace{\partial_x (\cos \phi \cos \theta \sin^2 \theta f^N)}_{[2]}$$

$$= -\partial_\theta (w_x \sin^3 \theta \cos \phi f^N) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)$$

For $k = 0, \dots, N$, $l = -2k, \dots, 2k$ we obtain for term [1]

$$\begin{aligned} & \int_0^{2\pi} \int_0^\pi \sin \theta \partial_t \left(\sum_{n=0}^N \sum_{i=-2n}^{2n} c_{2n}^i(x, t) \cdot P_{2n}^i(\phi, \theta) \right) P_{2k}^l(\phi, \theta) \\ &= \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) \int_0^{2\pi} \int_0^\pi \sin \theta P_{2n}^i(\phi, \theta) P_{2k}^l(\phi, \theta) d\phi d\theta \\ &= \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) (P_{2n}^i(\phi, \theta) P_{2k}^l(\phi, \theta))_{S^2} = \sum_{n=0}^N \sum_{i=-2n}^{2n} \partial_t c_{2n}^i(x, t) \cdot \delta_{n,k} \delta_{i,l} \\ &= \partial_t c_{2k}^l(x, t) \end{aligned}$$

This corresponds to this term $\partial_t Q + A \partial_x Q = D(w_x)Q + D_r EQ$.

Consider term [2]

$$\underbrace{\sin \theta \partial_t f^N(x, t, \phi, \theta)}_{[1]} + \underbrace{\partial_x (\cos \phi \cos \theta \sin^2 \theta f^N)}_{[2]} \\ = -\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)$$

Consider term [2]

$$\underbrace{\sin \theta \partial_t f^N(x, t, \phi, \theta)}_{[1]} + \underbrace{\partial_x (\cos \phi \cos \theta \sin^2 \theta f^N)}_{[2]}$$

$$= -\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right) + D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)$$

This represents the term $\partial_t Q + A \partial_x Q = D(w_x)Q + D_r EQ$

For $N = 1$ the matrix A has the form

$$\left[\begin{array}{c|c} A_{0,0} & A_{0,1} \\ \hline A_{0,1}^T & A_{1,1} \end{array} \right] = \left[\begin{array}{c|ccccc} 0 & 0 & \frac{1}{\sqrt{15}} & 0 & 0 & 0 \\ \hline 0 & 0 & \frac{1}{7} & 0 & 0 & 0 \\ \frac{1}{\sqrt{15}} & \frac{1}{7} & 0 & \frac{\sqrt{3}}{21} & 0 & 0 \\ 0 & 0 & \frac{\sqrt{3}}{21} & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & \frac{1}{7} \\ 0 & 0 & 0 & 0 & \frac{1}{7} & 0 \end{array} \right].$$

For $N = 2$ the symmetric matrix A has the structure

$$\begin{bmatrix} A_{0,0} & A_{0,1} & \\ A_{0,1}^T & A_{1,1} & A_{1,2} \\ & & A_{1,2}^T & A_{2,2} \end{bmatrix}.$$

For any N the system of moment equations is hyperbolic.

Now consider the remaining terms:

$$\begin{aligned} \sin \theta \partial_t f^N(x, t, \phi, \theta) + \partial_x (\cos \phi \cos \theta \sin^2 \theta f^N) \\ = \underbrace{-\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right)}_{[3]} + \underbrace{D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)}_{[4]}. \end{aligned}$$

Now consider the remaining terms:

$$\begin{aligned} \sin \theta \partial_t f^N(x, t, \phi, \theta) + \partial_x (\cos \phi \cos \theta \sin^2 \theta f^N) \\ = \underbrace{-\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right)}_{[3]} + \underbrace{D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)}_{[4]}. \end{aligned}$$

- Term [4] corresponds to the Laplace-Beltrami operator, resulting in $D_r E Q$, where the matrix E is a diagonal matrix with the Laplace-Beltrami eigenvalues.

Now consider the remaining terms:

$$\sin \theta \partial_t f^N(x, t, \phi, \theta) + \partial_x (\cos \phi \cos \theta \sin^2 \theta f^N) \\ = \underbrace{-\partial_\theta \left(w_x \sin^3 \theta \cos \phi f^N \right)}_{[3]} + \underbrace{D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f^N \right) + \partial_\theta (\sin \theta \partial_\theta f^N) \right)}_{[4]}.$$

- Term [4] corresponds to the Laplace-Beltrami operator, resulting in $D_r E Q$, where the matrix E is a diagonal matrix with the Laplace-Beltrami eigenvalues.
- Term [3]: We apply the same approach by inserting the ansatz for f and projecting onto the polynomials, resulting in $D(w_x)Q$.

The system of moment equations: $\partial_t Q + A \partial_x Q = D(w_x)Q + D_r E Q$.

Overview

- 1 Motivation
- 2 Shear Flow
- 3 Hierarchy of Moment Equations for Shear Flow
- 4 Numerical Simulations

Approximation of Coupled Shear Flow Problem

Consider

$$\begin{aligned}\partial_t Q(x, t) + \partial_x Q(x, t) &= D(w_x)Q(x, t) + D_r EQ(x, t) \\ \partial_t w &= \partial_{xx} w + \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t)).\end{aligned}\tag{4}$$

Approximation of Coupled Shear Flow Problem

Consider

$$\begin{aligned}\partial_t Q(x, t) + \partial_x Q(x, t) &= D(w_x)Q(x, t) + D_r E Q(x, t) \\ \partial_t w &= \partial_{xx} w + \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t)).\end{aligned}\tag{4}$$

1.	$\frac{1}{2}\Delta t$ step on $\partial_t Q(x, t) = (D(w_x(x, t_n)) + D_r E)Q(x, t)$
2.	$\frac{1}{4}\Delta t$ step on $\partial_t w(x, t) = \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t))$
3.	$\frac{1}{2}\Delta t$ step on $\partial_t w(x, t) = \partial_{xx} w(x, t)$
4.	$\frac{1}{4}\Delta t$ step on $\partial_t w(x, t) = \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t))$
5.	Δt step on $\partial_t Q(x, t) + A\partial_x Q(x, t) = 0$
6.	$\frac{1}{4}\Delta t$ step on $\partial_t w(x, t) = \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t))$
7.	$\frac{1}{2}\Delta t$ step on $\partial_t w(x, t) = \partial_{xx} w(x, t)$
8.	$\frac{1}{4}\Delta t$ step on $\partial_t w(x, t) = \delta(\bar{\rho} - 2\sqrt{\pi}c_0^0(x, t))$
9.	$\frac{1}{2}\Delta t$ step on $\partial_t Q(x, t) = (D(w_x(x, t_{n+1})) + D_r E)Q(x, t)$

Table 1: Splitting algorithm for solving the coupled shear flow problem ([1])

We use an ODE solver for 1. + 9., LeVeque's high resolution wave propagation algorithm for 5. and finite difference methods for the evolution of w .







Figure 1: Numerical solution of the drift-diffusion term with constant externally imposed velocity gradient corresponding to shear flow using different values of Dr , and $N = 1, 6$.

Accuracy Study

Let $c_0^0(x, 0) = \exp(-(x - 50)^2)/(2 \cdot \sqrt{\pi})$ be the initial value.

	N = 1		N = 2		N = 3	
grid	L1-Error	EOC	L1-Error	EOC	L1-Error	EOC
256	$2.7197 \cdot 10^{-1}$		$1.9174 \cdot 10^{-2}$		$1.6585 \cdot 10^{-1}$	
512	$1.0421 \cdot 10^{-1}$	1.38	$6.4197 \cdot 10^{-2}$	1.57	$5.4157 \cdot 10^{-2}$	1.61
1024	$3.0275 \cdot 10^{-2}$	1.78	$1.7984 \cdot 10^{-2}$	1.83	$1.5270 \cdot 10^{-2}$	1.82
2048	$7.6037 \cdot 10^{-3}$	1.99	$4.4721 \cdot 10^{-3}$	2.0	$3.6918 \cdot 10^{-3}$	2.04

Table 2: Accuracy study for the component c_0^0 of the coupled problem for shear flow using $D_r = 1$. The reference solution, computed on a grid with 8192 cells, uses the same number of moment equations as the coarse solution. In all computations the time step was limited by a CFL condition with $cfl \leq 0.8$.

Accuracy Study

	N = 1		N = 2		N = 3	
grid	L1-Error	EOC	L1-Error	EOC	L1-Error	EOC
256	$1.1624 \cdot 10^{-2}$		$2.6060 \cdot 10^{-3}$		$6.0421 \cdot 10^{-3}$	
512	$1.2524 \cdot 10^{-2}$	-0.10	$1.1655 \cdot 10^{-3}$	1.16	$1.1655 \cdot 10^{-3}$	2.37
1024	$1.3168 \cdot 10^{-2}$	-0.07	$3.1649 \cdot 10^{-3}$	-1.44	$8.0673 \cdot 10^{-4}$	0.53
2048	$1.3310 \cdot 10^{-2}$	-0.01	$3.4125 \cdot 10^{-3}$	-0.10	$5.5722 \cdot 10^{-4}$	0.53

Table 3: Accuracy analysis for the component c_0^0 of the coupled problem for shear flow using $D_r = 0.01$. The reference solution, computed on a grid with 8192 cells using $N = 6$. In all computations the time step was limited by a CFL condition with $cfl \leq 0.8$.

grid	N = 4		N = 5	
	L1-Error	EOC	L1-Error	EOC
256	$5.9343 \cdot 10^{-3}$		$6.2261 \cdot 10^{-3}$	
512	$2.1285 \cdot 10^{-3}$	1.47	$2.3204 \cdot 10^{-3}$	1.42
1024	$6.1323 \cdot 10^{-4}$	1.79	$6.8919 \cdot 10^{-4}$	1.75
2048	$2.4303 \cdot 10^{-4}$	1.33	$1.7118 \cdot 10^{-4}$	2.0

Table 4: Accuracy analysis for the component c_0^0 of the coupled problem for shear flow using $D_r = 0.01$. The reference solution, computed on a grid with 8192 cells using $N = 6$. In all computations the time step was limited by a CFL condition with $cfl \leq 0.8$.

	N = 1		N = 2		N = 3	
grid	L1-Error	EOC	L1-Error	EOC	L1-Error	EOC
256	$1.4093 \cdot 10^{-2}$		$8.4036 \cdot 10^{-3}$		$6.6520 \cdot 10^{-3}$	
512	$3.4409 \cdot 10^{-3}$	2.03	$2.0240 \cdot 10^{-3}$	2.05	$2.0034 \cdot 10^{-3}$	1.73
1024	$1.5602 \cdot 10^{-3}$	1.14	$4.3070 \cdot 10^{-4}$	2.23	$5.4486 \cdot 10^{-4}$	1.87
2048	$1.4673 \cdot 10^{-3}$	0.08	$1.2731 \cdot 10^{-4}$	1.75	$1.3623 \cdot 10^{-4}$	1.99

Table 5: Accuracy analysis for the component c_0^0 of the coupled problem for shear flow using $D_r = 0.05$. The reference solution, computed on a grid with 8192 cells using $N = 6$. In all computations the time step was limited by a CFL condition with $cfl \leq 0.8$.

Accuracy Study

grid	N = 1		N = 2		N = 3	
	L1-Error	EOC	L1-Error	EOC	L1-Error	EOC
256	$2.7228 \cdot 10^{-1}$		$1.9183 \cdot 10^{-1}$		$1.6589 \cdot 10^{-1}$	
512	$1.0452 \cdot 10^{-1}$	1.38	$3.1259 \cdot 10^{-2}$	2.61	$5.4197 \cdot 10^{-2}$	1.61
1024	$3.0596 \cdot 10^{-2}$	1.77	$1.8077 \cdot 10^{-2}$	0.79	$1.5310 \cdot 10^{-2}$	1.82
2048	$7.9252 \cdot 10^{-3}$	1.94	$4.5655 \cdot 10^{-3}$	1.98	$3.7315 \cdot 10^{-3}$	2.03

Table 6: Accuracy analysis for the component c_0^0 of the coupled problem for shear flow using $D_r = 1$. The reference solution, computed on a grid with 8192 cells using $N = 6$. All simulations employed a time step constrained by a CFL condition with $cfl \leq 0.8$.

Cluster Formation

Let

$$c_0^0(x, 0) = (1 + (1 \cdot 10^{-4} \cdot \eta(x) - 5 \cdot 10^{-5})) / (2\sqrt{\pi}),$$

where $\eta(x)$ is a random variable taking values in the interval $\pm \frac{1}{2}$.




Figure 2: Approximation of the coupled problem for shear flow with $D_r = 0.05$. The plot shows the density at time $t = 30$ for $N = 1$ and $N = 2$ (blue line). A reference solution is calculated with $N = 6$ moment equations (black line).

Current Work in Progress: Coupled System for Rectilinear Flow

We consider $\mathbf{u} = (0, 0, w(x, y, t))^T$, $f(x, y, t, \phi, \theta)$. We get

$$\begin{aligned} & \sin \theta \partial_t f(x, y, t, \phi, \theta) + \partial_x (\cos \phi \sin \theta \cos \theta f) + \partial_y (\sin \phi \sin \theta \cos \theta f) \\ & + \partial_\theta ((w_x \sin^3 \theta \cos \phi + w_y \sin \phi \sin^3 \theta) f) = D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f \right) + \partial_\theta (\sin \theta \partial_\theta f) \right) \end{aligned} \quad (5)$$
$$Re \partial_t w(x, y, t) = \partial_{xx} w + \partial_{yy} w + \delta \left(\bar{\rho} - \int_0^{2\pi} \int_0^\pi f \sin \theta d\theta d\phi \right).$$

Current Work in Progress: Coupled System for Rectilinear Flow

We consider $\mathbf{u} = (0, 0, w(x, y, t))^T$, $f(x, y, t, \phi, \theta)$. We get

$$\begin{aligned} & \sin \theta \partial_t f(x, y, t, \phi, \theta) + \partial_x (\cos \phi \sin \theta \cos \theta f) + \partial_y (\sin \phi \sin \theta \cos \theta f) \\ & + \partial_\theta ((w_x \sin^3 \theta \cos \phi + w_y \sin \phi \sin^3 \theta) f) = D_r \left(\partial_\phi \left(\frac{1}{\sin \theta} \partial_\phi f \right) + \partial_\theta (\sin \theta \partial_\theta f) \right) \end{aligned} \quad (5)$$
$$Re \partial_t w(x, y, t) = \partial_{xx} w + \partial_{yy} w + \delta \left(\bar{\rho} - \int_0^{2\pi} \int_0^\pi f \sin \theta d\theta d\phi \right).$$

The system of hierarchy of moment equations is given as

$$\partial_t Q + A \partial_x Q + B \partial_y Q = D(w_x, w_y) Q + D_r E Q. \quad (6)$$





Figure 3: Numerical solution of the drift-diffusion term for fixed w_x and w_y .





Figure 4: Numerical results for c_0^0 at different times using $D_r = 1$ and $w_x = w_y = 1$ for $x < 50$ and $w_x = w_y = -1$ otherwise. A cluster with higher particle density splits into two, each moving in opposite directions.



S. Dahm, J. Giesselmann, and C. Helzel.

Numerical discretisation of hyperbolic systems of moment equations describing sedimentation in suspensions of rod-like particles, 2024.



S. Dahm and C. Helzel.

Hyperbolic systems of moment equations describing sedimentation in suspensions of rod-like particles.

Multiscale Modeling & Simulation, 20(3):1002–1039, 2022.



É. Guazzelli and J. F. Morris.

A physical introduction to suspension dynamics. With illustrations by Sylvie Pic.

Camb. Texts Appl. Math. Cambridge: Cambridge University Press, 2012.



C. Helzel and F. Otto.

Multiscale simulations for suspensions of rod-like molecules.

J. Comput. Phys., 216(1):52–75, 2006.



C. Helzel and M. Schneiders.

Numerical approximation of the Smoluchowski equation using radial basis functions.

J. Comput. Math., 38(1):176–194, 2020.



C. Helzel and A. E. Tzavaras.

A kinetic model for the sedimentation of rod-like particles.

Multiscale Model. Simul., 15(1):500–536, 2017.



M. Morimoto.

Analytic functionals on the sphere, volume 178 of *Transl. Math. Monogr.*

Providence, RI: American Mathematical Society, 1998.