

Using DatabaseConnector through DBI and dbplyr

Martijn J. Schuemie

2022-11-18

Contents

1	Introduction	1
2	Connecting	1
3	Querying	2
4	Using dbplyr	2
4.1	Allowed table and field names in dbplyr	3
5	Temp tables	3
5.1	Temp tables in dbplyr	4
5.2	Cleaning up emulated temp tables	4
6	Closing the connection	4

1 Introduction

This vignette describes how to use the `DatabaseConnector` package through the `DBI` and `dbplyr` interfaces. It assumes you already know how to create a connection as described in the ‘Connecting to a database’ vignette.

All functions of the `DatabaseConnector` DBI interface apply SQL translation, thus making it an interface to a virtual database platform speaking OHDSISql as defined in `SqlRender`.

2 Connecting

We can use the `dbConnect()` function, which is equivalent to the `connect()` function:

```
connection <- dbConnect(  
  DatabaseConnectorDriver(),  
  dbms = "postgresql",  
  server = "localhost/postgres",  
  user = "joe",
```

```
password = "secret"  
)
```

```
## Connecting using PostgreSQL driver
```

```
dbIsValid(conn)
```

```
## [1] TRUE
```

3 Querying

Querying and executing SQL can be done through the usual DBI functions, for example:

```
dbGetQuery(connection, "SELECT TOP 3 * FROM cdmv5.person")
```

```
##   person_id gender_concept_id year_of_birth  
## 1         1             8507         1975  
## 2         2             8507         1976  
## 3         3             8507         1977
```

Or:

```
res <- dbSendQuery(connection, "SELECT TOP 3 * FROM cdmv5.person")  
dbFetch(res)
```

```
##   person_id gender_concept_id year_of_birth  
## 1         1             8507         1975  
## 2         2             8507         1976  
## 3         3             8507         1977
```

```
dbHasCompleted(res)
```

```
## [1] TRUE
```

```
dbClearResult(res)  
dbDisconnect(res)
```

4 Using dbplyr

We can create a table based on a `DatabaseConnector` connection. The `inDatabaseSchema()` function allows us to use standard `databaseSchema` notation promoted by `SqlRender`:

```
library(dplyr)  
person <- tbl(connection, inDatabaseSchema("cdmv5", "person"))  
person
```

```
##   person_id gender_concept_id year_of_birth
## 1         1           8507         1975
## 2         2           8507         1976
## 3         3           8507         1977
```

we can apply the usual `dplyr` syntax:

```
person %>%
  filter(gender_concept_id == 8507) %>%
  count() %>%
  pull()
```

```
## [1] 1234
```

Because of `SqlRender` translation, we can even use non-standard SQL such as `DATEADD`:

```
observationPeriod <- tbl(connection, inDatabaseSchema("cdmv5", "observation_period"))
observationPeriod %>%
  filter(
    datediff(day, observation_period_start_date, observation_period_end_date) > 365
  ) %>%
  count() %>%
  pull()
```

```
## [1] 987
```

4.1 Allowed table and field names in `dbplyr`

Because of the many idiosyncrasies in how different dataplatforms store and transform table and field names, it is currently not possible to use any names that would require quotes. So for example the names `person`, `person_id`, and `observation_period` are fine, but `Person ID` and `Obs. Period` are not. In general, it is recommend to use lower case snake_case for database table and field names.

5 Temp tables

The DBI interface uses temp table emulation on those platforms that do not support real temp tables. This does require that for those platforms the user specify a `tempEmulationSchema`, preferably using

```
option(sqlRenderTempEmulationSchema = "a_schema")
```

Where `"a_schema"` refers to a schema where the user has write access. If we know we will need temp tables, we can use the `assertTempEmulationSchemaSet()` to verify this option has been set. This function will throw an error if it is not set, but only if the provided dbms is a platform that requires temp table emulation.

In `OHDSISql`, temp tables are referred to using a `#` prefix. For example:

```
dbWriteTable(connection, "#temp", cars)
```

```
## Inserting data took 0.053 secs
```

5.1 Temp tables in dbplyr

The `copy_to` function creates a temp table:

```
carsTable <- copy_to(connection, cars)
```

```
## Created a temporary table named #cars
```

The `compute()` function also creates a temp table, for example:

```
tempTable <- person %>%  
  filter(gender_concept_id == 8507) %>%  
  compute()
```

```
## Created a temporary table named #dbplyr_001
```

5.2 Cleaning up emulated temp tables

Emulated temp tables are not really temporary, and therefore have to be removed when no longer needed. A convenient way to drop all emulated temp tables created so far in an R session is using the `dropEmulatedTempTables()` function:

```
dropEmulatedTempTables(connection)
```

In our example, this does not do anything because we were using a PostgreSQL server, which does natively support temp tables.

6 Closing the connection

We can use the `dbDisconnect()` function, which is equivalent to the `disconnect()` function:

```
dbDisconnect(connection)
```