



UNIVERSITY OF PISA
School of Engineering

CLOUD COMPUTING

A MAPREDUCE IMPLEMENTATION OF BLOOM FILTERS

Supervisors

Nicola Tonellotto
Carlo Vallati

Students

Marco Pinna
Olgerti Xhanej
Federico Cristofani
Matteo Biondi

July 4, 2022

Contents

1	Introduction	2
2	Overview and design choices	4
2.1	Bloom filters	4
2.2	Algorithms design	5
2.2.1	Compute parameters	5
2.2.2	Create Bloom filters	6
2.2.3	Test filters	9
2.3	Considerations and hypotheses	10
3	Hadoop	11
4	Spark	14
5	Performance	15

Chapter 1

Introduction

This work concerns the design, implementation and testing of Bloom filters using the MapReduce framework, both in Java and in Python.

The specifications are detailed in the following:

You will build a bloom filter over the ratings of movies listed in the [IMDb datasets](#). The average ratings are rounded to the closest integer value, and you will compute a bloom filter for each rating value.

In your Hadoop implementation, you must use the following classes:

- `org.apache.hadoop.mapreduce.lib.input.NLineInputFormat`: splits N lines of input as one split;
- `org.apache.hadoop.util.hash.Hash.MURMUR_HASH`: the hash function family to use.

In your Spark implementation, you must use/implement analogous classes.

In this project you must:

1. design a MapReduce algorithm (using pseudocode) to implement the bloom filter construction;
2. implement the MapReduce bloom filter construction algorithm using the Hadoop framework;
3. implement the MapReduce bloom filter construction algorithm using the Spark framework;
4. test both implementations on the IMDb ratings dataset, computing the exact number of false positives for each rating;
5. write a project report detailing your design, implementations and reporting the experimental results.

The work is organized as follows:

- In chapter 2 a brief overview of Bloom filters is given. Then the general algorithm is presented, with two possible implementations, together with design choices and hypotheses or considerations that have been made about the dataset to be used or the use-cases of the Bloom filters.

- Chapter 3 concerns the Java implementation of the algorithm, that makes use of Hadoop framework.
- Chapter 4 concerns the Python implementation of the algorithm, that makes use of Spark framework
- In chapter 5 an evaluation of the performance of both implementation is provided.

The entire codebase is available at <https://github.com/MPinna/MapReduceBloomFilter>

Chapter 2

Overview and design choices

In this chapter we firstly present a brief overview of what Bloom filters are (partly taken from the project specifications); then we show the general algorithm, with two possible implementation along with their respective pseudo-code, together with design choices and hypotheses that have been made during the design process. Finally, some considerations about the dataset to be used and the use cases of the Bloom filter are made.

2.1 Bloom filters

A *Bloom filter* is a space-efficient probabilistic data structure that is used for membership testing.

A Bloom filter consists of a bit-vector with m elements and k hash functions to map n keys to the m elements of the bit-vector.

The two possible operations that can be done on a Bloom filter are **add** and **test**.

Given a key id_i , every hash function h_1, \dots, h_k computes the corresponding output positions and sets the bit in that position to 1.

The space efficiency of Bloom filters comes at the cost of having a non-zero probability of false positives. The false positive rate (FPR) of a Bloom filter is denoted by p .

Therefore the two possible outcomes of the **test** function of the Bloom filter are “Possibly in set” or “Definitely not in set”.

The relations between n , m , k and p are expressed by the following formulas, which can be used to compute the optimal value the Bloom filters parameters:

$$m = -\frac{n \ln p}{(\ln 2)^2}, \quad k = \frac{m}{n} \ln 2, \quad p \approx (1 - e^{-\frac{kn}{m}})^k \quad (2.1)$$

In this use case, Bloom filters will be used to check whether a movie in the IMDb dataset belongs to the set of movies having a certain average rating.

Movies in the IMDb datasets can be rated by users from 1.0 to 10.0. Rounding the

rating to the nearest integer yields 10 possible ratings. A total of 10 Bloom filter will then be built.

A total of three phases were designed for this purpose, each of which is carried out using MapReduce:

- **computation of the best parameters** for the filter, (possibly with constraints on the value of k): the distribution of movies among the different ratings is not uniform, therefore a different m for each of the 10 Bloom filters can be computed, according to how many movie that filter is going to contain;
- **creation of the Bloom filters**
- **testing of the Bloom filters**: the Bloom filters created in the previous step are designed with a certain FPR p . The testing is used to ensure that the filters do in fact have that FPR.

2.2 Algorithms design

2.2.1 Compute parameters

This initial phase takes care of counting how many movies belong to each of the 10 rating buckets and computing the optimal parameters to properly size the filters in the next phase; this is done to ensure that the filters have a certain FPR p without oversizing the bitArray, which would result in a waste of resources.

Algorithm 1 Compute Parameters Mapper

```

1: procedure COMPUTEPARAMSMAPPER(splitId a, split s)
2:   ratingCount  $\leftarrow$  new int[NUM_RATINGS]
3:   for movie m in split s do
4:     ratingCount[m.rating - 1]  $\leftarrow$  rating_count[m.rating - 1] + 1
5:   end for
6:   for i=1,2,...,MAX_RATING do
7:     emit(i, ratingCount[i-1])
8:   end for
9: end procedure

```

Algorithm 2 Compute Parameters Reducer

```

1: procedure COMPUTEPARAMSREDUCER(rating  $r$ , ratingCounts  $[c_1, c_2, \dots, c_{10}]$ )
2:   ratingCountSum  $\leftarrow 0$ 
3:   for ratingCount  $c$  in ratingCounts do
4:     ratingCountSum  $\leftarrow$  ratingCountSum +  $c$ 
5:   end for
6:   if no constraints on  $K$  then  $\triangleright$  passed as input to the script
7:      $m \leftarrow$  computeBestM(ratingCountSum,  $p$ )
8:      $k \leftarrow$  computeBestK(ratingCountSum,  $m$ )
9:   else
10:     $k \leftarrow$  constrainedK
11:     $m \leftarrow$  computeBestM(ratingCountSum,  $p$ ,  $k$ )
12:   end if
13:   emit( $r$ , ( $p$ , ratingCountSum,  $m$ ,  $k$ ))
14: end procedure

```

2.2.2 Create Bloom filters

The general idea of this MapReduce implementation is to split the IMDb dataset into partitions and have each mapper compute, from the movies contained in one partition, part of the information needed to build the relative final Bloom filters. The reducer(s) will then combine the data received from the mappers and merge it into a total of 10 Bloom filters.

Two different algorithms have been designed for the task: the first one computes the indexes on the mappers and sends them to the reducers which takes care of creating the Bloom filters; the second one creates the Bloom filters on the mapper(s), fills them partially and lets the reducers merge all the filters into the final 10 Bloom filters.

In the second implementation, since every mapper has to instantiate Let us see these two implementations more in detail:

With Indexes

Algorithm 3 Mapper

```

1: procedure MAPPERWITHINDEXES(splitId a, split s)
2:   for every movie m in split s do
3:     rating  $\leftarrow$  round(m.rating)
4:     len  $\leftarrow$  getBitArrayLen(rating)
5:     bitArrayIndexes  $\leftarrow$  new Array[k]
6:     for i=1,2,...,k do
7:       bitArrayIndexes[i]  $\leftarrow$   $h_i$ (m.id) % len
8:       emit(i, bitArrayIndexes)
9:     end for
10:  end for
11: end procedure

```

Algorithm 4 Reducer

```

1: procedure REDUCERWITHINDEXES(rating r, bitIndexes[b1[], b2[], ..., bj[]])
2:   len  $\leftarrow$  getBitArrayLen(rating)
3:   bloomFilter  $\leftarrow$  new BitArray[len]
4:   bloomFilter.set(allZeros)
5:   for every bitIndex b in bitIndexes do
6:     for every index i in b do
7:       bloomFilter[i]  $\leftarrow$  1
8:     end for
9:   end foremit(r, bloomFilter)
10: end procedure

```

With Bloom Filters

Algorithm 5 Mapper

```

1: procedure MAPPERWITHBLOOMFILTERS(splitId a, split s)
2:   for i=1,2,...,MAX_RATING do                                ▷ Create 10 empty Bloom filters
3:     len ← getBitArrayLen(i)
4:     bloomFilter_i ← new BitArray[len]
5:     bloomFilter_i.set(allZeros)
6:   end for
7:   for every movie m in splits do
8:     rating ← round(m.rating)
9:     bloomFilter_i.add(m.id)
10:  end for
11:  for i=1,2,...,MAX_RATING do
12:    emit(i, bloomFilter_i)
13:  end for
14: end procedure

```

Algorithm 6 Reducer

```

1: procedure REDUCERWITHBLOOMFILTERS(rating r, bloomFilters [bf1, bf2, ...,
  bfj])
2:   len ← getBloomFilterLen(r)
3:   bloomFilterResult ← new BitArray[len]
4:   bloomFilterResult.set(allZeros)
5:   for every bloomFilter bf in bloomFilters do
6:     bloomFilterResult ← bitwiseOr(bloomFilterResult, bf)
7:   end for
8:   emit(r, bloomFilterResult)
9: end procedure

```

2.2.3 Test filters

Algorithm 7 Testing mapper

```

1: procedure TESTMAPPER(splitId a, split s)
2:   savedBloomFilters  $\leftarrow$  loadBloomFiltersFromHDFS()
3:   trueNegativeCount  $\leftarrow$  new int[NUM_OF_RATINGS]
4:   falsePositiveCount  $\leftarrow$  new int[NUM_OF_RATINGS]
5:   for every movie m in split s do
6:     movieRating  $\leftarrow$  round(m.rating)
7:     for currentRating in 1,2,...,MAX_RATING do
8:       bloomFilter  $\leftarrow$  savedBloomFilters[currentRating]
9:       testResult = bloomFilter.test(m.id)
10:      if testResult == true and movieRating  $\neq$  currentRating then  $\leftarrow$  falsePos-
        itiveCount + 1
11:      end if
12:      if testResult == false and movieRating  $\neq$  currentRating then  $\leftarrow$  trueNeg-
        ativeCount + 1
13:      end if
14:    end for
15:  end for
16:  counter  $\leftarrow$  new int[2]
17:  for every bloomFilter in savedBloomFilters do
18:    bloomFilterRating  $\leftarrow$  bloomFilter.getRating()
19:    counter[0]  $\leftarrow$  falsePositiveCount[bloomFilterRating - 1]
20:    counter[1]  $\leftarrow$  trueNegativeCount[bloomFilterRating - 1]
21:    emit(bloomFilterRating, counter)
22:  end for
23: end procedure

```

Algorithm 8 Testing reducer

```

1: procedure TESTREDUCER(rating  $r$ , counters  $[c1[], c2[], \dots, cj[]]$ )
2:   falsePositiveCounter = 0
3:   trueNegativeCounter = 0
4:   for counter  $c$  in counters do
5:     if  $c[0] \geq 0$  and  $c[1] \geq 0$  then
6:       falsePositiveCounter  $\leftarrow$  falsePositiveCounter +  $c[0]$ 
7:       trueNegativeCounter  $\leftarrow$  trueNegativeCounter +  $c[1]$ 
8:     end if
9:   end for
10:  if falsePositiveCounter + trueNegativeCounter > 0 then
11:    FPR  $\leftarrow$  falsePositiveCounter / (falsePositiveCounter + trueNegativeCounter)
12:    emit( $r$ , FPR)
13:  end if
14: end procedure

```

2.3 Considerations and hypotheses

The IMDb dataset consists of a .tsv file with approximately 1200000 movies, one per row.

Although the IMDb dataset is updated daily, it was assumed that the Bloom filters to be designed are thought to be used with a constant dataset.

Chapter 3

Hadoop

The first version to be implemented in Java, using the Hadoop framework.
The folder structure of the project is the following:

```
hadoop
├── main/java/it/unipi/hadoop
│   ├── BloomFilter.java
│   ├── MapRedComputeParams.java
│   ├── MapRedBloomFilter.java
│   ├── MapRedFalsePositiveRate.java
│   └── Util.java
```

- The `BloomFilter.java` class contains the implementation the Bloom filter.
The *bitArray* structure of the Bloom filter was realized by using the `BitSet` class available in the `java.util.BitSet` Java library. It already comes with built-in methods for setting/resetting all the bits, performing bit-wise operations on it and serializing/deserializing the array. The family of hash functions that was used — as requested in the specifications — is the MurmurHash, which can be found in the `org.apache.hadoop.util.hash.MurmurHash` Java library.
- The `MapRedComputeParams.java` class is used to compute the optimal filter parameters according to the constraints passed as input via command line.
- The `MapRedBloomFilter.java` is the main class that contains all the MapReduce logic for the creation of the Bloom filters. It contains both the versions of the algorithm: the one *withIndexes* and the one *withBloomFilters*. One can toggle between the two by simply changing one command line argument when launching the program on the cluster.

- The `MapRedFalsePositiveRate.java` is used to test the Bloom filters created by the previous class and check if the empirical FPR is actually consistent with the theoretical one that was yielded by `MapRedComputeParams.java` and used by `MapRedBloomFilter.java`.
- The `Util.java` class contains constants and utility functions that are used in the rest of the code, such as the ones for parsing and splitting the input rows.

All the `MapRed*` classes take as command line argument — among the other parameters — the size of the split to be given as input to each mappers (i.e. the `num_lines_per_split` argument); this parameter directly controls the number of mappers that are instantiate during the Map phase. To do this, the `NLineInputFormat` class was used, as required by the specification, which can be found in the `org.apache.hadoop.mapreduce.lib.input.NLineInputFormat` Java library.

The three `MapRed*` classes can be run with the following commands:

```
hadoop jar it/unipi/hadoop/BloomFilter/1.0/BloomFilter-1.0.jar
it.unipi.hadoop.MapRedComputeParams title.ratings.tsv output
0.01 157000
```

`title.ratings.tsv` is the input file, `output` is the name of the output file `0.01` is the desired value for the p and `157000` is the size of the partition to be handled to each mapper.

```
hadoop jar it/unipi/hadoop/BloomFilter/1.0/BloomFilter-1.0.jar
it.unipi.hadoop.MapRedBloomFilter title.ratings.tsv output
157000 24404 63482 171928 420900 990060 2117062 3578304
3406703 1092505 156103 7 WithBloomFilters
```

`title.ratings.tsv` is the input file, `output` is the name of the output file, `157000` is the size of the partition to be handled to each mapper, the ten numbers that follow are the values for m for each filter, `7` is the value for k and `WithBloomFilters` is a flag that toggles which of the two implementations is to be run.

```
hadoop jar it/unipi/hadoop/BloomFilter/1.0/BloomFilter-1.0.jar
it.unipi.hadoop.MapRedFalsePositiveRateTest title.ratings.
tsv testOutput 157000 output/part-r-00000 hadoop-namenode
9820
```

`title.ratings.tsv` is the input file, `testOutput` is the name of the output file, `157000`

is the size of the partition to be handled to each mapper, `output/part-r-00000` is the file from which the saved Bloom filters have to be read, `hadoop-namenode` is the host and `9820` is the port.

Chapter 4

Spark

Chapter 5

Performance

This final chapter concerns the performance evaluation of the different implementations of the algorithms.

Deployment and testing were both performed on a cluster of four virtual machines provided by the University. Each of them was a Ubuntu machine with 2 cores and 8 GB of RAM.