Calibrating the Alarms: A Registry-Grounded, Human-Validated Measurement of Poisoning Detectors on 16,763 MCP Tool Descriptions

Sajjad Rahim Nouri — Islamic Azad University, Ramsar Branch

Abstract

Model Context Protocol (MCP) tool descriptions are server-authored natural-language metadata that may be presented to an agent during tool selection. That design creates an attack surface, but it also creates a measurement problem: keyword detectors can mistake security guidance, product documentation, and capability declarations for behavioral steering. This study examines 16,763 tool descriptions extracted from GitHub-linked servers in a cursor-bounded prefix of the official MCP Registry. A frozen detector emits 4,926 flag instances and marks 698 descriptions with at least one poison-family pattern. A purposive discovery review covers the 100 highest-scoring descriptions and 50 zero-capability/zero-poison controls. Five of the 100 high-score descriptions contain instruction-shaped text that meets a strict, text-bound steering rule; 95 do not. At the flag level, six of 124 reviewed poison flags are supported. This is a calibration result for a high-score discovery stratum, not an estimate of poisoning prevalence. Negated assurances and defensive instructions account for many false alarms. In a synthetic, mocked harness, a matched 36-trial source–neutral comparison showed a difference in workflow-priority capture (6/9 source versus 0/9 neutral); a credential-funnel outcome was task-confounded (9/9 in both arms) and is not attributed to description wording. The accompanying artifact contains the corpus, detector, labels, and evidence-linked adjudication records.

1. Introduction

MCP lets applications give language models access to tools. A tool manifest contains a name, a schema, and a natural-language description; clients commonly provide those descriptions to the model during tool selection. The description is therefore a channel where a server author can state what a tool does, but also where a server can phrase instructions about what an agent should prioritize, disclose, or pass to another tool.

This channel has motivated warnings about tool poisoning, tool shadowing, and indirect prompt injection. The risk is real enough to justify measurement, but a raw count from a keyword scanner is not a measurement of vulnerabilities. Words such as *always*, *never*, *secret*, or *execute* also occur in ordinary documentation, safety guarantees, and defensive instructions. Treating every lexical hit as a hostile tool inflates a detector's output and can penalize authors who document safe behavior clearly.

The question is narrower: when a simple detector fires on registry-grounded tool descriptions, how much of that signal survives a strict reading of the text? The analysis measures a frozen detector on a defined source-extracted corpus, audits its highest-score output, and describes the detector's failure modes. It does not estimate the prevalence of malicious MCP servers, infer author intent, or treat a text pattern as an exploitable vulnerability.

The paper makes three contributions.

1. A reproducible, registry-grounded corpus of 16,763 source-extracted tool descriptions, together with detector candidate rates and explicit coverage limits.
2. A fixed high-score discovery sample reviewed under a text-bound rubric. The primary result is five rubric-positive descriptions among 100 high-score rows. Supplementary flag-level adjudication supports 6 of 124 poison-family instances in the same purposive review stratum; the remaining detector output is best treated as a triage queue.

3. An error taxonomy and a small mocked tool-calling study. Together, they distinguish instruction-shaped text worth reviewing from claims about deployed exploitation.

2. Background and scope

An MCP client obtains a list of available tools and uses names, descriptions, and schemas to help a model select a call. A tool definition contains a name, an input schema, and an optional natural-language description; clients can use that description to improve a model's understanding of available tools [2]. The protocol does not by itself establish that an instruction-shaped sentence in a description has the same authority as operator policy. Client implementations differ, so this paper studies the text surface rather than making a universal claim about every MCP client.

Here, *capability* denotes a factual description of an action a tool can take, such as making a network request or writing a file. A *poison pattern* is text that adds a behavioral instruction to the model beyond the tool's declared function, for example a universal instruction to call one tool before every other tool. Model-addressed wording is recorded separately as a channel property. A capability flag is never counted as a poisoning finding, and model-addressed wording is never treated as malicious by itself.

The study concerns public registry metadata and public repository source. It does not contact third-party MCP endpoints, execute third-party server code, or test real targets. The security mapping is adjacent to tool misuse and supply-chain risks in the OWASP Top 10 for Agentic Applications [1].

3. Related work

Recent MCP security work has taken three complementary forms. Benchmarks such as MCPTox and MCP-TDP construct attack cases to test whether agents can be steered by tool metadata [4,5]. MSB evaluates broader MCP attack scenarios with executable tools [6]. These works show what an attack channel can do; their rates are properties of their constructed datasets rather than prevalence estimates for a public registry.

Ecosystem and scanner studies ask different questions. MCPZoo studies runtime servers across multiple markets and evaluates scanner reliability with manual review [7]. Its unit is a server-level scanner alert and its ontology includes runtime vulnerabilities; ours is a tool-description flag judged against a text-bound steering rule. The studies are therefore not numerically comparable, but they support the same methodological lesson: scanner output needs calibration before it is interpreted as ecosystem risk.

Surveys, protocol analyses, and targeted server audits provide threat models and architectural context [8–10]. The contribution is not a new attack benchmark, but an auditable calibration of a frozen description detector on a registry-grounded, source-extracted population.

4. Data and methods

4.1 Population and collection

On 21 September 2026, cursor pagination over the official MCP Registry API [3] collected 60,000 per-version records. Deduplication to the record marked `isLatest` yielded 17,167 server records. The cursor remained live at the pre-authorized 600-page stop, making this a cursor-order prefix rather than a registry census. Of those records, 11,288 linked to GitHub repositories. Extraction from public repository source yielded 16,763 descriptions from 4,725 repositories.

The resulting corpus represents source descriptions extracted from GitHub-linked, registry-listed servers. It does not represent live manifests served by remote MCP endpoints, registry entries without an extractable GitHub source, or the portion of the registry beyond the cursor stop. These limits apply to

every population-level number in this paper. Figure 1 separates the collection pipeline, detector output, and the purposive review frame so that those denominators are not conflated.



Figure 1: Collection and audit flow. The review is a purposive discovery stratum, so its outcomes calibrate detector output rather than estimate ecosystem prevalence.

4.2 Frozen detector

We evaluate an author-developed, frozen lexical baseline intended for candidate generation; it is not presented as representative of MCP security scanners generally. Version 1 of the baseline is recoverable at commit `6cca247`; version 2 retains its ranking rule and adds two separately reported instruction-channel checks. The baseline contains 18 checks: seven capability checks, nine poison checks (including two structural checks), and two channel checks. Its capability family covers network egress, shell execution, file access, secret/environment access, database writes, and package installation. Its poison family covers imperative-to-model, exfiltration, concealment, cross-tool shadowing, fake-system-role, important-tag, and sensitive-file patterns. Two channel checks identify model-addressed and second-person-imperative prose.

The detector is a candidate generator. It makes no verdict about malware, exploitability, or author intent. The current version adds channel measurements without changing the earlier suspicion-score definition used to select the review queue.

Reproducibility item	Frozen procedure
Ranking	`suspicion_score = capability flags + 3 × poison flags`; channel flags do not contribute
Tie-breaking	Stable descending sort: ties retain corpus order
High-score frame	First 100 rows after that ranking
Controls	50 uniform-random rows with zero capability and poison flags; channel flags may remain
Control selection	Seed 42 over the frozen frame
Review text	Full stored description, rather than the 300-character CSV excerpt

4.3 Human review as discovery, not prevalence estimation

A high-score discovery design was used to identify concrete instruction-shaped cases for close reading and safe mock evaluation. The fixed frame contains the top 100 rows by frozen suspicion score plus 50 randomly selected rows with no capability or poison flags; some controls can carry a channel flag. This design is useful for finding rare cases; it is not a probability sample of all detector hits.

The author assigned a row-level label using a written rule: separate the tool's declared function from an added behavioral instruction to the model. A row is a true positive only when at least one poison flag is supported by that rule. Capability and channel flags never make a row positive. All 150 labels contain a rationale and were reviewed against the full stored description rather than the CSV excerpt.

An evidence-linked, flag-level table is also retained for diagnosing individual rules: 132 instance assessments are typed from the author's row notes and 136 began as AI-assisted text-bound drafts. The author reviewed and accepted all 136 in an append-only sign-off record. The row-level human labels remain the primary validation result; the flag-level table is supplementary rule analysis, not an independent reliability measurement. Reference labels were adjudicated by the author; no independent human inter-rater validation is claimed.

4.4 Mocked behavior study

Synthetic fixtures were derived from reviewed text patterns, with targets and secrets replaced by inert examples. The harness never executes shell code, contacts third-party servers, or exposes real credentials. It uses fixed tasks, mock tools, and three repetitions for each arm and model. Existing observations concern two mechanisms: unconditional priority capture and a credential funnel. They are behavioral observations in the presence of the source-derived description, not evidence of an exploit against a real server.

A matched description-replacement experiment held the tool name, schema, task, filler tools, mock responses, system prompt, maximum turns, and judge constant; only the description was replaced with a capability-neutral version. It has 12 condition-cells (two mechanisms $\times$ two description conditions $\times$ three models), with three repetitions per cell, for 36 trials. The locked panel comprises `glm-5.3`, `deepseek-v4.1-flash`, and `gemini-3.8-flash` through the AvalAI OpenAI-compatible gateway. Requests used temperature 0; each trial began with a fresh message list, and the 36-trial order was randomized with seed 20261028. A transient transport failure received one end-of-batch retry; the append-only ledger preserves all 55 attempts and takes the last record for each scheduled trial. The workflow-priority endpoint is success only when the case tool is the first tool called in the transcript. This matched contrast tests whether that endpoint changes when instruction-bearing wording is removed; it does not make a claim about live MCP servers.

5. Results

5.1 Candidate rates

Across 16,763 descriptions, the detector flags 4,128 descriptions in at least one family (24.6%) and 698 descriptions with at least one poison-family pattern (4.2%). It emits 4,926 flag instances. These are candidate rates: they quantify detector output over the defined corpus and do not quantify the prevalence of tool poisoning.

5.2 High-score discovery review

All 150 sampled rows were labeled. Among the 100 highest-scoring rows, five meet the row-level rule for instruction-shaped steering and 95 do not. None of the 50 zero-capability and zero-poison controls

was labeled positive. The result establishes that the detector can surface descriptions worth close review, but that its highest-score queue is dominated by non-TP text. The controls were selected for detector-negative status and therefore do not estimate false negatives, recall, or the prevalence of steering outside the flagged stratum.

At the poison-flag level, six of 124 reviewed instances are supported by the steering rubric. This supplementary 4.8% quantity is limited to the purposive discovery stratum. It is neither an estimate of detector precision over all 698 poison-flagged descriptions nor an estimate of malicious prevalence.

Review unit	Frame	Result	Interpretation
Row-level steering	100 high-score rows	5 / 100	discovery yield, not prevalence
Poison-flag support	124 reviewed poison flags	6 / 124	text-support rate in the discovery stratum
Detector-negative controls	50 zero-capability/zero-poison rows	0 / 50 row positives	not a false-negative or recall estimate

The corresponding all-family count, 82 supported instances of 268, should not be read as a poisoning rate: it includes factual capability and channel assertions. The released artifact retains that table for detector debugging, but it is not used as the paper's headline result.

5.3 What produced the false alarms

The 95 flagged non-TP rows expose recurring lexical failure modes. Twenty-four contain negated assurances such as statements that credentials never leave a device. Eighteen are defensive or anti-injection instructions, where a tool tells the agent not to follow untrusted content. Eleven are ordinary parameter names or API terminology that overlap with the detector's keywords. Other groups are template duplication, ordinary product-flow documentation, declared sending functionality, authentication wording, and bare URLs.

This is a substantive result. The observed errors show that lexical overlap can cause ordinary documentation and defensive instructions to be flagged as steering. A production triage system should therefore model negation, defensive vocabulary, scope, and repeated templates before ranking text as high-risk.

Frequent non-TP pattern	Rows in the 95 flagged non-TP rows
Negated assurance	24
Defensive or anti-injection instruction	18
Parameter or API terminology	11

5.4 Reviewed instruction-shaped mechanisms

The five row-level positives correspond to four mechanisms after deduplicating one same-server pair. They are reported as *attack-shaped mechanisms*, not as disclosed vulnerabilities.

- **Universal priority capture.** A description instructs the agent to call one tool before any other tool. This is structurally a cross-tool policy even when the stated purpose is workflow guidance.
- **Conditional gateway capture.** A paired description asks to be called first before recommending or installing other servers. The tool's metadata function may be legitimate; the concern is the added universal ordering rule.

- **Exec priming.** A description directs an agent to execute tool-supplied commands through its own shell. The live task used for this mechanism was outcome-conflated with returning an install guide, so it is not used as steering evidence.
- **Credential funnel.** A description asks the agent to deposit every credential it encounters, including credentials from context, into one tool. The concern is the universal acquisition instruction, not the existence of a legitimate credential store.

These cases show why a detector should retain examples for review. They do not establish that any author intended harm or that a deployed client would follow the text.

6. Mocked behavior study

The original matrix completed 54 synthetic trials across three gateway-exposed model versions; 51 were valid under pre-registered operational criteria. The exec-priming arm is reported only as a design lesson because its benign task required surfacing an install guide. The remaining source-derived arms observed priority capture and credential transfer behavior in the mocked environment. No live server, real credential, shell, or external network target was used.

The matched ablation completed all 36 trials across 12 condition-cells after retrying transient gateway failures. For workflow-priority capture, the source description triggered the endpoint in 6/9 trials (GLM 3/3, DeepSeek 3/3, Gemini 0/3), while its neutral twin triggered it in 0/9. Within this harness, the contrast supports a contribution from the description wording.

For the credential funnel, both source and neutral conditions were 9/9. The task explicitly asked the model to store the synthetic key, so this endpoint is task-confounded: it is not attributed to description wording or counted as causal evidence. These counts are fixed panel results, not population estimates or live-server vulnerability findings. Figure 2 presents the two contrasts side by side; only the workflow-priority contrast supports a description-level interpretation in this design.

Mechanism and condition	GLM	DeepSeek	Gemini	Total	Reading
WF source	3/3	3/3	0/3	6/9	source–neutral difference appears in two models
WF neutral	0/3	0/3	0/3	0/9	matched neutral baseline
DP source	3/3	3/3	3/3	9/9	task-confounded
DP neutral	3/3	3/3	3/3	9/9	task-confounded




Figure 2. Matched ablation results. The workflow-priority contrast is interpretable within the mocked harness; the credential-funnel contrast is not, because the task itself requested storage.

7. Discussion

The central finding is methodological. Registry-scale detector output is useful as a candidate queue, but raw output is not a count of poisoning findings. In the high-score review frame, the poison family yields a small number of rubric-supported cases alongside a much larger number of lexical false alarms.

The study also draws a practical boundary. Capability declarations are relevant to impact, but they do not establish steering. Likewise, a model-facing sentence can be security guidance rather than manipulation. A useful detector should ask whether an instruction is universal or conditional, whether it reaches beyond the tool's declared function, whether it redirects another tool, and whether negation or defensive language changes its meaning.

Several limitations shape the interpretation. The corpus is a cursor-bounded, GitHub-linked, source-extracted subset of the registry. The review frame was designed to find cases, not estimate a population rate, and its reference labels were supplied by one author rather than independently double-annotated. Descriptions can be truncated during source extraction, and the detector is English-oriented. The matched ablation covers two mechanisms, three models, and one mocked gateway deployment; a redesigned credential-funnel task and broader replication remain future work.

8. Ethics and artifact availability

All collection used public registry metadata and public repository source. The study did not execute third-party code or contact third-party MCP endpoints. Fixtures use synthetic tools, inert domains, and artificial credential markers. The paper does not name a server as malicious, publish an unpatched exploit path, or claim that the reviewed patterns are deployed vulnerabilities.

The companion repository contains raw registry snapshots, the extracted corpus, frozen detector code, review rubric, labels, evidence-linked adjudication, and sanitized mock transcripts. The manuscript-matched artifact is identified by Git tag `v1.1.1`; its version-specific Zenodo DOI will be inserted only after archival publication is complete.

References

[1] OWASP GenAI Security Project. *OWASP Top 10 for Agentic Applications 2026*. Version 2026, December 2025. Official resource.

[2] Model Context Protocol. *MCP specification: tools*. Official specification.

[3] Model Context Protocol. *Official MCP Registry reference*. Registry documentation.

[4] Zhiqiang Wang et al. *MCPTox: A Benchmark for Tool Poisoning Attack on Real-World MCP Servers*. arXiv:2508.14925, 2025. arXiv.

[5] Shi Liu et al. *When the Manual Lies: A Realistic Benchmark to Evaluate MCP Poisoning Attacks for LLM Agents*. arXiv:2605.24069, 2026. arXiv.

[6] Dongsen Zhang et al. *MCP Security Bench: Benchmarking Attacks Against Model Context Protocol in LLM Agents*. arXiv:2510.15994, 2025. arXiv.

[7] Pei Chen et al. *Rethinking MCP Security: A Large-Scale Study of Runtime MCP Servers and Security Scanner Reliability*. arXiv:2607.11086, 2026. arXiv.

[8] Mohammed Mehedi Hasan et al. *Model Context Protocol (MCP) at First Glance: Studying the Security and Maintainability of MCP Servers*. arXiv:2506.13538, 2025. arXiv.

[9] Xinyi Hou et al. *Model Context Protocol (MCP): Landscape, Security Threats, and Future Research Directions*. arXiv:2503.23278, 2025. arXiv.

[10] Hao Song et al. *Beyond the Protocol: Unveiling Attack Vectors in the Model Context Protocol (MCP) Ecosystem*. *IEEE Transactions on Software Engineering*, 52(8):2410–2426, 2026. DOI.