NAME: M R GANGAMMA

USN: 1RUA25BCA0056

LAB 9

Program 1: Implementation of a Basic Stored Procedure

Query/Input:

```
DELIMITER //
CREATE PROCEDURE GetEmployees()
BEGIN
  SELECT * FROM EMPLOYEE;
END //
DELIMITER ;
CALL GetEmployees();
```

Output:

Output:

emp_id	emp_name	dept_id
101	Clark	1
102	Dave	2
103	Ava	1
104	Emma	3
105	John	NULL

Program 2: Stored Procedure for INSERT Operation

Query/Input:

```
DELIMITER //
CREATE PROCEDURE InsertEmployee(
  IN p_emp_id INT,
  IN p_emp_name VARCHAR(50),
```

```
    IN p_dept_id INT
)
BEGIN
    INSERT INTO EMPLOYEE (emp_id, emp_name, dept_id)
    VALUES (p_emp_id, p_emp_name, p_dept_id);
END //
DELIMITER ;
CALL InsertEmployee(106, 'Peter', 2);
SELECT * FROM EMPLOYEE;
```

Output:

Output:

```
+--------+----------+---------+
| emp_id | emp_name | dept_id |
+--------+----------+---------+
|    101 | Clark    |       1 |
|    102 | Dave     |       2 |
|    103 | Ava      |       1 |
|    104 | Emma     |       3 |
|    105 | John     |    NULL |
|    106 | Peter    |       2 |
+--------+----------+---------+
```

.

Program 3: Stored Procedure for UPDATE Operation

Query/Input:

```
DELIMITER //
CREATE PROCEDURE UpdateEmployee(
    IN p_emp_id INT,
    IN p_new_dept_id INT
)
BEGIN
    UPDATE EMPLOYEE
```

```
    SET dept_id = p_new_dept_id
    WHERE emp_id = p_emp_id;
END //
DELIMITER ;
CALL UpdateEmployee(106, 3);
SELECT * FROM EMPLOYEE;
```

Output:

Output:

emp_id	emp_name	dept_id
101	Clark	1
102	Dave	2
103	Ava	1
104	Emma	3
105	John	NULL

Program 4: Stored Procedure for DELETE Operation

Query/Input:

```
DELIMITER //
CREATE PROCEDURE DeleteEmployee(
    IN p_emp_id INT
)
BEGIN
    DELETE FROM EMPLOYEE
    WHERE emp_id = p_emp_id;
END //
DELIMITER ;
CALL DeleteEmployee(106);
SELECT * FROM EMPLOYEE;
```

Output:

emp_id	emp_name	dept_id
101	Clark	1
102	Dave	2
103	Ava	1
104	Emma	3
105	John	NULL