# So You Wanna Get Good At LATEX

Marcell Howard

August 16, 2025

► There are a bunch of packages we can import but which ones should we import? We'll break it up in order of decreasing importance

- ► There are a bunch of packages we can import but which ones should we import? We'll break it up in order of decreasing importance
  - amsmath, amssymb, graphicx,

- ► There are a bunch of packages we can import but which ones should we import? We'll break it up in order of decreasing importance
  - amsmath, amssymb, graphicx,
  - physics, hyperref, caption, subcaption, wrapfig, xparse, physunits

- ► There are a bunch of packages we can import but which ones should we import? We'll break it up in order of decreasing importance
  - amsmath, amssymb, graphicx,
  - physics, hyperref, caption, subcaption, wrapfig, xparse, physunits
  - inputenc, chngcntr, nccmath, tensor,

amsmath

amssymb

graphicx

- amsmath
  - Contains every environment to write equations in
  - Allows for specified alignment of objects in aforementioned environments
- amssymb

graphicx

- amsmath
  - Contains every environment to write equations in
  - Allows for specified alignment of objects in aforementioned environments
- amssymb
  - Contains just about any math symbol you've encountered in your life
- graphicx

- amsmath
  - Contains every environment to write equations in
  - Allows for specified alignment of objects in aforementioned environments
- amssymb
  - Contains just about any math symbol you've encountered in your life
- graphicx
  - Use if want to include figures

physics

hyperref

- caption/subcaption
- wrapfig
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref

- caption/subcaption
- wrapfig
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
- caption/subcaption
- wrapfig
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
  - Makes urls hyperlinkable in bibliography
- caption/subcaption
- wrapfig
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
  - Makes urls hyperlinkable in bibliography
- caption/subcaption
  - Provides flexibility for captioning figures and subfigures
- wrapfig
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
  - Makes urls hyperlinkable in bibliography
- caption/subcaption
  - Provides flexibility for captioning figures and subfigures
- wrapfig
  - Allows for figures to be wrapped around the text
- xparse



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
  - Makes urls hyperlinkable in bibliography
- caption/subcaption
  - Provides flexibility for captioning figures and subfigures
- wrapfig
  - Allows for figures to be wrapped around the text
- xparse
  - Allows for creating new commands (using the \newcommands{}{})
- physunits



- physics
  - Contains just about everything a physicist could want
    - Macros for special/transcendental functions, derivatives, matrices, etc.
- hyperref
  - ► Makes the \ref command hyperlinkable
  - Makes urls hyperlinkable in bibliography
- caption/subcaption
  - Provides flexibility for captioning figures and subfigures
- wrapfig
  - Allows for figures to be wrapped around the text
- xparse
  - Allows for creating new commands (using the \newcommands{}{})
- physunits
  - Nice and intuitive commands for SI units

- nccmath
- tensor

- chngctr
- inputenc

- nccmath
  - ▶ Basically the amsmath package but more
- tensor

- chngctr
- inputenc

- nccmath
  - Basically the amsmath package but more
- tensor
  - Allows for phantom indices for coding matrices i.e.  $A^{\mu}_{\ \nu}$  instead of  $A^{\mu}_{\nu}$
- chngctr
- inputenc

- nccmath
  - Basically the amsmath package but more
- tensor
  - Allows for phantom indices for coding matrices i.e.  $A^{\mu}_{\ \nu}$  instead of  $A^{\mu}_{\ \nu}$
- chngctr
  - ► Resets counter for equations/figures/tables etc.
- inputenc

- nccmath
  - Basically the amsmath package but more
- tensor
  - Allows for phantom indices for coding matrices i.e.  $A^{\mu}_{\nu}$  instead of  $A^{\mu}_{\nu}$
- chngctr
  - ► Resets counter for equations/figures/tables etc.
- inputenc
  - Sets the unicode version for LATEX but is now obsolete

physics

- physics
  - ▶ \qty

- vector notation
- special functions

matrix macros

- physics
  - ► \qty
    - Can't use when using newline in an equation environment. Must use \left and \right with \ at the beginning and end of each line break
  - vector notation
  - special functions

matrix macros

- physics
  - ► \qty
    - Can't use when using newline in an equation environment. Must use \left and \right with \ at the beginning and end of each line break
  - vector notation
    - ▶ \vb{a}, \va{a}, \vu{a},
  - special functions

matrix macros

- physics
  - ► \qty
    - Can't use when using newline in an equation environment. Must use \left and \right with \ at the beginning and end of each line break
  - vector notation
    - ▶ \vb{a}, \va{a}, \vu{a},
  - special functions
    - $\triangleright$  \sin, \cos, \ldots,  $\rightarrow$  sin, cos, . . .
    - $ightharpoonup \langle \text{exp}, \text{log}, \text{ln}, \text{erf}, \text{ldots} \rightarrow \text{exp}, \text{log}, \text{ln}, \text{erf}, \dots \rangle$
  - matrix macros

- physics
  - \qty
    - Can't use when using newline in an equation environment. Must use \left and \right with \ at the beginning and end of each line break
  - vector notation
    - ▶ \vb{a}, \va{a}, \vu{a},
  - special functions
    - $\triangleright$  \sin, \cos, \ldots,  $\rightarrow$  sin, cos, . . .
    - $ightharpoonup \langle \text{exp}, \langle \text{log}, \langle \text{In}, \langle \text{erf}, \rangle \rangle \rangle + \exp, \log, \ln, \text{erf}, \dots$
  - matrix macros
    - \mqty(\imat{3}), \mqty(\pmat{3}), \mqty(\zmat{2}{2})

$$\to \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}, \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}, \begin{pmatrix} 0 & 0 \\ 0 & 0 \end{pmatrix}$$



amsmath

- amsmath
  - align
  - split

- amsmath
  - align
    - Aligns equations via placement of &
      - Updates equation counter
  - split
- physunits

- amsmath
  - align
    - Aligns equations via placement of &
      - Updates equation counter
  - split
    - Also aligns equations via placement of &
    - Does not update equation counter
- physunits

- amsmath
  - align
    - Aligns equations via placement of &
      - Updates equation counter
  - split
    - Also aligns equations via placement of &
    - Does not update equation counter
- physunits
  - ▶ Putting prefixes in front of units is very convenient i.e. kilometers becomes  $\mbox{\sc m[k]}$  to get  $\mbox{\sc km}$  and gigayears becomes  $\mbox{\sc y[G]}$  to get  $\mbox{\sc Gy}$

► Can use the back slash for spacing in text and equations

- Can use the back slash for spacing in text and equations
- Using ~ for a non-breaking space (so write Marcell Howard to prevent a line break between Marcell and Howard)

- Can use the back slash for spacing in text and equations
- Using ~ for a non-breaking space (so write Marcell Howard to prevent a line break between Marcell and Howard)
- ▶ Spacing in equations (-; = thick -: = medium -, = thin, -(space) = single space, -! = negative thin space,)

- Can use the back slash for spacing in text and equations
- Using ~ for a non-breaking space (so write Marcell Howard to prevent a line break between Marcell and Howard)
- Spacing in equations (-; = thick -: = medium -, = thin, -(space) = single space, -! = negative thin space,)
- Can use a double back slash for newlines

- Can use the back slash for spacing in text and equations
- Using ~ for a non-breaking space (so write Marcell Howard to prevent a line break between Marcell and Howard)
- Spacing in equations (-; = thick -: = medium -, = thin, -(space) = single space, -! = negative thin space,)
- Can use a double back slash for newlines
- ► The \rm command un-italicizes letters

## For Big Projects

► We can store the preamble, chapters, etc. in different TeX files and call them!

### For Big Projects

- ► We can store the preamble, chapters, etc. in different TeX files and call them!
- Use the \input, \include, or \import functions