

LINUX FILESYSTEM

DATE: 28/9/2025

By Saumya Arya

INTRODUCTION

The Linux filesystem is like the main storage system that keeps everything on a Linux computer organized. It helps the operating system know where different files, folders, and programs are stored. Just like how we keep our things in different drawers and shelves at home, the Linux filesystem keeps files in different directories.

Everything in Linux starts from a single root directory, written as a forward slash (/). From there, all other folders and files branch out like a tree. This system makes it easy to find and manage files in a neat and logical way.

In simple terms, the Linux filesystem is what allows users and the system to save, access, and organize data properly. Without it, the computer wouldn't know where anything is kept.

Introduction to Linux Filesystem

The Linux filesystem is the way Linux organizes and stores all data on a computer. Unlike Windows, which uses letters like C and D to identify drives, Linux uses a single root directory, written as `/`, and everything in the system is stored under it. This includes user files, programs, system configurations, and even devices.

One of the main ideas behind the Linux filesystem is that everything is treated as a file. This makes it easier for both the user and the system to access, manage, and interact with different types of data. For example, a printer, a hard drive, or a running process can all be accessed like a file.

The Linux filesystem has three important layers:

- **Logical File System:** The user-friendly interface that allows programs to read, write, or manage files.
- **Virtual File System:** A layer that lets multiple types of filesystems work together smoothly.
- **Physical File System:** The layer that actually manages data storage on disk drives, keeping everything organized at the hardware level.

This design ensures that Linux remains flexible, efficient, and reliable for both desktop and server systems.

Key features of Linux Filesystem

Linux filesystems have several features that make them powerful and secure. These include:

1. Hierarchical Structure

The Linux filesystem follows a tree-like structure, beginning at the root directory `/`. This hierarchy branches into various subdirectories, each serving a specific purpose, such as storing user data, system configurations, or executable programs.

2. Everything is a File

In Linux, everything is treated as a file. This includes not just regular data files but also directories, devices, and even system processes. This uniform approach simplifies the system's design and user interactions.

3. Device Files

Linux uses device files to represent hardware devices. These files are located in the `/dev` directory and allow programs to interact with hardware components like hard drives, printers, and terminals as if they were regular files.

4. Permissions and Security

Linux employs a robust permission system to control access to files and directories. Each file and directory has associated read, write, and execute permissions for the owner, group, and others. This system enhances security by ensuring that only authorized users can access or modify sensitive data.

5. Mounting

Linux allows the integration of different storage devices and filesystems into the main directory tree through a process called mounting. This means that external drives, network shares, or additional partitions can be accessed seamlessly within the existing directory structure.

6. Filesystem Hierarchy Standard (FHS)

The FHS defines the directory structure and directory contents in Unix-like operating systems. It provides guidelines for the placement of files and directories, ensuring consistency across different Linux distributions.

Some other features:

- **Journaling:** Some filesystems keep a log of changes that helps recover data in case of system failure.
- **Versioning:** Certain filesystems can save previous versions of files, providing automatic backups.
- **Inodes:** Linux uses inodes to store metadata like file size, location, ownership, and permissions.

Directory Structure

The Linux directory structure is organized under the root directory /, with each subdirectory serving a specific function. Here's an overview of the most common directories:

1. / (Root Directory)

The root directory is the top-level directory in the Linux filesystem hierarchy. All other directories and files are located under this directory. It contains essential system files and directories required for the system to function properly.

2. /bin

The /bin directory contains essential binary executables that are required for the system's basic operations. These include commands like ls, cp, and mv, which are used for listing files, copying files, and moving files, respectively.

3. /boot

The /boot directory holds files necessary for the system's boot process, including the bootloader and kernel images. These files are crucial for starting the operating system.

4. /dev

The /dev directory contains device files that represent hardware devices. These files allow programs to interact with hardware components like hard drives, printers, and terminals.

5. /etc

The /etc directory contains system-wide configuration files. These files control the behavior of various system services and applications.

6. /home

The /home directory is where user-specific files and directories are stored. Each user has a subdirectory under /home, typically named after their username, where personal files and settings are kept.

7. /lib

The /lib directory contains shared library files that are required by system programs and applications. These libraries provide essential functions and services to programs.

8. /media

The /media directory is used for mounting removable media devices, such as USB drives and CD-ROMs. When these devices are connected, they are mounted under this directory.

9. /mnt

The /mnt directory is traditionally used for mounting temporary filesystems. It serves as a mount point for filesystems that are temporarily mounted during system maintenance or troubleshooting.

10. /opt

The /opt directory is used for installing optional application software packages. These packages are typically third-party applications that are not part of the core operating system.

11. /proc

The /proc directory is a virtual filesystem that provides information about running processes and kernel parameters. It allows users and programs to access system information and control kernel parameters.

12. /root

The /root directory is the home directory for the root user, the system administrator. It is separate from the /home directory to enhance security and prevent accidental modification of system files.

13. /sbin

The /sbin directory contains system binary executables that are used for system maintenance and administrative tasks. These commands are typically used by the root user.

14. /srv

The /srv directory contains data for services provided by the system. For example, it may include files for web servers or FTP servers.

15. /sys

The /sys directory is a virtual filesystem that provides information and configuration options for the kernel and devices. It allows users and programs to interact with kernel parameters and device settings.

16. /tmp

The /tmp directory is used for storing temporary files. These files are typically created by applications during their operation and can be deleted after use.

17. /usr

The /usr directory contains user-related programs and data. It includes subdirectories like /usr/bin for user binaries, /usr/lib for libraries, and /usr/share for shared data.

18. /var

The /var directory contains variable data files, such as logs, mail, and spool files. These files are expected to change in size and content during system operation.

Basic Linux Commands

To navigate and interact with the Linux filesystem, several basic commands are commonly used:

- `ls`: Lists the contents of a directory.
- `cd`: Changes the current directory.
- `pwd`: Prints the current working directory.
- `cp`: Copies files or directories.
- `mv`: Moves or renames files or directories.
- `rm`: Removes files or directories.
- `mkdir`: Creates a new directory.
- `rmdir`: Removes an empty directory.
- `touch`: Creates an empty file or updates the timestamp of an existing file.
- `cat`: Displays the contents of a file.
- `chmod`: Changes the permissions of a file or directory.
- `chown`: Changes the ownership of a file or directory.
- `sudo`: Runs a command with superuser (root) privileges.
- `nano`: Opens the Nano text editor to create or edit files.
- `man`: Displays the manual or help page for a command.
- `grep`: Searches for text or patterns in files.
- `find`: Searches for files and directories in the filesystem.
- `ssh`: Connects to another computer securely over a network.
- `scp`: Copies files between computers over SSH.
- `ps`: Lists running processes.
- `kill`: Terminates a running process using its process ID.

References:

- <https://medium.com/@redswitches/linux-a-comprehensive-guide-to-linux-file-systems-fcdf73ae8a83>
- <https://www.geeksforgeeks.org/linux-unix/linux-file-system/>

*******END*******