# Rovers

13/09/2026 Aryan Singh

## Introduction

Rovers are one of the most interesting applications of robotics because they are designed to operate in environments where direct human control is difficult, dangerous or sometimes impossible. Unlike ordinary machines that simply move from one point to another, a rover has to understand its surroundings, make decisions and interact with unfamiliar terrain.

Planetary rovers are especially important in space exploration. Since communication between Earth and another planet has a significant delay, a rover cannot depend on humans for every small movement. It therefore needs sensors, onboard computing and autonomous navigation capabilities to safely explore its surroundings.

This report covers what a rover is, the sensors used on a rover, the difference between a robot and a rover, and the autonomous tasks that rovers are expected to perform.

## What is a Rover?

A rover is a mobile robotic system designed to travel across a surface while carrying out a specific mission. Unlike a stationary robot, a rover is built around mobility, allowing it to move through different types of terrain and reach locations that may be difficult or dangerous for humans.

Rovers can be used on Earth for applications such as mining, agriculture, inspection and disaster response. In planetary exploration, they are used to investigate places such as the Moon and Mars, where sending humans directly may be expensive or currently impractical.

A planetary rover generally consists of several major subsystems:

Mobility system: Wheels, suspension, motors and steering mechanisms that allow the rover to travel through various terrains.


Sensing system: Cameras and other sensors that help the rover understand its surroundings.

Computing system: Onboard computers that process sensor data and execute control and navigation algorithms.

Communication system: Enables the rover to exchange commands and data with a remote operator or base station.

Power system: Provides energy to the electronics, motors and scientific instruments.

Science system: Robotic arms and scientific instruments can be used to interact with objects, collect samples or perform measurements.



NASA's Mars Perseverance rover acquired this image using its SHERLOC WATSON camera, located on the turret at the end of the rover's robotic arm.
Credits: NASA/JPL-Caltech

## Sensors used on a Rover

1. Cameras:

Cameras are among the most important sensors on a rover because they provide visual information about the surrounding environment.

Stereo cameras are particularly useful because two cameras can observe the same scene from slightly different viewpoints. The difference between the two images can be used to estimate depth and construct information about the terrain.

Uses:

- ➢ Obstacle detection
- ➢ Terrain mapping
- ➢ Visual localization
- ➢ Target detection
- ➢ Scientific imaging

2. LiDAR

LiDAR stands for Light Detection and Ranging.

It sends laser pulses toward the surroundings and measures how long they take to return. This allows the system to estimate distances and construct a 3D representation of the environment.

For a rover, LiDAR can be useful for identifying:

- ➢ rocks
- ➢ walls
- ➢ obstacles
- ➢ terrain boundaries
- ➢ changes in elevation

## 3 IMU

An IMU (Inertial Measurement Unit) measures motion-related quantities such as acceleration and rotational motion.

It is commonly used to estimate the rover's:

- ➢ orientation
- ➢ angular movement
- ➢ acceleration
- ➢ change in pose

For example, if the rover is moving over an uneven surface, the IMU can help estimate how the rover is tilting.

## 4. Wheel Encoders

Wheel encoders measure the rotation of a rover's wheels.

From wheel rotations, the rover can estimate how far it has moved. This is called odometry.

However, wheel odometry is not perfect. If a wheel slips on loose soil, the wheel may rotate even though the rover has not moved by the expected amount.

That is why rover navigation generally benefits from combining multiple sensors instead of relying on just one.

## 5 Proximity / Range Sensors

Depending on the rover, short-range sensors can also be used to detect nearby objects.

Examples include:

- ➢ ultrasonic sensors
- ➢ infrared sensors
- ➢ time-of-flight sensors

These can provide information about nearby obstacles and can complement cameras or LiDAR.

6. Environmental Sensors

Rovers can also carry sensors for environmental measurements such as:

- ➢ temperature
- ➢ pressure
- ➢ humidity
- ➢ radiation
- ➢ atmospheric composition

These are especially important for scientific missions because the rover isn't only trying to move, it is also trying to learn about the environment.


7. Scientific Sensors

These are different from navigation sensors.

Scientific instruments may be used to study:

- ➢ rocks
- ➢ soil
- ➢ minerals
- ➢ atmospheric conditions
- ➢ chemical composition

Depending on the rover's design and mission the sensors are installed, not all sensors are mandatory for every mission and rover.




Selected sensing and scientific instruments onboard NASA's Curiosity rover.
Credits: NASA/JPL-Caltech

| Sensor | What it measures | Main rover use |
|---|---|---|
| Camera | Images/visual information | Perception, navigation, target detection |
| Stereo camera | Depth + images | 3D terrain reconstruction |
| LiDAR | Distance/3D geometry | Obstacle detection and mapping |
| IMU | Acceleration + rotation | Orientation and motion estimation |
| Wheel encoder | Wheel rotation | Odometry |
| Proximity sensor | Nearby objects | Short-range obstacle detection |
| Temperature sensor | Temperature | Environmental monitoring |
| Scientific sensors | Physical/chemical properties | Scientific investigation |


## Difference between a rover and a robot

The terms robot and rover are sometimes used interchangeably, but they do not describe exactly the same thing. A robot is a broad category of programmable machines capable of sensing, processing information and performing actions. A rover is a type of robot specifically designed for mobile operation across a surface.

Therefore, every rover can be considered a robot, but not every robot is a rover.

| Feature | Robot | Rover |
|---|---|---|
| Meaning | Broad category of automated machines | Type of mobile robot |
| Mobility | May be fixed, wheeled, legged or flying | Primarily designed for surface mobility |
| Main purpose | Depends on application | Exploration, transportation, inspection or surface tasks |
| Terrain | Depends on design | Usually designed specifically for a particular terrain |
| Example | Industrial robotic arm | Mars rover |
| Navigation | May or may not navigate | Usually an important part of the system |

In simple terms, "robot" describes the larger family, while "rover" describes a particular kind of robot that explores or operates by moving across a surface.



Comparison between a general robotic system and a planetary rover.
Credits: NASA/JPL-Caltech.

## Autonomous tasks rovers are expected to perform

1. Autonomous Navigation:

The rover should be able to move toward a target without requiring a human to control every wheel movement.

2. Obstacle Detection and Avoidance:

A rover must detect obstacles such as:

- ➢ rocks
- ➢ holes
- ➢ steep slopes
- ➢ uneven terrain
- ➢ wheel traps

The rover processes sensor data and chooses a safer path.

3. Localization:

The rover needs to estimate:

"Where am I?"

This is called localization.

It can combine information from cameras, IMUs and wheel encoders to estimate its position and orientation.

This is particularly important because GPS is not available on the Martian surface like it is for a vehicle on Earth.

4. Path Planning

After determining where it is and identifying obstacles, the rover must decide:

"Which route should I take?"

The system can evaluate different possible paths and choose one that balances:

- ➢ safety
- ➢ distance
- ➢ terrain difficulty
- ➢ energy consumption
- ➢ mission objectives

5. Autonomous Target Detection:

A rover can use its cameras to identify scientifically interesting objects.

NASA/JPL's AEGIS system allows a Mars rover to detect, rank and select scientific targets without requiring Earth operators to select every target manually.

6. Autonomous Approach and Manipulation:

Some advanced rover systems are expected to approach a target and position a robotic arm or instrument with limited human intervention.

JPL has researched autonomous target approach and instrument placement using stereo cameras and visual target tracking.

7. Scientific Data Collection:

A rover can autonomously:

1. identify a target,
2. approach it,
3. position an instrument,
4. collect measurements,
5. store the data,
6. communicate the results later.

This reduces the number of communication cycles required between the rover and Earth.


8. Handling Unexpected Situations:

A truly useful autonomous rover should not simply follow a pre-programmed path.


It should respond when the environment changes.

For example:

> Rover detects rock → path becomes unsafe → rover stops → sensors inspect surroundings → alternative path is selected → rover continues.




NASA's Perseverance rover using AutoNav to autonomously plan a safe path around an obstacle
Credits: NASA/JPL-Caltech.




Basic autonomous navigation loop of a rover.

## Conclusion

A rover is much more than a vehicle with wheels. It is an integrated robotic system that combines mechanical design, electronics, sensing, computing and control to operate in challenging environments. Sensors allow the rover to observe its surroundings, while onboard algorithms convert that information into decisions about where and how to move.

The distinction between a robot and a rover is therefore mainly one of specialization: a rover is a mobile robotic platform designed to operate across a surface. As rover technology develops, greater autonomy is becoming increasingly important. Navigation, obstacle avoidance, localization, path planning, target detection and scientific data collection can all be performed with reduced dependence on human intervention.

Understanding these fundamentals provides a strong foundation for studying and contributing to the systems involved in planetary rover development.




MAHE Mars Rover

Credits: Manipal Academy of Higher Education (MAHE)

## References

NASA Science — Rover Basics
https://science.nasa.gov/planetary-science/programs/mars-exploration/rover-basics/

NASA/JPL — Rover Navigation
https://robotics.jpl.nasa.gov/what-we-do/flight-projects/mars-science-laboratory/surface-system-software-and-rover-navigation/

NASA/JPL — MER Surface Navigation
https://robotics.jpl.nasa.gov/what-we-do/flight-projects/mars-exploration-rovers/surface-navigation/

NASA/JPL — AEGIS Autonomous Science
https://ai.jpl.nasa.gov/public/projects/aegis/

NASA Science — Mars Exploration Rover Instruments
https://science.nasa.gov/mission/mars-exploration-rovers-spirit-and-opportunity/science-instruments/