



Java Class Methods

[< Previous](#)[Next >](#)

Java Class Methods

You learned from the [Java Methods](#) chapter that methods are declared within a class, and that they are used to perform certain actions:

Create a method named `myMethod()` in Main:

```
public class Main {  
  
    System.out.println("Hello World!");  
}  
}
```

`myMethod()` prints a text (the action), when it is **called**. To call a method, write the method's name followed by two parentheses `()` and a semicolon;

Example

[Get your own Java Server](#)

Inside `main`, call `myMethod()`:

```
public class Main {  
    static void myMethod() {  
        System.out.println("Hello World!");  
    }  
  
    public static void main(String[] args) {
```

[Try it Yourself »](#)

Access Methods With an Object

Example

Create a Car object named `myCar`. Call the `fullThrottle()` and `speed()` methods on the `myCar` object, and run the program:

```
// Create a Main class
public class Main {

    // Create a fullThrottle() method
    public void fullThrottle() {
        System.out.println("The car is going as fast as it can!");
    }

    // Create a speed() method and add a parameter
    public void speed(int maxSpeed) {
        System.out.println("Max speed is: " + maxSpeed);
    }

    // Inside main, call the methods on the myCar object
    public static void main(String[] args) {
        Main myCar = new Main();    // Create a myCar object
        myCar.fullThrottle();        // Call the fullThrottle() method
        myCar.speed(200);            // Call the speed() method
    }
}

// The car is going as fast as it can!
// Max speed is: 200
```



Example explained

- 1) We created a custom `Main` class with the `class` keyword.
- 2) We created the `fullThrottle()` and `speed()` methods in the `Main` class.
- 3) The `fullThrottle()` method and the `speed()` method will print out some text, when they are called.
- 4) The `speed()` method accepts an `int` parameter called `maxSpeed` - we will use this in **8**).
- 5) In order to use the `Main` class and its methods, we need to create an **object** of the `Main` Class.
- 6) Then, go to the `main()` method, which you know by now is a built-in Java method that runs your program (any code inside main is executed).
- 7) By using the `new` keyword we created an object with the name `myCar` .
- 8) Then, we call the `fullThrottle()` and `speed()` methods on the `myCar` object, and run the program using the name of the object (`myCar`), followed by a dot (`.`), followed by the name of the method (`fullThrottle();` and `speed(200);`). Notice that we add an `int` parameter of **200** inside the `speed()` method.

Remember that..

The dot (`.`) is used to access the object's attributes and methods.

To call a method in Java, write the method name followed by a set of parentheses **()**, followed by a semicolon (`;`).

A class must have a matching filename (`Main` and **`Main.java`**).

[REMOVE ADS](#)



access it in another class.

Remember that the name of the java file should match the class name. In this example, we have created two files in the same directory:

- Main.java
- Second.java

Main.java

Second.java

```
class Second {  
    public static void main(String[] args) {  
        Main myCar = new Main();    // Create a myCar object  
        myCar.fullThrottle();        // Call the fullThrottle() method  
        myCar.speed(200);            // Call the speed() method  
    }  
}
```

When both files have been compiled:

```
C:\Users\Your Name>javac Main.java  
C:\Users\Your Name>javac Second.java
```

Run the Second.java file:

```
C:\Users\Your Name>java Second
```

And the output will be:

```
The car is going as fast as it can!
```

[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

Exercise [?]

Call the method inside main .

```
public class Main {  
    static void myMethod() {  
        System.out.println("Hello World!");  
    }  
  
    public static void main(String[] args) {  
        myMethod    ();  
    }  
}
```

Main

void

class

[];

[Submit Answer »](#)

[◀ Previous](#)[Sign in to track progress](#)[Next >](#)