

Matheus S. D'Andrea Alves

Recognition of (r, ℓ) -partite Graphs

2019

Abstract

The complexity to recognize if a graph has an (r, ℓ) -partition, i.e. if it can be partitioned into r cliques and ℓ independent sets, is well defined(1). However, as we will demonstrate, the literature-stabilished values for those on the P class can be improved. The following work provides a set of strategies and algortihms that pushes the previous results for the $(2, 1)$ -partite (from n^4 to $n * m$), $(1, 2)$ -partite (from n^4 to $n * m$) and $(2, 2)$ -partite (from n^{12} to $n^2 * m$) recognition.

Keywords— (r, ℓ) -graphs, (r, ℓ) -partitions

List of Figures

List of Tables

Table 1	– Incomplete complexity analysis of the (r, ℓ) -partite recognition problem	3
Table 2	– Incomplete complexity analysis of the (r, ℓ) -partite recognition problem	4
Table 3	– Current complexity analysis of the (r, ℓ) -partite recognition problem . .	4

Contents

	Contents	2
1	INTRODUCTION	3
1.1	Current results	3
1.1.1	m -bounded results	3
1.1.2	NP -Complete results	3
1.1.3	Frontier results	4
	BIBLIOGRAPHY	5

1 Introduction

1.1 Current results

In this section we will explore the current state of the complexity analysis as r and ℓ grows. As we fullfill the following table we expose the strategies and how those can be used to enlight the more complex results.

The most trivial result is the recognition of the $(1, 0)$ -graphs, as in order to recognize it we just need to know if $|E(G)| > 0$. Therefore it's complexity is $\mathcal{O}(1)$.

$r \backslash \ell$	0	1	2	3	4	...
0	-	?	?	?	?	...
1	$\mathcal{O}(1)$?	?	?	?	...
2	?	?	?	?	?	...
3	?	?	?	?	?	...
4	?	?	?	?	?	...
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\ddots

Table 1 – Incomplete complexity analysis of the (r, ℓ) -partite recognition problem

1.1.1 m -bounded results

Naturally, we wish to find the complexity for those problems of small partition cardinality.

At (2), König showed that it takes $\mathcal{O}(m)$ steps to recognize a bipartite graph. For complete graphs, is enough to check if $|E(G)| = n(n-1)/2$, if it doesn't then we have an answer; If it does, checking vertex by vertex if it's neighborhood contains all other vertex is $\mathcal{O}(m)$.

For co-bipartite graphs recognition, we need only to verify if it's complement is a bipartite graph. The recognition of a split graph can be done using their vertex degrees (??), obtaining all vertices degrees is $\mathcal{O}(m)$ therefore the recognition of split graphs is $\mathcal{O}(m)$

1.1.2 NP -Complete results

A adequate strategy at this moment is to find when the recognition problem gets NP -Complete.

At (3) is shown that 3-coloring a graph (i.e. assign a color between three possibles to each vertex such that no neighborhood repeats a color) is NP -Complete, it's trivial to

see how the 3-coloring of a graph can be reduced to the problem of finding if a graph is a $(3, 0)$ -graph, therefore the recognition of $(3, 0)$ -graphs is *NP*-Complete.

It's noticeable that the recognition of (r, ℓ) -graphs is monotonic, and therefore if the recognition of $(3, 0)$ -graphs are *NP*-Complete then the recognition of any $(r, 0)$ -graph or $(3, \ell)$ -graph is *NP*-Complete for $r > 3$ and $\ell > 0$.

We can extrapolate these findings and argument that the recognition of a $(0, 3)$ -graph is also *NP*-Complete, as it is the same as recognize it's complement as a $(3, 0)$ -graph, and use the property of monotonicity to state that the recognition of any $(r, 3)$ -graph or $(0, \ell)$ -graph is *NP*-Complete for $r > 0$ and $\ell > 3$.

$r \backslash \ell$	0	1	2	3	4	...
0	-	$\mathcal{O}(m)$	$\mathcal{O}(m)$	<i>NPc</i>	<i>NPc</i>	...
1	$\mathcal{O}(1)$	$\mathcal{O}(m)$?	<i>NPc</i>	<i>NPc</i>	...
2	$\mathcal{O}(m)$?	?	<i>NPc</i>	<i>NPc</i>	...
3	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	...
4	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	...
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\ddots

Table 2 – Incomplete complexity analysis of the (r, ℓ) -partite recognition problem

1.1.3 Frontier results

Finally, the frontier cases $(1, 2), (2, 1)$ and $(2, 2)$ were subject of studies by Brandstädt(1, 4). He's findings show that:

- Recognition of $(1, 2)$ -graphs are $\mathcal{O}(n^4)$.
- Recognition of $(2, 1)$ -graphs are $\mathcal{O}(n^4)$.
- Recognition of $(2, 2)$ -graphs are $\mathcal{O}(n^{12})$.

$r \backslash \ell$	0	1	2	3	4	...
0	-	$\mathcal{O}(m)$	$\mathcal{O}(m)$	<i>NPc</i>	<i>NPc</i>	...
1	$\mathcal{O}(1)$	$\mathcal{O}(m)$	$\mathcal{O}(n^4)$	<i>NPc</i>	<i>NPc</i>	...
2	$\mathcal{O}(m)$	$\mathcal{O}(n^4)$	$\mathcal{O}(n^{12})$	<i>NPc</i>	<i>NPc</i>	...
3	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	...
4	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	<i>NPc</i>	...
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\ddots

Table 3 – Current complexity analysis of the (r, ℓ) -partite recognition problem

Bibliography

- 1 BRANDSTÄDT, A. *Partitions of graphs into one or two independent sets and cliques*. 1984.
- 2 KÖNIG, D. *Theorie der endlichen und unendlichen Graphen: Kombinatorische Topologie der Streckenkomplexe*. [S.l.]: Akademische Verlagsgesellschaft mbh, 1936. v. 16.
- 3 GAREY, M. R.; JOHNSON, D. S. *Computers and intractability*. [S.l.]: wh freeman New York, 2002. v. 29.
- 4 BRANDSTÄDT, A. Partitions of graphs into one or two independent sets and cliques. *Discrete Mathematics*, Elsevier, v. 152, n. 1-3, p. 47–54, 1996.