```
call npm install
call npm run build
```

Advanced ∨

≡ **Execute Windows batch command** ?   ✕

Command
See the list of available environment variables

```
rmdir /S /Q "C:\Program Files\Apache Software Foundation\Tomcat 9.0\webapps\ecommerce"

mkdir "C:\Program Files\Apache Software Foundation\Tomcat 9.0\webapps\ecommerce"

xcopy /E /I /Y dist\* "C:\Program Files\Apache Software Foundation\Tomcat 9.0\webapps\ecommerce"
```

Advanced ∨

≡ **Execute Windows batch command** ?   ✕

Command
See the list of available environment variables

```
net stop Tomcat9
net start Tomcat9
```

Post-build Actions

Define what happens after a build completes, like sending notifications, archiving artifacts, or triggering other jobs.

≡ **Deploy war/ear to a container**   ✕

WAR/EAR files ?

```
**/*.war
```

Context path ?

```
back1
```

Containers

≡ **Tomcat 9.x Remote**   ✕

Credentials

```
admin/******                                                          ∨
```

+ Add

Tomcat URL ?

```
http://localhost:9090/
```

Build Steps

Automate your build process with ordered tasks like code compilation, testing, and deployment.

≡ **Invoke top-level Maven targets** ?   ×

Maven Version

MAVEN_HOME   ⌄

Goals

clean compile package   ⌄

Advanced ⌄

Add build step ⌄