

ios App Audit Report

App Information

MD5	d41d8cd98f00b204e9800998ecf8427e
sha256	e3b0c44298fc1c149afbf4c8996fb92427ae41e4649b934ca495991b7852b855
Scan time	Thu, 27 Jun 2024 10:59:18 GMT
App name	
App version	
Average CVSS	0
Build	
Bundle id	tw.com.easycard.easycardwallet
Filename	
Minimum OS require	
SDK name	iphoneos13.3.1

Scan Report

Result	Rule
✓ Passed	<p>lab_1 - SSL connection check</p> <p>Standard Testing Guide of Industrial Development Board, R.O.C.: 4.1.2.4.1 - The mobile application shall apply appropriate and effective key length and encryption algorithm(s) for secure encryption when transmitting sensitive data via network. 4.1.2.1.2 - The mobile application shall provide users with the right to refuse the collection of sensitive data.</p> <p>MSTG: MSTG-STORAGE 4 MSTG-NETWORK-1 MSTG-NETWORK-2</p> <p>OWASP MOBILE: M3</p> <p>Description: URL with http found, please check if this URL need to be protected with SSL or not ,Keyword: NSURL with http / NSURL startswith(http://)</p> <p>詳細資訊: .</p>

lab_2 - Make use of security method

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.6 - Sensitive data shall be encrypted with appropriate and effective key length and encryption algorithm(s) before being stored.

MSTG:

MSTG-STORAGE-14

MSTG CRYPTO

✓ Passed

Description:

Cipher function found. Ensure no weak cipher function used in this application. Message digest function found. Ensure no weak message digest function used in this application. Signature function found. Ensure no weak signature function used in this application. MAC function found. Ensure no weak MAC function used in this application.

詳細資訊:

.

lab_3 - Make use of security class

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.6 - Sensitive data shall be encrypted with appropriate and effective key length and encryption algorithm(s) before being stored.

MSTG:

MSTG-STORAGE-14

MSTG CRYPTO

✓ Passed

Description:

Cipher function found. Ensure no weak cipher function used in this application. Message digest function found. Ensure no weak message digest function used in this application. Signature function found. Ensure no weak signature function used in this application. MAC function found. Ensure no weak MAC function used in this application.

詳細資訊:

.

lab_4 - Master Key Vulnerability checking

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.1.2 - The mobile application shall avoid information security vulnerabilities.

✓ Passed

MSTG:

MSTG-CRYPTO-2

MSTG-CRYPTO-4

詳細資訊:

.

lab_5 - Network access

✓ Passed

MSTG:

MSTG-NETWORK-3

詳細資訊:

.

lab_6 - Make use of SQLite deprecated functions

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.3.1 - When the library referred by the mobile application is updated, the corresponding updated version shall be prepared. Regarding the update method, please consult subsection: 4.1.1. Security regarding Mobile Application Release.

✓ Passed

MSTG:

MSTG-NETWORK-6

MSTG-CODE-5

Description:

sqlite3_aggregate_count', 'sqlite3_expired', 'sqlite3_global_recover', 'sqlite3_memory_alarm', 'sqlite3_soft_heap_limit', 'sqlite3_thread_cleanup', 'sqlite3_transfer_bindings' These functions are deprecated. In order to maintain backwards compatibility with older code, these functions continue to be supported. However, new applications should avoid the use of these functions.
Keyword: libsqlite3.dylib

詳細資訊:

.

lab_7 - List all native method

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.2.2.1.2 - When the mobile application renders functions in the Webview, the connected domain shall be a secure domain.

✓ Passed

MSTG:

MSTG-PLATFORM-6

詳細資訊:

.

lab_8 - Clipboard manipulation check

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.13 - The user interface in the mobile application shall avoid the leakage of sensitive data.

✓ Passed

MSTG:

MSTG-STORAGE-7

OWASP MOBILE:

M4

Description:

Any app on an iOS device can access the most recent thing copied to your clipboard. Theoretically, a malicious app can read what's on your iOS clipboard and then feed that information back to a remote server. That remote server can be easily accessed by someone stealing your personal and sensitive information.
Keyword: Foundation, copy, cut, paste:

詳細資訊:

.

lab_9 - Make use of SMS related code

OWASP MOBILE:

M3

Description:

This application sends SMS message. One of the most common vulnerabilities of SMS verification codes is weak security protocols. Many SMS verification codes are sent over unencrypted channels, making them vulnerable to interception. Make sure it do this action with user permission. Keyword: MFMessageComposeViewController, canSendText

✓ Passed

詳細資訊:

.

lab_10 - Certificate check

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.1.2 - The mobile application shall avoid information security vulnerabilities.

✓ Passed

MSTG:

MSTG-NETWORK-3

MSTG-NETWORK-4

Description:

Check the SSL Certificate information. We use SSLlab to check your cert, more information <https://www.ssllabs.com/ssltest/> Keyword: NSURL startswith https://

詳細資訊:

.

lab_11 - Base64 String decoding

✓ Passed

MSTG:

MSTG-CRYPTO-1

MSTG-CRYPTO-2

MSTG-CRYPTO-3

OWASP MOBILE:

M3

Description:

Base64-encoded or base64-decoded string found Applications may Base64-encode parameters to conceal them from users or to ease the transfer of binary data. The existence of Base64-encoded data might suggest security-sensitive information or functionality that should be investigated further. Keyword: Base64

詳細資訊:

.

lab_12 - Make use of javascript in webview

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.2.2.1.2 - When the mobile application renders functions in the Webview, the connected domain shall be a secure domain.

MSTG:

MSTG-ARCH-2

MSTG-NETWORK-4

MSTG-PLATFORM-5

MSTG-PLATFORM-6

MSTG-PLATFORM-7

✓ Passed

Description:

Webview JavaScript Enabled, the webview use setJavaScriptEnabled to allow javascript. It is potentially dangerous because it may allow the external website to do XSS attack in the webview. Keyword: UIWebView - stringByEvaluatingJavaScriptFromString in webview

詳細資訊:

.

lab_13 - Screenshot detection

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.9 - The mobile application shall actively alert the user when non-user-initiated screenshots are taken.

MSTG:

MSTG-STORAGE-12

OWASP MOBILE:

M10

✓ Passed

Description:

This application allows users to take screenshots. Please check screenshots function and turn it off. Keyword: UIApplication - _handleScreenshot to detect screenshot

詳細資訊:

.

lab_14 - HTTPS ALLOW_ALL_HOSTNAME_VERIFIER check

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.4.2.3 - The mobile application shall confirm that the server certificate is issued by a trusted certificate authority.

4.1.4.2.4 - mas.4.1.4.2.4

4.1.5.1.2 - The mobile application shall avoid information security vulnerabilities.

✓ Passed

MSTG:

MSTG-NETWORK-3

OWASP MOBILE:

M5

Description:

This application use ALLOW_ALL_HOSTNAME_VERIFIER to verify all the CN. It is dangerous and may cause man-in-the-middle attack.

詳細資訊:

.

lab_15 - SSL Certificate check

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.1.2 - The mobile application shall avoid information security vulnerabilities.

✓ Passed

MSTG:

MSTG-CODE-5

MSTG-PLATFORM-8

MSTG-PLATFORM-9

OWASP MOBILE:

M5

Description:

Check the SSL Certificate information.

詳細資訊:

.

lab_16 - Potential XSS in webview

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.4.2 - The mobile application shall provide protection mechanism(s) relevant to injection attacks.

✓ Passed

MSTG:

MSTG-PLATFORM-2

OWASP MOBILE:

詳細資訊:

.

lab_17 - Use SQLite database

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.5.1.1 - The mobile application shall avoid containing malicious code.

✓ Passed

MSTG:

MSTG-STORAGE-1

MSTG-STORAGE-2

詳細資訊:

.

lab_18 - WebView setAllowFileAccess

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.7 - In order to prevent unauthorized access by other applications, sensitive data shall be stored in the areas protected by the OS.

4.1.2.5.3 - Accesses from unauthorized mobile applications shall be avoided when the mobile application is sharing sensitive data.

✓ Passed

MSTG:

MSTG-STORAGE 4

MSTG-PLATFORM-3

MSTG-PLATFORM-4

OWASP MOBILE:

M3

Description:

Allow local file access with webview. Please ensure your code not to allow path traversal.

詳細資訊:

.

lab_19 - SSL Verification Fail

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.4.2.2 - The mobile application shall verify the validity of the server certificate.

4.1.4.2.3 - The mobile application shall confirm that the server certificate is issued by a trusted certificate authority.

✓ Passed

MSTG:

MSTG-NETWORK-3

MSTG-NETWORK-4

OWASP MOBILE:

M3

Description:

Check the SSL Certificate information.

詳細資訊:

.

<p>✓ Passed</p>	<p>lab_20 - Possible hardcoded information</p> <p>Description: The use of a hard-coded password increases the possibility of password guessing tremendously. Keyword: CCCrypt, CCAAlgorithm</p> <p>詳細資訊: ·</p>
<p>✓ Passed</p>	<p>lab_21 - USE URL</p> <p>Description: URL found during analysis, check if there are some suspicious URL. Keyword:Use URL schemes with</p> <p>詳細資訊: · Use URL schemes with appcenter-7b9ae5ce-0d51-432c-a28a-5debe1f43073://</p>
<p>⚠ Detected</p>	<p>lab_22 - ENCRYPTION_AES/DES/MD5 Cipher&Degist; Method found</p> <p>Standard Testing Guide of Industrial Development Board, R.O.C.: 4.1.2.3.6 - Sensitive data shall be encrypted with appropriate and effective key length and encryption algorithm(s) before being stored.</p> <p>MSTG: MSTG-STORAGE-14 MSTG-CRYPTO</p> <p>OWASP MOBILE:</p> <p>詳細資訊: · Use CC_MD5 with ["434F251E-811A-46F4-A3A5-B245B2F1AEAC\x01", "36", ""] Use CC_MD5 with ["0xfaa189080e1a0108", "428", ""] Use CC_MD5 with ["434F251E-811A-46F4-A3A5-B245B2F1AEAC\x02", "36", ""] Use CC_MD5 with ["434F251E-811A-46F4-A3A5-B245B2F1AEAC", "36", ""]</p>

lab_23 - Local Data Storage

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.10 - The mobile application shall use system credential storage facilities appropriately to store sensitive data.

MSTG:

MSTG-STORAGE-1

MSTG-STORAGE-14

✓ Passed

Description:

While it can improve the efficiency and availability of the application, it also carries risks. To protect the security of sensitive user information, a better approach is to store data in iOS's secure storage areas, such as the Secure Enclave.

Keyword: PrivateFrameworks

詳細資訊:

.

lab_24 - Make use of log function

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.4 - The mobile application shall avoid storing sensitive data in redundant files or log files after closure and/or log-out.

4.1.2.3.5 - The mobile application shall avoid storing sensitive data in redundant files or log files.

MSTG:

MSTG-STORAGE-3

MSTG-STORAGE-13

⚠ Detected

OWASP MOBILE:

M10

Description:

Log function in this application, you should notice is there sensitive information in these logs. Keyword: Foundation, NSLog

詳細資訊:

· Make use of log function NSLog with ["XPC connection interrupted"] Make use of log function NSLog with ["%s Failed to access remote service: %@",] Make use of log function NSLog with ["Can't find keyplane that supports type %ld for keyboard %@; using %@",]

lab_25 - Keyboard cache

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.1.2.3.11 - The mobile application shall disable the keyboard cache mechanism when the user is entering sensitive data.

MSTG:

MSTG-STORAGE-5

MSTG-PLATFORM-11

⚠ Detected

Description:

Because the keyboard cache file is stored on the device, if the device is lost, it may be recovered, thereby revealing any sensitive information contained within. Check the keyboard cache ability open or not. Keyword: libSystem.B.dylib, Caches

詳細資訊:

· Autocorrecting keyboard is detected, Please close the function by setting the UITextField

lab_26 - Domain Check

Standard Testing Guide of Industrial Development Board, R.O.C.:

4.2.2.1.2 - When the mobile application renders functions in the Webview, the connected domain shall be a secure domain.

MSTG:

MSTG-ARCH-2

MSTG-NETWORK-4

MSTG-PLATFORM-5

MSTG-PLATFORM-6

MSTG-PLATFORM-7

✓ Passed

Description:

Connecting to an insecure domain may result in consequences such as virus/malware infection, data theft, identity theft, computer ransom, etc. It's important to only connect to secure domains and use up-to-date anti-virus software, firewall, and browser, and avoid entering sensitive information on insecure websites.

詳細資訊:

.

<p>✓ Passed</p>	<p>lab_27 - use of PIE</p> <p>Standard Testing Guide of Industrial Development Board, R.O.C.: 4.1.5.1.2 - The mobile application shall avoid information security vulnerabilities.</p> <p>MSTG: MSTG-CODE-5 MSTG-CODE-8</p> <p>Description: Enabling Position Independent Executable (PIE) are mainly related to enhancing the security of applications.</p> <p>詳細資訊: .</p>
<p>✓ Passed</p>	<p>lab_28 - debug mode</p> <p>Standard Testing Guide of Industrial Development Board, R.O.C.: 4.1.5.5.9 - mas.4.1.5.5.9</p> <p>MSTG: MSTG-CODE-2 MSTG-CODE-6</p> <p>Description: Mobile applications should disable debug mode.</p> <p>詳細資訊: · Debug mode is disabled.</p>
<p>✓ Passed</p>	<p>lab_29 - IPC check</p> <p>Standard Testing Guide of Industrial Development Board, R.O.C.: 4.1.2.3.3 - mas.4.1.2.3.3</p> <p>MSTG: MSTG-STORAGE 4 MSTG-NETWORK-1 MSTG-NETWORK-2</p> <p>Description: Applications should not leak sensitive data when using IPC transfers.</p> <p>詳細資訊: .</p>

URL in the App

No URL detected in app