Question 2

Revisit Later

Consider that an analyst is tasked with clustering a high-dimensional dataset containing both numerical and categorical features, where traditional distance metrics may fall short. The dataset represents customer profiles from an e-commerce platform. The goal is to identify distinct customer segments based on various attributes such as purchase history, demographics, and product preferences.

Which clustering algorithm will be most appropriate for handling mixed data types and high-dimensional spaces in this challenging scenario?

a) K-Means Clustering
b) Agglomerative Hierarchical Clustering
c) Gaussian Mixture Model (GMM)
d) DBSCAN (Density-Based Spatial Clustering of Applications with Noise)

Refer to the given list and select the option with the correct answer.

Select an option

- a and b
- b and c
- a and d
- c and d

6. Technical Skills

1 2 3 4 5 6 7 8 9 10

Attempted: 0/25

Question 1

Revisit Later

The following table shows the 2*2 confusion matrix that describes the performance of classification model for the classes positive and negative.

	Positive	Negative
Positive	70	20
Negative	30	80

What is the value of specificity (i.e., actual negative cases that are correctly identified) for the given confusion matrix?

Select an option

- 0.8
- 0.7
- 0.72
- 0.85

Question 4

Revisit Later

Which of the following statements about sklearn.cluster.Kmeans are true?

A. There is a parameter to specify the maximum number of iterations of the k-means algorithm for a single run.
B. Users are allowed to customize initial centroids.
C. There is no parameter to specify the maximum number of iterations of the k-means algorithm for a single run.
D. Users are not allowed to customize initial centroids.

Select an option

- A and B
- A and D
- A and B
- A and D

Question 3

Revisit Later

Which of the following statements about K-means clustering is/are true?

A. In K-means clustering, each example belongs to at least one of the K clusters.
B. In K-means clustering, no example belongs to more than one clusters.
C. In K-means clustering, K's value is set before running the algorithm.
D. In K-means clustering, K's value can be changed while the algorithm is running.

Select an option

- Only A
- Both A and B
- A, B and C
- A, B and D

Attempted: 5/25

Question 6

Revisit Later

What is the output of the given code snippet?

```
1  a=(2,"country",5,"43",12)
2  def fetch_my_data(my_data):
3      if isinstance(my_data,tuple):
4          return my_data*2
5  def shredder(data):
6      del data
7  def len_printer(func):
8      return len(func)
9
10 print(len_printer(fetch_my_data(a)))
11 shredder(a)
12 if a:
13     print(len_printer(fetch_my_data(a)))
14 else:
15     print("a does not exist")
```

Select an option

- 10
  10
- 10
  a does not exist
- 5
  a does not exist
- Error

Attempted: 6/25

Question 7

Revisit Later

What will be the output of the following code?

```
class Process_values:
    def __init__(self):
        self.mydata=("1",2,"3",4,"5")

    def add_values(self):
        for i in self.myvalues:
            if isinstance(i,int):
                self.mydata.append(i+1)
            else:
                self.mydata.append(i)
try:
    values=Process_values()
    values.add_values()
except TypeError:
    print("TypeError Occurred")
except IndexError:
    print("IndexError Occurred")
except AssertionError:
    print("AssertionError Occurred")
except AttributeError:
    print("AttributeError Occurred")
```

Select an option

- AssertionError Occurred
- AttributeError Occurred
- TypeError Occurred
- IndexError Occurred

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90602

6. Technical Skills

1 2 3 4 5 6 7 8 9 10

Attempted: 4/25

Question 5

Revisit Later

What will be the output of the following in Python 3?

```
1 a = tuple('abcde')
2 a, b, c, d, e = a
3 b = c = '*'
4 a = (a, b, c, d, e)
5 print(a)
```

Select an option

- ('a', '*', '*', 'd', 'e')
- ('a', '*', 'b', '*', 'e')
- ('a', 'b, 'b', 'c, '*')
- ('*', '*', 'b', 'c', 'c')

6. Technical Skills

< 1 2 3 4 5 6 7 8 9 10 >

Attempted: 8/25

Previous Next

Question 9

Revisit Later

Which one of the following queries can be used to display EmployeeName of employees whose manager is younger than the employee? Refer table below.

EmployeeNumber	EmployeeName	Salary	DepartmentCode	DateOfBirth	ManagerEmployeeNumber
101	John	10000	123	01-01-1995	102
102	Deepak	80000	456	11-01-1995	106
103	Mohit	70000	123	09-09-1996	106
104	Mike	60000	567	11-11-1994	102
105	Adam	40000	456	21-01-1990	106
106	Ankit	30000	123	31-11-1994	103
107	Raj	50000	567	17-07-1993	102

```
SELECT EmployeeName FROM Employee E1
WHERE E1.DateOfBirth < (SELECT E2.DateOfBirth FROM Employee
E2 WHERE
E2.ManagerEmployeeNumber = E1.ManagerEmployeeNumber);
```

```
SELECT EmployeeName FROM Employee E1
WHERE E1.DateOfBirth < (SELECT E2.DateOfBirth FROM Employee
E2 WHERE
E2.EmployeeNumber = E1.EmployeeNumber);
```

```
SELECT EmployeeName FROM Employee E1
WHERE E1.DateOfBirth < (SELECT E2.DateOfBirth FROM Employee
E2 WHERE
E2.EmployeeNumber = E1.ManagerEmployeeNumber);
```

```
SELECT EmployeeName FROM Employee E1
WHERE E1.DateOfBirth > (SELECT E2.DateOfBirth FROM Employee
E2 WHERE
E2.EmployeeNumber = E1.ManagerEmployeeNumber);
```

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471 90902

Browser 2.0.2

What will be the output of the following code?

```
from functools import reduce

final_list = list()


def get_char():
    try:
        my_alphas = ["a", "e", "i", "o", "u"]
        my_alphas2 = ["a", "g", "t", "j", "f"]

        red1 = reduce(lambda x, y: x.join(y), my_alphas)
        red2 = reduce(lambda x, y: y.join(x), my_alphas2)
        final_list.extend([red1, red2])

        return reduce(lambda a, b: b.join(a), final_list)
    except TypeError:
        print("TypeError Occurred")
        return None


if __name__ == '__main__':
    output = get_char()
    print(output)
```

Select an option

- u
- f
- a
- TypeError Occurred

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90982

6. Technical Skills

9 10 11 12 13 14 15 16 17 18

Attempted: 13/25

Question 14

Revisit Later

A user has planned to choose an optimal model that fits the data using the 'Forward selection' technique. In this, he/she will start with the null model (M0) and finally have a set of models up to (Mk) and use the best fit from those models. How many variables are there in the dataset, if he/she created 29 models using the variable to find the best model?

Select an option

- 4
- 7
- 5
- 6

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90902

Question 10

Attempted: 9/25

Revisit Later

Which one of the following queries can be used to display CustomerName and PhoneNumer of customers who have placed a single order of over $ 45,000. Refer table below.

Customer Table

CustomerId	CustomerName	PhoneNumber
1001	Deepak	12345
1002	Ajay	54321
1003	Rahul	87654

OrderMaster Table

CustomerId	TotalOrderAmount	OrderDate
1001	47000	10-Jun-2016
1002	10000	01-Jan-2016
1001	14000	19-Jun-2016
1003	53000	04-Feb-2016
1002	60000	26-Jun-2016

Select an option

Clear Response

```
1 SELECT CustomerName,PhoneNumber FROM Customer WHERE
2 CustomerId = (SELECT CustomerId FROM OrderMaster WHERE
  TotalOrderAmount>45000);
```

```
1 SELECT CustomerName,PhoneNumber FROM Customer WHERE
2 CustomerId IN (SELECT CustomerId FROM OrderMaster WHERE
  TotalOrderAmount>45000);
```

```
1 SELECT CustomerName,PhoneNumber FROM Customer WHERE
2 CustomerId = (SELECT CustomerId FROM Customer WHERE
  TotalOrderAmount>45000);
```

```
1 SELECT CustomerName,PhoneNumber FROM Customer WHERE
2 CustomerId IN (SELECT CustomerId FROM Customer WHERE
  TotalOrderAmount>45000);
```

Attempted: 14/25

Question 15

Revisit Later

A research data suggests that as cool drinks sales increases in a state, the rate of registration at swimming clubs also increases. What kind of analytical relation does this Cooldrinks and Swimming club registrations suggest?

Select an option

- Causual Relation
- Correlation
- Probability
- Cause and Effect Relation

6. Technical Skills

6 7 8 9 10 11 12 13 14 15

Attempted: 10/25

Previous Next

Question 11

Revisit Later

On the EMPLOYEES table, EMPLOYEE_ID is the primary key. MGR_ID is the ID of managers and refers to the EMPLOYEE_ID. On the DEPARTMENTS table, DEPARTMENT_ID is the primary key. What will happen when the following UPDATE statement is executed?

```
1 UPDATE employees SET mgr_id = (SELECT mgr_id FROM employees WHERE dept_id =
  (SELECT department_id FROM departments WHERE department_name = 'Administration')
  ), salary = (SELECT salary FROM employees WHERE emp_name = 'Smith') WHERE job_id
  = 'IT_ADMIN';
```

Select an option

Clear Response

- The statement executes successfully, leaves the manager ID as the existing value, and changes the salary to 4000 for the employees with ID 103 and 105
- The statement executes successfully, changes the manager ID to NULL, and changes the salary to 4000 for the employees with ID 103 and 105
- The statement executes successfully, changes the manager ID to NULL, and changes the salary to 3000 for the employees with ID 103 and 105
- None of the given options

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90902

er 2.0.2

Attempted: 11/25

Question 12

Revisit Later

You are given the following table 'WORKERDETAILS':

ID	WORKERNAME	AGE	PLACE	WAGE
1	Rophy	32	Thrissur	20000
2	Vimal	25	Kannur	150.00
3	Dravid	23	Bengaluru	200.00
4	George	25	Mumbai	650.00
5	Sony	27	Kolkata	850.00
6	Cleetus	22	Indore	450.00
7	Thilak	24	Manipal	1000.00

A worker with ID '5', shifted her/his place to Goa. Which of the following codes will you use to make this change in the table?

Select an option

- SQL> UPDATE WORKERDETAILS SET ID=5 PLACE= 'Goa';
- SQL> UPDATE WORKERDETAILS SET PLACE= 'Goa' WHERE ID = 5;
- SQL> UPDATE SET PLACE= 'Goa' WHERE ID = 5;
- SQL> UPDATE WORKERDETAILS SET PLACE= 'Goa' ID = 5;

6. Technical Skills

11 12 13 14 15 16 17 18 19 20

Attempted: 15/25

Question 16

Revisit Later

You are developing a threshold-based insurance fraud detection system with an AUROC of 86.42%. What will happen to the efficacy of the model if the threshold is decreased?

Select an option

- TN and FN will increase
- TP and FP will increase
- TN and FN will decrease
- TP and FP will decrease

Question 13

Attempted: 12/25

Revisit Later

Which of the following statements will you use to return all records sorted in a descending order of their first names from a table named 'Persons'?

Select an option

Clear Response

```
1 SELECT * FROM Persons ORDER BY FirstName DESC;
```

```
1 SELECT * FROM Persons ORDER FirstName DESC;
```

```
1 SELECT * FROM Persons SORT BY 'FirstName' DESC;
```

```
1 SELECT * FROM Persons SORT 'FirstName' DESC;
```

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90902

13 14 15 16 17 18 19 20 21 22

Attempted: 17/25

Previous Next

Question 18

Revisit Later

Select an option

Clear Response

Choose the correct option which will print the reverse of a given string.

Input: Input string
- "There are many great leaders in India"

Output: Prints reversed characters of string
- "aidnI ni sredael taerg ynam era ereht"

```
string1 = "there are many great leaders in India"
p = string1[::-1]
print(p)
```

```
string1 = "there are many great leaders in India"
p = string1[: 1]
print(p)
```

```
string1 = "There are many great leaders in India"
p = string1[ 1]
print(p)
```

```
string1 = "There are many great leaders in India"
p = string1[-1::]
print(p)
```

Need Help? Contact us (Please add country code while dialing) +91 63669 37447 +91 80471 90902

ser 2.0.2

6. Technical Skills

12 13 14 15 16 17 18 19 20 21

Attempted 16/25

Previous Next

Question 17

Revisit Later

Which of the following statements about a support vector machine with a quadratic kernel and slack penalty C is/are true?

Select an option

Clear Response

- The decision boundary is a line and large C means high penalty for misclassification.
- The decision boundary is a parabola and large C means high penalty for misclassification.
- The decision boundary is a line and large C means low penalty for misclassification.
- All of the given options

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471 90902

2

6. Technical Skills

15 16 17 18 19 20 21 22 23 24

Attempted: 19/25

Previous Next

Question 20

Revisit Later

Consider the given code for framing the SAS dataset:

```
1  data sample;
2  input Name $ EmployeeId $ Designation;
3  datalines;
4  Williams 0100 Engineer
5  Sandeep 0101 Developer
6  Jones 0102 Tester
7  Nivin 0112 Developer
8  Janes 0231 Engineer
9  Stephen 0312 Developer
10 ;
11 run;
```

In order to frame the below output, Which of the given options will you run?

Column	Emp1	Emp2	Emp3	Emp4	Emp5	Emp6
EmployeeId	96	76	76	50	62	92

○ You will run the below line of code :

```
1 proc transpose data = sample varname=Column column_prefix=Emp
  out= newdata;
2 run;
```

○ You will run the below line of code :

```
1 proc transpose data = sample column=Column column_prefix=Emp
  out= newdata;
2 run;
```

○ You will run the below line of code :

```
1 proc transpose data = sample column=Column prefix=Emp out=
  newdata;
2 run;
```

○ You will run the below line of code :

```
1 proc transpose data = sample name=Column prefix=Emp out=
  newdata;
2 run;
```

Attempted: 18/25

Question 19

Revisit Later

Select an option

What is the output of the following code snippet in python 3?

```
1 class myclass:
2   def myfunc( city, city2='Delhi'):
3     print(city)
4     print (city2)
5 o1 = myclass()
6 o1.myfunc('Chennai', 'Mumbai')
```

- Chennai
  Mumbai
- Chennai
  Delhi
- Delhi
  Mumbai
- Type error

6. Technical Skills

16 17 18 19 20 21 22 23 24 25

Attempted: 21/25

Previous

Question 22

Revisit Later

Which of the following PROC PRINT steps creates the following output?

Record	Dep	Flag	Flight
1	232	18	219
2	231	13	219
3	233	33	219

```
proc print data = flights.laguardia noobs;
    var Dept Flag flight;
    where record >= 5;
    run;
```

```
proc print data = flights.laguardia obs = 'Flight';
    var record Dept Flag;
    where Flag > 3;
    run;
```

```
proc print data = flights.laguardia label obs = 'Record';
    var boarded transferred flight;
    label boarded = 'Dept' transferred = 'Changed';
    where flight = '219';
    run;
```

```
proc print DATA=flights.laguardia noobs;
    var record Dept Flag flight;
    where flight = '219';
    run;
```

while dialing) +91 83669-37447 +91 80471-90902

6. Technical Skills

16 17 18 19 20 21 22 23 24 25

Attempted: 22/25

Question 23

Revisit Later

According to the following code, what would be the length of empcode in temp?

```
1 data temp;
2 set tem1.a
3     tem2.b;
4 length empcode $12.;
5 run;
```

Select an option

- 5
- 8
- 12
- Syntax Error

6. Technical Skills

16 17 18 19 20 21 22 23 24 25

Attempted: 20/25

Question 21

Revisit Later

Which of the following statements assigns a reference named DEMAND to a permanent SAS data library?

Select an option

```
1 libref DEMAND 'SAS-data-library'
```

```
1 libname DEMAND 'SAS-data-library'
```

```
1 libref DEMAND 'SAS-data-library';
```

```
1 libname DEMAND 'SAS-data-library';
```

6. Technical Skills

16 17 18 19 20 21 22 23 24 25

Attempted: 23/25

Question 24

Revisit Later

Which of the following PROC PRINT steps correctly prints labels instead of variable names?

Select an option

```
1 proc print data = Empdet.Deptots label;
2     label region8 = 'Region 8 Yearly Deptots';
3     run;
```

```
1 proc print data = Empdet.Deptots label noobs;
2     run;
3
```

```
1 proc print Empdet.Deptots label;
2     label region8 = 'Region 8 Yearly Deptots';
3     run;
```

+91 63669-37447 +91 80471-90902

6. Technical Skills

16 17 18 19 20 21 22 23 24 25

Attempted: 24/25

Question 25

Revisit Later

How many syntax errors does the following code contain?

```
1 data staff_temp;
2  infile 'raw-data-file';
3  input LName $ 1-20
4          FName $ 21-30
5          JTitle $ 36-43
6          Salary 54-59;
7 proc print data=staff_temp
8 run;
```

Select an option

- 0
- 1
- 2
- 3

Need Help? Contact us (Please add country code while dialing) +91 63669-37447 +91 80471-90902

202