

# **Week 2: Data Validation**

**CS 203: Software Tools and Techniques for AI**

Prof. Nipun Batra

IIT Gandhinagar

# Continuing the Netflix Story

**Last week:** We collected movie data from OMDb API

**The data we have:**

- 50+ movies in JSON format
- Features: title, year, genre, rating, director, etc.
- Saved in `movies_raw.json` and `movies.csv`

**This week:** Before we can train a model, we need to validate and clean this data

**The problem:** Real-world data is messy!

# The Reality of Data Quality

**Question:** Is our collected data ready for machine learning?

**Answer:** Almost certainly not!

**Common issues we'll find:**

- Missing values (some movies lack box office data)
- Wrong data types (ratings as strings instead of numbers)
- Inconsistent formats (runtime: "148 min" vs "148")
  - Duplicates (same movie collected twice)
  - Outliers (impossible values)

**Today's goal:** Detect, validate, and fix these issues

# The Data Validation Pipeline

RAW DATA → INSPECT → VALIDATE → CLEAN → VERIFIED DATA

## Week 2 (Today):

1. **Inspect:** Use command-line tools (jq, csvkit)
2. **Validate:** Define schemas with Pydantic
3. **Clean:** Fix issues with pandas
4. **Verify:** Confirm data quality

**Output:** Clean, validated dataset ready for ML

# Today's Agenda

1. **Understanding Data Quality** (what can go wrong)
2. **Tool #1: jq** (inspect and filter JSON)
3. **Tool #2: csvkit** (analyze CSV files)
4. **Tool #3: Pydantic** (schema validation)
5. **Tool #4: pandas** (data cleaning)
6. **Best Practices** (validation pipelines)

# Part 1: Understanding Data Quality

What makes data "good" for machine learning?

# Characteristics of Good Data

## 1. Completeness:

- All required fields are present
- Missing values are minimal and documented

## 2. Accuracy:

- Values are correct and match reality
  - No typos or data entry errors

## 3. Consistency:

- Same format across all records
  - Units are standardized

# Characteristics of Good Data (continued)

## 4. Validity:

- Values are within acceptable ranges
- Data types match expectations

## 5. Uniqueness:

- No duplicate records
- Clear primary keys

## 6. Timeliness:

- Data is current and up-to-date
- Timestamps are accurate



# Data Quality Issues in Our Movie Dataset

Let me show examples from our actual data:

## Issue 1: Missing Values

```
{  
  "Title": "Inception",  
  "BoxOffice": "N/A",  
  "Metascore": "N/A"  
}
```

## Issue 2: String Numbers

```
{  
  "imdbRating": "8.8",  
  "Year": "2010"  
}
```

# Data Quality Issues (continued)

## Issue 3: Inconsistent Formats

```
{  
  "Runtime": "148 min"  
}  
vs  
{  
  "Runtime": "90 minutes"  
}
```

## Issue 4: Comma-Separated Strings

```
{  
  "Genre": "Action, Sci-Fi, Thriller",  
  "Actors": "Leonardo DiCaprio, Joseph Gordon-Levitt"  
}
```

# Impact on Machine Learning

**Why these issues matter:**

**Missing values:**

- Can't compute features
- Models may crash or give wrong predictions

**Wrong types:**

- Mathematical operations fail
- "8.8" + "7.5" = "8.87.5" (string concatenation!)

**Inconsistent formats:**

- Feature extraction breaks
- "148 min" parsed differently than "90 minutes"

# Part 2: jq - JSON Validation

Command-line JSON processor

# What is jq?

**jq**: Lightweight command-line JSON processor

## Why use it?

- Quickly inspect JSON structure
  - Filter and transform data
  - Validate JSON syntax
  - Extract specific fields
- Count records, find unique values

## Installation:

```
# Mac  
brew install jq
```

```
# Linux
```

# Basic jq Usage

## Pretty-print JSON:

```
cat movies_raw.json | jq
```

## Get number of movies:

```
cat movies_raw.json | jq 'length'  
# Output: 52
```

## Extract single field:

```
cat movies_raw.json | jq '.[0].Title'  
# Output: "Inception"
```

# Inspecting Our Movie Data

Get all titles:

```
cat movies_raw.json | jq '[][.Title]'
```

Get titles and ratings:

```
cat movies_raw.json | jq '[] | {title: .Title, rating: .imdbRating}'
```

Count movies by year:

```
cat movies_raw.json | jq '[][.Year]' | sort | uniq -c
```

# Finding Data Quality Issues with jq

Find movies with missing box office:

```
cat movies_raw.json | jq '[] | select(.BoxOffice == "N/A") | .Title'
```

Find movies with no Metascore:

```
cat movies_raw.json | jq '[] | select(.Metascore == "N/A") | .Title'
```

Check for missing fields:

```
cat movies_raw.json | jq '[] | select(.Genre == null or .Genre == "")'
```



# Filtering with jq

**Movies rated above 8.0:**

```
cat movies_raw.json | jq '.[] | select(.imdbRating | tonumber > 8.0) | .Title'
```

**Movies from 2010s:**

```
cat movies_raw.json | jq '.[] | select(.Year | tonumber >= 2010 and tonumber < 2020)'
```

**Action movies only:**

```
cat movies_raw.json | jq '.[] | select(.Genre | contains("Action"))'
```

# Statistics with jq

Average rating:

```
cat movies_raw.json | jq '[.[] IMDbRating | tonumber] | add/length'
```

Min and max year:

```
cat movies_raw.json | jq '[.[] Year | tonumber] | min, max'
```

Count by genre (first genre only):

```
cat movies_raw.json | jq '.[] Genre' | cut -d',' -f1 | sort | uniq -c
```

# Part 3: csvkit - CSV Analysis

Swiss Army knife for CSV files

# What is csvkit?

**csvkit:** Suite of command-line tools for working with CSV

## Why use it?

- Inspect CSV structure and statistics
  - Convert between formats
  - Query CSVs like databases
  - Clean and validate data

## Installation:

```
pip install csvkit
```

# csvkit Tools

## Main tools:

- `csvstat` : Summary statistics
- `csvlook` : Pretty-print CSV
- `csvcut` : Select columns
  - `csvgrep` : Filter rows
- `csvsort` : Sort by column
- `csvjoin` : Join CSV files
- `csvstack` : Concatenate CSVs

# Inspecting CSV with csvlook

View first few rows:

```
csvlook movies.csv | head -20
```

Pretty table output:

title	year	rating	genre
Inception	2010	8.8	Action, Sci-Fi
The Matrix	1999	8.7	Action, Sci-Fi

Much more readable than raw CSV!

# Summary Statistics with csvstat

Get statistics for all columns:

```
csvstat movies.csv
```

**Output includes:**

- Number of rows and columns
  - Data types detected
  - Unique values count
- Min, max, mean (for numbers)
  - Most common values
  - Missing values count

# csvstat Example Output

```
1. title
  Type of data:      Text
  Contains null values: False
  Unique values:      52
  Longest value:      45 characters
  Most common values: Inception (1x)
```

```
2. rating
  Type of data:      Number
  Contains null values: True
  Unique values:      48
  Min:               7.5
  Max:               9.3
  Mean:              8.12
```



# Filtering with csvgrep

**Movies rated above 8.5:**

```
csvgrep -c rating -r "[89]\." movies.csv
```

**Movies from 2010:**

```
csvgrep -c year -m 2010 movies.csv
```

**Action movies:**

```
csvgrep -c genre -m "Action" movies.csv
```

# Selecting Columns with csvcut

**Get only title and rating:**

```
csvcut -c title,rating movies.csv
```

**Get columns 1, 3, and 5:**

```
csvcut -c 1,3,5 movies.csv
```

**List all column names:**

```
csvcut -n movies.csv
```

# Sorting with csvsort

**Sort by rating (descending):**

```
csvsort -c rating -r movies.csv
```

**Sort by year, then rating:**

```
csvsort -c year,rating movies.csv
```

**Save sorted output:**

```
csvsort -c rating -r movies.csv > movies_sorted.csv
```

# Finding Issues with csvkit

Check for missing values:

```
csvstat movies.csv | grep "Contains null"
```

Find duplicate titles:

```
csvcut -c title movies.csv | tail -n +2 | sort | uniq -d
```

Check data types:

```
csvstat -c rating movies.csv  
# Should be Number, not Text!
```

# Part 4: Pydantic - Schema Validation

Type-safe data validation in Python

# What is Pydantic?

**Pydantic:** Python library for data validation using type hints

## Why use it?

- Define expected data structure
- Automatically validate incoming data
  - Convert types when possible
- Raise clear errors for invalid data
  - Generate JSON schemas

## Installation:

```
pip install pydantic
```

# Defining a Movie Schema

```
from pydantic import BaseModel, Field
from typing import Optional

class Movie(BaseModel):
    title: str
    year: int
    genre: str
    director: str
    rating: float = Field(ge=0, le=10)
    votes: Optional[int] = None
    runtime: Optional[str] = None
    box_office: Optional[str] = None
```

**This schema defines:**

- Required vs optional fields
- Data types for each field

# Using the Schema

```
# Valid movie
movie_data = {
    "title": "Inception",
    "year": 2010,
    "genre": "Action, Sci-Fi",
    "director": "Christopher Nolan",
    "rating": 8.8
}

movie = Movie(**movie_data)
print(movie.title) # "Inception"
print(movie.rating) # 8.8
```

**Pydantic automatically validates!**



# Validation Errors

```
# Invalid: rating out of range
bad_movie = {
    "title": "Bad Movie",
    "year": 2020,
    "genre": "Drama",
    "director": "Someone",
    "rating": 15.0 # Invalid!
}

try:
    movie = Movie(**bad_movie)
except ValidationError as e:
    print(e)
```

**Output:**

```
rating: ensure this value is less than or equal to 10
```

# Type Conversion

```
# Pydantic converts types when possible
movie_data = {
    "title": "Inception",
    "year": "2010",          # String -> int
    "genre": "Action",
    "director": "Nolan",
    "rating": "8.8"          # String -> float
}

movie = Movie(**movie_data)
print(type(movie.year))     # <class 'int'>
print(type(movie.rating))   # <class 'float'>
```

**Automatic type coercion!**

# Custom Validators

```
from pydantic import validator

class Movie(BaseModel):
    title: str
    year: int
    rating: float

    @validator('year')
    def year_must_be_reasonable(cls, v):
        if v < 1888 or v > 2030:
            raise ValueError('invalid year')
        return v

    @validator('title')
    def title_must_not_be_empty(cls, v):
        if not v or v.strip() == '':
            raise ValueError('title cannot be empty')
        return v
```

# Validating Our Movie Dataset

```
import json
from typing import List
from pydantic import ValidationError

# Load raw data
with open('movies_raw.json') as f:
    movies_data = json.load(f)

# Validate each movie
valid_movies = []
errors = []

for i, movie_data in enumerate(movies_data):
    try:
        movie = Movie(**movie_data)
        valid_movies.append(movie)
    except ValidationError as e:
        errors.append({
            'index': i,
            'title': movie_data.get('Title'),
            'errors': e.errors()
        })
```

# Handling Validation Errors

```
# Report errors
print(f"Valid movies: {len(valid_movies)}")
print(f"Invalid movies: {len(errors)}")

# Show first few errors
for error in errors[:3]:
    print(f"\nMovie: {error['title']}")
    for err in error['errors']:
        field = err['loc'][0]
        message = err['msg']
    print(f"    {field}: {message}")
```

## Output:

```
Valid movies: 48
Invalid movies: 4
```

```
Movie: Some Movie
```

# Part 5: pandas - Data Cleaning

Powerful data manipulation library

# Why pandas for Validation?

**pandas:** Python library for data analysis

## **Use cases:**

- Load and inspect data
- Handle missing values
  - Convert data types
  - Remove duplicates
  - Detect outliers
- Compute statistics

**Already installed** (part of common ML stack)

# Loading Our Movie Data

```
import pandas as pd

# Load from CSV
df = pd.read_csv('movies.csv')

# Or from JSON
with open('movies_raw.json') as f:
    movies_data = json.load(f)
df = pd.DataFrame(movies_data)

# Basic info
print(df.shape)          # (52, 13)
print(df.columns)        # List of columns
print(df.head())         # First 5 rows
```



# Inspecting Data Quality

```
# Check data types
print(df.dtypes)

# Check for missing values
print(df.isnull().sum())

# Get summary statistics
print(df.describe())

# Check for duplicates
print(df.duplicated().sum())
```

# Example: Missing Values

```
# Count missing per column  
missing = df.isnull().sum()  
print(missing[missing > 0])
```

## Output:

box_office	15
metascore	8
awards	3

## Interpretation:

- 15 movies missing box office data
- 8 movies missing metascore
- 3 movies missing awards

# Handling Missing Values

## Strategy 1: Drop rows with missing critical fields:

```
# Drop if rating is missing  
df_clean = df.dropna(subset=['rating'])
```

## Strategy 2: Fill with defaults:

```
# Fill missing box_office with 0  
df['box_office'] = df['box_office'].fillna(0)
```

## Strategy 3: Drop columns with too many missing:

```
# Drop if > 50% missing  
threshold = len(df) * 0.5  
df_clean = df.dropna(thresh=threshold, axis=1)
```

# Type Conversion

```
# Check current types
print(df['rating'].dtype) # object (string!)

# Convert to numeric
df['rating'] = pd.to_numeric(df['rating'], errors='coerce')
df['year'] = pd.to_numeric(df['year'], errors='coerce')

# Convert to int
df['votes'] = df['votes'].str.replace(',', '', ' ').astype(int)

# Check again
print(df['rating'].dtype) # float64
```

# Cleaning String Data

```
# Extract runtime as integer
df['runtime_minutes'] = (
    df['runtime']
    .str.extract(r'(\d+)')[0]
    .astype(int)
)

# Before: "148 min"
# After:  148

# Clean box office (remove $ and commas)
df['box_office_clean'] = (
    df['box_office']
    .str.replace('$', '')
    .str.replace(',', '')
    .astype(float)
)
```

# Removing Duplicates

```
# Check for duplicate titles
duplicates = df[df.duplicated(subset=['title'], keep=False)]
print(f"Found {len(duplicates)} duplicate titles")

# Remove duplicates (keep first)
df_clean = df.drop_duplicates(subset=['title'], keep='first')

# Or keep the one with more data
df_clean = df.sort_values('rating', ascending=False)
df_clean = df_clean.drop_duplicates(subset=['title'], keep='first')
```

# Detecting Outliers

```
# Check rating distribution
print(df['rating'].describe())

# Find potential outliers (> 3 std deviations)
mean = df['rating'].mean()
std = df['rating'].std()

outliers = df[
    (df['rating'] < mean - 3*std) |
    (df['rating'] > mean + 3*std)
]

print(f"Found {len(outliers)} outliers")
print(outliers[['title', 'rating']])
```

# Validating Value Ranges

```
# Check if ratings are in valid range
invalid_ratings = df[
    (df['rating'] < 0) | (df['rating'] > 10)
]
print(f"Invalid ratings: {len(invalid_ratings)}")

# Check if years are reasonable
invalid_years = df[
    (df['year'] < 1888) | (df['year'] > 2030)
]
print(f"Invalid years: {len(invalid_years)}")
```



# Complete Cleaning Pipeline

```
def clean_movie_data(df):  
    # 1. Remove duplicates  
    df = df.drop_duplicates(subset=['title'])  
  
    # 2. Convert types  
    df['rating'] = pd.to_numeric(df['rating'], errors='coerce')  
    df['year'] = pd.to_numeric(df['year'], errors='coerce')  
  
    # 3. Drop rows with missing critical fields  
    df = df.dropna(subset=['title', 'year', 'rating'])  
  
    # 4. Validate ranges  
    df = df[  
        (df['rating'] >= 0) & (df['rating'] <= 10) &  
        (df['year'] >= 1888) & (df['year'] <= 2030)  
    ]  
  
    # 5. Clean string columns  
    df['runtime_min'] = df['runtime'].str.extract(r'(\d+)')[0]  
  
    return df
```

# Running the Pipeline

```
# Load raw data
df_raw = pd.read_csv('movies_raw.csv')
print(f"Raw data: {len(df_raw)} movies")

# Clean
df_clean = clean_movie_data(df_raw)
print(f"Clean data: {len(df_clean)} movies")


# Validate
print("\nData quality report:")
print(f"Missing values:\n{df_clean.isnull().sum()}")
print(f"\nDuplicates: {df_clean.duplicated().sum()}")
print(f"\nData types:\n{df_clean.dtypes}")

# Save
df_clean.to_csv('movies_clean.csv', index=False)
```

# **Part 6: Building a Validation Pipeline**

Putting it all together

# Validation Pipeline Architecture



# Step 1: Schema Validation

```
from pydantic import BaseModel, ValidationError
import json

class Movie(BaseModel):
    title: str
    year: int
    rating: float
    genre: str
    director: str

# Load and validate
with open('movies_raw.json') as f:
    raw_data = json.load(f)

    valid = []
    invalid = []

    for movie in raw_data:
        try:
            m = Movie(**movie)
            valid.append(m.dict())
        except ValidationError:
            invalid.append(movie)
```

## Step 2: Data Cleaning

```
import pandas as pd

# Convert to DataFrame
df = pd.DataFrame(valid)

# Clean
df['rating'] = pd.to_numeric(df['rating'], errors='coerce')
df['year'] = pd.to_numeric(df['year'], errors='coerce')

# Remove duplicates
df = df.drop_duplicates(subset=['title'])

# Handle missing
df = df.dropna(subset=['rating', 'year'])

# Validate ranges
df = df[(df['rating'] >= 0) & (df['rating'] <= 10)]
```

## Step 3: Generate Report

```
def generate_validation_report(raw, clean, invalid):  
    report = []  
  
    report.append("DATA VALIDATION REPORT")  
    report.append("=" * 50)  
    report.append(f"Input records: {len(raw)}")  
    report.append(f"Schema failures: {len(invalid)}")  
    report.append(f"Output records: {len(clean)}")  
    report.append(f"Records dropped: {len(raw) - len(clean)}")  
    report.append("")  
  
    report.append("Data Quality Metrics:")  
    report.append(f"    Completeness: {len(clean)/len(raw)*100:.1f}%")  
    report.append(f"    Duplicates removed: {len(raw) - len(clean.drop_duplicates())}")  
  
    return "\n".join(report)
```

# Complete Validation Script

```
# validate_movies.py
import json
import pandas as pd
from pydantic import BaseModel, ValidationError

class Movie(BaseModel):
    title: str
    year: int
    rating: float
    genre: str

def validate_and_clean(input_file, output_file):
    # Load
    with open(input_file) as f:
        raw = json.load(f)

    # Validate with Pydantic
    valid = []
    for movie in raw:
        try:
            valid.append(Movie(**movie).dict())
        except ValidationError:
            pass
```



## Complete Script (continued)

```
        # Clean with pandas
        df = pd.DataFrame(valid)
df['rating'] = pd.to_numeric(df['rating'], errors='coerce')
        df = df.dropna()
        df = df.drop_duplicates()

        # Save
df.to_csv(output_file, index=False)

        # Report
print(f"Validated {len(df)}/{len(raw)} movies")
        return df

        # Run
if __name__ == "__main__":
df = validate_and_clean('movies_raw.json', 'movies_clean.csv')
```

# Best Practices

## 1. Validate early:

- Check data as soon as you collect it
- Catch issues before they propagate

## 2. Be explicit:

- Define schemas clearly
- Document validation rules

## 3. Log everything:

- Record what was rejected and why
  - Generate validation reports

# Best Practices (continued)

## 4. Fail gracefully:

- Don't crash on bad data
- Handle errors and continue

## 5. Preserve raw data:

- Keep original files
- Cleaning is separate step

## 6. Automate:

- Make validation repeatable
- Run on every new data batch

# Summary: Validation Workflow

For our Netflix movie dataset:

1. **Inspect:** Use jq and csvkit to explore
2. **Define schema:** Create Pydantic models
3. **Validate:** Check against schema
4. **Clean:** Fix issues with pandas
5. **Report:** Document data quality
6. **Save:** Export clean dataset

**Output:** Validated `movies_clean.csv` ready for feature engineering

# Next Steps

## Week 3: Data Labeling

- Annotation tasks for vision and text
  - Using Label Studio
  - Inter-annotator agreement
- Building high-quality training data

## Homework:

- Validate your Week 1 movie dataset
  - Fix all data quality issues
  - Generate a validation report
- Prepare for Week 3 labeling exercises

# Key Takeaways

1.

**Data validation is critical:** Bad data = bad models

2.

**Use multiple tools:** jq for quick checks, Pydantic for schemas, pandas for cleaning

3.

**Automate validation:** Build repeatable pipelines

4.

**Document everything:** Track what was changed and why

5.

**Preserve raw data:** Never overwrite originals

# Resources

## Command-line tools:

- jq: <https://stedolan.github.io/jq/>
- csvkit: <https://csvkit.readthedocs.io/>

## Python libraries:

- Pydantic: <https://pydantic-docs.helpmanual.io/>
  - pandas: <https://pandas.pydata.org/>

## Additional reading:

- Data validation patterns
- Schema design best practices

# Questions?

**Next class:** Lab session - hands-on data validation with your movie dataset