


PadhAI: From Convolution Operation to Neural Network

One Fourth Labs


Max Pooling and Non-Linearities

What is the max pooling operation?

1. Let us look at a diagram of a CNN to better understand what max pooling does.



2. Here, as we have discussed earlier, the first operation performed is a convolutional transformation using a filter.




- a. Here, by passing the filter over an image (with or without padding), we get a transformed matrix of values

PadhAI: From Convolution Operation to Neural Network

One Fourth Labs

3. Now, we perform max-pooling over the convoluted input to select the max-value from each position of the kernel, as specified by stride length.




- Here, we select a stride length of 2 and a 2x2 filter, meaning the 4x4 convoluted output is split into 4 quadrants.
- The max value of each of these quadrants is taken and a 2x2 matrix is generated.
- Max pooling is done to select the most prominent or salient point within a neighborhood. It is also known as subsampling, as we are sampling just a single value from a region.
- Similar to Max pooling, average pooling is also done sometimes and it's carried out by taking the average value in a sampled neighborhood.
- The idea behind Max Pooling is to condense the convolutional input into a smaller size, thereby making it easier to manage.

PadhAI: From Convolution Operation to Neural Network

One Fourth Labs

4. Another point to consider is the application of nonlinearities to the convoluted output.



- Here, we can consider the convoluted output to be similar to the pre-activation layer of a neuron.
- By applying a non-linear transformation like sigmoid, tanh, ReLU etc, we are effectively transforming the convoluted output
- The resultant transformed matrix is then passed through the subsequent stages in the CNN, such as Max Pooling etc.
- Thus, we are creating a non-linear relationship between the input and the output, thereby allowing us to approximate more complex functions.
- Yet at the same time, we avoid over-complexity by reducing the number of parameters by weight sharing and condensing the convoluted output using max pooling.