

Implementation and Evaluation of Recent Neuroevolution Algorithms

Master Thesis



Implementation and Evaluation of Recent Neuroevolution Algorithms

Master Thesis
June, 2023

By
Samy Haffoudhi

Copyright: Reproduction of this publication in whole or in part must include the customary bibliographic citation, including author attribution, report title, etc.

Cover photo: Vibeke Hempler, 2012

Published by: DTU, Department of Applied Mathematics and Computer Science, Richard Petersens Plads, Building 324, 2800 Kgs. Lyngby Denmark
www.compute.dtu.dk

ISSN: [0000-0000] (electronic version)

ISBN: [000-00-0000-000-0] (electronic version)

ISSN: [0000-0000] (printed version)

ISBN: [000-00-0000-000-0] (printed version)

Approval

This thesis has been prepared over five months at the Department of Applied Mathematics and Computer Science at the Technical University of Denmark, DTU, in partial fulfilment for the degree Master of Computer Science & Engineering. The project has been supervised by Prof. Carsten Witt and corresponds to 30 ECTS points.

It is assumed that the reader has fundamental knowledge of computer science.

Samy Haffoudhi - s222887

.....
Signature

.....
Date

Abstract

Neuroevolution is a method for optimizing the topology or parameters of neural networks by means of evolutionary algorithms. This technique is more general than white-box approaches, such as supervised learning, and can therefore be applied to a wider range of problems. It has been studied in research for decades and has been successfully applied to problems such as artificial life, evolutionary robotics and continuous domains of reinforcement learning. In this thesis, we present a framework that implements neuroevolution algorithms and that is used to evaluate these algorithms on a selection of benchmark problems. Algorithms and benchmarks were collected from the state of the art in applied and theoretical research in the field of neuroevolution. The framework, implemented in Rust, allows for a visualization of key problem characteristics and the evolution process through a graphical user interface. Selected algorithms and benchmarks are presented in detail. Results collected from the conducted experiments are analyzed, discussed and used to provide a series of guidelines for the choice of algorithms and parameters with respect to problem classes.

TODO Discuss results, guidelines...

Acknowledgements

TODO

Contents

Preface	ii
Abstract	iii
Acknowledgements	iv
1 Introduction	2
2 Literature Review	4
2.1 Neuroevolution algorithms	4
2.2 Neuroevolution benchmarks	5
Bibliography	6
A Title	7

Chapter 1

Introduction

Neuroevolution is a subfield of artificial intelligence which consists in the evolution of ANNs (artificial neural networks). ANNs are traditionally trained using gradient-based methods, such as stochastic gradient descent. Over the years, these methods have been successfully applied to a variety of problems, such as image classification, speech recognition and natural language processing. Such problems allow for supervised learning, where ANNs are trained on a dataset of input-output pairs. However, there is a class of problems for which supervised learning is not applicable, where instead of input-output pairs, only a measure of performance is available. In addition, the performance of ANNs is also heavily impacted by their architectures. The design of ANNs architecture is a complex and time-consuming task, which is typically done by hand, based on experience.

Neuroevolution, on the other hand, as a more general approach, can in particular be applied to this other class of problems, as well as to the design of ANNs architectures. This method is based on evolutionary algorithms, which are inspired by the process of natural selection. These algorithms maintain a population of individuals, which are mutated and recombined to evolve towards optimal solutions. They have shown success for black-box problems and have successfully been applied to a wide range of engineering problems.

The field of neuroevolution has been researched for over 40 years, hence many different algorithms, benchmarks and applications have been proposed. As a matter of fact, neuroevolution encapsulates algorithms with different goals, such as the optimization of the weights of a fixed topology, the evolution of a network topology alongside the use of gradient-based methods for optimizing weights, the evolution of both the topology and weights, as well as the evolution of hyperparameters or reinforcement learning policies. In this thesis, we are interested in approaches relying entirely on neuroevolution, without the need for gradient-based methods, for evolving neural network parameters, using evolved or fixed topologies. In addition to these approaches, Various benchmark problems covering different problem classes such as classification, continuous control or game planning, have also been proposed in the literature for evaluating and comparing the different algorithms.

The focus of this thesis is the development of a framework that implements a selection of neuroevolution algorithms. The framework is used to evaluate and compare the algorithms on a selection of benchmarks. The framework is implemented in Rust. It allows for the visualization of the problems and the solution process through a graphical user interface. The algorithms can be run and tested through a command line interface, in order to allow for the execution of experiments and the collection of results.

Algorithms and benchmarks implemented in the framework were selected from the state-of-the

art in the theoretical and applied research in the field of neuroevolution, with a particular focus on recent algorithms and benchmarks proposed in 2023 and 2024 in the neuroevolution theory literature. In addition to these proposals, NEAT (NeuroEvolution of Augmenting Topologies), a classic algorithm in the field, and the use of evolution strategies with CMA-ES (Covariance Matrix Adaptation Evolution Strategy), achieving state-of-the-art results, were also considered. Regarding the benchmarks, in addition to the simple two dimensional binary classification benchmarks from the considered theory literature, the classic double pole balancing problem and the CANCER1 classification problem were also implemented.

1.0.1 Overview

The ordering of chapters in this report follows the chronological order of work performed for this project.

Chapter Chapter 2 gives the results of a literature review conducted on neuroevolution algorithms and benchmarks. It presents the state-of-the-art in the field, with a particular focus on recent algorithms and benchmarks proposed in the neuroevolution theory literature from 2023 and 2024. Moreover, it also presents the selection of algorithms and benchmarks that were considered in this thesis and implemented in the framework, motivating the choices and discussing the selected algorithms and benchmarks in further detail.

Furthermore, chapter ?? describes the process of designing and implementing the framework for running neuroevolution algorithms on benchmark problems, gathering statistics on these runs, and allowing for a visualization of the problems and solution process through a graphical user interface. This is done by first specifying the goals and requirements of the framework, followed by a walkthrough of the main design and implementation points of the framework.

Moreover, chapter ?? lays out the results collected from running experiments using the implemented framework. Results are presented for the selection of algorithms and benchmarks, and are discussed and compared in detail. Based on these results, a collection of observations, hypotheses and guidelines for algorithms and parameters selection, given the problem at hand, are presented. These observations are backed up by statistical tests compiled from additional experiments, which are also summarized in the chapter.

Finally, chapter ?? identifies the limitations of the project and discusses the potential lines of future work for refining and expanding on the results previously presented. The main work and contributions of this project are finally summed up in chapter ?? which concludes the report and reflects on its results.

Chapter 2

Literature Review

...

2.1 Neuroevolution algorithms

2.1.1 (1 + 1) NA

The (1 + 1) NA algorithm and its variants were introduced in Fischer, Larsen, and Witt 2023. In this work, the authors consider a simple neuroevolution setting where these algorithms are used to optimize the weights and activation function of a simple artificial neural network.

The artificial neural network

Artificial neurons with D inputs and a binary threshold activation function are considered. These neurons have D parameters, the input weights w_1, \dots, w_D and the threshold t . Let $x = (x_1, \dots, x_D) \in \mathbb{R}^D$ be the input of the neuron. The neuron outputs 1 if $\sum_{i=1}^D w_i x_i \geq t$ and 0 otherwise. This can be interpreted geometrically as the neuron outputting 1 if the input vector x is above or on the hyperplane with normal vector $w = (w_1, \dots, w_D)$ and bias t . Furthermore, an alternative representation of the decision hyperplane can be used by considering spherical coordinates. The normal vector to the decision hyperplane is described by $D - 1$ angles and the bias. As a matter of fact, for $D = 2$, the normal vector can be represented by its cartesian coordinates (x_1, x_2) or by its polar coordinates (r, θ) , where r is the distance from the origin and θ is the angle with the x_1 axis. Similarly, for $D = 3$, the normal vector can be represented by its cartesian coordinates (x_1, x_2, x_3) or by its spherical coordinates (r, θ, ϕ) , where r is the distance from the origin, θ is the angle with the x_1 axis and ϕ is the angle with the x_3 axis. It is easy to convert between these two representations. In addition, the spherical representation uses one less parameter than the cartesian representation, and hence, allows for the reduction of the number of inputs to the neurons to $D - 1$.

The ANNs which are considered in the study contain two layers, a hidden layer with $N > 1$ neurons and an output layer with a single neuron. Each of the hidden neurons are connected to the D inputs and output a binary value. The output neuron is connected to the N hidden neurons and computes the Boolean OR function of their outputs. This architecture is motivated by the problems which are considered in the study, described in ??.

The (1 + 1) NA algorithm

Let's consider an ANN with N neurons in the hidden layer and D inputs, with parameters $(\phi_{1,1}), \dots, \phi_{1,D-1}, b_1, \dots, \phi_{N,1}, \dots, \phi_{N,D-1}, b_N$. In the paper Fischer, Larsen, and Witt 2023, the search space $[0, 1]^{ND}$ is considered. Let $f : [0, 1]^{ND} \rightarrow [0, 1]$ be the fitness function which measures the performance of the ANN and is to be maximized.

The (1 + 1) NA algorithm is given in Algorithm 1.

Algorithm 1 $(1 + 1)$ NA

...

2.2 Neuroevolution benchmarks

...

Bibliography

Fischer, Paul, Emil Lundt Larsen, and Carsten Witt (2023). "First Steps Towards a Runtime Analysis of Neuroevolution". In: *Proceedings of the 17th ACM/SIGEVO Conference on Foundations of Genetic Algorithms*. Association for Computing Machinery", "61–72".

Appendix A

Title

Technical
University of
Denmark

Richard Petersens Plads, Building 324
2800 Kgs. Lyngby
Tlf. 4525 1700

www.compute.dtu.dk