

ANDROID STATIC ANALYSIS REPORT



COVID Alert NY (1.2.0)

File Name: COVID Alert NY_1.2.0_apkcombo.com.apk

Package Name: gov.ny.health.proximity

Average CVSS Score: 5.9

App Security Score: 30/100 (HIGH RISK)

Scan Date: April 22, 2022, 6:31 a.m.



File Name: COVID Alert NY_1.2.0_apkcombo.com.apk

Size: 106.24MB

MD5: 6a9afe032934080317026b45756c78b6

SHA1: 3dd54e6e21ffc655334ad2c8462609627da10013

SHA256: 91047da9f193ae804a27fa4106e681b698a8dd5bd00c6b2d8232e32ffc30d5a8

1 APP INFORMATION

App Name: COVID Alert NY

Package Name: gov.ny.health.proximity

Main Activity: gov.ny.health.proximity.MainActivity

Target SDK: 30 Min SDK: 23 Max SDK:

Android Version Name: 1.2.0 Android Version Code: 87

EE APP COMPONENTS

Activities: 2
Services: 11
Receivers: 15
Providers: 4
Exported Activities: 0
Exported Services: 3
Exported Receivers: 4
Exported Providers: 0

ECERTIFICATE INFORMATION

APK is signed v1 signature: True v2 signature: True v3 signature: True

Found 1 unique certificates

Subject: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2020-07-27 22:39:31+00:00 Valid To: 2050-07-27 22:39:31+00:00

Issuer: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android

Serial Number: 0x440852787cbb9c8939dbce4e5cbf3bdc384552e4

Hash Algorithm: sha256

md5: dc2d578109251f1fa27a0ceed85dd4b2

sha1: 741b862dd0fa2d0d659ef8cbe95f2707b74d59ca

sha256: d1ac765b2dcb237ab0c6e49e27ceb22412f4d23f0c55905e73981f45cba5fa76

 $sha512: 608c479 \\ de43 \\ d66 \\ c3a0007 \\ b6289 \\ ed80 \\ af38ecd72242 \\ b01 \\ fa7310915408545 \\ a22 \\ aa6ef8 \\ b5248 \\ bab2 \\ ad8 \\ bfd0 \\ b98090 \\ c77109 \\ a7699 \\ ff68ff3251 \\ b5a187 \\ d5ae9f7 \\ cedebar \\ b70 \\ cedebar \\ cedebar \\ b70 \\ cedebar \\ ce$

PublicKey Algorithm: rsa

Bit Size: 4096

Fingerprint: fb7e1562ae6323cd5b4e21c1f74f1ed51f3985b7eb0fa69f4b72c49ed6daa4f0

STATUS	DESCRIPTION
secure	Application is signed with a code signing certificate
warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android <7.0



PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.FOREGROUND_SERVICE	normal		Allows a regular application to use Service.startForeground.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.

MAPKID ANALYSIS

FILE	DETAILS						
	FINDINGS	DETAILS					
classes.dex	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check					
	Compiler	unknown (please file detection issue!)					

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
gov.ny.health.proximity.MainActivity	Schemes: gov.ny.health.proximity://, https://, Hosts: us-ny.en.express,

A NETWORK SECURITY

	NO	SCOPE	SEVERITY	DESCRIPTION
--	----	-------	----------	-------------

Q MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Broadcast Receiver (com.dieam.reactnativepushnotification.modules.RNPushNotificationBootEventReceiver) is not Protected. An intent-filter exists.	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Broadcast Receiver is explicitly exported.
2	Broadcast Receiver (ie.gov.tracing.nearby.ExposureNotificationBroadcastReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Service (com.google.android.gms.nearby.exposurenotification.WakeUpService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]	high	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Service (androidx.work.impl.background.gcm.WorkManagerGcmService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.permission.BIND_NETWORK_TASK_SERVICE [android:exported=true]	high	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
6	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	high	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
7	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/bumptech/glide/manager/f.java f/h/m/b.java expo/modules/filesystem/b.java h/e/a/b/g/b/c.java net/sqlcipher/database/SQLiteQuery.java h/e/a/b/g/b/m5.java f/h/n/a0.java f/h/n/b0/c.java com/bumptech/glide/load/n/a0/j.java com/bumptech/glide/load/n/b0/i.java com/bumptech/glide/load/m/j.java h/e/a/b/c/j.java com/bumptech/glide/load/m/j.java h/e/a/b/c/j.java com/bumptech/glide/load/p/c/s.java l/a/a/c.java i/a/i/a.java com/dieam/reactnativepushnotification/mo dules/RNPushNotificationListenerService.jav a f/h/e/e/a.java h/e/a/b/c/e.java com/dieam/reactnativepushnotification/mo dules/a.java h/e/a/b/g/h/p.java h/e/a/b/f/d.java net/sqlcipher/database/SQLiteDatabase.java com/bumptech/glide/load/m/l.java f/h/n/h.java h/b/a/r/l/a.java f/h/n/h.java net/sqlcipher/database/SQLiteProgram.java f/h/f/f.java net/sqlcipher/database/SQLiteProgram.java f/h/f/f.java net/sqlcipher/database/SQLiteCompiledSql.j ava h/b/a/m/e.java com/dieam/reactnativepushnotification/mo

NO	ISSUE	SEVERITY	STANDARDS	dules/c.java FUAFSjava com/bumptech/glide/load/m/o/c.java
1	The App logs information. Sensitive information should never be logged.	info	CVSS V2: 7.5 (high) CWE: CWE-532 Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	f/h/n/t.java com/bumptech/glide/load/n/h.java com/bumptech/glide/load/n/b0/e.java f/t/a/i.java f/t/a/i.java h/e/a/b/g/h/t3.java f/h/f/c.java com/bumptech/glide/load/p/g/a.java f/h/f/c.java org/unimodules/adapters/react/views/a.java net/sqlcipher/database/SQLiteQueryBuilder. java h/e/a/b/g/b/k.java i/a/c.java gov/ny/health/proximity/MainActivity.java h/e/a/b/g/h/s3.java com/bumptech/glide/load/o/d.java com/bumptech/glide/load/o/d.java com/bumptech/glide/manager/n.java f/a/k/a/a.java ie/gov/tracing/nearby/ExposureNotificationR epeaterBroadcastReceiver.java com/bumptech/glide/manager/k.java net/sqlcipher/database/SqliteWrapper.java h/e/a/b/g/l/d.java h/e/a/b/g/l/d.java h/e/a/b/c/u.java com/bumptech/glide/load/p/c/f.java f/s/y.java com/bumptech/glide/load/n/c0/a.java f/a/o/g.java ie/gov/tracing/common/g.java h/e/a/b/g/e/o.java f/h/f/g.jiava net/sqlcipher/database/SQLiteOpenHelper.j ava h/b/a/n/d.java com/bumptech/glide/load/p/c/c.java h/e/a/b/g/b/l.java net/sqlcipher/DatabaseUtils.java f/h/n/b.java com/bumptech/glide/load/p/c/h.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/k.java com/bumptech/glide/load/n/i.java f/h/f/j.java

NO	ISSUE	SEVERITY	STANDARDS	com/bumptech/glide/manager/SupportRequ Full SagerFragment.java h/d/i/c/f.java
				com/bumptech/glide/load/o/s.java f/h/e/a.java net/sqlcipher/database/SQLiteDebug.java com/th3rdwave/safeareacontext/g.java f/j/b/c.java h/e/a/b/n/a.java h/e/a/b/n/a.java com/bumptech/glide/load/n/q.java com/bumptech/glide/load/n/q.java com/dieam/reactnativepushnotification/mo dules/RNPushNotification.java f/r/a/c.java h/e/a/b/g/b/yS.java com/bumptech/glide/load/p/g/d.java h/e/a/b/g/h/jS.java h/b/a/p/h.java com/dieam/reactnativepushnotification/mo dules/e.java com/bumptech/glide/load/n/a0/k.java f/n/a/b.java com/bumptech/glide/load/n/a0/k.java f/n/a/b.java com/bumptech/glide/load/o/t.java com/bumptech/glide/load/o/f.java com/bumptech/glide/load/o/f.java com/bumptech/glide/load/o/f.java com/bumptech/glide/load/m/o/e.java h/e/a/b/b/a.java h/e/a/c/y/b.java f/hf/e.java h/e/a/c/l/h.java net/sqlcipher/database/SQLiteContentHelpe r.java com/bumptech/glide/load/m/b.java com/bumptech/glide/load/p/g/j.java h/e/a/b/g/l.java h/e/a/b/g/l.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/c/i.java h/e/a/b/g/h/e5.java h/e/a/b/g/h/e5.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/c/d.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/c/d.java h/e/a/b/g/b/f.java h/e/a/b/g/b/f.java h/e/a/b/c/d.java h/e/a/b/c/d.java h/e/a/b/c/d.java
2	The App uses an insecure Random Number Generator.	warning	CVSS V2: 7.5 (high) CWE: CWE-330 Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	k/b0/b.java ie/gov/tracing/nearby/StateUpdatedWorker.j ava k/b0/a.java com/dieam/reactnativepushnotification/mo dules/RNPushNotification.java com/dieam/reactnativepushnotification/mo dules/e.java n/b/d/a/d.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CVSS V2: 7.4 (high) CWE: CWE-312 Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	org/unimodules/adapters/react/NativeModu lesProxy.java ie/gov/tracing/network/PublishG.java com/pedrouid/crypto/RNSCRandomBytes.ja va com/bumptech/glide/load/n/p.java com/toyberman/RNSslPinningModule.java com/bumptech/glide/load/n/d.java com/bumptech/glide/load/h.java com/bumptech/glide/load/n/x.java
4	IP Address disclosure	warning	CVSS V2: 4.3 (medium) CWE: CWE-200 Information Exposure OWASP MASVS: MSTG-CODE-2	n/b/a/z1/a.java n/b/a/a2/e.java n/b/a/d2/j.java n/b/a/d2/x.java n/b/a/e2/g.java n/b/a/c2/e/b.java
5	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	CVSS V2: 5.9 (medium) CWE: CWE-89 Improper Neutralization of Special warning CWE: CWE-80 Improper Neutralization of Special Elements used in an SQL Command ('SQL f/q/a/g/a.java		h/e/a/a/i/x/j/h0_java f/q/a/g/a.java com/reactnativecommunity/asyncstorage/e.j ava
6	App creates temp file. Sensitive information should never be written into a temp file.	warning	CVSS V2: 5.5 (medium) CWE: CWE-276 Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/toyberman/b/a.java h/e/a/b/j/b.java h/d/b/b/a.java
7	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	CVSS V2: 0 (info) OWASP MASVS: MSTG-NETWORK-4	com/toyberman/b/a.java ie/gov/tracing/network/d.java
8	App can read/write to External Storage. Any App can read data written to External Storage.	high	CVSS V2: 5.5 (medium) CWE: CWE-276 Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	f/h/e/b.java h/a/a/a/a/a.java h/d/b/b/a.java f/h/e/a.java h/d/d/i/a.java
9	SHA-1 is a weak hash known to have hash collisions.	warning	CVSS V2: 5.9 (medium) CWE: CWE-327 Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	h/d/d/k/c.java
10	This App uses SQL Cipher. SQLCipher provides 256-bit AES encryption to sqlite database files.	info	CVSS V2: 0 (info) OWASP MASVS: MSTG-CRYPTO-1	net/sqlcipher/database/SupportHelper.java
11	App can write to App Directory. Sensitive Information should be encrypted.	info	CVSS V2: 3.9 (low) CWE: CWE-276 Incorrect Default Permissions OWASP MASVS: MSTG-STORAGE-14	i/a/h/c.java

► SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/arm64-v8a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
2	lib/arm64-v8a/libfb.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libfbjni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
4	lib/arm64- v8a/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/arm64-v8a/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
6	lib/arm64-v8a/libglog.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/arm64-v8a/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
8	lib/arm64-v8a/libhermes- executor-debug.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	lib/arm64-v8a/libhermes- executor-release.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
10	lib/arm64-v8a/libhermes- inspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	lib/arm64- v8a/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	lib/arm64-v8a/libjsc.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False Warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
13	lib/arm64-v8a/libjscexecutor.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False Warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	lib/arm64- v8a/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
15	lib/arm64-v8a/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	lib/arm64-v8a/libnative- filters.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	lib/arm64-v8a/libnative- imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
18	lib/arm64- v8a/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	lib/arm64- v8a/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
20	lib/arm64-v8a/libsqlcipher.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	lib/arm64-v8a/libyoga.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
22	lib/armeabi- v7a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	lib/armeabi-v7a/libfb.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
24	lib/armeabi-v7a/libfbjni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	lib/armeabi- v7a/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
26	lib/armeabi-v7a/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	lib/armeabi-v7a/libglog.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
28	lib/armeabi-v7a/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	lib/armeabi-v7a/libhermes- executor-debug.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
30	lib/armeabi-v7a/libhermes- executor-release.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	lib/armeabi-v7a/libhermes- inspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
32	lib/armeabi- v7a/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	lib/armeabi-v7a/libjsc.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
34	lib/armeabi- v7a/libjscexecutor.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	lib/armeabi- v7a/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
36	lib/armeabi- v7a/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	lib/armeabi-v7a/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
38	lib/armeabi-v7a/libnative- imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	lib/armeabi- v7a/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
40	lib/armeabi- v7a/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	lib/armeabi-v7a/libsqlcipher.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
42	lib/armeabi-v7a/libyoga.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	lib/x86/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
44	lib/x86/libfb.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	lib/x86/libfbjni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
46	lib/x86/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	lib/x86/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
48	lib/x86/libglog.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	lib/x86/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
50	lib/x86/libhermes-executor- debug.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	lib/x86/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
52	lib/x86/libhermes-inspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	lib/x86/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
54	lib/x86/libjsc.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	lib/x86/libjscexecutor.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
56	lib/x86/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	lib/x86/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
58	lib/x86/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	lib/x86/libnative- imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
60	lib/x86/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	lib/x86/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
62	lib/x86/libsqlcipher.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	lib/x86/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
64	lib/x86_64/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	lib/x86_64/libfb.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
66	lib/x86_64/libfbjni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	lib/x86_64/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
68	lib/x86_64/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	lib/x86_64/libglog.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
70	lib/x86_64/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	lib/x86_64/libhermes-executor- debug.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
72	lib/x86_64/libhermes-executor- release.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	lib/x86_64/libhermes- inspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
74	lib/x86_64/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	lib/x86_64/libjsc.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option - z,relro,- z,now to enable full RELRO and only - z,relro to enable partial RELRO.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
76	lib/x86_64/libjscexecutor.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	lib/x86_64/libjsijniprofiler.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
78	lib/x86_64/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	lib/x86_64/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
80	lib/x86_64/libnative- imagetranscoder.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	lib/x86_64/libreactnativeblob.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
82	lib/x86_64/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	lib/x86_64/libsqlcipher.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
84	lib/x86_64/libyoga.so	True info The shared object has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run- time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application invoke platform-provided DRBG functionality for its cryptographic operations.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application implement asymmetric key generation.
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity', 'bluetooth'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application implement functionality to encrypt sensitive data in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.
10	FCS_RBG_EXT.2.1,FCS_RBG_EXT.2.2	Selection-Based Security Functional Requirements	Random Bit Generation from Application	The application perform all deterministic random bit generation (DRBG) services in accordance with NIST Special Publication 800-90A using Hash_DRBG. The deterministic RBG is seeded by an entropy source that accumulates entropy from a platform-based DRBG and a software-based noise source, with a minimum of 256 bits of entropy at least equal to the greatest security strength (according to NIST SP 800-57) of the keys and hashes that it will generate.
11	FCS_CKM.1.1(1)	Selection-Based Security Functional Requirements	Cryptographic Asymmetric Key Generation	The application generate asymmetric cryptographic keys not in accordance with FCS_CKM.1.1(1) using key generation algorithm RSA schemes and cryptographic key sizes of 1024-bit or lower.
12	FCS_COP.1.1(1)	Selection-Based Security Functional Requirements	Cryptographic Operation - Encryption/Decryption	The application perform encryption/decryption not in accordance with FCS_COP.1.1(1), AES-ECB mode is being used.
13	FCS_COP.1.1(2)	Selection-Based Security Functional Requirements	Cryptographic Operation - Hashing	The application perform cryptographic hashing services not in accordance with FCS_COP.1.1(2) and uses the cryptographic algorithm RC2/RC4/MD4/MD5.
14	FCS_COP.1.1(3)	Selection-Based Security Functional Requirements	Cryptographic Operation - Signing	The application perform cryptographic signature services (generation and verification) in accordance with a specified cryptographic algorithm RSA schemes using cryptographic key sizes of 2048-bit or greater.
15	FCS_HTTPS_EXT.1.2	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement HTTPS using TLS.
16	FCS_HTTPS_EXT.1.3	Selection-Based Security Functional Requirements	HTTPS Protocol	The application notify the user and not establish the connection or request application authorization to establish the connection if the peer certificate is deemed invalid.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
17	FIA_X509_EXT.2.1	Selection-Based Security Functional Requirements	X.509 Certificate Authentication	The application use X.509v3 certificates as defined by RFC 5280 to support authentication for HTTPS , TLS.
18	FPT_TUD_EXT.2.1	Selection-Based Security Functional Requirements	Integrity for Installation and Update	The application shall be distributed using the format of the platform-supported package manager.
19	FCS_CKM.1.1(2)	Optional Security Functional Requirements	Cryptographic Symmetric Key Generation	The application shall generate symmetric cryptographic keys using a Random Bit Generator as specified in FCS_RBG_EXT.1 and specified cryptographic key sizes 128 bit or 256 bit.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.unicode.org	good	IP: 66.34.208.12 Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map
www.zetetic.net	good	IP: 13.225.71.35 Country: United States of America Region: New Jersey City: Newark Latitude: 40.735661 Longitude: -74.172371 View: Google Map
github.com	good	IP: 140.82.114.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
schemas.android.com	good	No Geolocation information available.
expo.io	good	IP: 34.132.55.135 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map

URLS

URL	FILE
data:image	com/bumptech/glide/load/o/e.java

URL	FILE
http://schemas.android.com/apk/res/android	f/h/e/e/g.java
https://expo.io	i/a/j/f.java
https://github.com/ReactiveX/RxJava/wiki/Plugins	j/a/b.java
https://github.com/ReactiveX/RxJava/wiki/What's-different-in-2.0#error-handling	j/a/g/e.java
https://www.zetetic.net/sqlcipher/ https://www.zetetic.net/sqlcipher/license/ https://github.com/sqlcipher/android-database-sqlcipher	Android String Resource
http://www.unicode.org/copyright.html	lib/arm64-v8a/libjsc.so
http://www.unicode.org/copyright.html	lib/armeabi-v7a/libjsc.so
http://www.unicode.org/copyright.html	lib/x86/libjsc.so
http://www.unicode.org/copyright.html	lib/x86_64/libjsc.so

P HARDCODED SECRETS

POSSIBLE SECRETS

"library_android_database_sqlcipher_author" : "Zetetic, LLC"

"library_android_database_sqlcipher_authorWebsite" : "https://www.zetetic.net/sqlcipher/"

App Security Score Calculation

Every app is given an ideal score of 100 to begin with.

For every findings with severity high we reduce 15 from the score.

For every findings with severity warning we reduce 10 from the score.

For every findings with severity good we add 5 to the score.

If the calculated score is greater than 100, then the app security score is considered as 100.

And if the calculated score is less than 0, then the app security score is considered as 10.

Risk Calculation

APP SECURITY SCORE	RISK
0 - 15	CRITICAL
16 - 40	HIGH
41 - 70	MEDIUM
71 - 100	LOW

Report Generated by - MobSF v3.4.5 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.