



ANDROID STATIC ANALYSIS REPORT



COVIDaware MN (1.17.12)

File Name:	COVIDaware MN_1.17.12_apkcombo.com.apk
Package Name:	org.pathcheck.covidsafepathsBt.mn
Average CVSS Score:	6.5
App Security Score:	40/100 (HIGH RISK)
Trackers Detection:	2/421
Scan Date:	March 11, 2022, 3:43 p.m.

FILE INFORMATION

File Name: COVIDaware MN_1.17.12_apkcombo.com.apk

Size: 73.9MB
MD5: bf107ce32b4fe1126d4d80f7ce344c59
SHA1: a5c1f550a1815417b4f10c2595835ee72929f8b0
SHA256: bdb8362bacf934251ae65ee83624ed9abcd23b45de5c2eafc98810fb7912d25d

i APP INFORMATION

App Name: COVIDaware MN
Package Name: org.pathcheck.covidsafepathsBt.mn
Main Activity: org.pathcheck.covidsafepaths.SplashActivity
Target SDK: 30
Min SDK: 23
Max SDK:
Android Version Name: 1.17.12
Android Version Code: 3503

APP COMPONENTS

Activities: 3
Services: 5
Receivers: 10
Providers: 2
Exported Activities: 1
Exported Services: 2
Exported Receivers: 3
Exported Providers: 0

CERTIFICATE INFORMATION

APK is signed
v1 signature: True
v2 signature: True
v3 signature: True
Found 1 unique certificates
Subject: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2020-08-12 22:34:33+00:00
Valid To: 2050-08-12 22:34:33+00:00
Issuer: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android
Serial Number: 0xa3be6f50bc1f0a1a20705deb612b0336fd623039
Hash Algorithm: sha256
md5: f6de0919f0e03c736a4d5f64cf935a77
sha1: 15d4e9268be8c333675425df833025cf14388b33
sha256: 62c6b7672ae15c8558036952f149c075ca6d3641a74f644ae41bc2c1a34b413c
sha512: a380e2c6488ced26aa92385f4cd9adfbcb891a0e5749006c6c56da40d63c976dd34404d0316b591ca88fe0f1c04adfc7544d6889cf24018739c68eed55e8acadf
PublicKey Algorithm: rsa
Bit Size: 4096
Fingerprint: 83ca69686cf5cbbd9bf314d7c44ea3601ab68d7681148e98e46a28c8e34ed7e7

STATUS	DESCRIPTION
secure	Application is signed with a code signing certificate
warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android <7.0

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.FOREGROUND_SERVICE	normal		Allows a regular application to use Service.startForeground.

APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check Build.TAGS check network operator name check
	Compiler	r8

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
org.pathcheck.covidsafepaths.MainActivity	Schemes: pathcheck://, https://, Hosts: exposureHistory, us-mn.en.express,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Activity (org.pathcheck.covidsafepaths.MainActivity) is not Protected. [android:exported=true]	high	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Broadcast Receiver (org.pathcheck.covidsafepaths.exposurenotifications.nearby.ExposureNotificationBroadcastReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Service (com.google.android.gms.nearby.exposurenotification.WakeUpService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]	high	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	high	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
6	Broadcast Receiver (org.matomo.sdk.extra.InstallReferrerReceiver) is not Protected. [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CVSS V2: 7.5 (high) CWE: CWE-532 Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/bottlerocketstudios/vault/keys/storage/CompatSharedPref KeyStorageFactory.java com/horcrux/svg/RadialGradientView.java com/bottlerocketstudios/vault/keys/wrapper/ObfuscatingSecre tKeyWrapper.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/EscrowVerificationClient\$refresh\$2.java io/realm/RealmCache.java org/pathcheck/covidsafepaths/exposurenotifications/network/ DiagnosisKeyDownloader.java com/bottlerocketstudios/vault/keys/storage/hardware/Android KeystoreTester.java com/bugsnag/android/Configuration.java org/pathcheck/covidsafepaths/exposurenotifications/reactmod ules/ExposureNotificationsModule.java com/horcrux/svg/RenderableView.java com/horcrux/svg/MaskView.java org/pathcheck/covidsafepaths/exposurenotifications/reactmod ules/UtilsModule.java com/bottlerocketstudios/vault/keys/storage/SharedPrefKeyStor age.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/DeviceIDHelper\$getDeviceID\$2.java com/swmansion/gesturehandler/react/RNGestureHandlerRoot View.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/EscrowVerificationClient\$authenticate\$2.java io/realm/internal/OsRealmConfig.java org/pathcheck/covidsafepaths/exposurenotifications/chaff/Chaf fRequestWorker\$startWork\$2.java com/reactnativecommunity/asyncstorage/AsyncStorageModule .java com/reactnativecommunity/webview/RNCWebViewModule.java io/realm/Realm.java org/pathcheck/covidsafepaths/exposurenotifications/nearby/Ex posureConfigurations\$refresh\$1\$responseListener\$1.java org/pathcheck/covidsafepaths/exposurenotifications/Exposure NotificationClientWrapper.java org/pathcheck/covidsafepaths/exposurenotifications/nearby/St ateUpdatedWorker.java org/pathcheck/covidsafepaths/exposurenotifications/nearby/Ex posureConfigurations\$refresh\$1\$errorListener\$1.java org/pathcheck/covidsafepaths/exposurenotifications/network/ Uris.java com/horcrux/svg/UseView.java org/pathcheck/covidsafepaths/exposurenotifications/storage/R ealmSecureStorageBte.java com/bugsnag/android/ExceptionHandler.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/EscrowVerificationClient\$postMetalInfo\$2.java com/swmansion/gesturehandler/react/RNGestureHandlerRoot Helper.java org/pathcheck/covidsafepaths/exposurenotifications/reactmod ules/\$\$Lambda\$ExposureNotificationsModule\$fq6jUihTgXtqXK Npq33_h3vKswk.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/EscrowVerificationClient\$postPositiveSubmission\$ 2.java io/realm/BaseRealm.java com/reactnativecommunity/webview/RNCWebViewManager.jav a com/bugsnag/android/DebugLogger.java com/horcrux/svg/PatternView.java org/pathcheck/covidsafepaths/exposurenotifications/network/e scrowserver/DeviceIDHelper.java com/horcrux/svg/ClipPathView.java com/th3rdwave/safeareacore/SafeAreaView.java com/horcrux/svg/VirtualView.java org/pathcheck/covidsafepaths/exposurenotifications/nearby/Pr ovideDiagnosisKeysWorker.java com/horcrux/svg/LinearGradientView.java com/horcrux/svg/ImageView.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	The App uses ECB mode in Cryptographic encryption algorithm. ECB mode is known to be weak as it results in the same ciphertext for identical blocks of plaintext.	high	CVSS V2: 5.9 (medium) CWE: CWE-327 Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-2	com/bottlerocketstudios/vault/keys/wrapper/ObfuscatingSecretKeyWrapper.java
3	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CVSS V2: 5.9 (medium) CWE: CWE-89 Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/reactnativecommunity/asyncstorage/ReactDatabaseSupplier.java
4	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CVSS V2: 7.4 (high) CWE: CWE-312 Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/bugsnag/android/BugsnagReactNative.java org/pathcheck/covidsafepaths/BuildConfig.java org/pathcheck/covidsafepaths/exposurenotifications/storage/objects/KeyValues.java com/pedrouid/crypto/RNSCRandomBytes.java
5	This App uses SafetyNet API.	secure	CVSS V2: 0 (info) OWASP MASVS: MSTG-RESILIENCE-7	org/pathcheck/covidsafepaths/exposurenotifications/network/escrowserver/DeviceIDHelper\$getDeviceID\$2.java
6	This App may have root detection capabilities.	secure	CVSS V2: 0 (info) OWASP MASVS: MSTG-RESILIENCE-1	com/bugsnag/android/DeviceDataCollector.java
7	App can read/write to External Storage. Any App can read data written to External Storage.	high	CVSS V2: 5.5 (medium) CWE: CWE-276 Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/reactnativecommunity/webview/RNCWebViewModule.java
8	App creates temp file. Sensitive information should never be written into a temp file.	warning	CVSS V2: 5.5 (medium) CWE: CWE-276 Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/reactnativecommunity/webview/RNCWebViewModule.java
9	The App uses an insecure Random Number Generator.	warning	CVSS V2: 7.5 (high) CWE: CWE-330 Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	org/matomo/sdk/Tracker.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	--------------	-------	-------	---------	---------	------------------

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/arm64-v8a/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions:</p> <pre>[__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__read_chk', '__strchr_chk', '__vsprintf_chk', '__strcpy_chk']</pre>	<p>True info</p> <p>Symbols are stripped.</p>
2	lib/arm64-v8a/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libc++_shared.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
4	lib/arm64-v8a/libfb.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/arm64-v8a/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
6	lib/arm64-v8a/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/arm64-v8a/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
8	lib/arm64-v8a/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	lib/arm64-v8a/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
10	lib/arm64-v8a/libhermes-executor-common-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	lib/arm64-v8a/libhermes-executor-common-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
12	lib/arm64-v8a/libhermes-executor-debug.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	lib/arm64-v8a/libhermes-executor-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
14	lib/arm64-v8a/libhermes-inspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	lib/arm64-v8a/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: <code>['__memcpy_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk']</code></p>	<p>True info</p> <p>Symbols are stripped.</p>
16	lib/arm64-v8a/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	lib/arm64-v8a/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
18	lib/arm64-v8a/libjsjniprofiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	lib/arm64-v8a/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
20	lib/arm64-v8a/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	lib/arm64-v8a/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
22	lib/arm64-v8a/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	lib/arm64-v8a/libreactnativejni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
24	lib/arm64-v8a/libreactnativeutilsjni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	lib/arm64-v8a/libreactperloggerjni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
26	lib/arm64-v8a/libreact_codegen_reactandroidspec.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	lib/arm64-v8a/libreact_nativemodule_core.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
28	lib/arm64-v8a/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__read_chk', '__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__vsnprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	lib/arm64-v8a/libturbomodulejsijni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
30	lib/arm64-v8a/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	lib/armeabi-v7a/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
32	lib/armeabi-v7a/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	lib/armeabi-v7a/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
34	lib/armeabi-v7a/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	lib/armeabi-v7a/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
36	lib/armeabi-v7a/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	lib/armeabi-v7a/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
38	lib/armeabi-v7a/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	lib/armeabi-v7a/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
40	lib/armeabi-v7a/libhermes-executor-common-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	lib/armeabi-v7a/libhermes-executor-common-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
42	lib/armeabi-v7a/libhermes-executor-debug.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	lib/armeabi-v7a/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
44	lib/armeabi-v7a/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	lib/armeabi-v7a/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
46	lib/armeabi-v7a/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	lib/armeabi-v7a/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
48	lib/armeabi-v7a/libjsjniprofiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	lib/armeabi-v7a/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
50	lib/armeabi-v7a/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	lib/armeabi-v7a/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
52	lib/armeabi-v7a/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	lib/armeabi-v7a/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
54	lib/armeabi-v7a/libreactnativeutilsjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	lib/armeabi-v7a/libreactperfloggerjni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
56	lib/armeabi-v7a/libreact_codegen_reactandroidspec.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	lib/armeabi-v7a/libreact_nativemodule_core.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
58	lib/armeabi-v7a/librealm-jni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	lib/armeabi-v7a/libturbomodulejsijni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
60	lib/armeabi-v7a/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	lib/x86/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
62	lib/x86/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	lib/x86/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
64	lib/x86/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	lib/x86/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
66	lib/x86/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	lib/x86/libfolly_json.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
68	lib/x86/libglog.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	lib/x86/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
70	lib/x86/libhermes-executor-common-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	lib/x86/libhermes-executor-common-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
72	lib/x86/libhermes-executor-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	lib/x86/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
74	lib/x86/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	lib/x86/libhermes.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
76	lib/x86/libimagepipeline.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	lib/x86/libjsccexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
78	lib/x86/libjsijni profiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	lib/x86/libjsinspector.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
80	lib/x86/libnative-filters.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	lib/x86/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
82	lib/x86/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	lib/x86/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
84	lib/x86/libreactnativeutilsjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	lib/x86/libreactperfloggerjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
86	lib/x86/libreact_codegen_reactandroidspec.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	lib/x86/libreact_nativemodule_core.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
88	lib/x86/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	lib/x86/libturbomodulejsijni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
90	lib/x86/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	lib/x86_64/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strcpy_chk', '__strchr_chk', '__memcpy_chk', '__memmove_chk', '__read_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>
92	lib/x86_64/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
93	lib/x86_64/libc++_shared.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
94	lib/x86_64/libfb.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
95	lib/x86_64/libfbjni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
96	lib/x86_64/libfolly_futures.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
97	lib/x86_64/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
98	lib/x86_64/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
99	lib/x86_64/libglog_init.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
100	lib/x86_64/libhermes-executor-common-debug.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
101	lib/x86_64/libhermes-executor-common-release.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
102	lib/x86_64/libhermes-executor-debug.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
103	lib/x86_64/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
104	lib/x86_64/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
105	lib/x86_64/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__vsnprintf_chk', '__strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>
106	lib/x86_64/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
107	lib/x86_64/libjscexecutor.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
108	lib/x86_64/libjsijni profiler.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
109	lib/x86_64/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
110	lib/x86_64/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
111	lib/x86_64/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
112	lib/x86_64/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
113	lib/x86_64/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
114	lib/x86_64/libreactnativeutilsjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
115	lib/x86_64/libreactperfloggerjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
116	lib/x86_64/libreact_codegen_reactandroidspec.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
117	lib/x86_64/libreact_nativemodule_core.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>
118	lib/x86_64/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__read_chk', '__vsnprintf_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
119	lib/x86_64/libturbomodulejsijni.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.
120	lib/x86_64/libyoga.so	True info The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	False info The shared object does not have run-time search path or RPATH set.	False info The shared object does not have RUNPATH set.	False warning The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
1	FCS_RBG_EXT.1.1	Security Functional Requirements	Random Bit Generation Services	The application invoke platform-provided DRBG functionality for its cryptographic operations.
2	FCS_STO_EXT.1.1	Security Functional Requirements	Storage of Credentials	The application does not store any credentials to non-volatile memory.
3	FCS_CKM_EXT.1.1	Security Functional Requirements	Cryptographic Key Generation Services	The application implement asymmetric key generation.

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
4	FDP_DEC_EXT.1.1	Security Functional Requirements	Access to Platform Resources	The application has access to ['network connectivity', 'bluetooth'].
5	FDP_DEC_EXT.1.2	Security Functional Requirements	Access to Platform Resources	The application has access to no sensitive information repositories.
6	FDP_NET_EXT.1.1	Security Functional Requirements	Network Communications	The application has user/application initiated network communications.
7	FDP_DAR_EXT.1.1	Security Functional Requirements	Encryption Of Sensitive Application Data	The application implement functionality to encrypt sensitive data in non-volatile memory.
8	FMT_MEC_EXT.1.1	Security Functional Requirements	Supported Configuration Mechanism	The application invoke the mechanisms recommended by the platform vendor for storing and setting configuration options.
9	FTP_DIT_EXT.1.1	Security Functional Requirements	Protection of Data in Transit	The application does encrypt some transmitted data with HTTPS/TLS/SSH between itself and another trusted IT product.
10	FCS_RBG_EXT.2.1,FCS_RBG_EXT.2.2	Selection-Based Security Functional Requirements	Random Bit Generation from Application	The application perform all deterministic random bit generation (DRBG) services in accordance with NIST Special Publication 800-90A using Hash_DRBG. The deterministic RBG is seeded by an entropy source that accumulates entropy from a platform-based DRBG and a software-based noise source, with a minimum of 256 bits of entropy at least equal to the greatest security strength (according to NIST SP 800-57) of the keys and hashes that it will generate.
11	FCS_CKM.1.1(1)	Selection-Based Security Functional Requirements	Cryptographic Asymmetric Key Generation	The application generate asymmetric cryptographic keys not in accordance with FCS_CKM.1.1(1) using key generation algorithm RSA schemes and cryptographic key sizes of 1024-bit or lower.
12	FCS_COP.1.1(1)	Selection-Based Security Functional Requirements	Cryptographic Operation - Encryption/Decryption	The application perform encryption/decryption not in accordance with FCS_COP.1.1(1), AES-ECB mode is being used.
13	FCS_COP.1.1(2)	Selection-Based Security Functional Requirements	Cryptographic Operation - Hashing	The application perform cryptographic hashing services not in accordance with FCS_COP.1.1(2) and uses the cryptographic algorithm RC2/RC4/MD4/MD5.
14	FCS_COP.1.1(3)	Selection-Based Security Functional Requirements	Cryptographic Operation - Signing	The application perform cryptographic signature services (generation and verification) in accordance with a specified cryptographic algorithm RSA schemes using cryptographic key sizes of 2048-bit or greater.
15	FCS_HTTPS_EXT.1.1	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement the HTTPS protocol that complies with RFC 2818.
16	FCS_HTTPS_EXT.1.2	Selection-Based Security Functional Requirements	HTTPS Protocol	The application implement HTTPS using TLS.
17	FCS_HTTPS_EXT.1.3	Selection-Based Security Functional Requirements	HTTPS Protocol	The application notify the user and not establish the connection or request application authorization to establish the connection if the peer certificate is deemed invalid.
18	FIA_X509_EXT.2.1	Selection-Based Security Functional Requirements	X.509 Certificate Authentication	The application use X.509v3 certificates as defined by RFC 5280 to support authentication for HTTPS , TLS.

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
--------	--------	-------------

DOMAIN	STATUS	GEOLOCATION
encdn.prod.exposurenotification.health	good	IP: 40.90.64.55 Country: Colombia Region: Distrito Capital de Bogota City: Bogota Latitude: 4.609710 Longitude: -74.081749 View: Google Map
cdn.projectaurora.cloud	good	IP: 35.244.172.56 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
play.google.com	good	IP: 142.251.35.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
covidawaremn.com	good	IP: 151.111.166.96 Country: United States of America Region: Minnesota City: Saint Paul Latitude: 44.962872 Longitude: -93.124031 View: Google Map
sessions.bugsnap.com	good	IP: 35.190.88.7 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
github.com	good	IP: 140.82.114.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
apiserver.encv.org	good	IP: 34.107.223.222 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
notify.bugsnap.com	good	IP: 35.186.205.6 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map

DOMAIN	STATUS	GEOLOCATION
bugsnag.com	good	IP: 13.33.60.31 Country: United States of America Region: New Jersey City: Newark Latitude: 40.735661 Longitude: -74.172371 View: Google Map
prod.exposurenotification.health	good	IP: 13.107.213.40 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
issuetracker.google.com	good	IP: 142.250.80.46 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
mn.gov	good	IP: 66.225.237.206 Country: United States of America Region: Illinois City: Chicago Latitude: 41.878201 Longitude: -87.625397 View: Google Map
realm.io	good	IP: 18.67.76.97 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
docs.bugsnag.com	good	IP: 68.183.29.183 Country: United States of America Region: New Jersey City: North Bergen Latitude: 40.804272 Longitude: -74.012077 View: Google Map

URLs

URL	FILE
https://docs.bugsnag.com/platforms/android/anr-link-errors	com/bugsnag/android/AnrPlugin.java
https://github.com/bugsnag/bugsnag-js	com/bugsnag/android/BugsnagReactNativePlugin.java
https://notify.bugsnag.com https://sessions.bugsnag.com	com/bugsnag/android/EndpointConfiguration.java
https://bugsnag.com	com/bugsnag/android/Notifier.java
https://github.com/software-mansion/react-native-screens/issues/17#issuecomment-424704067	com/swmansion/rnscreens/ScreenFragment.java

URL	FILE
https://github.com/software-mansion/react-native-screens/issues/17#issuecomment-424704067	com/swmansion/rnscreens/ScreenStackFragment.java
https://%/s/	com/terveystalo/react_native/matomo_sdk/RNMatomoSdkModule.java
https://github.com/ReactiveX/Rxjava/wiki/Plugins	io/reactivex/rxjava3/core/Observable.java
https://github.com/ReactiveX/Rxjava/wiki/Error-Handling	io/reactivex/rxjava3/exceptions/OnErrorNotImplementedException.java
https://github.com/ReactiveX/Rxjava/wiki/What's-different-in-2.0#error-handling	io/reactivex/rxjava3/exceptions/UndeliverableException.java
https://issuetracker.google.com/issues/36918154	io/realm/Realm.java
https://realm.io/news/android-installation-change/	io/realm/RealmConfiguration.java
https://cdn.projectaurora.cloud/mn/cfg/android/v1.6.config.json https://play.google.com/store/apps/details?id=org.pathcheck.covidsafepathsBt.mn https://cdn.projectaurora.cloud/mn/cfg/ios/v1.config.json https://cdn.projectaurora.cloud/mn/cfg/ios/v2.config.json https://mn.gov/covid19/for-minnesotans/covidawaremn/exposure-notification.jsp?ref=c1 https://encdn.prod.exposurenotification.health https://cdn.projectaurora.cloud/cfg/v1.config.json https://cdn.projectaurora.cloud/cfg/v1.6.config.json https://cdn.projectaurora.cloud/cfg https://apiserver.encv.org https://mn.gov/covid19/ https://covidawaremn.com/privacy-policy.shtml https://prod.exposurenotification.health https://covidawaremn.com https://covidawaremn.com/faq.shtml#verificationcodes	org/pathcheck/covidsafepaths/BuildConfig.java
https://encdn.prod.exposurenotification.health/	org/pathcheck/covidsafepaths/exposurenotifications/nearby/DiagnosisKeyFileSubmitter.java

EMAILS

EMAIL	FILE
help@realm.io	lib/arm64-v8a/librealm-jni.so
help@realm.io	lib/armeabi-v7a/librealm-jni.so
help@realm.io	lib/x86/librealm-jni.so
help@realm.io	lib/x86_64/librealm-jni.so

TRACKERS

TRACKER	CATEGORIES	URL
Bugsnap	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/207
Matomo (Piwik)	Analytics	https://reports.exodus-privacy.eu.org/trackers/138

App Security Score Calculation

Every app is given an ideal score of 100 to begin with.
For every findings with severity **high** we reduce 15 from the score.
For every findings with severity **warning** we reduce 10 from the score.
For every findings with severity **good** we add 5 to the score.
If the calculated score is greater than 100, then the app security score is considered as 100.
And if the calculated score is less than 0, then the app security score is considered as 10.

Risk Calculation

APP SECURITY SCORE	RISK
0 - 15	CRITICAL
16 - 40	HIGH
41 - 70	MEDIUM
71 - 100	LOW

Report Generated by - MobSF v3.4.5 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.