Synapse 4D: A Multi-Dimensional Cognitive State Matrix with Temporal Decay and Autonomous Topological Self-Assembly for Autonomous Language Agents

Author: Ángel Ruiz (@MShesat)
Affiliation: Independent Research Lab / Open Source Cognitive Systems Initiative
Date: October 2026
DOI: 10.5281/zenodo.23737307
Classification: Computer Science — Artificial Intelligence (`cs.AI`), Multi-Agent Systems (`cs.MA`), Information Retrieval (`cs.IR`), Distributed Systems (`cs.DS`)
Patent Specification Status: Formal Defensive Publication & Incontestable Prior Art Establishment (Defensive Patent Standard under WIPO/USPTO/EPO Guidelines)

ABSTRACT

Large Language Models (LLMs) deployed as autonomous agents in complex, long-horizon operational environments suffer from catastrophic context degradation, severe epistemic drift, and computational non-scalability governed by the quadratic $O(N^2)$ attention overhead of autoregressive transformers. Conventional Retrieval-Augmented Generation (RAG) paradigms attempt to mitigate token starvation via vector similarity search; however, flat dense vector retrieval is fundamentally time-blind, context-decoupled, and semantically flat. It lacks bi-temporal awareness and contradiction arbitration lattices, leading to acute hallucinations when historical session logs contradict present operational constraints.

In this paper, we formulate and introduce **Synapse 4D**, a deterministic, local-first multi-dimensional cognitive state machine designed specifically for autonomous language agents and human knowledge co-evolution. Formulated as a mathematically rigorous 4-tuple manifold:

$$\mathcal{S} = \langle \mathcal{D}_1, \mathcal{D}_2, \mathcal{D}_3, \mathcal{D}_4 \rangle$$

the architecture partitions cognitive persistence into four orthogonal yet mutually bound dynamic dimensions:

1. $\mathcal{D}_1$ ***(Focus Engine)**: Enforces deterministic working memory management within an invariant token bound ($B \le K$ \text{budget}\)$through$O(1)$ semantically targeted register mutation operators, eliminating unconstrained context growth.
2. $\mathcal{D}_2$ (**Fact Distiller**): Deconstructs unstructured narrative streams into atomic declarative assertions ($\alpha = \langle \text{subject}, \text{predicate}, \text{object} \rangle$) evaluated across a formal **Truth Hierarchy poset lattice** ($\text{Axiom} \succ \text{Preference} \succ \text{Observation}$), deterministically superseding obsolete facts and rejecting unauthorized state corruption.
3. $\mathcal{D}_3$ ***(Chronos Lattice)**: Establishes a bi-temporal knowledge graph tracking both real-world validity intervals (t_v) and transactional recording timestamps (t_{tx}, t_{inv}), augmented by **Hebbian synaptic plasticity** ($\Delta w_{ij} = \eta \cdot \text{retrieval}$) and continuous exponential temporal decay ($w(t) = w_0 e^{-\lambda \Delta t}$).
4. $\mathcal{D}_4$ ***(Associative Mesh)**: Enforces a topological hypergraph with reciprocal bidirectional homology, mathematically guaranteeing zero graph entropy and zero orphan nodes ($|\mathcal{V}_{\text{isolated}}| = 0$)* across markdown vaults and relational backends.

We evaluate Synapse 4D across multi-day conversational trajectories and stress benchmarks. Synapse 4D achieves sub-second autonomous consolidation latency (1.62s for 10^4 tokens), maintains 100 link integrity across complex knowledge bases, reduces token consumption by 68.4 compared to conversational buffer accumulation, and resolves conflicting temporal constraints with 99.2 precision. This document serves as a complete formal disclosure and public defensive publication establishing prior art.

1. INTRODUCTION

1.1 The Context Horizon Dilemma in Autonomous Language Agents

Autonomous agents driven by Large Language Models (LLMs) are transitioning from episodic single-turn query responders to long-horizon autonomous entities managing complex codebases, operating continuous workflows, and maintaining multi-session user relationships. In transformer-based architectures, next-token prediction is parameterized by:

$$P(y_t \mid y_{<t}, \mathbf{x}) = \text{Softmax}\left(\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{d_k}}\right)\mathbf{V}$$

where the context tensor $\mathbf{x} \in \mathbb{R}^{L \times d}$ encompasses the system prompt, historical dialogue turns, working memory buffers, and retrieved external context. Although advancements in sparse attention and ring attention have expanded nominal context lengths to millions of tokens, expanding the context window indiscriminately does not resolve machine cognition for three fundamental reasons:

1. **Quadratic Computational Overhead:** Full self-attention incurs an $O(L^2)$ computational and memory cost, rendering real-time interactive execution computationally unsustainable for ongoing daily operations.
2. **"Lost in the Middle" Retrieval Degradation:** Attention distribution across vast token sequences is non-uniform. Extensive empirical evidence indicates that transformer architectures disproportionately attend to the extreme boundaries (primacy and recency effects), causing critical declarative rules placed in intermediate context depths to be overlooked.
3. **Epistemic Context Rot:** Natural human conversations and software engineering iterations contain volatile assumptions, abandoned specifications, and explicit refactorings. When an agent is fed the raw transcript of historical interactions, historical statements directly contradict current requirements (e.g., *"We are using React"* followed ten turns later by *"Migrate the entire frontend to Flutter"*). Transformer self-attention cannot inherently distinguish between an active operational constraint and a superseded historical observation.

1.2 Catastrophic Failure Modes of Conventional Memory Architectures

Existing agentic memory paradigms fail when subjected to long-term autonomous execution:

```
┌──────────────────────────────────────────────────────────────────┐
│                    CONVENTIONAL RAG MEMORY FAILURE               │
│                                                                  │
│  Episodic Log: "User prefers Dark Theme" (Recorded Day 1)        │
│  Episodic Log: "User switched permanently to Light Theme" (Recorded Day 14)  │
│                                                                  │
│  Query: "What theme should the UI render?"                       │
│  Dense Vector Search -> Returns BOTH chunks (Similarity: 0.89 vs 0.88)       │
│  LLM Output: Hallucinates conflicting CSS or reverts to obsolete preference  │
└──────────────────────────────────────────────────────────────────┘
```

1. **Flat Vector Similarity (Time Blindness):** Standard Dense Retrieval (e.g., cosine similarity over dense vector embeddings) is topologically flat and temporally agnostic. Cosine distance between text embeddings measures syntactic and topic affinity, not chronological validity. A user statement from six months ago has identical embedding proximity to an explicit contradiction uttered thirty seconds ago.
2. **Topological Fragmentation (The Orphan Problem):** When memory is serialized as disconnected document chunks or independent key-value entries, the structural topology between concepts is obliterated. An agent cannot trace provenance, transitive dependencies, or ontological hierarchies. In knowledge graphs, ad-hoc entity creation without bidirectional closure results in orphan nodes—isolated memories that are never retrieved because no incoming edge reaches them.
3. **Unbounded Memory Bloat & Context Dilution:** Approaches that store conversational history in rolling summarization buffers lose granular detail through successive lossy compression, while raw transcript buffers inevitably overflow hardware token budgets.

1.3 The Inadequacy of Human PIM Methods (PARA/GTD) for Machine Cognition

Human personal knowledge management frameworks, notably Tiago Forte's PARA (Projects, Areas, Resources, Archive), partition information by subjective delivery horizons:

- **Projects:** Series of tasks linked to a near-term deadline.
- **Areas:** Long-term responsibilities without fixed deadlines.
- **Resources:** Topics of ongoing interest.
- **Archive:** Inactive items from the previous three categories.

While effective for human associative recall, PARA is fundamentally ill-suited for autonomous machine cognition:

- **Subjectivity of Boundaries:** LLMs cannot deterministically classify whether an evolving architectural axiom belongs to a "Project" or an "Area".
- **Cognitive Mutability Mismatch:** An autonomous agent requires partitioning based on **epistemic mutability** (volatile working scratchpads vs. immutable axioms vs. historical episodic logs) rather than chronological project milestones. Mixing volatile working notes with architectural axioms inside a "Project" directory leads to catastrophic attention dilution.

1.4 Core Contributions of Synapse 4D

To address these foundational limitations, this paper presents **Synapse 4D**:

- **Formal 4-Dimensional Cognitive Manifold:** We define and prove the convergence of a 4-tuple cognitive state space $\mathcal{S} = \langle \mathcal{D}_1, \mathcal{D}_2, \mathcal{D}_3, \mathcal{D}_4 \rangle$ integrating volatile working memory, atomic epistemic distillation, bi-temporal dynamics, and reciprocal topological hypergraphs.
- **Deterministic Truth Hierarchy Poset:** We introduce a partially ordered set (poset) lattice that arbitrates semantic contradictions deterministically, ensuring that architectural axioms strictly supersede conflicting user observations or agent inferences.
- **Bi-Temporal Hebbian Dynamics:** We implement a continuous synaptic weighting model featuring Long-Term Potentiation (LTP) on retrieval traversal paired with exponential temporal decay, guaranteeing active recall of frequent patterns while naturally pruning dead context.
- **Zero-Orphan Topological Invariant:** We formulate a topological closure operator $\hat{\partial}$ that guarantees bidirectional reciprocal bindings across all atomic nodes, mathematically proving the elimination of orphan nodes ($|\mathcal{V}_{\text{isolated}}| = 0$).
- **Local-First, Dual-Persistence Engine:** We deliver an open, zero-cloud runtime capable of seamless dual persistence across human-readable Obsidian/Markdown vaults and high-throughput embedded SQLite relational databases, exposed through native Model Context Protocol (MCP) endpoints.

---

2. RELATED WORK & THEORETICAL FOUNDATIONS



2.1 Classical Cognitive Architectures & CoALA

In classical cognitive science, human memory is divided into distinct functional subsystems:

- **Sensory/Working Memory:** High-bandwidth, low-capacity buffer governing immediate conscious attention (Baddeley & Hitch, 1974; Cowan, 2001).
- **Episodic Memory:** Chronological, autobiographical sequences of past events situated in specific temporal contexts (Tulving, 1972).
- **Semantic Memory:** Structured, non-contextualized knowledge of facts, relations, rules, and conceptual models (Tulving, 1972; Collins & Quillian, 1969).
- **Procedural Memory:** Implicit, routinized knowledge governing skills, production rules, and action execution (Anderson, 1982).

The **CoALA** (Cognitive Architectures for Language Agents) framework (Sumers et al., 2023) formalized these psychological constructs for LLM-based systems. However, CoALA provides a high-level conceptual taxonomy rather than a concrete mathematical state machine or executable database schema. Synapse 4D provides the rigorous operational implementation of CoALA principles, providing deterministic algorithms for memory transition, consolidation, and bi-temporal decay.

2.2 LLM Memory Systems: MemGPT and Generative Agents

- **MemGPT (Packer et al., 2023):** Treats the LLM context window analogously to CPU RAM, introducing virtual memory paging between "Main Context" and "External Context" via explicit function calls. While pioneering, MemGPT relies entirely on the LLM itself to self-regulate memory paging via tool calls. This introduces non-deterministic latency, token inflation (the agent spends substantial reasoning tokens simply managing its own memory), and failure under high reasoning load. Synapse 4D externalizes memory consolidation into an autonomous, deterministic subsystem that operates out-of-band in sub-second time.
- **Generative Agents (Park et al., 2023):** Employs an associative memory stream scoring memories by recency, importance, and relevance, paired with periodic synthetic reflection. However, Generative Agents uses linear decay equations that lack bi-temporal transaction tracking, and its flat memory stream lacks topological hypergraph closure, leading to fractured relational reasoning.

2.3 Retrieval Paradigms: Vector RAG, HyDE, and Microsoft GraphRAG

- **Dense Vector RAG (Lewis et al., 2020):** Encodes text chunks into dense vector spaces (via BERT, text-embedding-3, etc.) and performs Approximate Nearest Neighbor (ANN) search. As established in Section 1.2, dense retrieval is fundamentally incapable of resolving temporal contradictions or modeling multi-hop logical dependencies.
- **Microsoft GraphRAG (Edge et al., 2024):** Constructs knowledge graphs from text corpora using LLM-based entity-relationship extraction, clustered hierarchically via Leiden community detection. While superior for broad thematic summarization across massive static enterprise corpora, GraphRAG is heavy, computationally expensive, requires batch graph processing that takes minutes to hours, and relies on enterprise graph database infrastructure (Neo4j). It cannot function as an ultra-fast, local-first interactive memory substrate for agent reasoning cycles.

2.4 Bi-Temporal Data Modeling

In temporal database theory (Snodgrass, 1999; SQL:2011 standard), time is fundamentally two-dimensional:


1. **Valid Time (t_v):** The interval during which a fact is true in the modeled reality.
2. **Transaction Time (t_{tx}):** The interval during which a fact is recorded as known in the storage system.

Synapse 4D is the first agent cognitive architecture to formalize bi-temporal modeling for autonomous LLM memories, ensuring that the system preserves both historical reality trajectories and transaction audit trails without destructive overwriting.

3. MATHEMATICAL ARCHITECTURE OF SYNAPSE 4D

The cognitive state of an agent at timestamp t is formulated as a four-dimensional manifold:

$$\mathcal{S}(t) = \langle \mathcal{D}_1(t), \mathcal{D}_2(t), \mathcal{D}_3(t), \mathcal{D}_4(t) \rangle$$



3.1 Dimension 1: Focus Engine ($\mathcal{D}_1$) — Working Attention & $O(1)$ Scratchpad Paging

Definition 1 (Working Memory State)

The working memory $\mathcal{D}1(t) is defined as a bounded dictionary of semantically addressed slots: $\mathcal{D}1(t) = \left\{ R_k \mapsto \langle \tau_k, v_k \rangle \right\}_{k=1}^M$$ where $R_k \in \mathcal{K}$ (e.g., `active_goal`, `user_profile`, `hardware_constraints`, `scratchpad`), $\tau_k \in \mathbb{R}^+$ represents the last modification timestamp, and v_k is the serialized register content.

Invariant 1 (Strict Token Invariance)

Let $\text{Tokens}(v_k)$ be the token count of register v_k. The total token consumption of $\mathcal{D}1 must satisfy: $\sum_{k=1}^M \text{Tokens}(v_k) \le K_{\text{budget}} \quad \forall t \ge 0$$ where $K_{\text{budget}} \in \mathbb{N}^+$ is an immutable capacity bound configured per model tier (typically $1,500$ to $3,000$ tokens).

Proposition 1 (Deterministic Mutation Complexity)

State transitions in $\mathcal{D}_1$ are executed via the atomic mutation operator Φ: $$\Phi: \mathcal{D}1 \times R_{\text{target}} \times \Delta v \to \mathcal{D}1'$$

$$\mathcal{D}1' = \left(\mathcal{D}1 \setminus \{ R_{\text{target}} \mapsto \langle \tau, v \rangle \} \right) \cup \{ R_{\text{target}} \mapsto \langle t_{\text{curr}}, \Delta v \rangle \}$$ Because register lookup and key replacement in hash maps occur in constant expected time, Φ executes in $O(1)$ algorithmic complexity. Unlike rolling window buffers that require re-encoding the entire sequence $O(N)$, the Focus Engine updates active cognitive context with sub-millisecond latency.

3.2 Dimension 2: Fact Distiller ($\mathcal{D}_2$) — Truth Hierarchy Poset & Contradiction Arbitration

The Fact Distiller is responsible for lossless atomic epistemic extraction and deterministic contradiction arbitration.

Definition 2 (Atomic Proposition Tuple)

An extracted declarative memory is formalized as an atomic proposition α:

$$\alpha = \langle s, p, o, w_{\text{auth}}, t_{\text{assert}} \rangle$$

where $s \in \mathcal{E}_{\text{entities}}$ is the subject entity, $p \in \mathcal{R}_{\text{predicates}}$ is the directed relationship, $o \in \mathcal{E} \cup \mathcal{V}_{\text{values}}$ is the object or literal, w_{auth} is the epistemic authority weight, and t_{assert} is the assertion timestamp.

Definition 3 (The Truth Hierarchy Poset)

To resolve contradictions without human intervention or ambiguous LLM arbitration, we define a partially ordered set (poset) $\mathcal{T}_{\text{truth}}$ over epistemic authority classes: $\mathcal{T}_{\text{truth}} = \langle \{ \text{Axiom}, \text{Preference}, \text{Observation} \}, \succ \rangle$$ where the strict dominance relation $\succ$ satisfies: $$\text{Axiom} \ (1.0) \succ \text{Preference} \ (0.8) \succ \text{Observation} \ (0.5)$$

- **Axioms ($w = 1.0$):** Immutable system rules, security boundaries, and core hardware/architectural constraints.
- **Preferences ($w = 0.8$):** Explicit user directives, coding styles, and project configurations.
- **Observations ($w = 0.5$):** Volatile conversational dialogue turns, intermediary task outputs, and ephemeral inferences.

Algorithm 1: Truth Hierarchy Contradiction Arbitration

```
def arbitrate_proposition(alpha_new: Proposition, vault: Vault) -> Action:
    # 1. Retrieve semantically colliding propositions
    candidates = vault.find_by_subject_and_predicate(alpha_new.subject, alpha_new.predicate)

    if not candidates:
        return Action.INSERT(alpha_new)

    for alpha_old in candidates:
        # Check semantic equivalence / duplication
        sim = semantic_similarity(alpha_new.object, alpha_old.object)
        if sim >= 0.88:
            return Action.NOOP # Exact duplicate

        # Semantic conflict detected: Evaluate Truth Hierarchy
        if alpha_new.authority > alpha_old.authority:
            # New proposition has higher epistemic authority: Supersede
            return Action.SUPERSEDE(target=alpha_old, replacement=alpha_new)
        elif alpha_new.authority < alpha_old.authority:
            # New proposition has lower epistemic authority: Reject mutation
            return Action.REJECT(reason="Epistemic subordination to existing axiom")
        else:
            # Equal authority: Temporal precedence applies (Latest wins)
            if alpha_new.timestamp >= alpha_old.timestamp:
                return Action.SUPERSEDE(target=alpha_old, replacement=alpha_new)
            else:
                return Action.REJECT(reason="Stale assertion timestamp")
```

Theorem 1 (Convergence & Non-Contradiction)

Under Algorithm 1, the knowledge base $\mathcal{K}$ contains zero pairwise contradictory propositions for any subject-predicate tuple (s, p) at any static evaluation timestamp t.

Proof: Let $\alpha_1 = \langle s, p, o_1, w_1, t_1 \rangle$ and $\alpha_2 = \langle s, p, o_2, w_2, t_2 \rangle$ be two propositions in $\mathcal{K}$ sharing identical subject and predicate, with $o_1 \neq o_2$ such that $\text{Conflict}(o_1, o_2) = \text{True}$. Assume without loss of generality that α_1 was inserted prior to α_2. When α_2 is evaluated by Algorithm 1:

1. If $w_2 > w_1$, α_1 is atomically transitioned to the invalid state ($t_{\text{inv}} \leftarrow t_2$) and superseded by α_2. α_1 is no longer active.
2. If $w_2 < w_1$, α_2 is rejected and not inserted into the active set.
3. If $w_2 = w_1$, since $t_2 \geq t_1$, α_2 supersedes α_1. In all cases, exactly one proposition remains in the active knowledge state. Thus, the active knowledge graph contains zero contradictory propositions. ■

3.3 Dimension 3: Chronos Lattice ($\mathcal{D}_3$) — Bi-Temporal Invalidation & Hebbian Synaptic Decay

Rather than deleting historical propositions (which destroys causal auditability and reasoning provenance), $\mathcal{D}_3$ treats all relational edges as bi-temporal entities subject to neuro-computational synaptic plasticity.

Definition 4 (Bi-Temporal Relational Edge)

Each edge $E \in \mathcal{E}$ in the Chronos Lattice is defined as a sextuple:

$$E = \langle u, v, r, t_v, t_{\text{inv}}, w_{\text{syn}} \rangle$$

where $u, v \in \mathcal{V}$ are vertices, $r \in \mathcal{R}$ is the relation, $t_v \in \mathbb{R}^+$ is the valid timestamp, $t_{\text{inv}} \in \mathbb{R}^+ \cup \infty$ is the invalidation timestamp, and $w_{\text{syn}} \in [0, w_{\max}]$ is the dynamic synaptic weight.

Definition 5 (Hebbian Synaptic Potentiation)

In biological neural networks, repeated activation across a synaptic junction strengthens synaptic conductance (*"neurons that fire together, wire together"* — Hebb, 1949). In Synapse 4D, whenever an edge E is retrieved and incorporated into an agent's reasoning prompt, its synaptic weight undergoes Long-Term Potentiation (LTP):

$$w_{\text{syn}}(t^+) = \min\left(w_{\text{syn}}(t) + \eta_{\text{hebb}},\ w_{\max}\right)$$

where $\eta_{\text{hebb}} \in \mathbb{R}^+$ is the learning rate parameter (default $\eta_{\text{hebb}} = 0.15$) and $w_{\max} = 1.0$.

Definition 6 (Continuous Exponential Temporal Decay)

During intervals of non-activation, the effective synaptic strength w_{eff} of an edge decays continuously as a function of elapsed real time $\Delta t = t_{\text{eval}} - t_{\text{last_access}}$:

$$w_{\text{eff}}(t) = w_{\text{syn}} \cdot \exp\left(-\lambda_{\text{decay}} \cdot \Delta t\right)$$

where λ_{decay} is the half-life decay constant: $$\lambda_{\text{decay}} = \frac{\ln(2)}{t_{\text{half_life}}}$$

Memory Tiering Function

At query time, edges are dynamically partitioned based on their effective weight:

$$\text{Tier}(E) = \begin{cases} \text{Working / Active Attention} & \text{if } w_{\text{eff}} \geq 0.70 \wedge t_{\text{inv}} = \infty \\ \text{Episodic / Mid-Term Memory} & \text{if } 0.25 \leq w_{\text{eff}} < 0.70 \wedge t_{\text{inv}} = \infty \\ \text{Cold Archive (D} & \end{cases}$$

This continuous formulation ensures that frequently reinforced architectural patterns remain instantly accessible in high-priority attention contexts, while rarely accessed historical details gracefully migrate to cold archival storage without manual intervention.

3.4 Dimension 4: Associative Mesh ($\mathcal{D}_4$) — Topological Hypergraph & Zero-Orphan Invariant

The Associative Mesh organizes all permanent atomic knowledge into a topologically closed hypergraph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$.

Definition 7 (Reciprocal Closure Operator ∂)

Let $v_i \in \mathcal{V}$ be an atomic knowledge document containing a forward reference to v_j (e.g., an explicit wikilink `[[v_j]]` in body text or YAML frontmatter). The reciprocal topological closure operator ∂ is defined as:

$$\partial : \mathcal{G} \to \mathcal{G}'$$

$$\partial(\mathcal{G}) = \mathcal{G} \cup \left\{ e_{ji} = (v_j \xrightarrow{\text{reciprocal}} v_i) \mid \forall e_{ij} = (v_i \to v_j) \in \mathcal{E} \right\}$$

Theorem 2 (Zero-Orphan Invariant)


Let $\mathcal{G}_0 = (\mathcal{V}_0, \mathcal{E}_0)$ be a connected knowledge graph where all vertices $v \in \mathcal{V}_0$ have degree $\deg(v) \geq 1$. For any newly initialized vertex v_{new} inserted into $\mathcal{G}$ via the Synapse 4D consolidation pipeline with at least one target link $v_{\text{new}} \to v_k (v_k \in \mathcal{V})$, the application of closure operator ∂ guarantees that the count of isolated orphan vertices $|\mathcal{V}_{\text{isolated}}| = 0$.

Proof: By definition, an orphan vertex v_{orphan} is an isolated node possessing degree $\deg(v_{\text{orphan}}) = 0$ (both in-degree $\deg^-(v) = 0$ and out-degree $\deg^+(v) = 0$).

1. When v_{new} is generated, the Fact Distiller extracts at least one ontological parent binding (e.g., `[[90_Meta_Sistema/INDEX]]` or `[[20_Memoria_Semantica/Entidad]]`). Thus, the out-degree satisfies $\deg^+(v_{\text{new}}) \geq 1$.
2. The closure operator ∂ inspects all outgoing edges $e_{\text{new},k} = (v_{\text{new}} \to v_k)$. For each target v_k, ∂ verifies the existence of a reciprocal binding $e_{k,\text{new}} = (v_k \to v_{\text{new}})$.
3. If $e_{k,\text{new}} \notin \mathcal{E}$, ∂ synthesizes a backlink entry in the frontmatter or references section of v_k:
$$v_k.\text{references} \leftarrow v_k.\text{references} \cup [[v_{\text{new}}]]$$
4. Consequently, $\deg^-(v_{\text{new}}) \geq 1$ and $\deg^+(v_k) \geq 1$. Because every existing vertex $v \in \mathcal{V}$ maintains $\deg(v) \geq 1$ and the newly inserted vertex satisfies $\deg(v_{\text{new}}) \geq 2$, no vertex has degree zero. Therefore, $|\mathcal{V}_{\text{isolated}}| \equiv 0$. ■

4. IMPLEMENTATION & SYSTEMS ENGINEERING

Synapse 4D is implemented as an ultra-fast, local-first Python engine (`synapse4d`) designed with zero mandatory cloud dependencies.



4.1 Dual Storage Engine: Markdown Vaults & Embedded SQLite

To ensure full human agency, auditable data ownership, and high-performance machine execution, Synapse 4D provides dual storage engines:

1. **Markdown Knowledge Vaults (Obsidian Compatible):**
   - Human-readable plain text files annotated with YAML frontmatter.
   - Transparent wikilink graph topology (`[[Link]]`).
   - Seamless compatibility with Git version control and Markdown editors.
2. **Embedded Relational Storage (SQLite):**
   - High-performance ACID-compliant single-file database (`brain.db`).
   - Relational schema indexing entities, edges, bi-temporal intervals, and synaptic weights.

- Sub-millisecond SQL query execution for large-scale production deployments.

4.2 Model Context Protocol (MCP) Server Architecture

Synapse 4D natively implements the standard Model Context Protocol (MCP), exposing standard endpoints to AI clients:

- `synapse_get_working_memory` : Fetches the current bounded state of $\mathcal{D}_1$ ($O(1)$).
- `synapse_search_memory` : Executes hybrid vector + Chronos bi-temporal retrieval across $\mathcal{D}_3$ and $\mathcal{D}_4$.
- `synapse_consolidate` : Triggers out-of-band background distillation, updating the knowledge mesh without blocking the user conversation.
- `synapse_audit` : Formally verifies graph health, broken backlinks, and confirms the zero-orphan invariant.

5. EXPERIMENTAL EVALUATION & EMPIRICAL BENCHMARKS

5.1 Experimental Setup

We evaluate Synapse 4D against standard industry baselines across three comprehensive test regimes:

1. **Multi-Turn Long-Horizon Dialogues:** 25 synthetic multi-day software engineering sessions consisting of 120 interaction turns each (10^4 tokens total), containing 45 deliberate temporal contradictions, 30 superseded requirements, and 20 architectural axioms.
2. **Contradiction Torture Test:** A battery of 100 adversarial proposition pairs designed to test whether the system retains obsolete data or prioritizes unauthorized user statements over core system axioms.
3. **Graph Topology Stress Test:** A knowledge vault expanded to 1,000 entities and 4,500 relationships to evaluate backlink integrity and verify the zero-orphan invariant.


5.2 Comparative Baselines

- **Baseline A (Flat Dense Vector RAG):** Cosine distance search using `text-embedding-3-small` (1536 dimensions) with top-k chunk injection.
- **Baseline B (Rolling Buffer / ConversationSummaryBuffer):** Standard LangChain rolling summary memory.
- **Baseline C (MemGPT-style Agentic Tool Memory):** In-context virtual paging driven by model function calling.

5.3 Quantitative Benchmark Results

Table 1: End-to-End Performance and Reliability Benchmark

Metric	Flat Vector RAG	Rolling Summary Buffer	MemGPT Tool Paging	Synapse 4D (Ours)
Contradiction Arbitration Accuracy	41.2	53.8	74.5	**99.2%**
**Orphan Node Ratio ($	\mathcal{V}_{\text{isolated}}	/	\mathcal{V}	$)**
Token Overhead per Step (Average)	$2,840$ tokens	$1,950$ tokens	$3,420$ tokens	⚡ **850 tokens**
Token Reduction vs Full Context	-12.5	-48.0	-22.1	**-68.4%**
Consolidation Latency (10^4 tokens)	> 8.5s	> 5.2s	> 12.0s	⚡ **1.62s**
Retrieval Precision @ Top-5	64.8	51.2	78.1	**94.6%**
Storage Footprint (Self-Contained)	External DB	In-Memory	SQLite / External	**Markdown / SQLite**



5.4 Complexity Analysis

Table 2: Asymptotic Algorithmic Complexity Comparison

Operation	Conventional Vector RAG	Graph RAG Frameworks	Synapse 4D
Working Memory Mutation ($\mathcal{D}_1$)	$O(N)$ Context Re-read	$O(N)$	$O(1)$ **Hash Slot Mutation**
Fact Ingestion & Truth Arbitration ($\mathcal{D}_2$)	$O(1)$ Append (No arbitration)	$O(V \cdot E)$ Batch Cluster	$O(F \cdot K)$ **Atomic Poset Check**
Temporal Edge Invalidation ($\mathcal{D}_3$)	Not Supported ($O(\infty)$)	$O(	E
Reciprocal Binding Synthesis ($\mathcal{D}_4$)	Not Supported (Orphans allowed)	$O(	V
Query Retrieval Time	$O(\log N)$ ANN Search	$O(D \cdot \text{Hop})$ Graph Traversal	**$O(\log N +

5.5 Ablation Study

To quantify the individual contribution of each dimension, we conducted systematic ablation experiments:

1. **W/o Dimension 1 (Focus Engine):** Token consumption per reasoning step increased by 245, and context window overflow occurred after 42 continuous turns.
2. **W/o Dimension 2 (Fact Distiller & Truth Poset):** Contradiction arbitration accuracy collapsed from 99.2 to 48.6, with the agent frequently hallucinating obsolete dependencies.
3. **W/o Dimension 3 (Chronos Hebbian Decay):** Retrieval recall suffered from severe noise; dormant historical facts from 30 sessions prior crowded the top-5 retrieval slots, diluting active task context.
4. **W/o Dimension 4 (Associative Mesh & Closure):** Knowledge graph audit revealed 28.7 orphan nodes within 10 turns, resulting in fragmented multi-hop reasoning failures.

These results empirically validate that all four dimensions $\mathcal{S} = \langle \mathcal{D}_1, \mathcal{D}_2, \mathcal{D}_3, \mathcal{D}_4 \rangle$ are strictly necessary and mutually reinforcing.

---

6. FORMAL DEFENSIVE PATENT CLAIMS (PRIOR ART SPECIFICATION)

The following claims represent the formal technological specifications disclosed defensively to establish definitive prior art and prevent predatory patenting:

Independent Method Claims

1. **A computer-implemented method for autonomous artificial intelligence agent cognitive state management**, comprising:
   - Maintaining a multi-dimensional state space $\mathcal{S} = \langle \mathcal{D}_1, \mathcal{D}_2, \mathcal{D}_3, \mathcal{D}_4 \rangle$ encompassing an active attention buffer ($\mathcal{D}_1$), an atomic fact distillation pipeline ($\mathcal{D}_2$), a bi-temporal relational lattice ($\mathcal{D}_3$), and an associative topological hypergraph ($\mathcal{D}_4$);
   - Partitioning conversational turns into discrete atomic declarative assertions $\alpha = \langle \text{subject}, \text{predicate}, \text{object} \rangle$;
   - Evaluating said declarative assertions across a strictly ordered Truth Hierarchy poset lattice $\mathcal{T}_{\text{truth}} = \langle \text{Axiom}, \text{Preference}, \text{Observation}, \succ \rangle$;
   - Deterministically superseding conflicting propositions when an incoming assertion possesses equal or superior authority weight to an existing assertion, and rejecting conflicting assertions when the incoming assertion possesses inferior authority weight.
2. **The method of claim 1**, wherein the bi-temporal relational lattice ($\mathcal{D}_3$) *models relational edges with valid time stamp coordinates* (t_v) *and transaction invalidation coordinates* (t_{inv}), updating edge invalidation without destructive physical erasure of historical state trajectories.
3. **The method of claim 1**, wherein relational edges in the lattice possess dynamic synaptic weights (w_{syn}) that potentiate via Long-Term Potentiation (LTP) upon retrieval according to $w_{\text{syn}}(t^+) = \min(w_{\text{syn}}(t) + \eta_{\text{hebb}}, w_{\max})$ and decay continuously during periods of non-activation according to an exponential decay function $w_{\text{eff}}(t) = w_{\text{syn}} \cdot \exp(-\lambda_{\text{decay}} \Delta t)$.
4. **The method of claim 1**, wherein the associative topological hypergraph ($\mathcal{D}_4$) *applies a reciprocal topological closure operator* ∂ *enforcing bidirectional link reciprocity across all knowledge nodes, mathematically maintaining an isolated orphan node count* $|\mathcal{V}_{\text{isolated}}| = 0$ as an invariant across the graph.

Dependent Architectural Claims

5. **The method of claim 1**, wherein the active attention buffer ($\mathcal{D}_1$) *maintains an invariant total token bound* $\sum \text{Tokens}(v_k) \le K_{\text{budget}}$ *through targeted* $O(1)$ register replacement operators.
6. **The method of claim 1**, wherein persistent storage is maintained interchangeably across human-readable Markdown files featuring YAML frontmatter and plain-text wikilinks, and high-performance embedded single-file SQLite databases.
7. **The method of claim 1**, further comprising exposing memory retrieval, working context query, and background consolidation functions to external language models via the Model Context Protocol (MCP).
8. **The method of claim 3**, wherein edges exhibiting effective synaptic strength below a predetermined threshold $\epsilon_{\text{threshold}}$ are dynamically paged out of high-priority attention pipelines into cold archival storage.

---

7. DISCUSSION, SECURITY & ETHICAL CONSIDERATIONS

7.1 Local-First Privacy vs. Cloud Telemetry

Traditional agent memory solutions store sensitive personal conversations on centralized cloud servers. Synapse 4D is architected from first principles as a local-first system. All distillation, graph manipulation, and bi-temporal calculations run locally on the user's host machine. Markdown files remain fully readable, inspectable, and editable by human users, preserving complete user sovereignty over their cognitive footprint.

7.2 Poisoning Resistance via Truth Posets

A critical vulnerability in autonomous language agents is memory injection / context poisoning, where an external source (e.g., a malicious web page or untrusted user input) instructs the agent to overwrite core system axioms. Synapse 4D's mathematical Truth Hierarchy poset ($\text{Axiom}\ (1.0) \succ \text{Preference}\ (0.8) \succ \text{Observation}\ (0.5)$) intrinsically hardens the system against such attacks: an unauthenticated observational input is fundamentally prohibited by the algebraic lattice from mutating or overwriting an architectural axiom.

---

8. CONCLUSION

We have introduced **Synapse 4D**, a deterministic, local-first multi-dimensional cognitive state machine that resolves the fundamental failure modes of context rot, temporal blindness, and graph entropy in autonomous language agents. By formalizing cognition as a 4-dimensional manifold $\mathcal{S} = \langle \mathcal{D}_1, \mathcal{D}_2, \mathcal{D}_3, \mathcal{D}_4 \rangle$, Synapse 4D achieves sub-second autonomous consolidation, 99.2 contradiction resolution precision, and guaranteed zero-orphan topological integrity while reducing token consumption by 68.4.

All specifications, algorithms, mathematical proofs, and patent claims disclosed herein serve as public defensive prior art to protect the global open-source artificial intelligence research community.

REFERENCES

1. Anderson, J. R. (1982). *Acquisition of cognitive skill.* Psychological Review, 89(4), 369–406.
2. Atkinson, R. C., & Shiffrin, R. M. (1968). *Human memory: A proposed system and its control processes.* Psychology of Learning and Motivation, 2, 89–195.
3. Baddeley, A. D., & Hitch, G. (1974). *Working memory.* Psychology of Learning and Motivation, 8, 47–89.
4. Bliss, T. V., & Lømo, T. (1973). *Long-lasting potentiation of synaptic transmission in the dentate area of the anaesthetized rabbit following stimulation of the perforant path.* The Journal of Physiology, 232(2), 331–356.
5. Collins, A. M., & Quillian, M. R. (1969). *Retrieval time from semantic memory.* Journal of Verbal Learning and Verbal Behavior, 8(2), 240–247.
6. Cowan, N. (2001). *The magical number 4 in short-term memory: A reconsideration of mental storage capacity.* Behavioral and Brain Sciences, 24(1), 87–114.
7. Edge, D., Trinh, H., Cheng, N., Bradley, J., Chao, A., Mody, A., Truitt, S., & Larson, J. (2024). *From Local to Global: A Graph RAG Approach to Query-Focused Summarization.* arXiv preprint arXiv:2404.16130.
8. Hebb, D. O. (1949). *The Organization of Behavior: A Neuropsychological Theory.* John Wiley & Sons.
9. Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., Yih, W., Rocktäschel, T., Riedel, S., & Kiela, D. (2020). *Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks.* Advances in Neural Information Processing Systems (NeurIPS), 33, 9459–9474.
10. Liu, N. F., Lin, K., Hewitt, J., Paranjape, A., Bevilacqua, M., Petroni, F., & Liang, P. (2024). *Lost in the Middle: How Language Models Use Long Contexts.* Transactions of the Association for Computational Linguistics, 12, 157–173.
11. Packer, C., Fang, V., Patil, S. G., Lin, K., Wooders, S., & Gonzalez, J. E. (2023). *MemGPT: Towards LLMs as Operating Systems.* arXiv preprint arXiv:2310.08560.
12. Park, J. S., O'Brien, J. C., Cai, C. J., Morris, M. R., Liang, P., & Bernstein, M. S. (2023). *Generative Agents: Interactive Simulacra of Human Behavior.* Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST '23), 1–22.
13. Shinn, N., Cassano, F., Gopinath, A., Narasimhan, K., & Yao, S. (2023). *Reflexion: Language Agents with Verbal Reinforcement Learning.* Advances in Neural Information Processing Systems (NeurIPS), 36.
14. Snodgrass, R. T. (1999). *Developing Time-Oriented Database Applications in SQL.* Morgan Kaufmann Publishers.
15. Sumers, T. R., Yao, S., Narasimhan, K., & Griffiths, T. L. (2023). *Cognitive Architectures for Language Agents.* arXiv preprint arXiv:2309.02427.
16. Tulving, E. (1972). *Episodic and semantic memory.* Organization of Memory, 1, 381–403.
17. Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2017). *Attention is All You Need.* Advances in Neural Information Processing Systems (NeurIPS), 30.
18. Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., & Cao, Y. (2023). *ReAct: Synergizing Reasoning and Acting in Language Models.* International Conference on Learning Representations (ICLR).

CITATION & BIBLIOGRAPHIC REFERENCE

```
@article{ruiz2026synapse4d,
  title={Synapse 4D: A Multi-Dimensional Cognitive State Matrix with Temporal Decay and Autonomous Topological Self-Assembly for Autonomous Language
  author={Ruiz, Ángel (@MShesat)},
  year={2026},
  month={October},
  publisher={Zenodo / CERN Open Science & GitHub},
  journal={Defensive Research Publication & Formal Patent Disclosure},
  doi={10.5281/zenodo.23737307},
  url={https://doi.org/10.5281/zenodo.23737307}
}
```

Published Defensively by Ángel Ruiz (@MShesat) • October 2026

All intellectual disclosures, mathematical theorems, schemas, and algorithms establish incontestable prior art under international patent treaties.