

JavaScript DOM Methods Reference

innerText

Gets or sets the visible text content of a node.

Example:

```
document.getElementById("demo").innerText = "Hello World!";
```

innerHTML

Gets or sets the HTML content of an element.

Example:

```
document.getElementById("demo").innerHTML = "<strong>Hello</strong>";
```

textContent

Gets or sets the text content of a node and its descendants.

Example:

```
document.getElementById("demo").textContent = "Just text";
```

setAttribute

Sets the value of an attribute on the specified element.

Example:

```
document.getElementById("demo").setAttribute("class", "active");
```

getAttribute

Returns the value of a specified attribute.

Example:

```
let cls = document.getElementById("demo").getAttribute("class");
```

classList.add

Adds a class to the element.

Example:

```
document.getElementById("demo").classList.add("visible");
```

classList.remove

Removes a class from the element.

Example:

JavaScript DOM Methods Reference

```
document.getElementById("demo").classList.remove("hidden");
```

classList.toggle

Toggles a class on the element.

Example:

```
document.getElementById("demo").classList.toggle("highlight");
```

style.property

Sets inline styles on an element.

Example:

```
document.getElementById("demo").style.color = "blue";
```

appendChild

Adds a node to the end of the list of children of a specified parent node.

Example:

```
document.getElementById("list").appendChild(newItem);
```

removeChild

Removes a child node from the DOM.

Example:

```
document.getElementById("list").removeChild(item);
```

createElement

Creates a new element node.

Example:

```
let p = document.createElement("p");
```

createTextNode

Creates a new text node.

Example:

```
let text = document.createTextNode("Hello!");
```

querySelector

Returns the first element that matches a specified CSS selector.

JavaScript DOM Methods Reference

Example:

```
let el = document.querySelector(".class");
```

querySelectorAll

Returns all elements that match a specified CSS selector.

Example:

```
let all = document.querySelectorAll("p");
```

getElementById

Returns the element with the specified ID.

Example:

```
let el = document.getElementById("id");
```

getElementsByClassName

Returns a live HTMLCollection of all elements with the given class name.

Example:

```
let elements = document.getElementsByClassName("myClass");
```

getElementsByTagName

Returns a live HTMLCollection of elements with the given tag name.

Example:

```
let paras = document.getElementsByTagName("p");
```