

# **LAB # 13**

**Name : Usama Rehman**


**SID : 9894**

**Unsolved Task:-**



Logical Physical x: 961, y: 182

[Root] 12:01:00



Time: 00:52:13

Realtime Simulation



Automatically Choose Connection Type


Scenario 0

New


Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
●	Successful	usama-PC0	usama-PC5	ICMP	Blue	0.000	N
●	Successful	usama-PC19	usama-PC9	ICMP	Pink	0.000	N
●	Successful	usama-PC17	usama-PC2	ICMP	Yellow	0.000	N



Logical Physical x: 393, y: 285



Main-Switch0

Physical Config CLI Attributes

IOS Command Line Interface



```
main>show vtp s
main>en
main#show
main#show v
main#show vtp st
main#show vtp status
VTP Version           : 2
Configuration Revision : 10
Maximum VLANs supported locally : 255
Number of existing VLANs : 10
VTP Operating Mode    : Server
VTP Domain Name       : usama
VTP Pruning Mode      : Disabled
VTP V2 Mode           : Disabled
VTP Traps Generation  : Disabled
MD5 digest            : 0x45 0xFB 0x7C 0x78 0xE3 0xC2 0x00 0x0A
Configuration last modified by 0.0.0.0 at 3-1-93 00:10:03
Local updater ID is 0.0.0.0 (no valid interface found)
main#show vtp o
main#show vtp p
main#show vtp password
VTP Password: 9894
main#
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

Time: 00:56:08



Automatically Choose Connection Type

Scenario 0

New

Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N

FileEditOptionsViewToolsExtensionsHelp

LogicalPhysicalx: 395, y: 142

karachi-Switch1

PhysicalConfigCLIAttributes

IOS Command Line Interface

```
karachi>en
karachi#show vtp s
karachi#show vtp status
VTP Version           : 2
Configuration Revision : 10
Maximum VLANs supported locally : 255
Number of existing VLANs : 10
VTP Operating Mode     : Client
VTP Domain Name        : usama
VTP Pruning Mode       : Disabled
VTP V2 Mode            : Disabled
VTP Traps Generation   : Disabled
MD5 digest             : 0x45 0xFB 0x7C 0x78 0xE3 0xC2 0x00 0x0A
Configuration last modified by 0.0.0.0 at 3-1-93 00:10:03
karachi#show vtp p
karachi#show vtp password
VTP Password: 9894
karachi#
karachi#
```

Ctrl+F6 to exit CLI focus

CopyPaste

☐ Top

Time: 00:56:57

RealtimeSimulation

Scenario 0

NewDelete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N

Automatically Choose Connection Type

FileEditOptionsViewToolsExtensionsHelp

LogicalPhysicalx: 1009, y: 65

Time: 00:58:04

Automatically Choose Connection Type

Lahore-Switch2

PhysicalConfigCLIAttributes

IOS Command Line Interface

```
% Invalid input detected at '^' marker.

Lahore#
Lahore#
Lahore#
Lahore#show vtp status
VTP Version           : 2
Configuration Revision : 10
Maximum VLANs supported locally : 255
Number of existing VLANs : 10
VTP Operating Mode     : Client
VTP Domain Name        : usama
VTP Pruning Mode       : Disabled
VTP V2 Mode            : Disabled
VTP Traps Generation   : Disabled
MD5 digest             : 0x45 0xFB 0x7C 0x78 0xE3 0xC2 0x00 0x0A
Configuration last modified by 0.0.0.0 at 3-1-93 00:10:03
Lahore#show vtp p
Lahore#show vtp password
VTP Password: 9894
Lahore#
Lahore#
```

Ctrl+F6 to exit CLI focus

CopyPaste

☐ Top

Scenario 0

NewDelete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N

16:45:00

PT19  
tment  
0

Multan-Switch3

Physical Config CLI Attributes


IOS Command Line Interface

```
Multan>en
Multan#show vtp statu
Multan#show vtp status
VTP Version          : 2
Configuration Revision : 10
Maximum VLANs supported locally : 255
Number of existing VLANs : 10
VTP Operating Mode    : Client
VTP Domain Name       : usama
VTP Pruning Mode      : Disabled
VTP V2 Mode           : Disabled
VTP Traps Generation  : Disabled
MD5 digest            : 0x45 0xFB 0x7C 0x78 0xE3 0xC2 0x00 0x0A
Configuration last modified by 0.0.0.0 at 3-1-93 00:10:03
Multan#show vtp p
Multan#show vtp password
VTP Password: 9894
Multan#
Multan#
Multan#
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top



Time: 00:58:40

Realtime Simulation



Scenario 0

New Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N

File Edit Options View Tools Extensions Help

Logical

Sialkot-Switch4

Physical Config CLI Attributes

IOS Command Line Interface

```

Sialkot>en
Sialkot#show vtp s
Sialkot#show vtp status
VTP Version : 2
Configuration Revision : 10
Maximum VLANs supported locally : 255
Number of existing VLANs : 10
VTP Operating Mode : Client
VTP Domain Name : usama
VTP Pruning Mode : Disabled
VTP V2 Mode : Disabled
VTP Traps Generation : Disabled
MD5 digest : 0x45 0xFB 0x7C 0x78 0xE3 0xC2 0x00 0x0A
Configuration last modified by 0.0.0.0 at 3-1-93 00:10:03
Sialkot#show vtp p
Sialkot#show vtp password
VTP Password: 9894
Sialkot#
Sialkot#
Sialkot#

```

Ctrl+F6 to exit CLI focus

Copy Paste

Top

Time: 00:59:10

Realtime Simulation

Scenario 0

New Delete


Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
●	Successful	usama-PC0	usama-PC5	ICMP	Blue	0.000	N
●	Successful	usama-PC19	usama-PC9	ICMP	Pink	0.000	N
●	Successful	usama-PC17	usama-PC2	ICMP	Green	0.000	N


Automatically Choose Connection Type

Go to Settings to activate Windows.

Show vlan brief:-



Logical Physical x: 484, y: 413



Time: 01:01:08



Automatically Choose Connection Type

Main-Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
main#show vlan brief
```

VLAN Name	Status	Ports
1 default	active	Fa0/5, Fa0/6, Fa0/7, Fa0/8, Fa0/9, Fa0/10, Fa0/11, Fa0/12, Fa0/13, Fa0/14, Fa0/15, Fa0/16, Fa0/17, Fa0/18, Fa0/19, Fa0/20, Fa0/21, Fa0/22, Fa0/23, Fa0/24, Gig0/1, Gig0/2
10 faculty	active	
20 student	active	
30 guest	active	
40 management	active	
50 department	active	
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

Ctrl+F6 to exit CLI focus

Copy Paste


Top

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N





Logical Physical x: 653, y: 425



Time: 01:01:35



Automatically Choose Connection Type

karachi-Switch1

Physical Config CLI Attributes

IOS Command Line Interface

```
karachi#show vlan b
karachi#show vlan brief
```


VLAN Name	Status	Ports
1 default	active	Fa0/2, Fa0/3, Fa0/4, Fa0/6, Fa0/7, Fa0/9, Fa0/10, Fa0/12, Fa0/13, Fa0/14, Fa0/16, Fa0/17, Fa0/18, Fa0/19, Fa0/21, Fa0/22, Fa0/23, Fa0/24,
10 faculty	active	Fa0/5
20 student	active	Fa0/8
30 guest	active	Fa0/11
40 management	active	Fa0/15
50 department	active	Fa0/20
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N



Top

## Multan-Switch3

Physical Config CLI Attributes

## IOS Command Line Interface


Multan#show vlan brief

VLAN Name	Status	Ports
1 default	active	Fa0/2, Fa0/3, Fa0/4, Fa0/6
		Fa0/7, Fa0/9, Fa0/10, Fa0/12
		Fa0/13, Fa0/14, Fa0/16, Fa0/17
		Fa0/18, Fa0/19, Fa0/21, Fa0/22
		Fa0/23, Fa0/24, Gig0/1, Gig0/2
10 faculty	active	Fa0/5
20 student	active	Fa0/8
30 guest	active	Fa0/11
40 management	active	Fa0/15
50 department	active	Fa0/20
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

Ctrl+F6 to exit CLI focus


Copy

Paste

☐ Top

Time: 01:02:21

Realtime Simulation



Automatically Choose Connection Type

Scenario 0

New

Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
●	Successful	usama-PC0	usama-PC5	ICMP	Blue	0.000	N
●	Successful	usama-PC19	usama-PC9	ICMP	Pink	0.000	N
●	Successful	usama-PC17	usama-PC2	ICMP	Yellow	0.000	N

FileEditOptionsViewToolsExtensionsHelp

Sialkot-Switch4

PhysicalConfigCLIAttributes

IOS Command Line Interface

Sialkot#show vlan brief

VLAN Name	Status	Ports
1 default	active	Fa0/2, Fa0/3, Fa0/4, Fa0/6, Fa0/7, Fa0/9, Fa0/10, Fa0/12, Fa0/13, Fa0/14, Fa0/16, Fa0/17, Fa0/21, Fa0/22
10 faculty	active	Gig0/1, Gig0/2
20 student	active	Fa0/5
30 guest	active	Fa0/8
40 management	active	Fa0/11
50 department	active	Fa0/15
1002 fddi-default	active	Fa0/20
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

Ctrl+F6 to exit CLI focusCopyPaste

☐ Top

Logical

PC-PT usama-PC0

PC-PT usama-PC1

PC-PT usama-PC10

PC-PT usama-PC11

PC-PT usama-PC12

PC-PT usama-PC13

PC-PT usama-PC14

PC-PT usama-PC15

PC-PT usama-PC16

PC-PT usama-PC17

PC-PT usama-PC18

PC-PT usama-PC19

switch4

Time: 01:02:39

RealtimeSimulation

Scenario 0

NewDelete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic
	Successful	usama-PC0	usama-PC5	ICMP		0.000	N
	Successful	usama-PC19	usama-PC9	ICMP		0.000	N
	Successful	usama-PC17	usama-PC2	ICMP		0.000	N

