Reference Schematics For RK3588S

RK3588S_Tablet_Demo_SCH

Main Functions Introduction

1) Charger: 1Cell Battery_QC
2) PMIC: 1 x RK806-1+DiscretePower
3) RAM: 2 x 32bits LPDDR4/4x
4) ROM: eMMC5.1(Default)
5) Support: 1 x Type-C 3.0(with DP function)
6) Support: 1 x 4Lanes MIPI D/CPHY RX Camera
7) Support: 1 x 2Lanes MIPI DPHY RX Camera
8) Support: 1 x 4Lanes MIPI D/CPHY TX
9) Support: a/b/g/n/ac/ax 2T2R WIFI(PCIE) + BT5.0
11) Support: 1 x Headphone + 2 x Speaker out + 1 x Analog MIC
12) Support: 2 x PDM MIC Array
13) Support: Gyroscope+G-sensor+Ambient Light+Proximity

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	00.Cover Page				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	1 of 32

Table of Content

Note

The power suffix S0 or S3 means:

S3: Keep power On during sleeping

S0:Power off during sleeping

Generate Bill of Materials

Header:

Item\tPart\tDescription\tPCB Footprint\tReference\tQuantity\tOption

Combined property string:

{Item}\t{Value}\t{Description}\t{PCB Footprint}\t{Reference}\t{Quantity}\t{Option}

Description

Note

Option

Notes

NOTE 1:
Component parameter description
1. DNP stands for component not mounted temporarily
2. If Value or option is DNP, which means the area is reserved without being mounted

NOTE 2:
Please use our recommended components to avoid too many changes.
For more informations about the second source,please refer to our AVL.

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	01.Index and Notes				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	2 of 32

Revision History

Version	Date	By	Change Dsecription	Approved
V1.0	2022-01-05	Joseph.Wei	1:Revision preliminary version	
V1.1	2022-02-18	Joseph.Wei	1.C1604,C1612的电容改成1uF/4V。 2.为了减少待机功耗，将PMUIO2电源域改成1.8V，此IO域对应外设IO电压相应修改 3.把L2203，L2205，L2207，L2300，L2301，L2302电感由0.22uH(TDK)改为0.24uH(Sunlord); L2201的电感由0.22uH(TDK)改为0.22uH (Sunlord)，封装IND_404020。	

Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	02.Revision History				
Date:	Wednesday, February 23, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	3 of 32

RK3588S Tablet Demo Block Diagram for 1-Cell Charger



Power tree for 1-Cell Charger



Power Sequence



Power Supply	PMIC Channel	Supply Limit	Power Name	Time Slot	Default Voltage	Default ON/OFF	Sleep ON/OFF	Peak Current	Sleep Current
VCC_SYSIN	RK806-1_BUCK1	6.5A	VDD_GPU_S0	Slot:5	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK2	5A	VDD_CPU_LIT_S0	Slot:3	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK3	5A	VDD_LOG_S0	Slot:2	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK4	3A	VDD_VDENC_S0	Slot:5	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK5	2.5A	VDD_DDR_S0	Slot:2	0.85V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK6	2.5A	VDD2_DDR_S3	Slot:4	ADJ FB=0.5V	ON	ON	TBD	TBD
VCC_SYSIN	RK806-1_BUCK7	2.5A	VCC_2V0_PLDO_S3	Slot:1	2.0V	ON	ON	TBD	TBD
VCC_SYSIN	RK806-1_BUCK8	2.5A	VCC_3V3_S3	Slot:6	3.3V	ON	ON	TBD	TBD
VCC_SYSIN	RK806-1_BUCK9	2.5A	VDDQ_DDR_S0	Slot:6	ADJ FB=0.5V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_BUCK10	2.5A	VCC_1V8_S3	Slot:3	1.8V	ON	ON	TBD	TBD
VCC_2V0_PLDO_S3	RK806-1_PLDO1	0.5A	VCC_1V8_S0	Slot:3	1.8V	ON	OFF	TBD	TBD
	RK806-1_PLDO2	0.3A	VCCA_1V8_S0	Slot:3	1.8V	ON	OFF	TBD	TBD
	RK806-1_PLDO3	0.3A	VDDA_1V2_S0	Slot:4	1.2V	ON	OFF	TBD	TBD
VCC_SYSIN	RK806-1_PLDO4	0.5A	VCCA_3V3_S0	Slot:6	3.3V	ON	OFF	TBD	TBD
	RK806-1_PLDO5	0.3A	VCCIO_SD_S0	Slot:6	3.3V	ON	OFF	TBD	TBD
	RK806-1_PLDO6	0.3A	VCCA1V8_PLDO6_S3	Slot:3	1.8V	ON	ON	TBD	TBD
VCC_1V1_NLDO_S3	RK806-1_NLDO1	0.3A	VDD_0V75_S3	Slot:2	0.75V	ON	ON	TBD	TBD
	RK806-1_NLDO2	0.3A	VDDA_DDR_PLL_S0	Slot:2	0.85V	ON	OFF	TBD	TBD
	RK806-1_NLDO3	0.5A	VDDA_0V75_S0	Slot:2	0.75V	ON	OFF	TBD	TBD
VCC_1V1_NLDO_S3	RK806-1_NLDO4	0.5A	VDDA_0V85_S0	Slot:2	0.85V	ON	OFF	TBD	TBD
	RK806-1_NLDO5	0.3A	VDD_0V75_S0	Slot:2	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	BUCK_RK860-2	6A	VDD_CPU_BIG0_S0	Slot:6A	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	BUCK_RK860-3	6A	VDD_CPU_BIG1_S0	Slot:6A	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	BUCK_RK860-2	6A	VDD_NPU_S0	Slot:6A	0.75V	ON	OFF	TBD	TBD
VCC_SYSIN	EXT BUCK	2A	VCC_1V1_NLDO_S3	Slot:1	1.1V	ON	ON	TBD	TBD
VCC_SYSIN	EXT BUCK	2A	VDD2L_0V9_DDR_S3	Slot:5	0.9V	ON	ON	TBD	TBD
VCC_SYSIN	EXT BUCK	2.5A	VCC_3V3_SD_S0	Slot:6A	3.3V	ON	OFF	TBD	TBD
VCC_SYSIN	EXT_BUCK or LDO	2A	VCC_1V2_CAM_S0	OFF	1.2V	OFF	OFF	TBD	TBD
VCC_SYSIN	LDO	0.5A	VCC_1V8_CAM_S0	OFF	1.8V	OFF	OFF	TBD	TBD
VCC_SYSIN	LDO	0.5A	VCC_2V8_CAM_S0	OFF	2.8V	OFF	OFF	TBD	TBD

IO Power Domain Map

IO Domain	Pin Num	Support IO Voltage	Supply Power Pin Name	Power Source	Operating Voltage
PMUIO1	Pin N36 N37	1.8V Only	PMUIO1_1V8	VCC_1V8_S3	1.8V
PMUIO2	Pin V37 Y37 Pin V35 V36	1.8V or 3.3V	PMUIO2_1V8 PMUIO2_	VCC_1V8_S3 VCC_1V8_S3	1.8V 1.8V
EMMCIO	Pin AC35 Pin AC36	1.8V Only	EMMCIO_1V8	VCC_1V8_S0	1.8V
VCCIO1	Pin H31	1.8V Only	VCCIO1_1V8	VCC_1V8_S0	1.8V
VCCIO2	Pin AK11 Pin AK10	1.8V or 3.3V	VCCIO2_1V8 VCCIO2_	VCC_1V8_S0 VCC_IO_SD	1.8V 1.8V/3.3V
VCCIO4	Pin G27 G28 Pin G31	1.8V or 3.3V	VCCIO4_1V8 VCCIO4_	VCC_1V8_S0 VCC_3V3_S0	1.8V 1.8V
VCCIO5	Pin AF35 AF36 Pin AC33 AC34	1.8V or 3.3V	VCCIO5_1V8 VCCIO5_	VCC_1V8_S0 VCC_1V8_S0	1.8V 1.8V
VCCIO6	Pin AJ34 Pin AL33 AM33	1.8V or 3.3V	VCCIO6_1V8 VCCIO6_	VCC_1V8_S0 VCC_3V3_S0	1.8V 3.3V

Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	05.System Power Sequence				
Date:	Monday, January 24, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	5 of 32

I2C MAP



UART MAP



Rockchip	Rockchip Electronics Co., Ltd
Project:	RK3588S_Demo
File:	06.Lower-Speed Bus Map
Date:	Monday, January 24, 2022
Rev:	V10
Designed by:	Joseph
Reviewed by:	<Checker>
Sheet	6 of 32

USB Controller Configure Table

Controller Name	Pin Name	Type-C Function	DPx4Lane+USB20 OTG OPTION1	DPx4Lane+USB20 OTG OPTION2	USB30 OTG+DPx2Lane Function OPTION1	USB30 OTG+DPx2Lane Function OPTION2	USB20 OTG+DPx2Lane Function OPTION1	USB20 OTG+DPx2Lane Function OPTION2	USB20 OTG+DPx4Lane Function OPTION1	USB20 OTG+DPx4Lane Function OPTION2
USB30 OTG0 Device or Host	TYPEC0_SBU1/DP0_AUXP TYPEC0_SBU2/DP0_AUXN	TYPEC0_SBU1 TYPEC0_SBU2	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN	DP0_AUXP DP0_AUXN
	TYPEC0_SSRX1P/DP0_TX0P TYPEC0_SSRX1N/DP0_TX0N	TYPEC0_SSRX1P TYPEC0_SSRX1N	DP0_TX0P DP0_TX0N	DP0_TX2P DP0_TX2N	TYPEC0_SSRX1P TYPEC0_SSRX1N	DP0_TX0P DP0_TX0N	DP0_TX0P DP0_TX0N		DP0_TX0P DP0_TX0N	DP0_TX2P DP0_TX2N
	TYPEC0_SSTX1P/DP0_TX1P TYPEC0_SSTX1N/DP0_TX1N	TYPEC0_SSTX1P TYPEC0_SSTX1N	DP0_TX1P DP0_TX1N	DP0_TX3P DP0_TX3N	TYPEC0_SSTX1P TYPEC0_SSTX1N	DP0_TX1P DP0_TX1N	DP0_TX1P DP0_TX1N		DP0_TX1P DP0_TX1N	DP0_TX3P DP0_TX3N
	TYPEC0_SSRX2P/DP0_TX2P TYPEC0_SSRX2N/DP0_TX2N	TYPEC0_SSRX2P TYPEC0_SSRX2N	DP0_TX2P DP0_TX2N	DP0_TX0P DP0_TX0N	DP0_TX2P DP0_TX2N	TYPEC0_SSRX2P TYPEC0_SSRX2N		DP0_TX2P DP0_TX2N	DP0_TX2P DP0_TX2N	DP0_TX0P DP0_TX0N
	TYPEC0_SSTX2P/DP0_TX3P TYPEC0_SSTX2N/DP0_TX3N	TYPEC0_SSTX2P TYPEC0_SSTX2N	DP0_TX3P DP0_TX3N	DP0_TX1P DP0_TX1N	DP0_TX3P DP0_TX3N	TYPEC0_SSTX2P TYPEC0_SSTX2N		DP0_TX3P DP0_TX3N	DP0_TX3P DP0_TX3N	DP0_TX1P DP0_TX1N
USB20 OTG0 Device or Host	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM		TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM	TYPEC0_USB20_OTG_DP TYPEC0_USB20_OTG_DM
USB30 OTG2 Device or Host			OPTION1 USB30 HOST		OPTION2 USB30 HOST					
	PCIE20_2_TXP/SATA30_2_TXP/USB30_2_SSTXP PCIE20_2_TXN/SATA30_2_TXN/USB30_2_SSTXN		USB30_2_SSTXP USB30_2_SSTXN		USB30_2_SSTXP USB30_2_SSTXN					
	PCIE20_2_RXP/SATA30_2_RXP/USB30_2_SSRXP PCIE20_2_RXN/SATA30_2_RXN/USB30_2_SSRXN		USB30_2_SSRXP USB30_2_SSRXN		USB30_2_SSRXP USB30_2_SSRXN					
USB20 HOST0	USB20_HOST0_DP USB20_HOST0_DM		USB20_HOST0_DP USB20_HOST0_DM							
USB20 HOST1	USB20_HOST1_DP USB20_HOST1_DM				USB20_HOST1_DP USB20_HOST1_DM					

Note:
DP Lane swap enable
0:Lane0/1/2/3 TxData mapping to Lane0/1/2/3_TXDP/N
1:Lane0/1/2/3 TxData mapping to Lane2/3/0/1_TXDP/N



Rockchip Electronics Co., Ltd			
Project:	RK3588S_Demo		
File:	07.USB Controller Configure Tab		
Date:	Friday, January 07, 2022	Rev:	V10
Designed by: Joseph	Reviewed by: <Checker>	Sheet:	7 of 32

PCIe/SATA Connecter Diagram



PCIe Controller Configure Table

Controller Name	Data & Clk Lane Configure		Control GPIO
	CLK LANE	DATA LANE	
PCIE20X1_1 RC	PCIE20_2_REFCLKP PCIE20_2_REFCLKN	PCIE20_2_TX PCIE20_2_RX	PCIE20X1_1_CLKREQ_M* PCIE20X1_1_WAKEN_M* PCIE20X1_1_PERSTN_M* PCIE20X1_1_BUTTON_RSTN
PCIE20X1_2 RC	PCIE20_0_REFCLKP PCIE20_0_REFCLKN	PCIE20_0_TX PCIE20_0_RX	PCIE20X1_2_CLKREQ_M* PCIE20X1_2_WAKEN_M* PCIE20X1_2_PERSTN_M* PCIE20X1_2_BUTTON_RSTN

PCIe2.0 REFCLK



Note:

PCIE20_*_REFCLKP/N is output or input gpio

M*=Mean to M0 or M1 or M2,It's the same source,Just multiplex to M0 or M1 or M2,Only use one at the same time.

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	08.PCIE Fun Map				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	8 of 32

RK3588S (Power&Gnd)

lokum notebook

ROCKCHIP RK3588S 8GB MICRON/KINGSTON LPDDR4 DEBIAN LINUX ANDROID 12

SİSTEM_KONTROL_1

kapasitörler yeşil cizgi yi gecmeden yerleştirilmeli u1000 altına doğru.diger cap lar u1000 yakın olmalı.

Note:
The Caps between green line and U1000 should be placed under the U1000 package.Other caps should be placed close to the U1000 package





Rockchip	Rockchip Electronics Co., Ltd
Project:	RK3588S_Demo
File:	10.RK3588S_Power/GND
Date:	Friday, January 07, 2022
Rev:	V10
Designed by:	Joseph
Reviewed by:	<Checker>
Sheet	9 of 32

RK3588S(OSC/PLL/PMUIO1)

Note:
Adjusted the load capacitance according to the crystal specification

The CL is the load capacitance of the crystal that is recommended by the crystal vendors to obtain target clock frequency.

CL={CL1*CL2/(CL1+CL2))}+PCB strays
Total CL<=12pF

Note:
The Caps between green line and U1000 should be placed under the U1000 package.Other caps should be placed close to the U1000 package



RK3588S(PMUIO2)



Rockchip Electronics Co., Ltd

Project:	RK3588S_Demo		
File:	11.RK3588S_OSC/PLL/PMUIO		
Date:	Monday, January 24, 2022	Rev:	V10
Designed by:	Joseph	Reviewed by: <Checker>	Sheet: 10 of 32

RK3588S (DDR PHY) LPDDR5 MICRON-SAMSUNG VEYA KINGSTON



LPDDR4 FILTRE CAP



Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	12.RK3588S DDR Controler				
Date:	Monday, January 24, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	11 of 32

RK3588S(EMMCIO Domain)



RK3588S(VCCIO2 Domain)



Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	13.RK3588S Flash/SD Controller				
Date:	Wednesday, January 12, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	12 of 32

RK3588S(USB3.0/DP1.4)

USB_3.0 PORTLAR

USB30/DP1.4 Alt Mode Configuration

Option1	DP x4Lane	DP_TX_Lane0-3
Option2	TYPEC x4Lane	SSTX 1P/1N SSTX 2P/2N SSRX 1P/1N SSRX 2P/2N
Option3	USB30X2Lane+DPX2Lane	USB30:SSTX 1P/1N SSRX 1P/1N DP:Lane2 Lane3
Option4	USB30X2Lane+DPX2Lane	USB30:SSTX 2P/2N SSRX 2P/2N DP:Lane0 Lane1

DP Lane
Swap Off:
Lane0/1/2/3_TXdata mapping to Lane0/1/2/3_TXDP/N
Swap On:
Lane0/1/2/3_TXdata mapping to Lane2/3/0/1_TXDP/N



RK3588S(USB2.0)



Note:
The USB20_VBUSDET pin internal has a pull-down resistance(40K ohm) to ground,The resistance creates a voltage with the external series 24K ohm resistor.The VBUSDETpin voltage range <=3.3V.

Note:
TYPEC0_USB20_OTG:

DP/DM:Must used for download
ID:According to demand,if not used,Leave floating
VBUSDET:Must provide
REXT:200ohm 1% resistor must be connected externally
Power: Must supply power

USB20_HOST0/USB20_HOST1:

If not used:
DP/DM:Leave floating
REXT:Leave floating

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	14.RK3588S_USB20/USB30/DP PHY				
Date:	Wednesday, February 23, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	13 of 32

RK3588S(SARADC/OTP/TSADC)



BOOT MODE CONFIG



Item	Rup	Rdown	ADC	BOOT MODE(saradc_in5)
LEVEL1	DNP	100K	0	USB (Maskrom mode)
LEVEL2	100K	20K	682	SD Card-USB
LEVEL3	100K	51K	1365	EMMC-USB
LEVEL4	100K	100K	2047	FSPI M0-USB
LEVEL5	100K	200K	2730	FSPI M1-USB
LEVEL6	100K	499K	3412	FSPI M2-USB
LEVEL7	100K	DNP	4095	FSPI_M2-FSPI_M0-EMMC -SD Card-USB

RK3588S(VCCIO1 Domain)



Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Rockchip Electronics Co., Ltd

Project:	RK3588S_Demo
File:	15.RK3588S_SARADC/1.8V GPIO
Date:	Friday, January 14, 2022
Rev:	V10
Designed by:	Joseph
Reviewed by:	<Checker>
Sheet:	14 of 32

RK3588S(MIPI_DPHY CSI0 RX)



Note:
If not used:
Signal:leave floating
Power: Floating

Option1	*Sensor1 x4Lane*	*MIPI_CSI_RX_D0-3* *MIPI_CSI_RX_CLK0*
Option2	*Sensor1 x2Lane*	*MIPI_CSI_RX_D0-1* *MIPI_CSI_RX_CLK0*
	+	
	Sensor2 x2Lane	*MIPI_CSI_RX_D2-3* *MIPI_CSI_RX_CLK1*

Note:
When in single clock lane mode, CLK0P/0N is the clock lane from Data lane0 to Data lane3,but clock lane1 is invalid; In dual clock lanes mode,CLK0P/0N is the clock lane of Data lane0 and Data lane1,while CLK1P/1N is the clock lane of Data lane2 and Data lane3.

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

RK3588S(MIPI_D/C PHY0)



Note:
If not used:
Signal:leave floating
Power: Floating

RK3588S(MIPI_D/C PHY1)



Note:
If not used:
Signal:leave floating
Power: Floating

Rockchip Electronics Co., Ltd

Project:	RK3588S_Demo		
File:	16.RK3588S_MIPI Interface		
Date:	Monday, February 21, 2022	Rev:	V10
Designed by: Joseph	Reviewed by: <Checker>	Sheet:	15 of 32

RK3588S(HDMI2.1 TX/eDP1.3 TX)

HDMİ VERSIYON 2.1

Note:
The HDMI2.1 trace length is less than 100mm.
The HDMI2.1 differential trace impedance is 100 OHM.

eDP TX
100 Ohm ±10%

HDMI TX
100 Ohm ±10%



Note:
If not used:
Signal:leave floating
Power: Floating or tie to VSS

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	17.RK3588S_HDMI/eDP Interface				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	16 of 32

RK3588S(PCIE20/SATA30/USB30)

PCIE20 VE SATA PORT USB 3.0



CLK Differential Pair:
100 Ohm±10%
DATA Differential Pair:
PCIE20: 85 Ohm ±10%
SATA30: 100 Ohm ±10%
USB30: 90ohm ±10%

Note:
If not used:
Signal:leave floating
Power: Tie to VSS

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

PCIe2.0 PHY

Controller Name	Data & Clk Lane Configure		Control GPIO
	CLK LANE	DATA LANE	
PCIE20X1_1 RC	PCIE20_2_REFCLKP PCIE20_2_REFCLKN	PCIE20_2_TX PCIE20_2_RX	PCIE20X1_1_CLKREQ_M* PCIE20X1_1_WAKEN_M* PCIE20X1_1_PERSTN_M* PCIE20X1_1_BUTTON_RSTN
PCIE20X1_2 RC	PCIE20_0_REFCLKP PCIE20_0_REFCLKN	PCIE20_0_TX PCIE20_0_RX	PCIE20X1_2_CLKREQ_M* PCIE20X1_2_WAKEN_M* PCIE20X1_2_PERSTN_M* PCIE20X1_2_BUTTON_RSTN

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	18.RK3588S PCIE2/SATA3/USB3 PHY				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	17 of 32

RK3588S(VCCIO4 Domain)



RK3588S(VCCIO6 Domain)

RK3588S(VCCIO5 Domain)





Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Rockchip	Rockchip Electronics Co., Ltd		
Project:	RK3588S_Demo		
File:	19.RK3588S GPIO		
Date:	Friday, January 07, 2022	Rev:	V10
Designed by:	Joseph	Reviewed by: <Checker>	Sheet 18 of 32

USB Type-C Port



USB Type-C CC CTRL



USB Detection



Gas Gauge



Charger IC

ŞARJ DEVRESİ





Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	20.Power_1Cell_QC				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	19 of 32



PMIC1 RK806-1
SLEEP1_RESET1_DEVOFF1_VSEL1
VSEL4
VSEL5
PMIC_INT_L
PWRON_L
PMIC_RESET_L
PMIC_EXT_EN_OUT
PMIC_SPI_CLK
PMIC_SPI_CS
PMIC_SPI_MOSI
IF TVS UNMOUNTED, ESD OR SURGE SHOULD BE DAMAGE THE PMIC!!!
This device must be mounted.Replacing TVS mode is not recommended, if must, please choose the same specifications
Operating Supply Vltage : 5.5V(5.25-6V)
PeakPulse Current: >10A (tp=8/20uS)
Surge Clamping Voltage: <6.5V
DO NOT DELETE IT!
PMIC_PWR_CTRL2
PMIC_PWR_CTRL3
PMIC RK806-1 BUCK
Default:0.85V
Low frequency:
0.85V-->0.75V
Feedback from RK3588S
ANA GÜÇ REGÜLATOR DEVRESİ RK806-POWER UNIT IC
BUCK5 2.5A
BUCK1 6.5A
BUCK6 2.5A
BUCK2 5A
BUCK9 2.5A
BUCK3 5A
BUCK8 2.5A
BUCK4 5A
BUCK10 2.5A
BUCK7 2.5A
(FB=0.5V)
VDD_GPU_S0
VDD_CPU_LIT_S0
VDD_LOGIC_S0
VDD_VDENC_S0
VCC_2V0_PLDO_S3
LPDDR4/4x=1.1V 120K
LPDDR5=1.05V 110K
LPDDR4/4x=0.6V 20K 100K
LPDDR5=0.5V 0R DNP
Default:1.8V
RK806-1
PMIC RK806-1 Managerment
VCCIO
VCCA
RK3588S nPOR
TSADC_SHUT
RK806-1 RESETB
Reset Key
Note:
Reset Key Control Path
TSADC_SHUT Control Path
RK806-1 Control Path
PMIC RK806-1 LDO
PLDO
NLDO
Default:1.8V
Default:1.8V
Default:1.2V
Default:3.3V
Default:3.3V
Default:0.75V
Default:0.85V;
Low frequency:0.85V-->0.75V
Default:0.75V
Default:0.85V
Default:0.75V
Reserved
Rockchip Confidential
Rockchip Electronics Co., Ltd
Project: RK3588S_Demo
File: 22.Power-PMIC_RK806-1
Date: Wednesday, February 23, 2022
Rev: V10
Designed by: Joseph
Reviewed by: <Checker>
Sheet: 20 of 32

VDD_CPU_BIG0

ARM CPU BESLEME CPU-BIG



VDD_CPU_BIG1



VDD_NPU

YAPAY ZEKA ÇEKİRDEK BESLEME



VCC_1V1_NLDO



3.3V REGÜLATOR

VCC_3V3_S0





Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	23.Power_Ext Discrete				
Date:	Wednesday, February 23, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	21 of 32

ZAMANLAMA ÜNİTESİ

RTC IC



Address:Read A3H,Write A2H

Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	24.RTC				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	22 of 32

LPDDR4 HAFIZA MODÜLLERİ A / B KANAL



Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	38.DRAM-LPDDR4/4X_200P_2X32bit				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	23 of 32

eMMC Flash

MULTI MEDYA KART GİRİŞLER









Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	40.eMMC Flash				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	24 of 32

MIPI-CSI0_RX

KAMERA

前摄：OV16A10-GA5A-Z

MIPI_CSI0_RX_D0P
MIPI_CSI0_RX_D0N
MIPI_CSI0_RX_D1P
MIPI_CSI0_RX_D1N
MIPI_CSI0_RX_D2P
MIPI_CSI0_RX_D2N
MIPI_CSI0_RX_D3P
MIPI_CSI0_RX_D3N
MIPI_CSI0_RX_CLK0P
MIPI_CSI0_RX_CLK0N
MIPI_CAM3_CLKOUT
MIPI_CAM3_RST_L
MIPI_CAM3_PWREN_H
MIPI_CAM3_PDN_L
I2C8_SCL_M2_CAM
I2C8_SDA_M2_CAM









Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	46.VI-Camera MIPI CSI0-RX				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	25 of 32

VI-Camera DPHY_RX

后摄： S5K3L6XX03-FGX9





Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	47.VI-Camera_MIPI-DPHY-RX				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	26 of 32

MIPI DPHY TX

Power
REGÜLATÖR











Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	55.VO-MIPI DPHY-TX				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	27 of 32

PCIe WIFI6/BT Module-2T2R

WIFI-6 VE BLUETOOTH MODÜLLERİ VE BAGLANTILAR



Rockchip Confidential

Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	63.WIFI/BT-PCIe_2T2R(AP6275PR3)				
Date:	Monday, January 24, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	28 of 32

CODEC ES8388



SES ÜNİTELERİ

SPEAKER



Analog MIC



Rockchip Confidential

Rockchip Electronics Co., Ltd

Project:	RK3588S_Demo				
File:	70.Audio Codec-ES8388				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	29 of 32

Sensor

I2C3_SCL_M1_Sensor
I2C3_SDA_M1_Sensor
RGB_INT_L
ALPS_INT_L

I2C3_SCL_M1_Sensor — I2C_SCL_SENSOR

I2C3_SDA_M1_Sensor — I2C_SDA_SENSOR

VCC_1V8_S0
I2C_SCL_SENSOR
I2C_SDA_SENSOR
RGB_INT_L

J7006 CONTACT_L0475
J7007 CONTACT_L0475
J7008 CONTACT_L0475
J7009 CONTACT_L0475
J7010 CONTACT_L0475



MAX:1.5A

FLASH_LED — J1 CONTACT_L0475

J3 CONTACT_L0475

Flashlight

PLS+ALS



Rockchip Electronics Co., Ltd					
Project:	RK3588S_Demo				
File:	90.Sensor				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	30 of 32

KLAVYE ADC GİRİŞLER

KEY Array



Reset_Key

PWR_Key



Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	92.KEY Array				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	31 of 32

UART Debug

JTAG Debug



Rockchip	Rockchip Electronics Co., Ltd				
Project:	RK3588S_Demo				
File:	93.Debug UART/JTAG Port				
Date:	Friday, January 07, 2022			Rev:	V10
Designed by:	Joseph	Reviewed by:	<Checker>	Sheet:	32 of 32