## HG2-W-PIC18F67J60 - MCU INTERNET HAVA İSTASYONU RA1/LEDB/AN1 RA2/AN2/VREF-RA3/AN3/VREF+ RA4/T0CKI RA5/AN4 RB0/INT0/FLT0 R13 560 EXT-12 EXT-13 EXT-14 RB1/INT1 RB2/INT2 ferrite bead O 3.3V R14 49.9/1% R15 49.9/1% TPIN-TPIN+ RB3/INT3 RB4/KBI0 ■ EXT-15 RB5/KBI1 RB6/KBI2/PGC **3.3**V\_E TPOUT-C1 470uF/16V RC4/SDI1/SDA1 RC5/SDO1 RC6/TX1/CK1 RC7/RX1/DT1 R18 49.9/19 VDD VDD1 VDD2 MC34063AD SMD MBF R5 1.8K/1% R6 560 RD0/P1B RD1/ECCP3/P3A RD2/CCP4/P3D VSS VSS1 VSS2 VSS3 RE0/P2D RE1/P2C RE2/P2B RE3/P3C RE4/P3B RE5/P1C 100nF MURAN PARA ROS EXT-24 EXT-25 RF1/AN6/C2OUT RF2/AN7/C1OUT RF3/AN8 RF4/AN9 VSSTX RF5/AN10/CVREF RF6/AN11 AVDD AVSS RF7/#SS1 RG4/CCP5/P1D RS232 DB9\_female ■ EXT-29 Õ<sup>3.3∨</sup> R24 100K SCK SCK BUT /RESET/ VCC

1. L