RK3308_AI-VA_MB_RF-20180-

RAM: DDR3
ROM: eMMC/Nand/SPI Nor + TF card
Interface: ACODEC/I2S/PDM/SPDIF/LCDC/MAC

Rockchip 瑞芯微电子 Fuzhou Rockchip Electronics RK3308_AI-VA_MB_REF 00.Cover Page Wednesday, July 04, 2018 1 of 51 Designed by:

Rockchip Confidential

Content Index

00.Cover Page Page01 01.Index Page02 Page03 02.Revision History 03.Block Diagram Page04 Page05 04.I2C MAP Page06 05.PowerDiagram-Without Battery 06.PowerDiagram-2Cell Battery Page07 07.PowerDiagram-1Cell Battery Page08 Page09 10.RK3308 Power 11.RK3308 OSC/PLL Page10 Page11 12.RK3308 DDR Controller 13.RK3308 FLASH Controller Page12 14.RK3308 USB Controller Page13 15.RK3308 SARADC/OTP Page14 Page15 16.RK3308 LCDC/MAC/I2S1/JTAG Page16 17.RK3308 SDIO/SDMMC 18.RK3308 GPIO/I2S0/PDM/SPDIF Page17 19.RK3308 ACODEC Page18 Page19 20.12V IN Without BAT(OPT1) Page20 21.12V-IN With 2Cell BAT(OPT2) Page21 22.Discrete Power(OPT1&OPT2) Page22 25.USB Port(OPT1&OPT2) Page23 26.USB Port for RK816-3(OPT3) Page24 27.RK816-3 With 1Cell BAT(OPT3) Page 25 30.RAM-DDR3 1x16bit Page 26 31.RAM-LPDDR2 1x16bit Page27 32.RAM-DDR2 1x16bit Page28 40.Flash-eMMC Page29 41.Flash-Nand Flash 42.Flash-SPI Nor Flash Page30 50.LCM-RGB Panel Page31 Page32 51.LCM-MCU Panel Page33 52.LCM-SPI Panel Page34 60.WIFI/BT Module-1T1R Page35 61.WIFI/BT Module-2T2R Page36 62.WIFI/BT COB-RTL8723DS 65.10/100M PHY-RTL8201F Page37 Page38 70.AUDIO Headphone/LineIn Page39 71.AUDIO PA-XA9220/TPA3110 72.AUDIO_PA-XA8326 Page40 73.AUDIO PA-XA8872 Page41 Page42 74.MIC Array Connector-Analog Page43 75.MIC Array Connector-Digital 81.SPDIF IN/OUT-Optical Page44 Page45 82.SPDIF IN/OUT-Coaxial Page46 86.Encryption chip Page47 91.TF Card Page48 92.Recovery/Reset Key Page49 93.IR Receiver 96.UART Debug Port Page50 99.MARK/HOLE Page51

Note


NOTE 1:

Component parameter description

- 1. DNP stands for component not mounted temporarily
- 2. If Value or option is DNP, which means the area is reserved without being mounted
- 3. If Flash is compatible, please notice when eMMC is used, the option is that @eMMC is mounted, @Nand is not mounted when Nand is used, the option is that @Nand is mounted, @eMMC is not mounted

NOTE 2:

Please use our recommended components to avoid too many changes. For more informations about the second source, please refer to our AVL.



Bill of Materials

Header:

Item\tPart\tDescription\tPCB Footprint\tReference\tQuantitv\tOption

Combined property string:

{| ltem \t{Value}\t{Description}\t{PCB Footprint}\t{Reference}\t{Quantity}\t{Option}

Fuzhou Rockchip Electronics

Project: RK3308_AI-VA_MB_REF

File: 01.Index

Date: Wednesday, July 04, 2018 Rev: 1.1

Designed by: Joseph Sheet: 2 of 51

Revision History

Version	Date	Author	Change Note	Approved
V0.1	2018.03.07	Joseph.Wei	First edition	, Q.K.
V1.0	2018.05.11	Joseph.Wei	1 Update VDD_CORE&VDD_LOG Power supply circuits, they are seperated by different power supply 2 Update Analog MIC circurt,MIC1&MIC 2 as Loopback function, MIC3~MIC8 as MIC IN function. 3 Update VDD_LOG Power supply circuit, Set VDD_LOG default voltage as 1.04V,modify R2208=110K%1 4 Update TF Card circuits. 5 Update RMII circuits. 6 Update WiFi circuits. 7 ADD LPDDR2&DDR2 design circuits. 8 Upadate Hardware ID circuits. Detailed change point please check published document: 《RK3308 AI-VA REF V10 20180511 SCH Modify Notes》.	NIRATI
V1.2 M	2018.07.03	Joseph.Wei	1 ADD PMIC RK816-3 design circuits. 2 FLASH Default selecet Nand Flash. 3 ADD RTL8723DS design circuits. 4 Modify the ADC of Recovery to ADC_KEY_IN1. 5 Modify divider resistance of WIFI_REG_ON . 6 Modify divider resistance of CLK_32K_OUT . 7 ADD PowerAmp XA8872 design circuits. 8 VDD_1V0 Power Supply from VDD_LOG. 9 PDM MIC:PDM_CLK Unified modify to PIN T16 of RK3308. 10 Modify Loopback circuit parameter.	

Fuzhou Rockchip Electronics


Froject: RK3308_AI-VA_MB_REF

File: 02.Revision History

Date: Wednesday, July 04, 2018 Rev: 1.1

Designed by: Joseph Sheet: 3 of 51

2



D	5	1 RAT	RXA	1		. P	2	NR	ATIRXAN	2024.0
	Port	Pin name	Domain	Bus name	Pull-up voltage	Slave Device	Slave Addı (MS 7Bits)	Note	Slave Bus Capability	
С	12C0	GPIO1_D1/UART1_TX/12C0_SCL/SPI2_CSN0 GPIO1_D0/UART1_BX/12C0_SDA/SPI2_CLK	VCCIO1	I2C0_SCL I2C0_SDA	vcc_io	Reserve		SAA		C
→	1201	GA100_B4/I2C1_SCL GP100_B3/I2C1_SDA	VCCIO0	I2C1_SCL I2C1_SDA	VCC_IO	IS31FL3236A ATSHA204A-SSHDA-T XA8326 RK816-3	0x3C/0x3F 0x64 0x31/0x30 0x1A	MIC Array Connector-Anal	og	
000	S202	GPIO2_A3/UARTO_RTSN/SPIO_CSNO/I2C2_SCL GPIO2_A2/UARTO_CTSN/SPIO_CLK/I2C2_SDA	VCCIO2	I2C2_SCL I2C2_SDA	APIO2_VDD	Reserve				
B PYS	5		RXP	A202ª	3	RX23	2	File: 04.12C Date: Wednesc Designed by: Joseph	Fuzhou Rocko 8_AI-VA_MB_REF	Chip Electronics Rev: 1.1 Sheet: 5 of 51

