This is Why



- INVERTER TECHNOLOGY
- HIGH SEER
- ▶ 2-WAY AUTO AIR SWING
- ▶ 12-HOUR ON/OFF PROGRAMMABLE TIMER
- LCD WIRELESS REMOTE CONTROL
- AWAKENING FUNCTION
- ANTI-MOLD, DETACHABLE & WASHABLE AIR FILTER.

This Air Conditioner is a Single Type, wall mounted Standard Inverter product with Cool, Dry and Heat function.





► Capacity Cool (kW): 3,50
► Capacity Cool Min-Max (kW): 1,05-3,70
► Capacity Heat (kW): 3,50

► Capacity Heat Min-Max (kW): 1,05-4,50 ► Power supply (V-Hz): 220-240/single/50 Running current Cool (A): 4,70 (EN14511)
Running current Heat (A): 4,60 (EN14511)

▶ Power input Cool (W): 1060

▶ Power input Cool Min-Max (W): 290-1330

▶ Power input Heat (W): 1010

▶ Power input Heat Min-Max (W): 290-1700

▶ EER Cool: 3,40 (EN14511) ▶ COP Heat: 3,47 (EN14511) ▶ SEER Cool: 5,70 (EN14825) ▶ SCOP Heat: 3,80 (EN14825) ▶ Energy efficiency class: Cool: A+

▶ Annual Energy consumption (kWh): 215 (COOL) 1290 (HEAT) ▶ Energy efficiency class: Heat (average climate): A (Average Climate)

▶ Sound pressure level (Indoor) (Hi/Lo, Cool) in dB(A): 38/26

Sound pressure level (Outdoor) in dB(A): 52 ▶ Sound power level (Indoor) (Hi, Cool) in dB: 57 Sound power level (Outdoor) in dB: 62

Air flow volume Indoor (Hi, Cool) in m³/min: 10,00 Dimensions Indoor (WxHxD) in mm: 800 x 280 x 183 Dimensions Outdoor (WxHxD) in mm: 700 x 551 x 256

Net weight Indoor (kg): 10
Net weight Outdoor (kg): 26 ▶ Pipe diameter Liquid side (inch): 1/4 ▶ Pipe diameter Gas side (inch): 1/2 ▶ Refrigerant: **R-410A** (1975) ▶ Min-Max Pipe length (m): 1-15 Maximum chargeless length (m): 5
 Maximum height difference (m): 5

www.sharp-cee.com



HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE A-1020 VIENNA HANDELSKAI 342 AUSTRIA

PHONE: +43 1 72719-0 FAX: +43 1 72719-289

INTERNET: WWW.SHARP-CEE.COM