

Served-Realization Tree Verification for Recurrent Hybrid Language Models

Zhiyuan Ma

Abstract—GDN Tree-Scan is a served-realization verifier for recurrent-hybrid speculative decoding in vLLM. It combines a forked FlashAttention-2 decode path with tree ancestry bias, a branch-local Triton Gated-DeltaNet scan/replay kernel, device-side multidraft commitment, and accepted-chain-only state publication for Qwen/Qwen3.6-27B-FP8. Unlike cache/scheduler-layer hybrid serving, algebraic state-sharing designs, or FPGA-oriented SSM speculation, the contribution is a fused vLLM/FA2/GDN realization at the target-verifier boundary. In a clean B=1, temperature-0.6, four-task SWE/Codex gate, the six-node root-branch tree reaches 23.88 token-weighted decode tokens/s versus 18.80 for native E5, a 27.0% decode-throughput gain. The same run is only 4.0% faster under a per-request-equal latency view, and end-to-end task wall time remains prefill-heavy. The lossless claim is scoped: the current gate is a sampled clear-margin p-rescore that closes within the observed native recurrent-oracle flip floor, not a full distribution-distance or request-cluster-bootstrap proof. We report the verifier contract, implementation seams, evidence gates, and failed routes that define this scoped decode-throughput result.

Index Terms—speculative decoding, recurrent models, Gated DeltaNet, vLLM, FlashAttention, ML systems

I. INTRODUCTION

Speculative decoding accelerates autoregressive generation by drafting candidate tokens and asking the target model to verify them in parallel. Tree-shaped speculative decoding generalizes a single draft chain into a candidate token tree, improving the opportunity set for each target forward pass while preserving the target distribution under the verifier acceptance rule [1]–[4]. For attention-only Transformer stacks, the central verifier problem is largely an ancestry problem: row i may attend to the prompt and its ancestors, but not to sibling branches [1], [3].

Recurrent hybrid models break that simplification. Qwen 3.6-style hybrid stacks contain many Gated-DeltaNet (GDN) recurrent layers in addition to softmax-attention layers, so a valid tree row needs two path-local facts: attention ancestry and recurrent state lineage [5], [6]. The verifier must ensure that a node’s GDN state equals the state native sequential decode would have produced along that node’s root-to-node path. If sibling rows share a packed recurrent accumulator, a correct attention mask can still verify tokens from an impossible recurrent history.

This paper reports a served verifier for a recurrent hybrid target inside vLLM. The contribution is not “tree speculative decoding” in the abstract. It is served-realization equivalence as an implementation target: forked FlashAttention-2 (FA2) tree bias for attention, branch-local GDN scan and accepted-

chain replay for recurrence, and vLLM state publication that makes rejected branch state non-durable [7]–[9].

The measured result is deliberately narrow. In a clean B=1, temperature-0.6 deployment trace over four SWE/Codex tasks, cat6root, a six-node tree with a depth-5 native spine plus one root sibling, reaches 23.8768 token-weighted decode tokens/s versus 18.7962 for native E5, a 27.0% decode-throughput gain. The root sibling is a depth-0 alternative: when native MTP would lose an event because the first spine token is rejected, the verifier can still commit the sibling branch, raising committed tokens/event from 4.112 to 4.821 while adding almost no verify-forward time. The per-request-equal latency view is 18.5056 versus 17.8018 tokens/s, or +4.0%; this is useful but underweights long decode turns where most generated tokens occur. Both cat6root and cat9 close within the observed native recurrent-oracle flip floor in a 40-turn B=1 p-rescore, but full distribution-distance evidence, request-level bootstrap, more seeds, B=4, and Stage D timing remain open gates.

The paper makes three concrete contributions:

- A served verifier contract for recurrent hybrid token trees: attention ancestry, path-local GDN state, SpecInfer-style residual commitment, and accepted-chain-only durable publication.
- A vLLM/FA2/GDN implementation path that preserves native serving machinery where possible and adds tree-specific state only at explicit seams.
- An evidence ledger that separates clean B=1 decode throughput, per-request latency, recurrent-oracle p-rescore, end-to-end wall caveats, and contaminated or still-open measurements.

II. BACKGROUND AND RELATED WORK

Speculative decoding uses a cheaper draft path to propose future tokens and verifies them with the target model. SpecInfer introduced tree-based speculative inference and parallel verification for LLM serving, while Sequoia, EAGLE-2, and OPT-Tree study hardware-aware, dynamic, or adaptive draft-tree structure [1]–[4]. These systems establish the candidate-tree and verifier-acceptance framing, but the usual target-forward assumption is too high-level for a served recurrent hybrid.

STree is the closest prior work for stateful tree decoding. It extends tree speculative decoding to SSM and hybrid architectures by exploiting accumulated state-transition structure [10]. That framing transfers directly: stateful models need tree-aware state construction, not only tree-aware attention. The

missing layer for this artifact is realization. The served target path has fp8/bf16 seams, branch co-residency, a specific FA2 attention implementation, GDN state writeback, and rejection sampling inside vLLM.

Recent hybrid serving and SSM speculation work sharpens the same boundary. SpecMamba identifies hidden-state backtracking, tree-verification incompatibility, and draft/target workload mismatch for Mamba speculative decoding, then targets an FPGA dataflow [11]. Component-aware self-speculation shows that hybrid component structure matters: Falcon-H1 and Qwen3.5 behave differently because of how SSM/linear-attention components are integrated [12]. These papers explain why hybrid models create new verifier questions, but they do not close the vLLM/FA2/GDN served-realization path.

SGLang is the closest adjacent production comparison and should be treated carefully. Its hybrid-model writeup separates KV cache from request-level Mamba state, introduces MambaRadixCache, and handles speculative verification with independent state slots and parent tracing [13]. Its Qwen3-Next documentation and speculative-decoding documentation show active support for GDN/MTP-style hybrid models [14], [15]. That is not an apple-to-apple fused-kernel baseline for this paper: much of the mechanism is cache/scheduler-layer work, while this artifact’s shipped contribution is lower in the stack, at the vLLM, forked-FA2, branch-local GDN scan/replay, and publication boundary [9], [16].

III. CLAIM SCOPE AND EVIDENCE MAP

The contribution is easiest to evaluate when each claim names its mechanism, measurement basis, and caveat. Table II makes that boundary explicit. The artifact receipts remain in the source trail; the paper body carries the facts needed to evaluate the argument without following every repository link.

IV. VERIFIER CONTRACT

GDN Tree-Scan verifies an arbitrary candidate tree, not only the native MTP drafter used in the current implementation. The input contract is a prefix state, a parent array, candidate token ids, and sampling state. The output contract is stronger: after verification and commitment, the next served decode event must start from the same observable token prefix and recurrent state that native sequential decode would have reached on the accepted tokens, up to the observed native recurrent-oracle numerical floor.

The contract can be summarized as an engineering invariant. Assume the tree contains only candidate ids and parent links; attention rows see only prefix plus ancestors; every GDN row is computed from its parent row’s recurrent state; the committer applies the same residual rule as the target verifier; and durable state is replayed or published only for the accepted chain. Then the next served decode event has the same intended token-prefix and recurrent-state boundary as native sequential decode on the accepted prefix. The current

Algorithm 1 Tree verification on a recurrent hybrid target

Require: prefix state S_0 , candidate tree $T = (V, E)$, token ids x_i , sampling state

- 1: Pack candidate ids, parent indices, and ancestry masks into vLLM decode metadata.
- 2: Run softmax-attention layers with FA2 tree bias so row i sees prefix and ancestors only.
- 3: **for** each GDN layer **do**
- 4: **for** each node i in topological order **do**
- 5: Load $S_{\text{parent}(i)}$ from S_0 or branch-local `h_cache`.
- 6: Compute $S_i, o_i \leftarrow \text{GDNStep}(S_{\text{parent}(i)}, x_i)$.
- 7: Store S_i in `h_cache[i]` for children.
- 8: **end for**
- 9: **end for**
- 10: Apply the residual speculative acceptance rule on device.
- 11: Replay accepted path in native order and publish only accepted GDN/conv state.
- 12: **return** committed tokens and durable recurrent state for the next decode event.




Fig. 1. The tree shape is a cross-layer contract. Candidate packing, attention metadata, recurrent scan, commitment, replay, and metrics must consume the same descriptor.

evidence checks this boundary through recurrent-oracle p-rescore and targeted scan/replay gates rather than through a full distribution-distance proof [1].

V. SYSTEM DESIGN

Figure 1 shows the served path. The drafter currently uses Qwen’s native MTP head: root and spine tokens come from the same logits tensor, with runner-up leaves read as top- k candidates. The verifier should not depend on that drafter. Its stable boundary is a tree descriptor with parent indices, candidate ids, visibility masks, and accepted-path rows that can be replayed into native state.

The attention side needed a real FA2 fork. vLLM’s generic tree attention path could express an additive ancestry bias through a Triton `unified_attention` route, but that route was not the same realization as native FA2 decode. The forked path adds an fp32 `tree_bias` after the QK score tile and

TABLE I

COMPARISON LAYER FOR PRIOR AND ADJACENT WORK. THE GOAL IS TO AVOID PROMOTING ADJACENT SERVING WORK INTO A DIRECT FUSED-KERNEL BASELINE.

Line of work	What transfers	What breaks for this target	What GDN Tree-Scan adds
SpecInfer, Sequoia, EAGLE-2, OPT-Tree	Candidate trees, verifier acceptance, dynamic or hardware-aware shape selection [1]–[4].	The target verification forward is assumed to realize the target distribution once attention ancestry is correct.	Recurrent-state verification and deployment lossless gates.
STree	Stateful models need tree-aware state construction [10].	Algebraic state sharing is not the same as matching native served GDN under bf16/tp8 and vLLM writeback.	A GDN scan/replay kernel gated against native/deployment oracles.
SpecMamba	Hidden-state backtracking and tree verification are first-class SSM obstacles [11].	FPGA dataflow and FIFO verification are not a served GPU/vLLM path for Qwen GDN.	Fused GPU kernels, FA2/vLLM compatibility, and deployment gates.
Component-aware self-speculation	Hybrid component structure determines speculative viability [12].	Research Python implementation leaves fused CUDA, batched verification, and cache sharing as systems gaps.	A fused served path for Qwen GDN tree verification.
SGLang hybrid serving	Adjacent production mechanisms: dual memory pools, MambaRadixCache, parent tracing, MTP/EAGLE surfaces [13]–[15].	Cache/scheduler-layer mechanisms are not directly comparable to this fused vLLM GDN tree-scan kernel.	A different layer of realization: vLLM + forked FA2 tree bias + branch-local GDN scan/replay + observed recurrent-oracle gates.

TABLE II

CLAIM, GATE, AND CAVEAT MAP. THE REPOSITORY HAS A LONGER RECEIPT LEDGER; THIS TABLE KEEPS THE ACADEMIC CLAIM BOUNDARY EXPLICIT.

Claim	In-paper evidence	Gate	Status and limit
The systems contribution is served-realization equivalence for Qwen GDN in vLLM. cat6root is faster than native E5 on clean B=1 decode throughput.	FA2 tree-bias decode, branch-local GDN scan/replay, device multidraft commitment, and accepted-chain-only durable publication. Table V: 23.8768 versus 18.7962 token-weighted decode tokens/s.	All target-verifier surfaces consume the same tree descriptor and accepted path. Matched pure-decode GPU timer, probes off, temp-0.6, four SWE/Codex tasks.	Closed for the shipped B=1 path; not a claim of first GDN speculation. +27.0% decode-only; per-request-equal latency is +4.0%.
cat9 and cat6root close within the native recurrent-oracle floor.	Section VIII: 13.28% and 13.09% clear-margin flips versus native E5 at 12.90%.	Each arm is compared with its own no-spec recurrent oracle in the B=1 p-rescore.	Closed for this 40-turn sample; no TV-distance or request-cluster bootstrap yet.
The measurement discipline is part of the result.	Speed runs disable probes; lossless runs enable oracle capture; token-weighted and per-request views are reported separately.	No mixing of raw prompt probes, oracle capture, B=4 co-residency, or denominator conventions.	Prevents false speed wins and false lossless failures; B=4 remains open.

TABLE III

ENGINEERING FORM OF THE ACCEPTED-STATE VERIFIER CONTRACT.

Part	Formal content	Served implementation
Inputs	Prefix state, parent array, candidate ids, sampling state.	vLLM tree packing plus multidraft metadata.
Attention	Row i sees prompt tokens and ancestors of i , not siblings.	Forked FA2 adds <code>tree_bias</code> before softmax; prefill stays native.
GDN	$S_i = \text{GDNStep}(S_{\text{parent}(i)}, x_i)$.	Triton GDN tree scan with branch-local <code>h_cache</code> .
Acceptance	Apply the same residual speculative rule as target verification.	Device multidraft commit at temperature 0.6.
Publication	Only accepted-prefix tokens and their state become durable.	Accepted-chain replay and vLLM state writeback/remap.

TABLE IV

SURFACES THAT MUST AGREE ON THE SAME TREE CONTRACT. MOST FAILED ROUTES BROKE ONE OF THESE ALIGNMENTS.

Surface	Required alignment	Typical failure if isolated
Candidate descriptor	Parent indices, candidate ids, visibility masks, and accepted-path rows match.	A drafter-specific shortcut cannot be replayed into native state.
FA2 attention	Decode rows see prefix plus ancestors, with prefill left on native FA2.	A correct abstract mask runs on a non-native attention realization.
GDN scan	Each node loads its parent recurrent state, not the previous packed row.	Sibling rows inherit impossible recurrent histories.
Committer	The residual speculative rule is applied to the same candidate rows verified by the target.	Accepted tokens are counted against stale or mismatched probabilities.
Publication	Only the accepted chain is replayed and made durable.	Rejected branch state leaks into the next decode event.

before softmax inside the FA2 varlen decode path, while keeping prefill on native FA2 [7]. This makes the attention half of tree verification a minimal extension of the native served carrier.

The recurrent side needed branch-local state and publication discipline. During verification, each candidate row computes a GDN post-state from its parent row, not from the previous packed row. During commitment, the accepted chain is replayed in native order before durable state is written back. Rejected rows can influence acceptance decisions, but they must not become future model memory [16].

VI. GDN SCAN AND REPLAY KERNEL

The GDN recurrence is a stateful linear-attention update. For one value tile, the served kernel implements the same




Fig. 2. The evaluated shapes. cat9 adds runner-up leaves to the depth-5 spine; cat6root keeps the spine and adds only a root sibling, reducing verifier work while preserving most of the acceptance gain.




Fig. 3. The scan verifies all candidate nodes with parent-indexed recurrent state. Replay re-executes only the accepted chain and publishes durable GDN/conv state.

rank-1 update body used by the native path:

$$S'_t = \exp(g_t) S_{t-1}, \quad (1)$$

$$\Delta_t = \beta_t (v_t - S'_t k_t), \quad (2)$$

$$S_t = S'_t + \Delta_t k_t^\top, \quad (3)$$

$$o_t = S_t q_t. \quad (4)$$

For a tree node i , the invariant is $S_i = \text{native_scan}(\text{tokens}(\text{root} \rightarrow i))$. This is simple to state and easy to violate in a packed GPU implementation [5].

The kernel keeps a post-state for each padded node in h_cache . That table has shape $[N_{\text{PAD}}, BV, DIM_K]$ in fp32, where BV is the value-channel tile width. This is the main local resource constraint: native-match geometry such as $BV32$, one warp, and three stages can spill for a full $N_{\text{PAD}} = 16$ tree because the per-node state table becomes too large. The deployed scan uses $BV16$, eight warps, and pad16 for cat9; cat6root uses the smaller six-node tree and pad8-style shape economics while sharing the same verifier contract.

The numeric seams are also explicit. The scan alignment tracks beta’s bf16 round trip, q/k normalization by division rather than reciprocal-square-root, and the carried-state bf16 boundary after output computation. These details are not cosmetic. In speculative decoding, a small branch-local numerical difference matters if it changes a clear-margin argmax or a residual sampling decision after many recurrent and attention layers.

VII. EXPERIMENTAL SETUP

The target checkpoint is the public Hugging Face model Qwen/Qwen3.6-27B-FP8, a 64-layer hybrid model whose documented layout has 48 GDN recurrent layers and 16 softmax-attention layers [6]. The serving environment mounts it at `/models/qwen3.6-27b-fp8`

and exposes it as qwen3.6-27b on GB10. The source-of-truth runtime is a vllm/vllm-openai image pinned to digest sha256:3dbe092ec5b2cef63b6104d33fa75d6ce53a7870962

529ada69f78bbbc38e776, corresponding to vLLM 0.19.2rc1.dev134+gfe9c3d6c5, plus the forked FA2 .so swap and the boot-time tree-GDN patcher. The clean B=1 tree arms use the forked FA2 tree-server launcher; cat9 also has a locked wrapper, native E5 uses the native speed launcher, and the B=1 deploy wrapper pins GPU_UTIL=0.82, MAX_NUM_SEQS=1, and MAX_MODEL_LEN=131072. The receipts pin the mounted model path and runtime image but not the immutable Hugging Face revision hash downloaded into that mount; exact reproduction should record that revision at artifact packaging time. The workload is four SWE/Codex tasks in clean B=1 mode, temperature 0.6, with true sequential windows and num_running near zero.

Speed and lossless evidence are measured in separate modes. Speed runs disable heavy capture/oracle probes; lossless runs enable recurrent-oracle capture and p-rescore. This separation is not bookkeeping. Several earlier readings were confounded by raw prompt probes, B=4 co-residency, instrumentation overhead, or denominator mistakes, so the final result reports token-weighted decode throughput, per-request latency, lossless p-rescore, and end-to-end wall caveats as different measurements.

Table V is the core speed result. cat6root commits 4.821 tokens/event versus 4.112 for native E5, a 17.2% committed-token gain, while keeping verify-forward time essentially native. The gain comes from the root sibling’s position in the tree: it is a depth-0 alternative that recovers events native MTP loses when the first spine token is rejected, instead of spending most of its extra work on deeper leaves whose ancestors must all survive. The older +4.0% number is still true for the per-request-equal latency view, but that view weights a short tool-call turn like a long edit turn. The token-weighted aggregate is the fair decode-throughput basis for this scoped mechanism result.

The request anatomy explains why these metrics differ. In the cat6root B=1 trace, 24.7% of turns have at most 64 output tokens, but those turns account for only 3% of output tokens; they are mostly short shell-tool calls in the Codex agent loop. Speculative decoding helps more on longer turns, so per-request-equal averaging undercounts the decode-token gain. This does not imply a 27% end-to-end task-wall gain, because the same workload repeatedly sends roughly 11k–14k prompt tokens and prefix caching is off for this hybrid setup.

VIII. LOSSLESS EVIDENCE AND MEASUREMENT DISCIPLINE

The empirical lossless claim in this artifact is closure within the observed native recurrent-oracle flip floor. The exact B=1 depth-5 p-rescore compares each arm against its own no-spec recurrent oracle under temperature 0.6. Native E5 has 630 clear-margin flips over 4,883 positions, or 12.90%; cat9 has 645 over 4,858, or 13.28%; cat6root has about 636 over about

TABLE V
CLEAN B=1 DECODE RESULT. THROUGHPUT DELTA IS TOKEN-WEIGHTED DECODE TPS RELATIVE TO NATIVE E5.

Arm	Tree	Per-request TPS	Token-weighted TPS	Delta	s/fwd_gpu	Accept/event
Native E5	Native 5-step MTP spine	17.8018	18.7962	baseline	0.136955	3.1122
cat9	9-node caterpillar: 5-spine + 4 leaves	18.4366	22.6307	+20.4%	0.144030	3.6406
cat6root	6-node root branch: 5-spine + root sibling	18.5056	23.8768	+27.0%	0.137719	3.8214

TABLE VI
LOSSLESS CLOSURE GATES AND INTERPRETATION.

Gate	Checked	Status
Depth-5 p-rescore	E5/cat9/cat6root temp-0.6 recurrent oracle.	Within native floor.
GDN scan A/B	$BV16 = BV32 = 0.0$ in controlled scan.	Scan alone is clean.
Native path oracle	Path-local state versus native decode order.	Core invariant.
Device committer	Same residual-mix rule on device.	Residual-rule gate.
Broad cat9 floor	Big-denom deployment consolidation.	Overlapping floor intervals.

4,860, or 13.09%. Both tree arms are within the native E5 floor by less than one position-level standard error, but this is not a TV-distance estimate and not a request-cluster bootstrap.

The statistical caveat matters. The p-rescore sample has roughly 4.9k positions per arm, but positions inside one SWE/Codex turn are correlated. The result is therefore clean B=1 closure for the observed sample, not a universal guarantee across all seeds, batch sizes, or prompt distributions. Request-cluster bootstrap, additional seeds, and full distribution-distance measurements are follow-up gates.

The measurement infrastructure is part of the contribution because it prevented false wins and false losses. The canonical formulas are:

$$s/fwd_gpu = \frac{\text{decode forward GPU seconds}}{\text{pure decode drafts}}, \quad (5)$$

$$\text{accept/event} = \frac{\text{accepted draft tokens}}{\text{draft events}}, \quad (6)$$

$$\text{committed/event} = \text{accept/event} + 1, \quad (7)$$

$$\text{deploy TPS} = \frac{\text{request decode tokens}}{\text{request decode seconds}}. \quad (8)$$

Probe separation, deployment-path-only measurement, token weighting, and oracle-mode separation are all needed to make the numbers interpretable. This is why raw `/v1/completions` probes, B=4 screens, and oracle-enabled lossless traces are not treated as substitutes for the clean B=1 deployment-speed gate.

IX. DESIGN EVOLUTION AND NEGATIVE RESULTS

The failure library explains why the final verifier has its particular contract. It separates three questions that can otherwise blur together: whether the verifier preserves the target distribution within the native floor, whether the kernel is fast enough to matter, and whether the measurement regime is timing the served path. Table VII condenses the HTML failure library into paper form.

Several rows are useful future work rather than dead ends. WY-style whole-tree algebra may still become a speed route if it can be tied back to the served sequential oracle. Cache-side or radix-style state sharing in vLLM would also be complementary to the current verifier rather than a replacement for it. The important point is that none of those routes is allowed to stand in for accepted-chain replay, path-local GDN state, or the deployment/lossless separation used in the reported result.

X. THREATS TO VALIDITY

The result is strong for clean B=1 decode throughput and within-floor closure under the current recurrent-oracle p-rescore. It does not claim that every deployment bottleneck is solved.

- **Lossless sample size.** The exact cat9/cat6root p-rescore is a 40-turn B=1 sample per arm. The position-level standard error is informative but optimistic because positions within a turn are correlated; request-level bootstrap and more seeds remain open.
- **Decode is not full task wall.** The +27.0% number is decode throughput. SWE/Codex requests repeatedly send large repository context, and prefix caching is off for this hybrid setup, so end-to-end wall gains are smaller.
- **B=4 needs refreshed treatment.** The clean mechanism result is B=1. Batching changes co-residency, scheduler pressure, and prefill/decode overlap, so the old B=4 diagnostics are not a final verdict.
- **Stage D timing is open.** Drafter, verify forward, and isolated committer compute are near E5, but live phase attribution still needs direct step-wall timers.

XI. CANONICAL CONFIGURATION

The shipped cat9 and cat6root arms share one tree-serving configuration. The only intended per-arm difference is the speculative tree shape: cat9 is a 9-node depth-5 spine plus leaves, while cat6root is a 6-node depth-5 spine plus root sibling. Table VIII lists the load-bearing choices most likely to invalidate the result if changed.

The committer row follows the later bake addendum: the older canonical-config catalog still lists `FR13_DEVICE_MULTIDRAFT` as diagnostic/off, while the addendum records that it was baked default-on for tree arms after verifying that native E5 does not read the tree committer gate. Some flags remain explicit on purpose. The FA2 tree-bias and native-prefill flags are default-off in the patcher to preserve patch idempotency anchors; baking them would require a separate re-patch verification task. The fixed-row in-projection pad should not be baked globally because it can

TABLE VII

NEGATIVE RESULTS AND SUPERSEDED INTERPRETATIONS THAT SHAPED THE FINAL VERIFIER. THESE ARE NOT ALL MATHEMATICAL IMPOSSIBILITIES; SEVERAL ARE REJECTED ONLY AS SERVED-PROOF ROUTES FOR THIS ARTIFACT.

Route or interpretation	Why it looked plausible	What failed	Paper consequence
Attention-mask-only tree	Tree verification for attention-only LLMs mainly needs ancestry.	GDN rows still carried sibling-contaminated recurrent state.	Attention ancestry is necessary but not sufficient.
Shared packed recurrent accumulator	Co-resident rows are efficient if packed sequentially.	Packed order is not native branch order, so sibling states leak.	The scan must be parent-indexed and branch-local.
SSTree-style state sharing as direct transplant	SSTree gives the right stateful-tree problem lens.	Algebraic state construction is not the same as matching served bf16/fp8 GDN writeback.	SSTree is prior work, not the served-realization proof.
Triton TREE_ATTN as proof path	It can express a tree mask.	It is not the same FA2 decode realization as native serving.	The reported path uses a forked FA2 tree-bias decode kernel.
WY / whole-tree algebra	It could reduce state traffic and expose more parallelism.	Different summation trees and bf16 boundaries are not the native sequential verify oracle.	Kept as future speed work; not the lossless proof route.
Literal 0.0 max-abs as only lossless bar	Bit equality is easy to state.	Native recurrent-oracle comparisons already have a numerical flip floor.	The paper uses within-native-floor p-rescore, not bit-exact intermediate equality.
cat10 and broad B=4 screens	Wider trees and batching are deployment-relevant.	Contaminated reads violated the expectation that a strict tree superset should not accept fewer spine tokens than native.	Clean B=1 is the mechanism proof; B=4 needs a refreshed carrier-clean run.
Per-request TPS as headline	It is a latency-friendly summary.	It weights a short shell-tool turn like a long edit turn.	Token-weighted decode TPS is the throughput headline; per-request TPS is a caveat.

TABLE VIII

LOAD-BEARING CONFIGURATION CHOICES IN THE SHIPPED TREE PATH.

Surface	Choice
Tree mode	FR10_ENABLE_TREE_GDN=1, FR10_DECODE_MODE_DEFAULT=tree_mtp.
Attention	FR13_FA2_TREE_BIAS=1, FR13_FA2_PREFILL_NATIVE=1.
GDN batch variance fix	LUMO_FB_KERNEL_ROWS=1, LUMO_FB_PROJ_PAD_ROWS=16.
Committer	FR13_DEVICE_MULTIDRAFT=1 default-on for tree arms.
Safety	FR10_ALLOW_LINEAR_FALLBACK unset.
Operational B=1	GPU_UTIL=0.82, MAX_NUM_SEQS=1.

perturb native E5 bytes, which define the recurrent-oracle baseline.

XII. CONCLUSION

GDN Tree-Scan turns a token tree into a served verifier for a recurrent hybrid language model by treating recurrent state as part of the tree contract. Attention ancestry is necessary, but not sufficient. The shipped path adds FA2 tree bias for softmax layers, branch-local GDN scan/replay for recurrent layers, and accepted-chain-only state publication for vLLM. Under the clean B=1 deployment gate, cat6root improves token-weighted decode throughput by 27.0% while closing within the observed native recurrent-oracle flip floor. The result should be read with its caveats attached: decode-only, B=1, 40-turn p-rescore, no request-cluster bootstrap, no full distribution-distance estimate, prefill-heavy workload, and open B=4/Stage D follow-up.

ARTIFACT AND SOURCE TRAIL

The source blueprint is the live GitHub Pages paper, fetched and byte-matched to the local `gh-pages` worktree on June 18, 2026 [9]. This provenance is intentionally separated from the main technical framing. The consolidated source receipts are the deployed TPS correction, B=1 lossless verdict, request anatomy, Stage D localization, vLLM source-of-truth ledger,

launchers, FA2 fork correction, GDN tree kernel, vLLM tree wiring patch, device multidraft committer, measurement harness, canonical config ledger, and bake addendum [17].

REFERENCES

- [1] X. Miao, G. Oliaro, Z. Zhang, X. Cheng, Z. Wang, Z. Zhang, R. Y. Y. Wong, A. Zhu, L. Yang, X. Shi, C. Shi, Z. Chen, D. Arfeen, R. Abhyankar, and Z. Jia, “Specinfer: Accelerating generative large language model serving with tree-based speculative inference and verification,” 2024.
- [2] Z. Chen, A. May, R. Svirschevski, Y. Huang, M. Ryabinin, Z. Jia, and B. Chen, “Sequoia: Scalable, robust, and hardware-aware speculative decoding,” 2025.
- [3] Y. Li, F. Wei, C. Zhang, and H. Zhang, “Eagle-2: Faster inference of language models with dynamic draft trees,” 2024.
- [4] J. Wang, Y. Su, J. Li, Q. Xia, Z. Ye, X. Duan, Z. Wang, and M. Zhang, “Opt-tree: Speculative decoding with adaptive draft tree structure,” 2025.
- [5] S. Yang, J. Kautz, and A. Hatamizadeh, “Gated delta networks: Improving mamba2 with delta rule,” 2025.
- [6] Qwen Team, “Qwen3.6-27B-FP8.” <https://huggingface.co/Qwen/Qwen3.6-27B-FP8>, 2026. Public Hugging Face model page; accessed 2026-06-18.
- [7] T. Dao, “Flashattention-2: Faster attention with better parallelism and work partitioning,” 2023.
- [8] W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, “Efficient memory management for large language model serving with pagedattention,” 2023.
- [9] Z. Ma, “GDN Tree-Scan GitHub Pages blueprint.” https://macoredroid.github.io/Lumo_FlyWheel/gdn-tree-scan.html, 2026. Live source page; fetched and byte-matched to local `gh-pages` source on 2026-06-18.
- [10] Y. Wu, Z. Qin, A. Wong, and S. Soatto, “Stree: Speculative tree decoding for hybrid state-space models,” 2025.
- [11] L. Zhong, S. Xu, H. Wen, T. Xie, Q. Guo, Y. Wang, and M. Li, “Specmamba: Accelerating mamba inference on fpga with speculative decoding,” 2025.
- [12] H. Borobia, E. Seguí-Mas, and G. Tormo-Carbó, “Component-aware self-speculative decoding in hybrid language models,” 2026.
- [13] SGLang Team, “Hybrid Models Meet SGLang: More than Full Attention.” <https://pytorch.org/blog/hybrid-models-meet-sglang-more-than-full-attention/>, 2025.
- [14] SGLang Project, “Qwen3-Next SGLang documentation.” <https://lmsysorg.mintlify.app/cookbook/autoregressive/Qwen/Qwen3-Next>, 2026.
- [15] SGLang Project, “Speculative Decoding Documentation.” https://sgl-project.github.io/advanced_features/speculative_decoding.html, 2026.

- [16] SGLang Project, “Hybrid-GDN MTP speculative decoding is not lossless on Ascend NPU.” <https://github.com/sgl-project/sglang/issues/25587>, 2026.
- [17] Z. Ma, “GDN Tree-Scan consolidated implementation and measurement receipts.” https://github.com/MaCoredroid/Lumo_FlyWheel/tree/55f55854328b37f262e97d57b5863d8fadd7ff76, 2026. Commit-pinned repository receipts for deploy TPS, lossless gates, runtime, launchers, kernels, and configuration.