Status	Finished
Started	Sunday, 11 October 2026, 4:17 PM
Completed	Sunday, 11 October 2026, 4:21 PM
Duration	3 mins 31 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open(file = "c:\\scores.txt", "w")

b. outfile = open("c:\\scores.txt", "rw")

c. outfile = open("c:\\scores.txt", "a") ✓

d. outfile = open(file = "c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. ftell()

b. tell()

c. fseek()

d. seek() ✓

The correct answer is: seek()

Question **3**

Incorrect

Mark 0.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Appends to an existing file

b. Creates a new file for writing

c. Opens an existing file in read mode ✗

d. Opens a file in binary mode

The correct answer is: Creates a new file for writing

Question **4**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It appends data to the file

b. It clears the old data and starts fresh ✓

c. It does nothing

d. It raises an error

The correct answer is: It clears the old data and starts fresh

Question **5**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlines() ✓

b. readlist()

c. read()

d. readline()

The correct answer is: readlines()

Question **6**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readlines()
b. readline(size)
c. readline() ✓
d. read()

The correct answer is: readline()

Question **7**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. ab+
b. wb+
c. r
d. rw+ ✓

The correct answer is: rw+

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. truncate() ✓
b. shrink()
c. reduce()
d. resize()

The correct answer is: truncate()

Question **9**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. • Move file pointer five characters ahead from the current position. ✓

b. • Move file pointer five characters behind ahead from the end of a file.

c. Move file pointer five characters ahead from the beginning

d. • Move file pointer five characters behind from the current position.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for writing in binary format?

a. wb ✓

b. r+

c. rb

d. w

The correct answer is: wb

Question **11**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. moves the file pointer to the end of a file

b. move the file pointer to beginning of the file

c. move the file pointer five characters behind from the current position

d. move the file pointer five characters ahead from the current position ✓

The correct answer is:
move the file pointer five characters ahead from the current position

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

a. It reads a single line from the file

b. It reads the file and returns it as a dictionary

c. It reads the entire file and returns it as a string

d. It reads the entire file and returns it as a list of lines ✓

The correct answer is: It reads the entire file and returns it as a list of lines

Question **13**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓

False

The correct answer is 'True'.

Question **14**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)

b. infile = open(“a.txt”, “r”) ✓

c. infile = open(file = “a.txt”, “r”)

d. infile = open(file, “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **15**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

a. read(1)

b. readlines(1)

c. readline() ✓

d. line()

The correct answer is: readline()