

Theory of Relational Database Design

1 Informal Design Guidelines for Relational Databases (1)

- What is relational database design?
The grouping of attributes to form "good" relation schemas
- Design is concerned mainly with base relations
- What are the criteria for "good" base relations?

Informal Design Guidelines for Relational Databases (2)

- We first discuss informal guidelines for good relational design
- Then we discuss formal concepts of functional dependencies and normal forms
 - 1NF (First Normal Form)
 - 2NF (Second Normal Form)
 - 3NF (Third Normal Form)
 - BCNF (Boyce-Codd Normal Form)
- Additional types of dependencies, further normal forms, relational design algorithms by synthesis will be discussed later

1.1 Semantics of the Relation Attributes


GUIDELINE 1: Informally, each tuple in a relation should represent one entity or relationship instance. (Applies to individual relations and their attributes).

- Attributes of different entities (EMPLOYEES, DEPARTMENTS, PROJECTs) should not be mixed in the same relation
- Only foreign keys should be used to refer to other entities

Bottom Line: Design a schema that can be explained easily relation by relation. The semantics of attributes should be easy to interpret.

A simplified COMPANY relational database schema

Figure 14.1 Simplified version of the COMPANY relational database schema.



© Addison Wesley Longman, Inc. 2000, Elmasri/Navathe, Fundamentals of Database Systems, Third Edition

1.2 Redundant Information in Tuples and Update Anomalies

- Mixing attributes of multiple entities may cause problems
- Information is stored redundantly wasting storage
- Problems with update anomalies
 - Insertion anomalies
 - Deletion anomalies
 - Modification anomalies

EXAMPLE OF AN UPDATE ANOMALY (1)

Consider the relation:


EMP_PROJ (Emp#, Proj#, Ename, Pname, No_hours)

- **Update Anomaly:** Changing the name of project number P1 from “Billing” to “Customer-Accounting” may cause this update to be made for all 100 employees working on project P1.

EXAMPLE OF AN UPDATE ANOMALY (2)

- **Insert Anomaly:** Cannot insert a project unless an employee is assigned to .
Inversely - Cannot insert an employee unless he/she is assigned to a project.
- **Delete Anomaly:** When a project is deleted, it will result in deleting all the employees who work on that project. Alternately, if an employee is the sole employee on a project, deleting that employee would result in deleting the corresponding project.

Two relation schemas suffering from update anomalies.



Example States for EMP_DEPT and EMP_PROJ

Figure 14.4 Example relations for the schemas in Figure 14.3 that result from applying NATURAL JOIN to the relations in Figure 14.2. These may be stored as base relations for performance reasons.

EMP_DEPT						
ENAME	SSN	BDATE	ADDRESS	DNUMBER	DNAME	DMGRSSN
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	972 Fir Oak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

EMP_PROJ					
SSN	PNUMBER	HOURS	ENAME	PNAME	PLOCATION
123456789	1	32.5	Smith, John B.	ProductX	Bellaire
123456789	2	7.5	Smith, John B.	ProductY	Sugarland
666884444	3	40.0	Narayan, Ramesh K.	ProductZ	Houston
453453453	1	20.0	English, Joyce A.	ProductX	Bellaire
453453453	2	20.0	English, Joyce A.	ProductY	Sugarland
333445555	2	10.0	Wong, Franklin T.	ProductY	Sugarland
333445555	3	10.0	Wong, Franklin T.	ProductZ	Houston
333445555	10	10.0	Wong, Franklin T.	Computerization	Stafford
333445555	20	10.0	Wong, Franklin T.	Reorganization	Houston
999887777	30	30.0	Zelaya, Alicia J.	Newbenefits	Stafford
999887777	10	10.0	Zelaya, Alicia J.	Computerization	Stafford
987987987	10	35.0	Jabbar, Ahmad V.	Computerization	Stafford
987987987	30	5.0	Jabbar, Ahmad V.	Newbenefits	Stafford
987654321	30	20.0	Wallace, Jennifer S.	Newbenefits	Stafford
987654321	20	15.0	Wallace, Jennifer S.	Reorganization	Houston
888665555	20	null	Borg, James E.	Reorganization	Houston

© Addison Wesley Longman, Inc. 2000, Elmasri/Navathe, Fundamentals of Database Systems, Third Edition

Guideline to Redundant Information in Tuples and Update Anomalies

- **GUIDELINE 2:** Design a schema that does not suffer from the insertion, deletion and update anomalies. If there are any present, then note them so that applications can be made to take them into account

1.3 Null Values in Tuples

GUIDELINE 3: Relations should be designed such that their tuples will have as few NULL values as possible

- Attributes that are NULL frequently could be placed in separate relations (with the primary key)
- Reasons for nulls:
 - attribute not applicable or invalid
 - attribute value unknown (may exist)
 - value known to exist, but unavailable

1.4 Spurious Tuples

- Bad designs for a relational database may result in erroneous results for certain JOIN operations
- The "lossless join" property is used to guarantee meaningful results for join operations

GUIDELINE 4: The relations should be designed to satisfy the lossless join condition. No spurious tuples should be generated by doing a natural-join of any relations.

Design relation schemas so that they can be joined with equality conditions on attributes that are either primary keys or foreign keys.

Avoid relations that contain matching attributes that are not (foreign key, primary key) combinations.

FIGURE 10.5
Particularly poor design for the EMP_PROJ relation of Figure 10.3b.

(a) The two relation schemas EMP_LOCS and EMP_PROJ1. (b) The result of projecting the extension of EMP_PROJ from Figure 10.4 onto the relations EMP_LOCS and EMP_PROJ1.




FIGURE 10.5 (continued)

Particularly poor design for the EMP_PROJ relation of Figure 10.3b.
 (a) The two relation schemas EMP_LOCS and EMP_PROJ1. (b) The
 result of projecting the extension of EMP_PROJ from Figure 10.4 onto
 the relations EMP_LOCS and EMP_PROJ1.

EMP_PROJ1

SSN	PNUMBER	HOURS	PNAME	PLOCATION
123456789	1	32.5	Product X	Bellaire
123456789	2	7.5	Product Y	Sugarland
666884444	3	40.0	Product Z	Houston
453453453	1	20.0	Product X	Bellaire
453453453	2	20.0	Product Y	Sugarland
333445555	2	10.0	Product Y	Sugarland
333445555	3	10.0	Product Z	Houston
333445555	10	10.0	Computerization	Stafford
333445555	20	10.0	Reorganization	Houston
999887777	30	30.0	Newbenefits	Stafford
999887777	10	10.0	Computerization	Stafford
987987987	10	35.0	Computerization	Stafford
987987987	30	5.0	Newbenefits	Stafford
987654321	30	20.0	Newbenefits	Stafford
987654321	20	15.0	Reorganization	Houston
888665555	20	null	Reorganization	Houston

Result of applying NATURAL JOIN to the tuples above the
 dotted lines in EMP_PROJ1 and EMP_LOCS

SSN	PNUMBER	HOURS	PNAME	PLOCATION	
123456789	1	32.5	ProductX	Bellaire	Smith,John B.
123456789	1	32.5	ProductX	Bellaire	English,Joyce A.
123456789	2	7.5	ProductY	Sugarland	Smith,John B.
123456789	2	7.5	ProductY	Sugarland	English,Joyce A.
123456789	2	7.5	ProductY	Sugarland	Wong,Franklin T.
666884444	3	40.0	ProductZ	Houston	Narayan,Ramesh K.
666884444	3	40.0	ProductZ	Houston	Wong,Franklin T.
453453453	1	20.0	ProductX	Bellaire	Smith,John B.
453453453	1	20.0	ProductX	Bellaire	English,Joyce A.
453453453	2	20.0	ProductY	Sugarland	Smith,John B.
453453453	2	20.0	ProductY	Sugarland	English,Joyce A.
453453453	2	20.0	ProductY	Sugarland	Wong,Franklin T.
333445555	2	10.0	ProductY	Sugarland	Smith,John B.
333445555	2	10.0	ProductY	Sugarland	English,Joyce A.
333445555	2	10.0	ProductY	Sugarland	Wong,Franklin T.
333445555	3	10.0	ProductZ	Houston	Narayan,Ramesh K.
333445555	3	10.0	ProductZ	Houston	Wong,Franklin T.
333445555	10	10.0	Computerization	Stafford	Wong,Franklin T.
333445555	20	10.0	Reorganization	Houston	Narayan,Ramesh K.
333445555	20	10.0	Reorganization	Houston	Wong,Franklin T.

⋮

Spurious Tuples (2)

There are two important properties of decompositions:

- (a) non-additive or losslessness of the corresponding join
- (b) preservation of the functional dependencies.

Note that property (a) is extremely important and *cannot* be sacrificed. Property (b) is less stringent and may be sacrificed.

Acknowledgement

Reference for this lecture is

- Ramez Elmasri and Shamkant B. Navathe,
Fundamentals of Database Systems, Pearson
Education.

The authors and the publishers are gratefully acknowledged.