AX-TOOLBOX

Flight Analysis Scripting Language

Table of Contents

0 Introduction	5
0.1 Language basics	5
0.1.1 Settings	5
0.1.2 Constructors	5
0.1.3 Comments and blank characters	5
0.2 Notation Conventions	5
0.2.1 Names	5
0.2.2 Distances and altitudes	5
0.2.3 Time definitions	5
0.2.4 Colors	6
1 SET instruction	7
1.1 Definition	7
1.1.1 Key LOGFILE: log file	7
1.1.2 Key ALTITUDECORRECTIONSFILE: logger altitude corrections file	7
1.1.3 Key DATETIME: flight date and time	7
1.1.4 Key DATUM	7
1.1.5 Key UTMZONE	7
1.1.6 Key QNH	7
1.1.7 Key SMOOTHNESS	8
1.1.8 Key MINSPEED	8
1.1.9 Key MAXACCELERATION	8
1.2 Examples	8
2 MAP class	9
2.1 Constructors	9
2.1.1 Type BITMAP: Bitmap file	9
2.1.2 Type BLANK: Blank map	9
2.2 Display modes	9
2.2.1 Mode GRID	9
2.3 Examples	9
3 TASK class	10
3.1 Constructors	10
3.1.1 PDG - Pilot Declared Goal	10
3.1.2 JDG - Judge Declared Goal	10
3.1.3 HWZ - Hesitation Waltz	10
3.1.4 FIN - Fly In	10

3.1.5 FON - Fly On	10
3.1.6 HNH - Hare And Hounds	10
3.1.7 WSD - Watership Down	10
3.1.8 GBM - Gordon Bennett Memorial	10
3.1.9 CRT - Calculated Rate Of Approach	10
3.1.10 RTA - Race To An Area	11
3.1.11 ELB - Elbow	11
3.1.12 LRN - Land Run	11
3.1.13 MDT - Minimum Distance	11
3.1.14 SFL - Shortest Flight	11
3.1.15 MDD - Minimum Distance Double Drop	11
3.1.16 XDT - Maximum Distance Time	11
3.1.17 XDI - Maximum Distance	11
3.1.18 XDD - Maximum Distance Double Drop	11
3.1.19 ANG - Angle	11
3.1.20 3DT - 3D Shape Task	11
3.2 Examples	11
4 AREA class	12
4.1 Constructors	12
4.1.1 Type CIRCLE: Circular area	12
4.1.2 Type DOME: Dome shaped area	12
4.1.3 Type POLY: Polygonal area	12
4.2 Display modes	12
4.2.1 Mode NONE	12
4.2.2 Mode DEFAULT	12
4.3 Examples	13
5 FILTER class	14
5.1 Constructors	14
5.1.1 INSIDE	14
5.1.2 OUTSIDE	14
5.1.3 BEFORETIME	14
5.1.4 AFTERTIME	14
5.1.5 BEFOREPOINT	14
5.1.6 AFTERPOINT	14
5.1.7 ABOVE	
5.1.8 BELOW	15
5.1.9 NONE	
5.2 Examples	
6 POINT class	16
6.1 Static point (S) constructors	16
6.1.1 Type SLL: WGS84 lat/long	16

6.1.2 Type SUTM: UTM	16
6.2 Point from a list (L) constructors	16
6.2.1 Type LNP: nearest to point	16
6.2.2 Type LFT: first in time	16
6.2.3 Type LLT: last in time	17
6.2.4 Type LFNN: first not null	17
6.2.5 Type LLNN: last not null	17
6.3 Logger mark (M) constructors	17
6.3.1 Type MVMD: virtual marker drop	17
6.3.2 Type MPDG: pilot declared goal	17
6.4 Track point (T) constructors	17
6.4.1 Type TLCH: launch	17
6.4.2 Type TLND: landing	17
6.4.3 Type TPT: on point time	18
6.4.4 Type TNP: nearest to point	18
6.4.5 Type TNL: nearest to point list	18
6.4.6 Type TDT: delayed in time	18
6.4.7 Type TDD: delayed in distance	18
6.4.8 Type TAFI: area first in	19
6.4.9 Type TAFO: area first out	19
6.4.10 Type TALI: area last in	19
6.4.11 Type TALO: area last out	19
6.5 Display modes	19
6.5.1 Mode NONE	19
6.5.2 Mode WAYPOINT	19
6.5.3 Mode TARGET	20
6.5.4 Mode MARKER	20
6.5.5 Mode CROSSHAIRS	20
6.6 Examples	20
7 RESULT class	21
7.1 Constructors	21
7.1.1 Type D2D: distance in 2D	
7.1.2 Type D3D: distance in 3D	21
7.1.3 Type DRAD: relative altitude dependent distance	21
7.1.4 Type DACC: accumulated distance	21
7.1.5 Type TSEC: time in seconds	21
7.1.6 Type TMIN: time in minutes	21
7.1.7 Type ATRI: area of triangle	22
7.1.8 Type ANG3P: angle between 3 points	22
7.1.9 Type ANGN: angle to the north	22
7.1.10 Type ANGSD: angle to a set direction	22

7.2 Examples	22
8 RESTRICTION class	23
8.1 Constructors	23
8.1.1 Type DMAX: maximum distance	23
8.1.2 Type DMIN: minimum distance	23
8.1.3 Type DVMAX: maximum vertical distance	23
8.1.4 Type DVMIN: minimum vertical distance	23
8.1.5 Type TMAX: maximum time	23
8.1.6 Type TMIN: minimum time	24
8.1.7 Type TBTOD: before time of day	24
8.1.8 Type TATOD: after time of day	24
8.2 Examples	24
9 PENALTY class	25
9.1 Constructors	25
9.1.1 Type BPZ: blue PZ	25
9.1.2 Type RPZ: red PZ	25
9.1.3 Type VSMAX: maximum vertical speed	25
10 Full task examples	26
10.1 Judge Declared Goal (nearest track point)	26
10.2 Hesitation Waltz (logger marker drop)	26
10.3 Gordon Bennett Memorial (logger marker drop)	26
10.4 Maximum Distance Double Drop (first in / last out)	27
11 Bugs and ideas	28

0 INTRODUCTION

0.1 Language basics

The flight analysis scripting language have two kind of instructions: settings and object constructors. The settings are used to set up some program options and variables and the constructors are used to define the flight tasks.

0.1.1 Settings

The setting instructions have the following syntax:

```
SET <key> = <one or more values>
```

The distinct values are separated by commas.

0.1.2 Constructors

The constructor instructions have the following syntax:

```
<class> <name> = <type>(<zero or more parameters>)
```

The distinct parameters are separated by commas.

0.1.3 Comments and blank characters

Any line whose first non space characters are double slashes '//' will be ignored. All blank lines are also ignored as well as all blank characters (spaces or tabs) before or after any symbol (instruction, name, key, type, value or parameter).

0.2 Notation Conventions

0.2.1 Names

Names can be any sequence of characters. All characters are allowed except commas ','. Names are case sensitive.

0.2.2 Distances and altitudes

Distance and altitude definitions are double precision floating point numbers with dot '.' decimal separator. The known units of measure are meters 'm', kilometers 'km', feet 'ft', miles 'mi' or nautical miles 'nm'.

Examples:

```
500m
1640.42ft
```

0.2.3 Time definitions

Time definitions are in the format 'HH:MM:SS' (hours, minutes and seconds). The seconds part is optional.

Applies to absolute times (time of day) as well to relative times (time span).

Examples:

10:30:00 10:30

0.2.4 Colors

Only the following colors are allowed: blue, brown, gray, green, orange, pink, red, violet, white and yellow.

1 SET INSTRUCTION

```
SET <key> = <value>[, <value>...]
```

Allows to set different options.

1.1 Definition

1.1.1 Key LOGFILE: log file

```
set LOGFILE = <filename>
```

Sets the file where to log all scripting operations

<filename> is the name of the log file

1.1.2 Key ALTITUDECORRECTIONSFILE: logger altitude corrections file

```
set ALTITUDECORRECTIONSFILE = <filename>
```

Sets the file with the logger altitude corrections

<filename> is the name of the file

1.1.3 Key DATETIME: flight date and time

```
set DATETIME = <date>, <time>
```

Sets the flight date and time

<date> is the flight date in format yyyy/mm/dd <time> is either AM or PM

1.1.4 Key DATUM

```
set DATUM = <datumName>
```

Sets the default datum.

<datumName> is the datum name

Supported datums: Corrego Alegre, European 1950, NAD27 CONUS, OSGB36, WGS72, WGS84.

1.1.5 Key UTMZONE

```
set UTMZONE = <zone>
```

Sets the default UTM zone.

<zone> is the UTM zone

1.1.6 Key QNH

```
set QNH = <value>
```

Sets the QNH value

<value> is the qnh value

1.1.7 Key SMOOTHNESS

```
set SMOOTHNESS = <value>
```

Sets the smoothness factor (moving average values) used in automatic launch and landing detection. If undefined, 3 will be assumed.

<value> is the smoothness factor

1.1.8 Key MINSPEED

```
set MINSPEED = <speed>
```

Sets the minimum speed (in m/s) considered as movement in automatic launch and landing detection. If undefined, 0.5 will be assumed.

<speed> is the minimum speed

1.1.9 Key MAXACCELERATION

```
set MAXACCELERATION = <acceleration>
```

Sets the maximum acceleration (in m/s^2) allowed in normal flight. Track points with greater acceleration will be discarded as bogus (spikes). If undefined, 0.3 will be assumed.

<acceleration> is the maximum acceleration

1.2 Examples

```
set DATETIME = 2010/09/19, AM
set DATUM = European 1950
set QNH = 1013
set MINSPEED = 0.3
set MAXDISTTOCROSSING = 300m
```

2 MAP CLASS

```
MAP <mapName> = <mapType>(<map params>)
```

There must be one and only one map file per script. If more than one is defined, only the last is used. The area covered by the map is assumed to be the competition area.

2.1 Constructors

```
<mapType>(<map params>)
```

2.1.1 Type BITMAP: Bitmap file

```
BITMAP(<fileName>)
```

<fileName> is a bitmap file name. Compatible bitmap types are bmp, gif, jpg, png, tif. A corresponding world file must exist. See http://en.wikipedia.org/wiki/World_file for more information.

2.1.2 Type BLANK: Blank map

```
Blank(<topLeft>, <bottomRight>)
```

- <topLeft> is a previously defined point name designing the top-left corner of the map.
-

2.2 Display modes

```
<displayMode>(<display params>)
```

2.2.1 Mode GRID

```
GRID(<width>)
```

<width> is the desired grid spacing between lines.

Draws a grid over the map.

2.3 Examples

```
MAP CompetitionMap = BITMAP(map.png) grid(1000)
MAP OfficialMap = Blank(TopLeftPoint,BottomRightPoint)
```

3 TASK CLASS

```
TASK <taskName> = <taskType>(<number>)
<taskType> is one of the AXMER allowed task type.
<number> is the task number in the competition.
```

3.1 Constructors

```
<taskType>(<number>)
```

3.1.1 PDG - Pilot Declared Goal

PDG(<number>)

3.1.2 JDG - Judge Declared Goal

JDG(<number>)

3.1.3 HWZ - Hesitation Waltz

HWZ(<number>)

3.1.4 FIN - Fly In

FIN(<number>)

3.1.5 FON - Fly On

FON(<number>)

3.1.6 HNH - Hare And Hounds

HNH(<number>)

3.1.7 WSD - Watership Down

WSD(<number>)

3.1.8 GBM - Gordon Bennett Memorial

GBM(<number>)

3.1.9 CRT - Calculated Rate Of Approach

CRT(<number>)

3.1.10 RTA - Race To An Area

RTA(<number>)

3.1.11 ELB - Elbow

ELB(<number>)

3.1.12 LRN - Land Run

LRN(<number>)

3.1.13 MDT - Minimum Distance

MDT (<number>)

3.1.14 SFL - Shortest Flight

SFL(<number>)

3.1.15 MDD - Minimum Distance Double Drop

MDD(<number>)

3.1.16 XDT - Maximum Distance Time

XDT(<number>)

3.1.17 XDI - Maximum Distance

XDI(<number>)

3.1.18 XDD - Maximum Distance Double Drop

XDD(<number>)

3.1.19 ANG - Angle

ANG(<number>)

3.1.20 3DT - 3D Shape Task

3DT(<number>)

3.2 Examples

```
TASK Task3HWZ = HWZ(5)
TASK Task2 = JDG(3)
```

4 AREA CLASS

```
AREA <name> = <areaType>(<area params>) [<displayMode>(<display
params>)]
```

4.1 Constructors

```
<areaType>(<area params>)
```

4.1.1 Type CIRCLE: Circular area

```
CIRCLE(<center>, <radius>[, <lowerLimit>[, <upperLimit>]])
<center> is a point name used as the circle center
<radius> is the circle radius
<lowerLimit> is the lower altitude limit
<upperLimit> is the upper altitude limit
```

4.1.2 Type DOME: Dome shaped area

```
DOME (<center>, <radius>)
<center> is a point name used as the dome base center
<radius> is the dome radius
```

4.1.3 Type POLY: Polygonal area

```
POLY (<fileName>[, <lowerLimit>[, <upperLimit>]])

<fileName> is the name of a track file containing the polygon (trk, igc)
<lowerLimit> is the lower altitude limit
<upperLimit> is the upper altitude limit
```

4.2 Display modes

```
<displayMode>(<display params>)
```

The display mode is optional. If it is not specified, DEFAULT(blue) is used.

4.2.1 Mode NONE

```
NONE ()
```

The area will not be displayed.

4.2.2 Mode DEFAULT

```
DEFAULT([<color>])
```

Draws the area according to its type.

<color> is one of blue, brown, gray, green, orange, pink, red, violet, white, yellow. If no color is specified, blue will be used.

4.3 Examples

```
area Area1 = CIRCLE(P10, 100m) DEFAULT(green)
area Area2 = POLY(area2.trk, 100m, 1000m)
area Area3 = CIRCLE(P10, 500) NONE()
```

5 FILTER CLASS

Filter track points for the current task. Points filtered out are not considered in further computations. Successive filters in the same task are applied in definition order.

```
FILTER <name> = <filterType>(<filter params>)
```

5.1 Constructors

5.1.1 INSIDE

```
INSIDE(<areaName>)
```

Selects all the track points inside the specified area.

<areaName> is the name of a previously defined area

5.1.2 OUTSIDE

```
OUTSIDE(<areaName>)
```

Selects all the track points outside the specified area.

<areaName> is the name of a previously defined area

5.1.3 BEFORETIME

```
BEFORETIME(<time>)
```

Selects all the track points earlier than specified time.

<time> desired time in hh:mm:ss

5.1.4 AFTERTIME

```
AFTERTIME (<time>)
```

Selects all the track points later than specified time.

<time> desired time in hh:mm:ss

5.1.5 BEFOREPOINT

```
BEFOREPOINT(<pointName>)
```

Selects all the track points earlier than specified point.

<pointName> is the name of a previously defined point

5.1.6 AFTERPOINT

```
AFTERPOINT(<pointName>)
```

Selects all the track points later than specified point.

<pointName> is the name of a previously defined point

5.1.7 **ABOVE**

```
ABOVE (<altitude>)
```

Selects all the track points above a given altitude

<altitude> is the desired altitude limit in feet

5.1.8 **BELOW**

```
BELOW(<altitude>)
```

Selects all the track points below a given altitude

<altitude> is the desired altitude limit in feet

5.1.9 NONE

NONE()

Clears all the active filters for the current task. Previous computations are not affected.

5.2 Examples

```
FILTER InArea = INSIDE(GBMArea)
FILTER Before10:00 = BEFORETIME(10:00:00)
```

6 POINT CLASS

```
POINT <name> = <pointType>(<point params>) [<displayMode>(<display
params>)]
```

6.1 Static point (S) constructors

The S constructors return a statically defined point.

6.1.1 Type SLL: WGS84 lat/long

```
SLL(<lat>, <long>, <altitude>)
```

Returns a statically defined point using WGS lat/lon coordinates.

```
<lat> is the latitude coordinate
```

long> is the longitude coordinate

<altitude> is the altitude (in feet)

6.1.2 Type SUTM: UTM

```
SUTM(<easting>, <northing>, <altitude>)
```

Returns a statically defined point using UTM coordinates in the default datum and zone.

```
<easting> is the easting coordinate
```

<northing> is the northing coordinate

<altitude> is the altitude (in feet)

6.2 Point from a list (L) constructors

The L constructors return a point chosen form a list of predefined points.

6.2.1 Type LNP: nearest to point

```
LNP(<desiredPoint>, <listPoint1>, <listPoint2>, ...,
<altitudeThreshold>)
```

Returns the point closest to a desired one from a list of predefined points. It uses altitude dependent distance measurement (see DRAD result class).

<altitude Threshold>: distance 2D measurement is used below this altitude difference. 3D otherwise.

6.2.2 Type LFT: first in time

```
LFT(<listPoint1>, <listPoint2>, ...)
```

Returns the earliest point from a list of points.

6.2.3 Type LLT: last in time

```
LLT(<listPoint1>, <listPoint2>, ...)
```

Returns the latest point from a list of points.

6.2.4 Type LFNN: first not null

```
LFNN(<listPoint1>, <listPoint2>, ...)
```

Returns the first non null point from a list of points.

6.2.5 Type LLNN: last not null

```
LLNN(<listPoint1>, <listPoint2>, ...)
```

Returns the last non null point from a list of points.

6.3 Logger mark (M) constructors

The M constructors return a point defined with a logger mark.

6.3.1 Type MVMD: virtual marker drop

```
MVMD(<number>)
```

Returns the first occurrence of the desired virtual marker drop. The filters applied to track points are enforced because virtual marker drops must coincide with a valid track point.

<number> desired marker number

6.3.2 Type MPDG: pilot declared goal

```
MPDG(<number>)
```

Returns the last occurrence of the desired pilot declared goal within time limits.

<number> desired pilot declared goal number

6.4 Track point (T) constructors

The T constructors return a point from the track log.

6.4.1 Type TLCH: launch

```
TLCH()
```

Returns the launch point.

6.4.2 Type TLND: landing

TLND()

Returns the landing point.

6.4.3 Type TPT: on point time

```
TPT(<pointName>)
```

Returns the track point with the same timestamp as a given point.

<pointName> is the name of a previously defined point

6.4.4 Type TNP: nearest to point

```
TNP(<pointName>, <altitudeThreshold>)
```

Returns the closest valid track point to the specified point.

<pointName> is the name of a previously defined point
<a href="

6.4.5 Type TNL: nearest to point list

```
TNL(<listPoint1>, <listPoint2>, ..., <altitudeThreshold>)
```

Returns the closest valid track point to any the specified points.

6.4.6 Type TDT: delayed in time

```
TDT(<pointName>, <timeDelay>[, <maxTime>])
```

If <maxTime> is not specified, returns the first valid track point after <timeDelay> minutes have elapsed over the desired point time.

If <maxTime> is specified, returns the last valid track point after <timeDelay> minutes have elapsed over the desired point time but before <maxTime>.

```
<pointName> is the name of another previously defined point
<timeDelay> desired time delay in minutes
<maxTime> desired time limit. This parameter is optional
```

6.4.7 Type TDD: delayed in distance

```
TDD(<pointName>, <distanceDelay>[, <maxTime>])
```

If <maxTime> is not specified, returns the first valid track point farther than <distanceDelay> from the desired point.

If <maxTime> is specified, returns the last valid track point before <maxTime> farther than <distanceDelay> from the desired point.

<pointName> is the name of another previously defined point

<distanceDelay> desired distance delay in meters

<maxTime> desired time limit. This parameter is optional

6.4.8 Type TAFI: area first in

```
TAFI(<areaName>)
```

Returns the first valid track point after entering the area for the first time.

<areaName> is the name of a previously defined area

6.4.9 Type TAFO: area first out

```
TAFO(<areaName>)
```

Returns the last valid track point before exiting the area for the first time.

<areaName> is the name of a previously defined area

6.4.10 Type TALI: area last in

```
TALI (<areaName>)
```

Returns the first valid track point after entering the area for the last time.

<areaName> is the name of a previously defined area

6.4.11 Type TALO: area last out

```
TALO(<areaName>)
```

Returns the last valid track point before exiting the area for the last time.

<areaName> is the name of a previously defined area

6.5 Display modes

```
<displayMode>(<display params>)
```

The display mode is optional. If it is not specified, WAYPOINT(blue) is used.

6.5.1 Mode NONE

```
NONE ()
```

The point will not be displayed.

6.5.2 Mode WAYPOINT

```
WAYPOINT([<color>])
```

Displays a waypoint map overlay.

<color> is one of blue, brown, gray, green, orange, pink, red, violet, white, yellow. If no color is specified, blue will be used.

6.5.3 Mode TARGET

```
TARGET(<radius>[, <color>])
```

Displays a target map overlay with a circular area of given radius.

<radius> circular area radius in meters.

<color> is one of blue, brown, gray, green, orange, pink, red, violet, white, yellow. If no color is specified, blue will be used.

6.5.4 Mode MARKER

```
MARKER([<color>])
```

Displays a flag map overlay.

<color> is one of blue, brown, gray, green, orange, pink, red, violet, white, yellow. If no color is specified, blue will be used.

6.5.5 Mode CROSSHAIRS

```
CROSSSHAIRS([<color>])
```

Displays a crosshairs map overlay.

<color> is one of blue, brown, gray, green, orange, pink, red, violet, white, yellow. If no color is specified, blue will be used.

6.6 Examples

```
point LAUNCH = TLCH() WAYPOINT(green)
point LANDING = TLND() WAYPOINT(red)
point G12 = SLL(42.12, 3.23, 1500) TARGET(100, green)
point G13 = SUTM(31T, 235123, 4612153, 850) TARGET(100, green)
point Best = TNL(G12, G13) MARKER(green)
```

7 RESULT CLASS

```
RESULT <resultName> = <resultType>(<result params>)
```

Computes a task result. The results are assigned to the last defined task.

7.1 Constructors

```
<resultType>(<result params>)
```

7.1.1 Type D2D: distance in 2D

```
D2D(<pointNameA>, <pointNameB>)
```

Computes the projected distance (in 2D) between two points.

7.1.2 Type D3D: distance in 3D

```
D3D(<pointNameA>, <pointNameB>)
```

Computes the distance in 3D between two points.

7.1.3 Type DRAD: relative altitude dependent distance

```
DRAD(<pointNameA>, <pointNameB>)
```

Computes the distance between two points. If the altitude difference between the two is less than the threshold specified in the settings part, 2D distance will be computed. Otherwise, 3D distance is used.

7.1.4 Type DACC: accumulated distance

```
DACC(<pointNameA>, <pointNameB>)
```

Computes the sum of the distances between consecutive valid track points from point 1 to point 2. In other words, It computes the total traveled distance between the two points.

7.1.5 Type TSEC: time in seconds

```
TSEC(<pointNameA>, <pointNameB>)
```

Computes the time elapsed in seconds between the two points.

7.1.6 Type TMIN: time in minutes

```
TMIN(<pointNameA>, <pointNameB>)
```

Computes the time elapsed in minutes between the two points.

7.1.7 Type ATRI: area of triangle

```
ATRI(<pointNameA>, <pointNameB>, <pointNameC>)
```

Computes the area in km² of the triangle delimited by the three points.

7.1.8 Type ANG3P: angle between 3 points

```
ANG3P(<pointNameA>, <pointNameB>, <pointNameC>)
```

Computes the direction change between AB and BC (180 - the angle ABC).

7.1.9 Type ANGN: angle to the north

```
ANGN(<pointNameA>, <pointNameB>)
```

Computes the angle between the line AB and the line north-south.

7.1.10 Type ANGSD: angle to a set direction

```
ANGSD(<pointNameA>, <pointNameB>, <setDirection>)
```

Computes the angle between the line AB and a set direction. 0 is north-south.

7.2 Examples

RESULT Task3Result=DRAD(Task3Marker,Task3Target,500)

8 RESTRICTION CLASS

```
RESTRICTION <restrictionName> = <restrictionType>(<restriction
params>)
```

Computes a restriction. If a restriction is infringed, the pilot will not achieve a result for the task (group B).

8.1 Constructors

```
<restrictionType>(<restriction params>)
```

8.1.1 Type DMAX: maximum distance

```
DMAX(<pointNameA>, <pointNameB>, <distance>, <description>)
```

The 2D distance between point A and point B must not be greater than the specified distance.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.2 Type DMIN: minimum distance

```
DMIN(<pointNameA>, <pointNameB>, <distance>, <description>)
```

The 2D distance between point A and point B must not be lesser than the specified distance.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.3 Type DVMAX: maximum vertical distance

```
DVMAX(<pointNameA>, <pointNameB>, <height>, <description>)
```

The vertical distance between point A and point B must be greater than the specified height.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.4 Type DVMIN: minimum vertical distance

```
DVMIN(<pointNameA>, <pointNameB>, <height>, <description>)
```

The vertical distance between point A and point B must be lesser than the specified height.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.5 Type TMAX: maximum time

```
PBP(<pointNameA>, <pointNameB>, <time>, <description>)
```

The point B must not happen more than the the specified time in minutes later than point A.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.6 Type TMIN: minimum time

```
TMIN(<pointNameA>, <pointNameB>, <time>, <description>)
```

The point B must happen more than the the specified time in minutes later than point A.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.7 Type TBTOD: before time of day

```
TBTOD(<pointNameA>, <time>, <description>)
```

The point A must happen before the specified time of day.

<description> is the description of the infringement (rule number will be included automatically when known).

8.1.8 Type TATOD: after time of day

```
TATOD(<pointNameA>, <time>, <description>)
```

The point A must happen after the specified time of day.

<description> is the description of the infringement (rule number will be included automatically when known).

8.2 Examples

```
RESTRICTION t2_dmin = DMIN(launch, task02_target, 1000m, "launch too
close to target")
RESTRICTION t3_declTime = TATOD(declaration_point, 10:00:00, "late
declaration")
```

9 PENALTY CLASS

```
PENALTY <penaltyName> = <penaltyType>(<penalty params>)
```

Computes a penalty. The penalty is applied to the last defined task.

9.1 Constructors

```
<penaltyType>(< penalty params>)
```

9.1.1 Type BPZ: blue PZ

```
BPZ(<area>)
```

Applies a BPZ penalty to all the remaining (non-filtered) track points inside the area.

//TODO: explain better

9.1.2 Type RPZ: red PZ

```
RPZ(<area>)
```

Applies a RPZ penalty to all the remaining (non-filtered) track points inside the area. Actually, the new 2011 formula is used with hypotenuse distance infringement and a scale factor of 8.

//TODO: explain better

9.1.3 Type VSMAX: maximum vertical speed

```
VSMAX(<verticalSpeed>)
```

Applies a result penalty if the vertical speed is over the given speed

//TODO: check the value of the applied penalty

10 FULL TASK EXAMPLES

10.1 Judge Declared Goal (nearest track point)

```
TASK Task02JDG = JDG(2)

POINT Task02target=UTM(31T,325000,4612000,650)

FILTER Task02scoringPeriod1=AFTER(09:00:00)

FILTER Task02scoringPeriod2=BEFORE(10:00:00)

POINT Task02marker=TNP(Task02target)

RESULT Task02result=DRAD(Task02target,Task02marker,500)
```

The first line defines the task type, JDG. The second line defines the target. The next two lines define the scoring period from 9:00 to 10:00. The fifth line defines the nearest track point to the target. The last line computes the result, a relative altitude dependent distance with an altitude limit of 500ft.

10.2 Hesitation Waltz (logger marker drop)

```
TASK Task03HWZ=HWZ(3)

POINT Task03t1=UTM(31T,325000,4612000,650)

POINT Task03t2=UTM(31T,325500,4612000,650)

POINT Task03t3=UTM(31T,325000,4612500,650)

POINT Task03marker=MVMD(3)

POINT Target=LNP(Task03marker,Task03t1,Task03t2,Task03t3)

RESULT Result=D3D(Marker,Target)
```

The first line defines the task type, HWZ. The next three lines define the targets. The fifth line defines the logger marker drop #3. The sixth line defines the closest target to the marker. The last line computes the result, a distance in 3D.

10.3 Gordon Bennett Memorial (logger marker drop)

```
TASK Task1=GBM(1)

AREA Tlarea=Area(tasklarea.trk)

POINT Tlgoal=SUTM(31T,3166732,4613455,350)

FILTER TlscoringPeriod=BEFORE(10:00:00)

POINT Tlmarker=MVMD(1)

RESULT=DRAD(TlGoal,Tlmarker,500)
```

The first line defines a GBM task. The second line defines the scoring area from a track file. The third line defines the goal, a fixed UTM point. The next line defines a scoring period until 10:00. The next defines the logger marker #1 (note that the scoring period filter also applies to VMDs). The last line computes a relative altitude dependent distance with a threshold of 500ft.

10.4 Maximum Distance Double Drop (first in / last out)

```
TASK Task4=XDD(4)

AREA T4area=Area(task4area.trk)

FILTER T4scoringPeriod=BEFORE(10:00:00)

POINT T4A=TAFI(T4area)

POINT T4B=TALO(T4area)

RESULT t4result=D2D(T4A,T4B)
```

The first line defines the task type, XDD. The second line defines the task area from a track file. The third line applies a filter: the valid track points are those before 10:00:00 (task scoring period up to 10:00). The next line defines the first scoring point, the first-in point. The next defines the second scoring point, the last-out point. The last line computes the result, a distance in 2D.

11 BUGS AND IDEAS

The point constructors LNP, TNP and TNL do not specify what kind of distance should be used (d2d, d3d or drad). Consider constructors that specify the distance method.

Example: LNPD2D, LNPD3D, LNPDRAD, TNPD2D, TNPD3D, TNPDRAD, etc.

Think about a method to score a 3DS task allowing entering and exiting the area multiple times.