

eBay Product API - Technical Documentation

FastAPI backend with SQLite session login and optional eBay Sandbox/Production integration

Purpose: This API lets a user register, log in, create products, view products, search products, and delete products. Each product is linked to the logged-in user, so users can only manage their own products. If eBay credentials are configured, product creation also attempts to create an eBay inventory item and offer.

Base URL: <http://127.0.0.1:8000> | **API Docs:** <http://127.0.0.1:8000/docs>

Authentication: After `/register` or `/login`, copy the `access_token` and send it in every protected request using: `Authorization: Bearer <access_token>`. If the word `Bearer` is missing, the API returns `Invalid Authorization format`.

Account Endpoints

POST /register

- Creates a new user account and immediately returns a login token. Body: `{"username":"X","password":"X"}`.
- Success returns message, username, `access_token`, and `token_type`. If the username already exists, it returns 409 Username already exists.
- This endpoint does not include Athena verification with Ebay Dev Program as for this it need to connect with AWS to validate the authentication and its not being implemented here.

POST /login

- Authenticates an existing user and returns a new session token.
- Body: `{"username":"X","password":"X"}`. If credentials are wrong, it returns 401 Invalid username or password.

POST /logout

- Logs out the current user by deactivating the session token.
- Requires Authorization header. No body is required. After logout, the same token cannot be used again.

Product Endpoints

POST /products

- Creates or replaces a product for the logged-in user. Requires Authorization header. Body includes `sku`, `category_id`, `title`, `description`, `price`, `quantity`, and `tags`. The product is saved locally in SQLite.
- If eBay credentials exist, the API also calls eBay Inventory and Offer APIs.
- If eBay credentials are missing, local creation still succeeds and eBay status is returned as skipped.

GET /products

- Returns all products owned by the logged-in user. Optional filters: `category_id`, `tag`, and `search`. Example: `/products?category_id=9355` or `/products?tag=electronics` or `/products?search=mouse`.

GET /products/{sku}

- Returns one product by SKU for the logged-in user. Example: `/products/SKU001`. If the product does not exist or belongs to another user, it returns 404 Product not found.

Delete Endpoints

DELETE /products/all

- Deletes all products owned by the logged-in user. Requires Authorization header. No body is required in Postman. Returns `deleted_count` and `deleted_skus`.

DELETE /products/{sku}

- Deletes one product by SKU. Example: `/products/SKU001`. Requires Authorization header. No body is required.

DELETE /products/category/{category_id}

- Deletes all products under one category for the logged-in user. Example: `/products/category/9355`.

DELETE /products/tag/{tag}

- Deletes all products matching a tag for the logged-in user. Example: `/products/tag/electronics`.

Debug Endpoint

GET /debug/users - Shows registered users and active status. This is useful during testing, but it should be removed or protected before production.

NOTE :-

- All this access point has been tested with Postman application.
- The endpoint is connected from one to another with bearer authentication - variable can be set in postman to automatically connect one end point with another as receive positive response from the login credentials endpoint .
- This endpoint were created with limited based on given assumption that the endpoint being applied to developer to perform following :-
 - Create product listing with ebay
 - View all or individual product that has been listed with ebay market place
 - Additional endpoint
 - Create registration, validation of login with hash password encryption algorithm