University College Dublin MSc. Data and Computational Science

High Performance Comp.(ICHEC)

ACM40640

Assignment – 2

Name: Prashanth Guntal Student id: 18200537

Question 1: Communication in a Ring

Here the program sends a message to its right neighbour and message terminates once it reached its originator rank. Message contains the sum of all the ranks.

Here are the commands to execute the code:

Using non-blocking communications:

Here I'm using MPI Issend to send and MPI Recv to receive message.

```
[[18200537@login Assignment]$ mpicc -o Question1.x Question1.c
[[18200537@login Assignment]$ mpirun -n 5 ./Question1.x
Process id: 0    Sum : 10
Process id: 1    Sum : 10
Process id: 2    Sum : 10
Process id: 3    Sum : 10
Process id: 4    Sum : 10
[18200537@login Assignment]$
```

Using MPI Ireduce calls:

Here I'm using MPI Ireduce to send message instead of MPI Issend.

Question 2: Determinant of 5x5 matrix

Here we are calculating the determinant of 5x5 matrix using Cramer's rules and printing the result on rank 0.

Steps:

- 1. Find the five (based on rank value) 4x4 submatrices of original 5x5 matrix i.e. from the original 5x5 matrix remove the respective column based on rank value and row number 0.
- 2. For each 4x4 submatrix determine four 3x3 matrices.
- 3. Find the determinant of each of the 3x3 matrices and multiple this return value with respective value and sign in 4x4 and similarly multiple this return value to with respective value in 5x5 and sign to obtain determinant based on rank.
- 4. Sum all these 5 determinants to obtain the final determinant of 5x5 matrix.

Command to execute:

```
[[18200537@login Assignment]$ mpicc -o Question2_1.x Question2_1.c [[18200537@login Assignment]$ mpirun -n 5 ./Question2_1.x D: -0.003612 Proc:1

D: -0.004155 Proc:2

D: -0.004090 Proc:3

D: -0.003867 Proc:4

D: -0.014407 Proc:0

Determinant of the matrix is : -0.0301308081031796

Actual Result: -0.0301308054048339 [18200537@login Assignment]$ |
```

Question 3:

Deadlock and removal of bugs:

Deadlock since MPI_Bcast involve all the processes grouped in a communicator and must be called by all the processes in the communicator here we need to remove the MPI_Bcast command outside the if condition (which tell to execute MPI_Bcast only if rank==0).

Bugs:

Since processor 0 reads from a file 25 random integers and processor 0 broadcasts these integers to all the other processors we need to change the value 1 to 0 and change MPI Double to MPI INT because we are broadcasting only integer values.

After modification code is taking less than 30 seconds to execute.

Given

```
ierr = MPI_Bcast( indata, 25, MPI_Double, 1, MPI_COMM_WORLD);
```

Modified:

ierr = MPI_Bcast(indata, 25, MPI_INT, 0, MPI_COMM_WORLD);

```
[[18200537@login Assignment]$ mpicc -o Question3.x Question3.c [[18200537@login Assignment]$ mpirun ./Question3.x Completed Successfully with 0.223397 seconds Completed Successfully with 0.341342 seconds Completed Successfully with 0.339127 seconds Completed Successfully with 0.339191 seconds Completed Successfully with 0.399902 seconds Completed Successfully with 0.188332 seconds Completed Successfully with 0.189334 seconds Completed Successfully with 0.1458332 seconds Completed Successfully with 0.425963 seconds Completed Successfully with 0.425963 seconds Completed Successfully with 0.388509 seconds Completed Successfully with 0.388509 seconds Completed Successfully with 0.257375 seconds Completed Successfully with 0.257375 seconds Completed Successfully with 0.373402 seconds Completed Successfully with 0.373402 seconds Completed Successfully with 0.278363 seconds Completed Successfully with 0.29381 seconds Completed Successfully with 0.248457 seconds Completed Successfully with 0.214402 seconds Completed Successfully with 0.214402 seconds Completed Successfully with 0.218457 secon
```