

Mini Paper — 2.1 Elements of Computational Thinking — ANSWER SHEET

Separate answer sheet / mark scheme — keep for marking.

Mark scheme

Total: 25 marks

Q1 [3] - (a) Abstraction = removing/hiding unnecessary detail so only information relevant to the problem remains. **[1]** - (b) One detail removed with reason (1): e.g. the colour/material of the walls, lighting, CCTV layout — irrelevant to tracking spaces or charging. **[1]** - One detail kept with reason (1): e.g. the number of bays / which bays are occupied / the tariff — essential to calculating availability and charges. **[1]** - *Examiner tip:* the marks are for the *justification* ("because it is/ isn't relevant to this problem"), not just naming a detail.

Q2 [4] - (a) Two inputs (1 each, max 2): barrier entry/exit sensor counts, a bay sensor signal, the driver's chosen car park / location, reservation request. **[2]** - (b) Precondition (1): e.g. at least one free bay must exist / the driver must be logged in / the chosen car park must be open — must be a condition true *before* reserving. Reason (1): so the reservation cannot be made against a full/closed car park (avoids invalid bookings). **[2]** - *Examiner tip:* an input is data *in* (a sensor reading), not a process like "count the cars" — don't confuse the two.

Q3 [4] - Caching explained (up to 2): store the computed "spaces free" figure in fast memory on the server (1); serve repeated app requests from the cache instead of recounting/querying sensors each time → faster response and less load on the database/sensors (1). **[2]** - Trade-off evaluated (up to 2): the cached count can become **stale** because cars enter/leave continuously (1), so a driver may see a space that is already taken; it must be refreshed/invalidated frequently (e.g. every few seconds), and caching uses extra memory — a judgement that a short refresh interval balances speed against accuracy (1). **[2]** - *Examiner tip:* "evaluate" needs both the benefit *and* a weighed downside (stale data) with a conclusion — a one-sided answer caps at 2.

Q4 [4] - (a) Four ordered sub-procedures (3): award up to 3 for a sensible decomposition in correct order, e.g. `readTicket()` → `calculateCharge()` → `takePayment()` → `openExitBarrier()` (also accept `printReceipt()`, `updateSpaceCount()`). Full 3 needs four named, correctly-ordered steps; 2 for minor order/naming slips. **[3]** - (b) Order justification (1): a data dependency — e.g. you cannot `takePayment()` before `calculateCharge()` because the amount isn't known, or cannot `openExitBarrier()` before payment is confirmed. **[1]** - *Examiner tip:* name *scenario-relevant* sub-procedures and show one step depends on the output of an earlier one.

Q5 [4] - Two decision points, each with a specific Boolean condition + both outcomes (2 marks each, max 4). Examples: - *Is payment sufficient?* `IF amountPaid >= chargeDue` → open barrier / give change; `ELSE` → request more money / reject. **[2]** - *Is the ticket valid?* `IF ticketExists AND NOT alreadyPaid` → process exit; `ELSE` → show error / call attendant. **[2]** - (Also accept: *grace period* `IF timeInCarPark <= freeMinutes` → charge £0 else charge tariff.) - *Examiner tip:* state the actual Boolean test (use `>=`, `AND`) and what happens on **both** the true and false branch — vague "if enough money" loses marks.

Q6 [6] Indicative content — credit a reasoned, applied discussion: - Tasks (a), (c) and (d) are independent (no task needs another's output) → candidates for concurrent execution; (b) "fetch availability for each car park" depends on (a) having returned the list, so it must follow (a) but the individual fetches can then run concurrently with each other (1–2). - Benefit: the home screen loads/appears far faster and stays responsive because fetches and rendering happen in parallel rather than one-after-another; better use of multi-core hardware and the network (1–2). - Trade-offs: harder to design/program/debug; results must be combined when all arrive; contention for limited mobile network bandwidth means speed-up is not linear; on a single core tasks are only time-sliced, not truly parallel; risk of a race condition if shared data is updated (1–2). - Justified judgement: concurrency is worthwhile here because most tasks are independent and I/O-bound, but the developer must respect the (a) → (b) dependency and manage synchronisation (1). - Bands: 5–6 = sustained, balanced discussion applied to the app with a justified conclusion (incl. the dependency); 3–4 = some application + some trade-offs; 1–2 = generic points with little scenario link. - *Examiner tip*: always check for a data dependency before claiming tasks are concurrent — spotting that (b) must wait for (a) is what separates the top band.