

Worksheet — 2.2 Problem Solving & Programming

OCR A Level Computer Science (H446) — Component 02, Section 2.2 (2.2.1 Programming techniques · 2.2.2 Computational methods). All code = OCR Exam Reference Language.

Name: _____ Date: _____

Time: ~60 min. Check against the answer key at the end.

Section A — Skills practice

1. Key-term match

Write the letter of the correct definition next to each term.

Term	Answer		Definition
1. Recursion	_____	A	A subroutine that performs a task and returns a single value.
2. Base case	_____	B	The region of a program where a variable can be accessed.
3. Scope	_____	C	A subroutine that calls itself, with a stopping condition and a recursive case.
4. Function	_____	D	Passing a copy of an argument so the original is unaffected.
5. Procedure	_____	E	The condition that stops recursion — no further recursive call is made.
6. By value	_____	F	Passing the memory address, so the original can be changed.
7. By reference	_____	G	A stack of frames holding parameters, locals and return addresses for active calls.
8. Call stack	_____	H	A subroutine that performs a task but returns no value.

2. Predict the output — variable SCOPE (local vs global)

Study the code, then answer below. Remember: a **local** variable declared inside a subroutine is separate from a **global** of the same name and **shadows** it inside that subroutine.

```

global score = 10

procedure addPoints()
    score = 99          // refers to the GLOBAL score
endprocedure

procedure tryLocal()
    score = 5           // LOCAL score, declared inside here
    print(score)
endprocedure

print(score)
tryLocal()
addPoints()
print(score)

```

- What is printed by the **first** `print(score)` ? _____
- What is printed **inside** `tryLocal()` ? _____
- What is printed by the **last** `print(score)` ? _____
- Explain, in one sentence, why the assignment inside `tryLocal()` does **not** change what the final `print` shows.

3. Predict the output — pass BY VALUE vs BY REFERENCE

The same subroutine is called twice. Recall: **by value** passes a **copy** (original unchanged); **by reference** passes the **address** (original can be changed).

```

procedure increase(byVal n)
    n = n + 100
endprocedure

procedure boost(byRef n)
    n = n + 100
endprocedure

a = 1
increase(a)
print(a)

b = 1
boost(b)
print(b)

```

a) What is printed for `a` ? _____

b) What is printed for `b` ? _____

c) State the **consequence** (the marks-worthy point) that explains the difference — not just "a copy is made".

4. Recursion TRACE — complete the call stack

Here is a recursive factorial function:

```
function factorial(n)
  if n == 0 then
    return 1
  else
    return n * factorial(n - 1)
  endif
endfunction

print(factorial(4))
```

(a) Complete the table of stack frames as they are **pushed** (calls going down), and the **returned value** as each frame is **popped** (LIFO, going back up). One row is done for you.

Call (frame pushed)	Base case reached?	Expression returned	Value returned (on pop)
factorial(4)	No	4 * factorial(3)	_____
factorial(3)	No	3 * factorial(2)	_____
factorial(2)	No	_____	_____
factorial(1)	No	_____	_____
factorial(0)	Yes	return 1	1

(b) Final value printed by `print(factorial(4))` : _____

(c) What error occurs, and why, if the base case `if n == 0` were removed?

5. Write/complete a class in OCR pseudocode (with inheritance)

Complete the two classes below. `Vehicle` should store **make** and **numWheels** as **private** attributes set by a constructor, plus a method `describe()` that prints them. `Car` should **inherit** from `Vehicle`, add a private attribute **doors**, and **override** `describe()` to also print the number of doors.

```

class Vehicle
  private make
  private numWheels

  public procedure new(m, w)
    _____ = m
    _____ = w
  endprocedure

  public procedure describe()
    print("Make: " + make + ", wheels: " + numWheels)
  endprocedure
endclass

class Car _____ Vehicle    // keyword for inheritance
  private doors

  public procedure new(m, w, d)
    super.new(_____, _____)  // call the parent constructor
    doors = _____
  endprocedure

  public procedure describe()
    // override: reuse parent then add doors
    _____
    print("Doors: " + doors)
  endprocedure
endclass

myCar = new Car("Ford", 4, 5)
myCar.describe()

```

a) Fill in every blank above.

b) Name the OOP principle shown by keeping `make / numWheels` **private** and only changing them through methods. _____

c) Name the OOP principle shown when `Car's describe()` replaces the inherited one.

6. Match the computational method to its use

Methods: **Backtracking** · **Data mining** · **Heuristics** · **Performance modelling** · **Pipelining** · **Visualisation**

Write the best-fit method next to each use.

a) Splitting CPU instruction handling into fetch–decode–execute **stages** so different instructions are processed at once. → _____


```

function sumDigits(n)
  if n < 10 then
    return n
  else
    return (n MOD 10) + sumDigits(n DIV 10)
  endif
endfunction

print(sumDigits(4726))

```

(a) Complete the call-stack table. Frames are **pushed** going down the table; values are **returned** as each frame is **popped**, in LIFO order.

Call (frame pushed)	Base case reached?	Expression returned	Value returned (on pop)
sumDigits(4726)	No	6 + sumDigits(472)	_____
sumDigits(_____)	No	_____ + sumDigits(_____)	_____
sumDigits(_____)	No	_____ + sumDigits(_____)	_____
sumDigits(_____)	Yes	return _____	_____

(b) Final value printed by `print(sumDigits(4726))` : _____

(c) What is the **maximum number of `sumDigits` frames** on the call stack at the same time?

(d) Which call **finishes (returns) first**, and why does the LIFO behaviour of the stack make this so?

9. Find and fix the error — debugging OCR pseudocode

The function below is **intended** to return the largest value in the array `arr` (which always contains at least one number, and may contain negative numbers). It contains **three errors**: one **syntax** error and two **logic** errors.

```

01 function findMax(arr:array)
02     max = 0
03     for i = 0 to arr.length
04         if arr[i] > max then
05             max = arr[i]
06     next i
07     return max
08 endfunction

```

(a) Complete the table — identify each error, classify it, and give the fix.

Line	Syntax or logic?	What is wrong	Corrected line / fix
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

(b) Write out the fully corrected function.

```
function findMax(arr:array)
```

```
endfunction
```

(c) Give suitable **test data** that would reveal the error on line 02 even after the other two errors were fixed, and state the expected vs actual result.

(d) Which of the three errors would be reported by the translator **before the program runs**, and why are the others only found by **testing**?

Section B — Exam practice (30 marks)

Answer all questions. Questions marked with an asterisk (*) assess the quality of your extended response. All code must be written in OCR Exam Reference Language.

Q1. Describe the difference between a **local variable** and a **global variable**. [2] (AO1)

Q2. A subroutine `updateScores(list)` is passed a very large array.

(i) Explain why passing the array **by reference** is more efficient than passing it **by value**. **[2]** (AO2)

(ii) State **one** risk of passing the array by reference. **[1]** (AO2)

Q3. The following function is written in OCR Exam Reference Language.

```
function mystery(a, b)
    r = 0
    while b > 0
        if b MOD 2 == 1 then
            r = r + a
        endif
        a = a * 2
        b = b DIV 2
    endwhile
    return r
endfunction

print(mystery(5, 6))
```

(i) Complete the trace table for the call `mystery(5, 6)`. Record the values of `a`, `b` and `r` at the **end of each iteration** of the while loop. The starting values are given. **[3]** (AO2)

a	b	r	Output
5	6	0	

(ii) State the purpose of the function `mystery` . **[1]** (AO2)

Q4. A program compiles and runs but produces the wrong output. Identify **two** features of an IDE that would help the programmer locate the logic error at run time. **[2]** (AO1)

Q5. An array `scores` holds an unknown number of integers (zero-indexed; `scores.length` gives the number of elements). Write a function `countMatches(scores, target)` using **OCR Exam Reference Language** that returns the number of elements in `scores` equal to `target` . Your function must work for an array of **any** length. **[5]** (AO3)

Q6. A game contains characters of type **Wizard** and **Warrior**. Both types have a `name` and `health` attribute and a `move()` method; Wizards additionally have a `castSpell()` method. Explain how **inheritance** could be used when implementing these characters. **[3]** (AO2)

Q7. A route-planning app must find a route across a road network with millions of junctions. Explain why the app uses a **heuristic** approach rather than examining every possible route. **[2]** (AO1)

Discuss how the developer could use **object-oriented programming** to implement this system. You should refer to **classes, inheritance, encapsulation and polymorphism** in your answer. [9] (AO3)