

MACCOR

SERIES 6500

High-Performance Regenerative
Battery Test System




Fast Dynamic Response

< 1 ms response for dynamic testing




Regenerative Energy Recovery

Up to 90% energy recovery efficiency




200A/400A

CHARGE / DISCHARGE
PER CHANNEL



3 RANGES

200 A / 20 A / 2 A
400 A / 40 A / 4 A



< 2.5ms


SWITCH TIME



UP TO 16 CH


per cabinet

ENGINEERED FOR RESULTS




High Accuracy Measurement

High-accuracy
measurement
control
and reporting
for better
data quality




Universal Platform

Platform
agnostic
battery testing
for emerging
chemistries



Waveform Streaming

Real-world
profile
simulation
for improved
battery
performance



Parallel Channels

Parallel
2 or 4
channels
for higher
current
testing

IDEAL FOR A WIDE RANGE OF APPLICATIONS



CELL DEVELOPMENT

Accelerate battery development




RESEARCH

Support advanced energy research



DRIVE CYCLE SIMULATION

Perform real-world testing



PRODUCTION TESTING

Improve throughput and efficiency




VALIDATION TESTING

Verify performance and durability



2 CH, 2 kW Module



ENGINEERED IN THE USA
Built with quality and reliability
you can trust



TOMORROW STARTS HERE
Seamlessly supports future
chemistries



GLOBAL SUPPORT
Expert support and service
around the world



maccor.com



sales@maccor.com




+1 918 446-1874



Made in America

YOUR
BLUEPRINT
FOR
SUCCESS!



CHANNEL SPECIFICATIONS

Parameter	Specification
Channel Current Range	200A/400A Charge / Discharge
Minimum Control Current	10 mA
Current Ranges (Multi-Range)	200A / 20A / 2A 400A / 40A / 4A
Current Accuracy	±0.025% FS of Range
Channel Voltage Range	0 to 5 V
Minimum Discharge Voltage	0 V
Voltage Accuracy	±0.02% FS (±1 mV)
Maximum Power Discharge/Charge	1 kW/2 kW

TIMING AND CONTROL

Parameter	Specification
Charge↔Discharge Switch Time (80% to 80%)	< 2.5 ms
Rise Time 10% to 90% (Charge / Discharge)	< 1 ms
Control / Adjust / Measure Interval	175 us / 175 us / 1 ms

POWER & SYSTEM

Parameter	Specification
AC Input	208 - 220 VAC 1Ø or 3Ø
Cooling	Air - Front to Rear
Regenerative Discharge	Yes
Efficiency	Up to 90%
Max Channels per cabinet	16
Interface Connections	Phoenix
Approximate Cabinet Dimensions (16 ch)	40"D x 25"W x 74"H


MIMS SOFTWARE SUITE

The system includes comprehensive, full featured software that is intuitive and easy to use, enabling efficient test management and data analysis. All applications are provided standard with the system at no additional cost. The software suite supports complete workflow integration from test creation through data analysis and reporting.

- 

BUILD TEST
Provides a grid-based, menu-driven interface for creating and editing custom test procedures and protocols.
- 

VIEW DATA
Displays and analyzes test data in real-time or post-test using spreadsheet and graphical visualization formats.
- 

EXPORT
Exports test results in Excel or text format to facilitate data sharing and integration with external analysis tools.
- 

MIMS CLIENT
Delivers statistical analysis and data visualization capabilities for comprehensive evaluation of test performance and results.
- 

MIMS SERVER
Automatically collects and backs up data from multiple test systems across a network for centralized data management and security.

