

MACCOR

CELL & BATTERY Test Systems

Maximize your testing capabilities with our comprehensive turnkey systems that bundle hardware and software essentials to jumpstart your process. Select from multiple configurations tailored to your needs, then leverage fully automated, computerized testing with high-speed data acquisition and control—designed to meet both your current demands and future growth.

 **UP TO 96 CH**
PER SYSTEM

 **2400 amp**
CHARGE/DISCHARGE

 **+28 kW**
MAXIMUM POWER

 **UP TO 4**
CURRENT RANGES

ENGINEERED FOR RESULTS



Industry Standard

The world's most reliable battery test platform 50+ countries 1,000+ facilities, proven since 1987




Full-Featured Software Suite

Comprehensive software suite provides real-time monitoring data analysis and management



Precision Measurement

Multiple current ranges and Maccor measurement architecture deliver reliable accuracy across diverse applications



Dynamic Step & Pulse Response

Achieve step times as low as 2 ms (or 500 μ s on 6000-series platforms) for HPPC, drive cycles, and fast electrochemical transient characterization.

IDEAL FOR A WIDE RANGE OF APPLICATIONS



Battery
Research



Cycle
Life



National
Defense



Performance
Testing



Consumer
Electronics



Medical
Devices



Advanced
Electronics



ENGINEERED IN THE USA
Built with quality and reliability
you can trust



TOMORROW STARTS HERE
Seamlessly supports future
chemistries



GLOBAL SUPPORT
Expert support and service
around the world



maccor.com



sales@maccor.com



+1 918 446-1874



Made in America

TECHNICAL SPECIFICATIONS

Parameter	4000 / 4000H	6000 / 6000H
Maximum Channels	96	96
Maximum Current (A)	1,440 / 2,400	1,440 / 2,400
Maximum Power (W)	14,400 / 28,800	14,400 / 28,800
Current Ranges	1 or 4 / 2 or 3	1 or 4 / 2 or 3
Minimum Step Time	10 ms	1 ms
Scope Trace	-	20 kHz
Records per Second	350	>10,000
Variables	15	50
Global Flags	32	64

AML^P

Parameter	4000/4000H	6000/6000H
Minimum Pulse width	-	100 μ s
Pulse width increment	-	1 μ s
Data Recording	-	100 μ s

WAVEFORMS

Parameter	4000/4000H	6000/6000H
Maximum Number of Steps	Unlimited	Unlimited
Minimum Step Width	50 ms	1 ms
Data Recording	50 ms	1 ms



ENHANCE YOUR TESTING

- Auxiliary Voltage
- Temperature
- Pressure
- SMBus (I²C)
- Cell Holders
- Digital I/O
- CAN
- AC Impedance Multiplexer
- External Charge or Discharge Controller
- Interface Cables

EXPANDABLE TESTING, BUILT FOR GROWTH

Start with as few as eight test channels and expand your system right in your facility as your testing demands and budget grow. Add channels to the same tester in the field with minimal disruption eliminating the costly delays and logistical burden of shipping your tester back to the factory for upgrades. Scale seamlessly as you need to.