



An Introduction to Manifold Learning and its use in time series analysis

Pedro L. C. Rodrigues – Machine Learning Seekers of Truth – 6th December 2017





Ronen Talmon, Israel Cohen, Sharon Gannot, and Ronald Coifman (2013) **Diffusion maps for signal processing: A deeper look at manifold-learning techniques based on kernels and graphs**

Stéphane Lafon (Ph.D. thesis, 2004)
Diffusion maps and Geometric Harmonics

Ronald Coifman and Stéphane Lafon (2006)
Diffusion maps

Outline

Introduction

Manifold Learning for Time-Series Analysis

Some results

Concluding remarks

Outline

Introduction


Manifold Learning for Time-Series Analysis

Some results

Concluding remarks

High-dimensionality is an **obstacle** to efficient data processing for a number of reasons :


- Norms in \mathbb{R}^n are not **numerically equivalent** when n is large
- Density estimation is **difficult** in big dimensions (needs too much data)
- Fast algorithms may become **prohibitively slow** in high dimensions



curse of dimensionality

High-dimensionality is an **obstacle** to efficient data processing for a number of reasons :

- Norms in \mathbb{R}^n are not **numerically equivalent** when n is large
- Density estimation is **difficult** in big dimensions (needs too much data)
- Fast algorithms may become **prohibitively slow** in high dimensions




curse of dimensionality

Data dimensions are often correlated via some **functional dependence**


Fundamental assumption : data lies on (or close to) a low-dimensional manifold





A video is composed of several **frames** $\left\{X_i\right\}_{i=1}^N$

Each frame is an image and can be associated to a **vector**




A video is composed of several **frames** $\left\{ X_i \right\}_{i=1}^N$

Each frame is an image and can be associated to a **vector**

Frames are points in a **very** high-dimensional space,

but there are not many **degrees of freedom** in the video

$$X_i \in \mathbb{R}^{W \times H} \Rightarrow \Phi(X_i) \in \mathbb{R}^d$$



- Classical techniques like PCA and MDS for **linear** dimensionality reduction
- Two papers in Science magazine (2000) presenting **Manifold Learning** : Isomap and LLE
- Previous methods are all **global** (except LLE)
- Diffusion maps and Laplacian Eigenmaps search for an embedding that respects **local** geometry

Think globally, act locally


Dimensionality Reduction for Multivariate Time-Series

Multivariate time-series often present **redundancy** among its dimensions

$$\boldsymbol{x}(n) = \begin{bmatrix} x_1(n) \\ \vdots \\ x_N(n) \end{bmatrix}$$

Dimensionality Reduction for Multivariate Time-Series

Multivariate time-series often present **redundancy** among its dimensions



$$\{X_1, X_2, \dots, X_K\}$$

$$X_i \in \mathbb{R}^{N \times T}$$

$\begin{cases} N - \text{electrodes} \\ T - \text{samples} \end{cases}$

$$\boldsymbol{x}(n) = \begin{bmatrix} x_1(n) \\ \vdots \\ x_N(n) \end{bmatrix}$$

Dimensionality Reduction for Multivariate Time-Series

Multivariate time-series often present **redundancy** among its dimensions

$$\mathbf{x}(n) = \begin{bmatrix} x_1(n) \\ \vdots \\ x_N(n) \end{bmatrix}$$

REDUNDANCY

COMPRESSION

$$\{X_1, X_2, \dots, X_K\}$$

$$X_i \in \mathbb{R}^{N \times T}$$

$$\{Y_1, Y_2, \dots, Y_K\}$$

$$Y_i \in \mathbb{R}^d$$

Two main categories of dimensionality reduction : **linear** and **non-linear** approaches

Dimensionality Reduction for Multivariate Time-Series

Spectral Embedding – Manifold Learning

Non-linear methods based on **three** basic steps

(Laplacian Eigenmaps, Diffusion Maps, Kernel PCA, etc.)


- 
- (1) Construct a **distance matrix**
 - (2) Define a **Laplacian matrix**
 - (3) Spectral **decomposition** of L

The distance matrix can be interpreted as defining a **weighted graph**
where the **nodes** are the trials and the **weights** their distances


What can we do with this ? Unsupervised time-series analysis

$\{X_1, X_2, \dots, X_K\}$
 $X_i \in \mathbb{R}^{N \times T}$

are **recordings** of different trials



are samples of a **sliding-window**





What can we do with this ? Unsupervised time-series analysis

$\{X_1, X_2, \dots, X_K\}$
 $X_i \in \mathbb{R}^{N \times T}$

are recordings of different trials


are samples of a **sliding-window**




Hau-tieng Wu, Ronen Talmon, and Yu-Lun Lo

Assess sleep stage by modern signal processing techniques

IEEE Transactions on Biomedical Engineering (2015)







What can we do with this ? Unsupervised time-series analysis

$\{X_1, X_2, \dots, X_K\}$
 $X_i \in \mathbb{R}^{N \times T}$

are **recordings** of different trials



are samples of a **sliding-window**



Ronen Talmon, Stéphane Mallat, Hitten Zavari, Ronald R. Coifman

Manifold Learning for Latent Variable Inference in Dynamical Systems

IEEE Transactions in Signal Processing (2015)



Outline

Introduction

Manifold Learning for Time-Series Analysis

Some results

Concluding remarks

Spectral embedding of Multivariate Time-Series


Construct a pairwise **distance matrix** between the different trials :

$$\{X_1, X_2, \dots, X_K\} \quad D_{ij} = d(X_i, X_j)$$

and use it to define an **affinity matrix** via a Gaussian kernel :

$$W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$$

There are **several** heuristics for the affinity matrix (k-NN, thresh.)



Spectral embedding of Multivariate Time-Series



Construct a pairwise **distance matrix** between the different trials :

$$\{X_1, X_2, \dots, X_K\} \quad D_{ij} = d(X_i, X_j)$$

and use it to define an **affinity matrix** via a Gaussian kernel :

$$W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$$

There are **several** heuristics for the affinity matrix (k-NN, thresh.)



Spectral embedding of Multivariate Time-Series

The embedding is done so to **minimize** a cost function involving the affinities between points

$$\mathcal{L} = \frac{1}{2} \sum_{i,j} (y_i - y_j)^2 \mathbf{W}_{ij}$$

and a normalization $\sum_i \mathbf{D}_{ii} y_i^2 = 1$ where $\mathbf{D}_{ii} = \sum_j \mathbf{W}_{ij}$

$\{X_1, X_2, \dots, X_K\}$

original points



$\{y_1, y_2, \dots, y_K\}$

embedded points

Spectral embedding of Multivariate Time-Series

Rewriting the terms and defining the **Laplacian** matrix as $\mathbf{L} = \mathbf{D} - \mathbf{W}$ we have that

$$\mathcal{L} = \frac{1}{2} \sum_{i,j} (y_i - y_j)^2 \quad \mathbf{W}_{ij} = \mathbf{y}^T \mathbf{L} \mathbf{y} \quad \text{with} \quad \mathbf{y} = [\ y_1 \ \dots \ y_K \]^T$$

The minimization of the cost function can be recast as a **generalized eigenvalue problem**

$$\text{minimize} \quad \mathbf{y}^T \mathbf{L} \mathbf{y}$$

$$\text{s.t.} \quad \mathbf{y}^T \mathbf{D} \mathbf{y} = 1$$

*The embedded coordinates are the elements
of the eigenvectors of the Laplacian matrix*

Summing up



$\{X_1, X_2, \dots, X_K\} \quad X_i \in \mathbb{R}^{N \times T}$ **Gather recordings on different trials**



$$\mathbf{D}_{ij} = d(X_i, X_j)$$



$$\mathbf{W}_{ij} = \exp\left(-\frac{\mathbf{D}_{ij}^2}{\varepsilon}\right)$$



$$\{Y_1, Y_2, \dots, Y_K\} \quad Y_i \in \mathbb{R}^d$$

Summing up

□ $\{X_1, X_2, \dots, X_K\} \quad X_i \in \mathbb{R}^{N \times T}$

■ $D_{ij} = d(X_i, X_j)$ Define a notion of **distance** between trials

□ $W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$

□ $\{Y_1, Y_2, \dots, Y_K\} \quad Y_i \in \mathbb{R}^d$

Summing up

□ $\{X_1, X_2, \dots, X_K\} \quad X_i \in \mathbb{R}^{N \times T}$

□ $D_{ij} = d(X_i, X_j)$

■ $W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$ **Construct** the affinity
and Laplacian matrices

Laplacian Eingenmaps and
Diffusion Maps define the affinity
matrix differently

□ $\{Y_1, Y_2, \dots, Y_K\} \quad Y_i \in \mathbb{R}^d$

Summing up

□ $\{X_1, X_2, \dots, X_K\} \quad X_i \in \mathbb{R}^{N \times T}$

□ $D_{ij} = d(X_i, X_j)$

□ $W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$

□ $\{Y_1, Y_2, \dots, Y_K\} \quad Y_i \in \mathbb{R}^d$ Get the spectral embedding

$$Y_i = \begin{bmatrix} \mathbf{y}_1(i) \\ \vdots \\ \mathbf{y}_d(i) \end{bmatrix}$$

where

$$\{\mathbf{y}_1, \dots, \mathbf{y}_d\}$$

are the first d eigenvectors of the Laplacian matrix

Summing up


□ $\{X_1, X_2, \dots, X_K\} \quad X_i \in \mathbb{R}^{N \times T}$

□ $D_{ij} = d(X_i, X_j)$


□ $W_{ij} = \exp\left(-\frac{D_{ij}^2}{\varepsilon}\right)$

□ $\{Y_1, Y_2, \dots, Y_K\} \quad Y_i \in \mathbb{R}^d$

Analyse the **distribution** of points




Example with video frames





$$d^2(X_i, X_j) = \sum_k \sum_\ell \left(X_i(k, \ell) - X_j(k, \ell) \right)^2$$

(other distances could be used)



Diffusion Matrix = Laplacian Matrix



How to define a distance between multivariate time-series ?

Distance between Multivariate Time-Series

For a zero-mean Gaussian **wide-sense stationary** multivariate time-series $\mathbf{x}(n)$ one has that :

(Autocovariances)

$$R_{\mathbf{xx}}(\tau) = \mathbb{E} [\mathbf{x}(n)\mathbf{x}(n - \tau)^T]$$

(Cross-spectral density)

$$S_{\mathbf{xx}}(f) = \sum_{k=-\infty}^{+\infty} R_{\mathbf{xx}}(k)e^{-j2\pi fk}$$

describes all the
statistical features of $\mathbf{x}(n)$



Distance between Multivariate Time-Series

For a zero-mean Gaussian **wide-sense stationary** multivariate time-series $\mathbf{x}(n)$ one has that :

$$\left. \begin{array}{l} (\text{Autocovariances}) \quad R_{\mathbf{xx}}(\tau) = \mathbb{E} [\mathbf{x}(n)\mathbf{x}(n-\tau)^T] \\ (\text{Cross-spectral density}) \quad S_{\mathbf{xx}}(f) = \sum_{k=-\infty}^{+\infty} R_{\mathbf{xx}}(k)e^{-j2\pi fk} \end{array} \right\} \text{describes all the statistical features of } \mathbf{x}(n)$$

Two multivariate time series can be compared based on the **parameters** of their statistical descriptions.

- Compare covariance matrices
- Compare cross-spectral densities
- Compare MVAR models
- Etc.

Distance between Multivariate Time-Series

Distance based on the **covariance matrices** of two time-series :

$$d_C^2(x_1(n), x_2(n)) = \delta_R^2(C_1, C_2)$$

The C_i are **positive definite**

$$\delta_R^2(A, B) = \left\| \log \left(A^{-\frac{1}{2}} B A^{-\frac{1}{2}} \right) \right\|_F^2$$

Affine-Invariant Riemannian distance

This distance can also be interpreted as the one obtained from the **Fisher-Rao** metric on the space of multivariate normal distributions

Distance between Multivariate Time-Series

Distance based on the **covariance matrices** of two time-series :

$$d_C^2(\mathbf{x}_1(n), \mathbf{x}_2(n)) = \delta_R^2(C_1, C_2)$$

The C_i are **positive definite**

$$\delta_R^2(A, B) = \left\| \log \left(A^{-\frac{1}{2}} B A^{-\frac{1}{2}} \right) \right\|_F^2$$

Affine-Invariant Riemannian distance

Distance based on the **cross-spectral density** matrices of two time-series :

$$d_S^2(\mathbf{x}_1(n), \mathbf{x}_2(n)) = \sum_{f_k \in \mathcal{F}} \delta_R^2(S_1(f_k), S_2(f_k)) \quad \text{where } \mathcal{F} \text{ is a set of frequencies}$$

Outline

Introduction

Manifold Learning for Time-Series Analysis

Some results

Concluding remarks

Results on **three** datasets with different kinds of EEG signals

BCI

BCI IV competition
(public)

SLEEP

Prague's dataset
(private)

EPILEPSY

Kaggle competition
(public)

Results on **three** datasets with different kinds of EEG signals

BCI

BCI IV competition
(public)

SLEEP

Prague's dataset
(private)


EPILEPSY


Kaggle competition
(public)


BCI dataset: BCI IV competition


Public dataset with recordings from **motor imagery BCI**


- EEG with 22 electrodes
- Four **classes** {left, right, tongue, feet} with 72 trials each
- Sampling frequency 250 Hz












<https://plcrodrigues.github.io/riemann-lab/>



Results on **three** datasets with different kinds of EEG signals

BCI

BCI IV competition
(public)

SLEEP

Prague's dataset
(private)

EPILEPSY

Kaggle competition
(public)

Sleep dataset: Prague's dataset

Private dataset from "National Institute for Mental Health" in Prague

- EEG with 19 electrodes, EOG with 2 electrodes, EMG with 2 electrodes
- Four **sleep stages** {S1, S2, S3, REM} with ~200 two-seconds clips for each



Results on **three** datasets with different kinds of EEG signals

BCI

BCI IV competition
(public)

SLEEP

Prague's dataset
(private)


EPILEPSY

Kaggle competition
(public)

Epilepsy: Kaggle's competition dataset

Dataset used in a Kaggle competition for **epileptic** seizure detection

- **Intracranial EEG** with 36 electrodes sampled at 5000 Hz
- Dataset has several 1s clips with recordings from a few minutes **before** seizure onset (interictal)



Outline

Introduction

Manifold Learning for Time-Series Analysis

Some results

Concluding remarks

It's important to use an **adequate** notion of distance between trials

Spectral embedding can be used for **static** and **dynamic** time-series analysis

How to use the spectral embedding for **semi-supervised** classification ?


How to **compare** embeddings of two datasets ?

Can we detect **landmark** trials from the Laplacian matrix ?

Thank you **very much** for your attention :)

Questions ?





Ronen Talmon, Israel Cohen, Sharon Gannot, and Ronald Coifman (2013)

Diffusion maps for signal processing: A deeper look at manifold-learning techniques based on kernels and graphs

Stéphane Lafon (Ph.D. thesis, 2004)
Diffusion maps and Geometric Harmonics

Ronald Coifman and Stéphane Lafon (2006)
Diffusion maps

An Introduction to Manifold Learning and its use in time series analysis

Pedro L. C. Rodrigues – Machine Learning Seekers of Truth – 6th December 2017

