

```
import numpy as np
import matplotlib.pyplot as plt
def fir_filter(x, b):
    M = len(b)
    y = np.zeros(len(x))
    for n in range(M, len(x)):
        y[n] = np.dot(b, x[n-M+1:n+1][::-1])
    return y
fs = 1000 # Sampling frequency
t = np.linspace(0, 1, fs)
x = np.sin(2 * np.pi * 5 * t) + 0.5 * np.random.randn(len(t)) #
Signal with noise
b = [1, -0.2, 0.5] # FIR coefficients
y = fir filter(x, b)
plt.figure(figsize=(10, 6))
plt.plot(t, x, label="Noisy Signal")
plt.plot(t, y, label="Filtered Signal", linewidth=2)
plt.legend()
plt.title("FIR Filter")
plt.xlabel("Time [s]")
plt.ylabel("Amplitude")
plt.grid()
plt.show()
```



```
import numpy as np
import matplotlib.pyplot as plt
def iir filter(x, b, a):
    M = len(b) # Length of numerator coefficients (b)
    N = len(a) # Length of denominator coefficients (a)
    y = np.zeros(len(x)) # Initialize output signal array
    # Apply filter to each sample in the input signal
    for n in range(len(x)):
        # Numerator part (feedforward)
        # Ensure we use the correct slice length for the convolution
        x \text{ slice} = x[\max(0, n-M+1):n+1] \# Input signal slice
        y[n] = np.dot(b[:len(x slice)], x slice[::-1]) # Apply
reverse convolution for numerator
        # Denominator part (feedback), skip the first sample
        if n >= 1:
            # Ensure we use the correct slice length for the feedback
part
            y slice = y[max(0, n-N+1):n] # Output signal slice
            y[n] = np.dot(a[1:min(N, len(y slice)+1)], y slice[::-1])
# Apply reverse convolution for feedback
    return y
```

```
# Example usage and plotting
# Create a noisy signal (for example, a sine wave with noise)
fs = 1000 # Sampling frequency
t = np.linspace(0, 1, fs) # Time vector
x = np.sin(2 * np.pi * 50 * t) + 0.5 * np.random.randn(len(t)) #
Noisy signal
# IIR filter coefficients
a = [1, 0.4] # Denominator coefficients (a 0 = 1 by convention)
b = [0.6, 0.3] # Numerator coefficients
# Apply the filter to the noisy signal
y = iir filter(x, b, a)
# Plot the results
plt.figure(figsize=(10, 6))
plt.plot(t, x, label="Noisy Signal")
plt.plot(t, y, label="Filtered Signal", linewidth=2)
plt.legend()
plt.title("IIR Filter Response")
plt.xlabel("Time [s]")
plt.ylabel("Amplitude")
plt.grid(True)
plt.show()
```



```
def lms filter(x, d, mu, num taps):
    n = len(x)
   w = np.zeros(num_taps)
   y = np.zeros(n)
    e = np.zeros(n)
    for i in range(num_taps, n):
        x = x[i-num taps:i][::-1]
        y[i] = np.dot(w, x_segment)
        e[i] = d[i] - y[i]
       w += mu * e[i] * x_segment
    return y, e, w
# Example usage and plotting
d = np.sin(2 * np.pi * 5 * t) # Desired signal
mu = 0.1 # Step size
num taps = 5
y, e, w = lms_filter(x, d, mu, num_taps)
plt.figure(figsize=(10, 6))
plt.plot(t, d, label="Desired Signal")
plt.plot(t, y, label="Filtered Signal", linewidth=2)
plt.legend()
plt.title("LMS Adaptive Filter")
plt.xlabel("Time [s]")
plt.ylabel("Amplitude")
plt.grid()
plt.show()
```

